




Tx. Spurious b 2462MHz Ref




Tx. Spurious b 2462MHz Emission




Tx. Spurious g 2412MHz Ref




Tx. Spurious g 2412MHz Emission




Tx. Spurious g 2437MHz Ref




Tx. Spurious g 2437MHz Emission




Tx. Spurious g 2462MHz Ref




Tx. Spurious g 2462MHz Emission




Tx. Spurious n20 2412MHz Ref




Tx. Spurious n20 2412MHz Emission




Tx. Spurious n20 2437MHz Ref




Tx. Spurious n20 2437MHz Emission




Tx. Spurious n20 2462MHz Ref




Tx. Spurious n20 2462MHz Emission




Tx. Spurious n40 2422MHz Ref




Tx. Spurious n40 2422MHz Emission




Tx. Spurious n40 2437MHz Ref




Tx. Spurious n40 2437MHz Emission




Tx. Spurious n40 2452MHz Ref




Tx. Spurious n40 2452MHz Emission




Tx. Spurious ax20 2412MHz Ref




Tx. Spurious ax20 2412MHz Emission




Tx. Spurious ax20 2437MHz Ref




Tx. Spurious ax20 2437MHz Emission




Tx. Spurious ax20 2462MHz Ref




Tx. Spurious ax20 2462MHz Emission




Tx. Spurious ax40 2422MHz Ref




Tx. Spurious ax40 2422MHz Emission




Tx. Spurious ax40 2437MHz Ref




Tx. Spurious ax40 2437MHz Emission



Tx. Spurious ax40 2452MHz Ref





Tx. Spurious ax40 2452MHz Emission




6.7. Radiated Spurious Emission Measurement

6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10: 2014				
Frequency Range:	9 kHz to 25 GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation mode:	Transmitting mode with modulation				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)
	0.009-0.490		2400/F(KHz)		300
	0.490-1.705		24000/F(KHz)		30
	1.705-30		30		30
	30-88		100		3
	88-216		150		3
	216-960		200		3
	Above 960		500		3
	Frequency		Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
	Above 1GHz		500	3	Average
		5000	3	Peak	
Test setup:	For radiated emissions below 30MHz				
					
	30MHz to 1GHz				



Above 1GHz



Test Procedure:

- For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

	3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 5. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test results:	PASS

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

6.7.2. Test Data(worst)

Please refer to following diagram for individual
Below 1GHz


Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	50.3700	37.99	-2.14	35.85	40.00	-4.15	QP
2		97.9000	41.76	-5.68	36.08	43.50	-7.42	QP
3		215.2700	34.01	-5.25	28.76	43.50	-14.74	QP
4		301.6000	31.77	-2.47	29.30	46.00	-16.70	QP
5		750.7100	26.16	5.68	31.84	46.00	-14.16	QP
6		985.4500	25.26	8.38	33.64	54.00	-20.36	QP

Report No.: WSCT-ANAB-R&E250500038A-Wi-Fi1
Vertical:

Issued Date: 20 June 2025



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	40.6699	36.68	-1.52	35.16	40.00	-4.84	QP
2		53.2800	35.38	-2.43	32.95	40.00	-7.05	QP
3		95.9600	38.61	-5.76	32.85	43.50	-10.65	QP
4		212.3600	32.05	-5.47	26.58	43.50	-16.92	QP
5		304.5100	30.94	-2.41	28.53	46.00	-17.47	QP
6		982.5400	25.75	8.37	34.12	54.00	-19.88	QP

Note1:

Freq.= Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Report No.: WSCT-ANAB-R&E250500038A-Wi-Fi1

Issued Date: 20 June 2025

Above 1GHz


Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

Note 3: Report and only recorded the worst-case scenario 802.11b.


1 GHz to 18 GHz, ANT H 802.11b Low Channel

Horizontal:

**Susputed Data List**

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1460.6250	40.4	25.04	15.36	74	-33.6	279.4	Horizontal	PK	Pass
1	1460.6250	30.23	25.04	5.19	54	-23.77	279.4	Horizontal	AV	Pass
2	2688.7500	46.51	27.83	18.68	74	-27.49	305.8	Horizontal	PK	Pass
2	2688.7500	36.23	27.83	8.4	54	-17.77	305.8	Horizontal	AV	Pass
3	5740.0000	60.28	32.38	27.9	74	-13.72	291.4	Horizontal	PK	Pass
3	5740.0000	48.69	32.38	16.31	54	-5.31	291.4	Horizontal	AV	Pass
4	6801.0000	40.8	5.62	35.18	74	-33.2	44.7	Horizontal	PK	Pass
4	6801.0000	32.27	5.62	26.65	54	-21.73	44.7	Horizontal	AV	Pass
5	11157.0000	46.89	15.8	31.09	74	-27.11	234.8	Horizontal	PK	Pass
5	11157.0000	38.99	15.8	23.19	54	-15.01	234.8	Horizontal	AV	Pass
6	17976.0000	54.03	23.76	30.27	74	-19.97	5.8	Horizontal	PK	Pass
6	17976.0000	46.7	23.76	22.94	54	-7.3	5.8	Horizontal	AV	Pass

Vertical :



Suspected Data List


NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1421.2500	39.75	25.08	14.67	74	-34.25	-0.1	Vertical	PK	Pass
1	1421.2500	30.48	25.08	5.4	54	-23.52	-0.1	Vertical	AV	Pass
2	2481.8750	47.05	27.54	19.51	74	-26.95	247.2	Vertical	PK	Pass
2	2481.8750	38.06	27.54	10.52	54	-15.94	247.2	Vertical	AV	Pass
3	5748.1250	65.22	32.4	32.82	74	-8.78	18.9	Vertical	PK	Pass
3	5748.1250	48.54	32.4	16.14	54	-5.46	18.9	Vertical	AV	Pass
4	7683.0000	41.64	7.95	33.69	74	-32.36	0.5	Vertical	PK	Pass
4	7683.0000	34.13	7.95	26.18	54	-19.87	0.5	Vertical	AV	Pass
5	10678.5000	46.33	14.57	31.76	74	-27.67	185.8	Vertical	PK	Pass
5	10678.5000	38.56	14.57	23.99	54	-15.44	185.8	Vertical	AV	Pass
6	17251.5000	50.14	19.82	30.32	74	-23.86	212.1	Vertical	PK	Pass
6	17251.5000	42.89	19.82	23.07	54	-11.11	212.1	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E250500038A-Wi-Fi1

Issued Date: 20 June 2025

1 GHz to 18 GHz, ANT H 802.11b Middle Channel

Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1094.3750	38.1	24.35	13.75	74	-35.9	54.6	Horizontal	PK	Pass
1	1094.3750	29.53	24.35	5.18	54	-24.47	54.6	Horizontal	AV	Pass
2	2428.7500	46.72	27.36	19.36	74	-27.28	-0.1	Horizontal	PK	Pass
2	2428.7500	37.26	27.36	9.9	54	-16.74	-0.1	Horizontal	AV	Pass
3	5747.5000	58.21	32.4	25.81	74	-15.79	-0.1	Horizontal	PK	Pass
3	5747.5000	48.48	32.4	16.08	54	-5.52	-0.1	Horizontal	AV	Pass
4	8221.5000	42.21	8.81	33.4	74	-31.79	62.6	Horizontal	PK	Pass
4	8221.5000	34.19	8.81	25.38	54	-19.81	62.6	Horizontal	AV	Pass
5	10518.0000	46.09	14.01	32.08	74	-27.91	99.8	Horizontal	PK	Pass
5	10518.0000	38.07	14.01	24.06	54	-15.93	99.8	Horizontal	AV	Pass
6	17655.0000	51.82	21.66	30.16	74	-22.18	188.2	Horizontal	PK	Pass
6	17655.0000	44.38	21.66	22.72	54	-9.62	188.2	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E250500038A-Wi-Fi1

Issued Date: 20 June 2025

Vertical :



Suspected Data List


NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1421.8750	39.25	25.08	14.17	74	-34.75	133.6	Vertical	PK	Pass
1	1421.8750	30.6	25.08	5.52	54	-23.4	133.6	Vertical	AV	Pass
2	2450.6250	46.16	27.43	18.73	74	-27.84	0	Vertical	PK	Pass
2	2450.6250	38.14	27.43	10.71	54	-15.86	0	Vertical	AV	Pass
3	5889.3750	58.06	32.62	25.44	74	-15.94	359.5	Vertical	PK	Pass
3	5889.3750	48.75	32.62	16.13	54	-5.25	359.5	Vertical	AV	Pass
4	7930.5000	41.45	8.08	33.37	74	-32.55	73.4	Vertical	PK	Pass
4	7930.5000	33.7	8.08	25.62	54	-20.3	73.4	Vertical	AV	Pass
5	11059.5000	45.7	15.81	29.89	74	-28.3	360	Vertical	PK	Pass
5	11059.5000	39.47	15.81	23.66	54	-14.53	360	Vertical	AV	Pass
6	17686.5000	51.59	21.87	29.72	74	-22.41	318.5	Vertical	PK	Pass
6	17686.5000	44.95	21.87	23.08	54	-9.05	318.5	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E250500038A-Wi-Fi1

Issued Date: 20 June 2025

1 GHz to 18 GHz, ANT H 802.11b High Channel


Horizontal:



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1332.5000	39.45	24.86	14.59	74	-34.55	232.9	Horizontal	PK	Pass
1	1332.5000	30.47	24.86	5.61	54	-23.53	232.9	Horizontal	AV	Pass
2	2451.8750	46.85	27.44	19.41	74	-27.15	350.6	Horizontal	PK	Pass
2	2451.8750	37.81	27.44	10.37	54	-16.19	350.6	Horizontal	AV	Pass
3	5711.8750	58.18	32.34	25.84	74	-15.82	147.9	Horizontal	PK	Pass
3	5711.8750	49.11	32.34	16.77	54	-4.89	147.9	Horizontal	AV	Pass
4	8077.5000	41.96	8.43	33.53	74	-32.04	87.7	Horizontal	PK	Pass
4	8077.5000	34.06	8.43	25.63	54	-19.94	87.7	Horizontal	AV	Pass
5	10929.0000	45.41	15.22	30.19	74	-28.59	0.9	Horizontal	PK	Pass
5	10929.0000	38.68	15.22	23.46	54	-15.32	0.9	Horizontal	AV	Pass
6	17418.0000	52.19	20.09	32.1	74	-21.81	135.5	Horizontal	PK	Pass
6	17418.0000	43.39	20.09	23.3	54	-10.61	135.5	Horizontal	AV	Pass

Vertical :



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1577.5000	39.52	24.92	14.6	74	-34.48	359.5	Vertical	PK	Pass
1	1577.5000	31.33	24.92	6.41	54	-22.67	359.5	Vertical	AV	Pass
2	2431.8750	46.3	27.37	18.93	74	-27.7	208.9	Vertical	PK	Pass
2	2431.8750	36.77	27.37	9.4	54	-17.23	208.9	Vertical	AV	Pass
3	5737.5000	60.13	32.38	27.75	74	-13.87	253.1	Vertical	PK	Pass
3	5737.5000	48.67	32.38	16.29	54	-5.33	253.1	Vertical	AV	Pass
4	7519.5000	40.98	7.6	33.38	74	-33.02	258.7	Vertical	PK	Pass
4	7519.5000	33.89	7.6	26.29	54	-20.11	258.7	Vertical	AV	Pass
5	10876.5000	45.89	14.93	30.96	74	-28.11	348.2	Vertical	PK	Pass
5	10876.5000	38.13	14.93	23.2	54	-15.87	348.2	Vertical	AV	Pass
6	17194.5000	51.59	19.91	31.68	74	-22.41	19.1	Vertical	PK	Pass
6	17194.5000	43.4	19.91	23.49	54	-10.6	19.1	Vertical	AV	Pass

Note:

1. All emissions not reported were more than 20dB below the specified limit or in the noise floor.
2. Emission Level= Reading Level+ Probe Factor +Cable Loss.
3. Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

6.7.3. Restricted Bands Requirements

Test result for 802.11b Mode (the worst case)

Frequency	Reading	Correct Factor	Emission Level	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel							
2390	65.54	-8.76	56.78	74	17.22	H	PK
2390	53.66	-8.76	44.90	54	9.10	H	AV
2390	66.75	-8.73	58.02	74	15.98	V	PK
2390	55.60	-8.73	46.87	54	7.13	V	AV
High Channel							
2483.5	66.21	-8.76	57.45	74	16.55	H	PK
2483.5	54.77	-8.76	46.01	54	7.99	H	AV
2483.5	68.92	-8.73	60.19	74	13.81	V	PK
2483.5	56.03	-8.73	47.30	54	6.70	V	AV

Note: Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = Attenuation factor + Cable loss

Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Level (dBμV) – Limits (dBμV)

7. Test Setup Photographs

Please refer to Annex "Set Up Photos-15C" for test setup photos

*******END OF REPORT*******