

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
Band 66 (BW: 20MHz)	1RB	Left Cheek	132322	1755.0	-0.03	0.146	100	1.00	23.18	23.50	1.076	0.157
		Left Tilt	132322	1755.0	0.02	0.241	100	1.00	23.18	23.50	1.076	0.259
		Right Cheek	132322	1755.0	-0.02	0.252	100	1.00	23.18	23.50	1.076	0.271
		Right Tilt	132322	1755.0	0.02	0.514	100	1.00	23.18	23.50	1.076	0.553
	50%RB	Left Cheek	132322	1755.0	0.03	0.121	100	1.00	23.18	23.50	1.076	0.130
		Left Tilt	132322	1755.0	0.00	0.224	100	1.00	23.18	23.50	1.076	0.241
		Right Cheek	132322	1755.0	-0.01	0.230	100	1.00	23.18	23.50	1.076	0.248
		Right Tilt	132322	1755.0	0.02	0.449	100	1.00	23.18	23.50	1.076	0.483
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
Band 66 (BW: 20MHz)	1RB	Front	132322	1755.0	0.08	0.062	100	1.00	23.18	23.50	1.076	0.067
		Back	132322	1755.0	-0.06	0.085	100	1.00	23.18	23.50	1.076	0.091
		Left	132322	1755.0	-0.05	0.044	100	1.00	23.18	23.50	1.076	0.047
		Right	132322	1755.0	-0.13	0.009	100	1.00	23.18	23.50	1.076	0.010
		Top	132322	1755.0	0.05	0.051	100	1.00	23.18	23.50	1.076	0.055
		Bottom	132322	1755.0	0.09	0.002	100	1.00	23.18	23.50	1.076	0.002
	50%RB	Front	132322	1755.0	-0.05	0.054	100	1.00	23.18	23.50	1.076	0.058
		Back	132322	1755.0	0.03	0.076	100	1.00	23.18	23.50	1.076	0.082
		Left	132322	1755.0	0.04	0.039	100	1.00	23.18	23.50	1.076	0.042
		Right	132322	1755.0	-0.17	0.004	100	1.00	23.18	23.50	1.076	0.004
		Top	132322	1755.0	0.08	0.041	100	1.00	23.18	23.50	1.076	0.044
		Bottom	132322	1755.0	-0.12	0.002	100	1.00	23.18	23.50	1.076	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n5 (BW: 20MHz)	1RB	Left Cheek	167300	836.5	-0.100	0.894	100	1.00	25.13	25.50	1.089	0.974
		Left Tilt	167300	836.5	0.030	0.178	100	1.00	25.13	25.50	1.089	0.194
		Right Cheek	167300	836.5	-0.010	0.488	100	1.00	25.13	25.50	1.089	0.531
		Right Tilt	167300	836.5	0.130	0.142	100	1.00	25.13	25.50	1.089	0.155
	50%RB	Left Cheek	167300	836.5	0.080	0.872	100	1.00	25.13	25.50	1.089	0.950
		Left Tilt	167300	836.5	-0.020	0.169	100	1.00	25.13	25.50	1.089	0.184
		Right Cheek	167300	836.5	0.040	0.489	100	1.00	25.13	25.50	1.089	0.532
		Right Tilt	167300	836.5	0.140	0.137	100	1.00	25.13	25.50	1.089	0.149
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n5 (BW: 20MHz)	1RB	Front	167300	836.5	0.060	0.492	100	1.00	25.13	25.50	1.089	0.536
		Back	167300	836.5	-0.070	0.861	100	1.00	25.13	25.50	1.089	0.938
		Left	167300	836.5	0.120	0.402	100	1.00	25.13	25.50	1.089	0.438
		Right	167300	836.5	0.070	0.164	100	1.00	25.13	25.50	1.089	0.179
		Top	167300	836.5	0.130	0.252	100	1.00	25.13	25.50	1.089	0.274
		Bottom	167300	836.5	-0.080	0.008	100	1.00	25.13	25.50	1.089	0.009
	50%RB	Front	167300	836.5	0.130	0.479	100	1.00	25.13	25.50	1.089	0.522
		Back	167300	836.5	-0.080	0.840	100	1.00	25.13	25.50	1.089	0.915
		Left	167300	836.5	0.070	0.392	100	1.00	25.13	25.50	1.089	0.427
		167300	167300	836.5	-0.150	0.160	100	1.00	25.13	25.50	1.089	0.174
		167300	167300	836.5	0.040	0.244	100	1.00	25.13	25.50	1.089	0.266
		167300	167300	836.5	0.050	0.006	100	1.00	25.13	25.50	1.089	0.007

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n7 (BW: 20MHz)	1RB	Left Cheek	501500	2507.5	0.01	0.257	100	1.00	24.61	25.00	1.094	0.281
		Left Tilt	501500	2507.5	-0.03	0.372	100	1.00	24.61	25.00	1.094	0.407
		Right Cheek	501500	2507.5	-0.04	0.553	100	1.00	24.61	25.00	1.094	0.605
		Right Tilt	501500	2507.5	0.01	0.849	100	1.00	24.61	25.00	1.094	0.929
	50%RB	Left Cheek	501500	2507.5	-0.03	0.181	100	1.00	24.61	25.00	1.094	0.198
		Left Tilt	501500	2507.5	0.01	0.294	100	1.00	24.61	25.00	1.094	0.322
		Right Cheek	501500	2507.5	0.06	0.461	100	1.00	24.61	25.00	1.094	0.504
		Right Tilt	501500	2507.5	0.02	0.783	100	1.00	24.61	25.00	1.094	0.857
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n7 (BW: 20MHz)	1RB	Front	501500	2507.5	-0.01	0.073	100	1.00	24.61	25.00	1.094	0.080
		Back	501500	2507.5	-0.07	0.114	100	1.00	24.61	25.00	1.094	0.125
		Left	501500	2507.5	-0.03	0.081	100	1.00	24.61	25.00	1.094	0.089
		Right	501500	2507.5	-0.02	0.035	100	1.00	24.61	25.00	1.094	0.038
		Top	501500	2507.5	0.03	0.089	100	1.00	24.61	25.00	1.094	0.097
		Bottom	501500	2507.5	0.08	0.002	100	1.00	24.61	25.00	1.094	0.002
	50%RB	Front	501500	2507.5	0.02	0.066	100	1.00	24.61	25.00	1.094	0.072
		Back	501500	2507.5	-0.03	0.102	100	1.00	24.61	25.00	1.094	0.112
		Left	501500	2507.5	0.01	0.071	100	1.00	24.61	25.00	1.094	0.078
		Right	501500	2507.5	0.04	0.027	100	1.00	24.61	25.00	1.094	0.030
		Top	501500	2507.5	-0.01	0.080	100	1.00	24.61	25.00	1.094	0.088
		Bottom	501500	2507.5	-0.10	0.002	100	1.00	24.61	25.00	1.094	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n12 (BW: 15MHz)	1RB	Left Cheek	141300	706.5	-0.03	0.738	100	1.00	25.43	25.50	1.016	0.750
		Left Tilt	141300	706.5	0.01	0.199	100	1.00	25.43	25.50	1.016	0.202
		Right Cheek	141300	706.5	-0.08	0.501	100	1.00	25.43	25.50	1.016	0.509
		Right Tilt	141300	706.5	0.02	0.124	100	1.00	25.43	25.50	1.016	0.126
	50%RB	Left Cheek	141300	706.5	0.04	0.685	100	1.00	25.43	25.50	1.016	0.696
		Left Tilt	141300	706.5	-0.03	0.175	100	1.00	25.43	25.50	1.016	0.178
		Right Cheek	141300	706.5	-0.01	0.459	100	1.00	25.43	25.50	1.016	0.466
		Right Tilt	141300	706.5	0.02	0.106	100	1.00	25.43	25.50	1.016	0.108
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n12 (BW: 15MHz)	1RB	Front	141300	706.5	-0.02	0.328	100	1.00	25.43	25.50	1.016	0.333
		Back	141300	706.5	-0.01	0.617	100	1.00	25.43	25.50	1.016	0.627
		Left	141300	706.5	0.02	0.385	100	1.00	25.43	25.50	1.016	0.391
		Right	141300	706.5	0.06	0.149	100	1.00	25.43	25.50	1.016	0.151
		Top	141300	706.5	-0.15	0.125	100	1.00	25.43	25.50	1.016	0.127
		Bottom	141300	706.5	-0.13	0.117	100	1.00	25.43	25.50	1.016	0.119
	50%RB	Front	141300	706.5	-0.01	0.301	100	1.00	25.43	25.50	1.016	0.306
		Back	141300	706.5	0.03	0.582	100	1.00	25.43	25.50	1.016	0.591
		Left	141300	706.5	0.05	0.339	100	1.00	25.43	25.50	1.016	0.345
		Right	141300	706.5	-0.03	0.136	100	1.00	25.43	25.50	1.016	0.138
		Top	141300	706.5	-0.08	0.111	100	1.00	25.43	25.50	1.016	0.113
		Bottom	141300	706.5	-0.11	0.103	100	1.00	25.43	25.50	1.016	0.105

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n38 (BW: 20MHz)	1RB	Left Cheek	522500	2580.0	0.02	0.159	100	1.00	25.00	25.50	1.122	0.178
		Left Tilt	522500	2580.0	-0.01	0.264	100	1.00	25.00	25.50	1.122	0.296
		Right Cheek	522500	2580.0	-0.05	0.276	100	1.00	25.00	25.50	1.122	0.310
		Right Tilt	522500	2580.0	-0.02	0.465	100	1.00	25.00	25.50	1.122	0.522
	50%RB	Left Cheek	522500	2580.0	0.02	0.146	100	1.00	25.00	25.50	1.122	0.164
		Left Tilt	522500	2580.0	-0.02	0.219	100	1.00	25.00	25.50	1.122	0.246
		Right Cheek	522500	2580.0	0.04	0.237	100	1.00	25.00	25.50	1.122	0.266
		Right Tilt	522500	2580.0	-0.03	0.403	100	1.00	25.00	25.50	1.122	0.452
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n38 (BW: 20MHz)	1RB	Front	522500	2580.0	0.02	0.036	100	1.00	25.00	25.50	1.122	0.040
		Back	522500	2580.0	0.05	0.072	100	1.00	25.00	25.50	1.122	0.081
		Left	522500	2580.0	-0.04	0.035	100	1.00	25.00	25.50	1.122	0.039
		Right	522500	2580.0	-0.03	0.009	100	1.00	25.00	25.50	1.122	0.010
		Top	522500	2580.0	0.05	0.054	100	1.00	25.00	25.50	1.122	0.061
		Bottom	522500	2580.0	-0.14	0.002	100	1.00	25.00	25.50	1.122	0.002
	50%RB	Front	522500	2580.0	0.03	0.031	100	1.00	25.00	25.50	1.122	0.035
		Back	522500	2580.0	0.02	0.063	100	1.00	25.00	25.50	1.122	0.071
		Left	522500	2580.0	-0.04	0.029	100	1.00	25.00	25.50	1.122	0.033
		Right	522500	2580.0	0.01	0.005	100	1.00	25.00	25.50	1.122	0.006
		Top	522500	2580.0	-0.01	0.026	100	1.00	25.00	25.50	1.122	0.029
		Bottom	522500	2580.0	-0.17	0.002	100	1.00	25.00	25.50	1.122	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n41 (BW:100MHz)	1RB	Left Cheek	518598	2593.0	0.02	0.164	100	1.00	24.68	25.00	1.076	0.177
		Left Tilt	518598	2593.0	-0.05	0.295	100	1.00	24.68	25.00	1.076	0.318
		Right Cheek	518598	2593.0	-0.01	0.361	100	1.00	24.68	25.00	1.076	0.389
		Right Tilt	518598	2593.0	0.08	0.535	100	1.00	24.68	25.00	1.076	0.576
	50%RB	Left Cheek	518598	2593.0	-0.01	0.148	100	1.00	24.68	25.00	1.076	0.159
		Left Tilt	518598	2593.0	-0.03	0.276	100	1.00	24.68	25.00	1.076	0.297
		Right Cheek	518598	2593.0	0.03	0.326	100	1.00	24.68	25.00	1.076	0.351
		Right Tilt	518598	2593.0	0.06	0.482	100	1.00	24.68	25.00	1.076	0.519
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n41 (BW:100MHz)	1RB	Front	518598	2593.0	-0.05	0.045	100	1.00	24.68	25.00	1.076	0.048
		Back	518598	2593.0	-0.08	0.080	100	1.00	24.68	25.00	1.076	0.086
		Left	518598	2593.0	0.02	0.049	100	1.00	24.68	25.00	1.076	0.053
		Right	518598	2593.0	-0.04	0.012	100	1.00	24.68	25.00	1.076	0.013
		Top	518598	2593.0	0.04	0.057	100	1.00	24.68	25.00	1.076	0.061
		Bottom	518598	2593.0	-0.13	0.002	100	1.00	24.68	25.00	1.076	0.002
	50%RB	Front	518598	2593.0	0.03	0.040	100	1.00	24.68	25.00	1.076	0.043
		Back	518598	2593.0	-0.03	0.071	100	1.00	24.68	25.00	1.076	0.076
		Left	518598	2593.0	0.02	0.041	100	1.00	24.68	25.00	1.076	0.044
		Right	518598	2593.0	0.04	0.008	100	1.00	24.68	25.00	1.076	0.009
		Top	518598	2593.0	-0.06	0.050	100	1.00	24.68	25.00	1.076	0.054
		Bottom	518598	2593.0	-0.15	0.002	100	1.00	24.68	25.00	1.076	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n66 (BW:40MHz)	1RB	Left Cheek	349000	1745.0	-0.01	0.194	100	1.00	25.06	25.50	1.107	0.215
		Left Tilt	349000	1745.0	-0.03	0.353	100	1.00	25.06	25.50	1.107	0.391
		Right Cheek	349000	1745.0	-0.04	0.376	100	1.00	25.06	25.50	1.107	0.416
		Right Tilt	349000	1745.0	-0.05	0.633	100	1.00	25.06	25.50	1.107	0.700
	50%RB	Left Cheek	349000	1745.0	-0.02	0.162	100	1.00	25.06	25.50	1.107	0.179
		Left Tilt	349000	1745.0	0.03	0.302	100	1.00	25.06	25.50	1.107	0.334
		Right Cheek	349000	1745.0	-0.04	0.315	100	1.00	25.06	25.50	1.107	0.349
		Right Tilt	349000	1745.0	0.02	0.569	100	1.00	25.06	25.50	1.107	0.630
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n66 (BW:40MHz)	1RB	Front	349000	1745.0	-0.01	0.072	100	1.00	25.06	25.50	1.107	0.080
		Back	349000	1745.0	-0.09	0.116	100	1.00	25.06	25.50	1.107	0.128
		Left	349000	1745.0	0.01	0.064	100	1.00	25.06	25.50	1.107	0.071
		Right	349000	1745.0	0.03	0.019	100	1.00	25.06	25.50	1.107	0.021
		Top	349000	1745.0	-0.02	0.089	100	1.00	25.06	25.50	1.107	0.098
		Bottom	349000	1745.0	-0.15	0.002	100	1.00	25.06	25.50	1.107	0.002
	50%RB	Front	349000	1745.0	0.05	0.063	100	1.00	25.06	25.50	1.107	0.070
		Back	349000	1745.0	-0.01	0.107	100	1.00	25.06	25.50	1.107	0.118
		Left	349000	1745.0	-0.03	0.051	100	1.00	25.06	25.50	1.107	0.056
		Right	349000	1745.0	0.02	0.012	100	1.00	25.06	25.50	1.107	0.013
		Top	349000	1745.0	0.06	0.080	100	1.00	25.06	25.50	1.107	0.089
		Bottom	349000	1745.0	-0.01	0.002	100	1.00	25.06	25.50	1.107	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n71 (BW:15MHz)	1RB	Left Cheek	133100	665.5	-0.030	0.576	100	1.00	25.33	25.50	1.040	0.599
		Left Tilt	133100	665.5	0.030	0.152	100	1.00	25.33	25.50	1.040	0.158
		Right Cheek	133100	665.5	-0.020	0.359	100	1.00	25.33	25.50	1.040	0.373
		Right Tilt	133100	665.5	0.050	0.141	100	1.00	25.33	25.50	1.040	0.147
	50%RB	Left Cheek	133100	665.5	0.060	0.551	100	1.00	25.33	25.50	1.040	0.573
		Left Tilt	133100	665.5	-0.090	0.144	100	1.00	25.33	25.50	1.040	0.150
		Right Cheek	133100	665.5	0.020	0.351	100	1.00	25.33	25.50	1.040	0.365
		Right Tilt	133100	665.5	0.140	0.137	100	1.00	25.33	25.50	1.040	0.142
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n71 (BW:15MHz)	1RB	Front	133100	665.5	0.080	0.376	100	1.00	25.33	25.50	1.040	0.391
		Back	133100	665.5	-0.030	0.570	100	1.00	25.33	25.50	1.040	0.593
		Left	133100	665.5	0.010	0.429	100	1.00	25.33	25.50	1.040	0.446
		Right	133100	665.5	0.050	0.120	100	1.00	25.33	25.50	1.040	0.125
		Top	133100	665.5	-0.060	0.292	100	1.00	25.33	25.50	1.040	0.304
		Bottom	133100	665.5	0.180	0.009	100	1.00	25.33	25.50	1.040	0.009
	50%RB	Front	133100	665.5	-0.080	0.361	100	1.00	25.33	25.50	1.040	0.375
		Back	133100	665.5	0.110	0.556	100	1.00	25.33	25.50	1.040	0.578
		Left	133100	665.5	0.080	0.418	100	1.00	25.33	25.50	1.040	0.435
		Right	133100	665.5	-0.020	0.115	100	1.00	25.33	25.50	1.040	0.120
		Top	133100	665.5	0.010	0.279	100	1.00	25.33	25.50	1.040	0.290
		Bottom	133100	665.5	-0.180	0.009	100	1.00	25.33	25.50	1.040	0.009

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n77 (BW:50MHz)	1RB	Left Cheek	633334	3500.0	-0.02	0.155	100	1.00	26.60	27.00	1.096	0.170
		Left Tilt	633334	3500.0	0.06	0.179	100	1.00	26.60	27.00	1.096	0.196
		Right Cheek	633334	3500.0	-0.01	0.421	100	1.00	26.60	27.00	1.096	0.462
		Right Tilt	633334	3500.0	0.04	0.575	100	1.00	26.60	27.00	1.096	0.630
	50%RB	Left Cheek	633334	3500.0	0.03	0.139	100	1.00	26.60	27.00	1.096	0.152
		Left Tilt	633334	3500.0	-0.03	0.166	100	1.00	26.60	27.00	1.096	0.182
		Right Cheek	633334	3500.0	0.01	0.412	100	1.00	26.60	27.00	1.096	0.452
		Right Tilt	633334	3500.0	0.04	0.496	100	1.00	26.60	27.00	1.096	0.544
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n77 (BW:50MHz)	1RB	Front	633334	3500.0	-0.02	0.098	100	1.00	26.60	27.00	1.096	0.107
		Back	633334	3500.0	-0.08	0.124	100	1.00	26.60	27.00	1.096	0.136
		Left	633334	3500.0	0.06	0.084	100	1.00	26.60	27.00	1.096	0.092
		Right	633334	3500.0	-0.01	0.029	100	1.00	26.60	27.00	1.096	0.032
		Top	633334	3500.0	0.13	0.078	100	1.00	26.60	27.00	1.096	0.086
		Bottom	633334	3500.0	0.04	0.002	100	1.00	26.60	27.00	1.096	0.002
	50%RB	Front	633334	3500.0	-0.05	0.090	100	1.00	26.60	27.00	1.096	0.099
		Back	633334	3500.0	-0.01	0.109	100	1.00	26.60	27.00	1.096	0.120
		Left	633334	3500.0	0.03	0.078	100	1.00	26.60	27.00	1.096	0.086
		Right	633334	3500.0	0.02	0.013	100	1.00	26.60	27.00	1.096	0.014
		Top	633334	3500.0	-0.08	0.069	100	1.00	26.60	27.00	1.096	0.076
		Bottom	633334	3500.0	-0.17	0.002	100	1.00	26.60	27.00	1.096	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n77 (BW:50MHz)	1RB	Left Cheek	637000	3560.0	-0.02	0.197	100	1.00	26.23	26.50	1.064	0.210
		Left Tilt	637000	3560.0	0.04	0.218	100	1.00	26.23	26.50	1.064	0.232
		Right Cheek	637000	3560.0	-0.01	0.586	100	1.00	26.23	26.50	1.064	0.624
		Right Tilt	637000	3560.0	0.01	0.728	100	1.00	26.23	26.50	1.064	0.775
	50%RB	Left Cheek	637000	3560.0	-0.03	0.184	100	1.00	26.23	26.50	1.064	0.196
		Left Tilt	637000	3560.0	0.05	0.202	100	1.00	26.23	26.50	1.064	0.215
		Right Cheek	637000	3560.0	-0.03	0.553	100	1.00	26.23	26.50	1.064	0.588
		Right Tilt	637000	3560.0	-0.01	0.694	100	1.00	26.23	26.50	1.064	0.739
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n77 (BW:50MHz)	1RB	Front	637000	3560.0	0.08	0.119	100	1.00	26.23	26.50	1.064	0.127
		Back	637000	3560.0	-0.13	0.149	100	1.00	26.23	26.50	1.064	0.159
		Left	637000	3560.0	0.03	0.107	100	1.00	26.23	26.50	1.064	0.114
		Right	637000	3560.0	-0.05	0.036	100	1.00	26.23	26.50	1.064	0.038
		Top	637000	3560.0	-0.06	0.089	100	1.00	26.23	26.50	1.064	0.095
		Bottom	637000	3560.0	0.14	0.002	100	1.00	26.23	26.50	1.064	0.002
	50%RB	Front	637000	3560.0	-0.02	0.108	100	1.00	26.23	26.50	1.064	0.115
		Back	637000	3560.0	0.05	0.137	100	1.00	26.23	26.50	1.064	0.146
		Left	637000	3560.0	0.04	0.099	100	1.00	26.23	26.50	1.064	0.105
		Right	637000	3560.0	0.03	0.029	100	1.00	26.23	26.50	1.064	0.031
		Top	637000	3560.0	-0.02	0.082	100	1.00	26.23	26.50	1.064	0.087
		Bottom	637000	3560.0	-0.12	0.002	100	1.00	26.23	26.50	1.064	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n77 (BW:50MHz)	1RB	Left Cheek	656000	3890.0	0.05	0.103	100	1.00	26.13	26.50	1.089	0.112
		Left Tilt	656000	3890.0	0.04	0.146	100	1.00	26.13	26.50	1.089	0.159
		Right Cheek	656000	3890.0	-0.03	0.403	100	1.00	26.13	26.50	1.089	0.439
		Right Tilt	656000	3890.0	0.04	0.521	100	1.00	26.13	26.50	1.089	0.567
	50%RB	Left Cheek	656000	3890.0	0.02	0.087	100	1.00	26.13	26.50	1.089	0.095
		Left Tilt	656000	3890.0	-0.03	0.129	100	1.00	26.13	26.50	1.089	0.140
		Right Cheek	656000	3890.0	-0.01	0.368	100	1.00	26.13	26.50	1.089	0.401
		Right Tilt	656000	3890.0	0.04	0.474	100	1.00	26.13	26.50	1.089	0.516
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n77 (BW:50MHz)	1RB	Front	656000	3890.0	0.07	0.090	100	1.00	26.13	26.50	1.089	0.098
		Back	656000	3890.0	-0.13	0.117	100	1.00	26.13	26.50	1.089	0.127
		Left	656000	3890.0	-0.02	0.076	100	1.00	26.13	26.50	1.089	0.083
		Right	656000	3890.0	0.06	0.019	100	1.00	26.13	26.50	1.089	0.021
		Top	656000	3890.0	0.08	0.071	100	1.00	26.13	26.50	1.089	0.077
		Bottom	656000	3890.0	-0.06	0.002	100	1.00	26.13	26.50	1.089	0.002
	50%RB	Front	656000	3890.0	0.02	0.085	100	1.00	26.13	26.50	1.089	0.093
		Back	656000	3890.0	-0.01	0.101	100	1.00	26.13	26.50	1.089	0.110
		Left	656000	3890.0	0.03	0.069	100	1.00	26.13	26.50	1.089	0.075
		Right	656000	3890.0	-0.03	0.016	100	1.00	26.13	26.50	1.089	0.017
		Top	656000	3890.0	-0.06	0.059	100	1.00	26.13	26.50	1.089	0.064
		Bottom	656000	3890.0	-0.13	0.002	100	1.00	26.13	26.50	1.089	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n78 (BW:50MHz)	1RB	Left Cheek	633334	3500.0	0.03	0.094	100	1.00	26.56	27.00	1.107	0.104
		Left Tilt	633334	3500.0	-0.04	0.139	100	1.00	26.56	27.00	1.107	0.154
		Right Cheek	633334	3500.0	-0.02	0.418	100	1.00	26.56	27.00	1.107	0.463
		Right Tilt	633334	3500.0	0.08	0.501	100	1.00	26.56	27.00	1.107	0.554
	50%RB	Left Cheek	633334	3500.0	-0.01	0.074	100	1.00	26.56	27.00	1.107	0.082
		Left Tilt	633334	3500.0	0.06	0.116	100	1.00	26.56	27.00	1.107	0.128
		Right Cheek	633334	3500.0	0.03	0.375	100	1.00	26.56	27.00	1.107	0.415
		Right Tilt	633334	3500.0	0.02	0.483	100	1.00	26.56	27.00	1.107	0.534
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n78 (BW:50MHz)	1RB	Front	633334	3500.0	-0.03	0.073	100	1.00	26.56	27.00	1.107	0.081
		Back	633334	3500.0	-0.10	0.098	100	1.00	26.56	27.00	1.107	0.108
		Left	633334	3500.0	0.07	0.062	100	1.00	26.56	27.00	1.107	0.069
		Right	633334	3500.0	-0.05	0.013	100	1.00	26.56	27.00	1.107	0.014
		Top	633334	3500.0	0.06	0.059	100	1.00	26.56	27.00	1.107	0.065
		Bottom	633334	3500.0	-0.11	0.002	100	1.00	26.56	27.00	1.107	0.002
	50%RB	Front	633334	3500.0	-0.04	0.068	100	1.00	26.56	27.00	1.107	0.075
		Back	633334	3500.0	-0.03	0.091	100	1.00	26.56	27.00	1.107	0.101
		Left	633334	3500.0	0.02	0.057	100	1.00	26.56	27.00	1.107	0.063
		Right	633334	3500.0	-0.02	0.008	100	1.00	26.56	27.00	1.107	0.009
		Top	633334	3500.0	-0.08	0.052	100	1.00	26.56	27.00	1.107	0.058
		Bottom	633334	3500.0	-0.17	0.002	100	1.00	26.56	27.00	1.107	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n78 (BW:50MHz)	1RB	Left Cheek	637000	3560.0	0.01	0.156	100	1.00	26.30	26.50	1.047	0.163
		Left Tilt	637000	3560.0	0.03	0.176	100	1.00	26.30	26.50	1.047	0.184
		Right Cheek	637000	3560.0	0.05	0.419	100	1.00	26.30	26.50	1.047	0.439
		Right Tilt	637000	3560.0	0.05	0.578	100	1.00	26.30	26.50	1.047	0.605
	50%RB	Left Cheek	637000	3560.0	0.02	0.142	100	1.00	26.30	26.50	1.047	0.149
		Left Tilt	637000	3560.0	-0.03	0.161	100	1.00	26.30	26.50	1.047	0.169
		Right Cheek	637000	3560.0	-0.02	0.382	100	1.00	26.30	26.50	1.047	0.400
		Right Tilt	637000	3560.0	-0.04	0.547	100	1.00	26.30	26.50	1.047	0.573
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n78 (BW:50MHz)	1RB	Front	637000	3560.0	-0.07	0.093	100	1.00	26.30	26.50	1.047	0.097
		Back	637000	3560.0	-0.09	0.119	100	1.00	26.30	26.50	1.047	0.125
		Left	637000	3560.0	-0.04	0.082	100	1.00	26.30	26.50	1.047	0.086
		Right	637000	3560.0	-0.03	0.024	100	1.00	26.30	26.50	1.047	0.025
		Top	637000	3560.0	0.04	0.076	100	1.00	26.30	26.50	1.047	0.080
		Bottom	637000	3560.0	-0.15	0.002	100	1.00	26.30	26.50	1.047	0.002
	50%RB	Front	637000	3560.0	-0.03	0.087	100	1.00	26.30	26.50	1.047	0.091
		Back	637000	3560.0	0.05	0.106	100	1.00	26.30	26.50	1.047	0.111
		Left	637000	3560.0	-0.01	0.073	100	1.00	26.30	26.50	1.047	0.076
		Right	637000	3560.0	0.02	0.017	100	1.00	26.30	26.50	1.047	0.018
		Top	637000	3560.0	-0.06	0.035	100	1.00	26.30	26.50	1.047	0.037
		Bottom	637000	3560.0	-0.18	0.002	100	1.00	26.30	26.50	1.047	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n78 (BW:50MHz)	1RB	Left Cheek	650000	3750.0	-0.04	0.117	100	1.00	26.14	26.50	1.086	0.127
		Left Tilt	650000	3750.0	0.01	0.152	100	1.00	26.14	26.50	1.086	0.165
		Right Cheek	650000	3750.0	0.03	0.335	100	1.00	26.14	26.50	1.086	0.364
		Right Tilt	650000	3750.0	0.04	0.518	100	1.00	26.14	26.50	1.086	0.563
	50%RB	Left Cheek	650000	3750.0	0.03	0.098	100	1.00	26.14	26.50	1.086	0.106
		Left Tilt	650000	3750.0	-0.02	0.136	100	1.00	26.14	26.50	1.086	0.148
		Right Cheek	650000	3750.0	-0.04	0.308	100	1.00	26.14	26.50	1.086	0.335
		Right Tilt	650000	3750.0	-0.07	0.492	100	1.00	26.14	26.50	1.086	0.535
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
NR n78 (BW:50MHz)	1RB	Front	650000	3750.0	0.03	0.086	100	1.00	26.14	26.50	1.086	0.093
		Back	650000	3750.0	-0.10	0.112	100	1.00	26.14	26.50	1.086	0.122
		Left	650000	3750.0	-0.01	0.083	100	1.00	26.14	26.50	1.086	0.090
		Right	650000	3750.0	-0.11	0.019	100	1.00	26.14	26.50	1.086	0.021
		Top	650000	3750.0	0.07	0.070	100	1.00	26.14	26.50	1.086	0.076
		Bottom	650000	3750.0	-0.15	0.002	100	1.00	26.14	26.50	1.086	0.002
	50%RB	Front	650000	3750.0	-0.05	0.079	100	1.00	26.14	26.50	1.086	0.086
		Back	650000	3750.0	-0.03	0.103	100	1.00	26.14	26.50	1.086	0.112
		Left	650000	3750.0	0.01	0.073	100	1.00	26.14	26.50	1.086	0.079
		Right	650000	3750.0	-0.12	0.014	100	1.00	26.14	26.50	1.086	0.015
		Top	650000	3750.0	-0.01	0.061	100	1.00	26.14	26.50	1.086	0.066
		Bottom	650000	3750.0	-0.14	0.002	100	1.00	26.14	26.50	1.086	0.002

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
2-n7 (BW: 20MHz)	1RB	Left Cheek	19175	1907.5	-2.240	0.496	100	1.00	21.82	22.00	1.042	0.517
		Left Tilt	19175	1907.5	0.390	0.951	100	1.00	21.82	22.00	1.042	0.991
		Right Cheek	19175	1907.5	-0.120	0.632	100	1.00	21.82	22.00	1.042	0.659
		Right Tilt	19175	1907.5	3.660	1.004	100	1.00	21.82	22.00	1.042	1.046
	50%RB	Left Cheek	19175	1907.5	1.240	0.296	100	1.00	21.82	22.00	1.042	0.309
		Left Tilt	19175	1907.5	0.750	0.701	100	1.00	21.82	22.00	1.042	0.731
		Right Cheek	19175	1907.5	-2.140	0.400	100	1.00	21.82	22.00	1.042	0.417
		Right Tilt	19175	1907.5	-0.110	0.774	100	1.00	21.82	22.00	1.042	0.807
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
2-n7 (BW: 20MHz)	1RB	Front	19175	1907.5	0.780	0.502	100	1.00	21.82	22.00	1.042	0.523
		Back	19175	1907.5	4.540	0.586	100	1.00	21.82	22.00	1.042	0.611
		Left	19175	1907.5	-2.950	0.426	100	1.00	21.82	22.00	1.042	0.444
		Right	19175	1907.5	-3.900	0.028	100	1.00	21.82	22.00	1.042	0.029
		Top	19175	1907.5	1.090	0.379	100	1.00	21.82	22.00	1.042	0.395
		Bottom	19175	1907.5	-4.310	0.017	100	1.00	21.82	22.00	1.042	0.018
	50%RB	Front	19175	1907.5	-1.780	0.367	100	1.00	21.82	22.00	1.042	0.383
		Back	19175	1907.5	2.540	0.411	100	1.00	21.82	22.00	1.042	0.428
		Left	19175	1907.5	1.360	0.297	100	1.00	21.82	22.00	1.042	0.310
		Right	19175	1907.5	2.040	0.021	100	1.00	21.82	22.00	1.042	0.022
		Top	19175	1907.5	-2.310	0.206	100	1.00	21.82	22.00	1.042	0.215
		Bottom	19175	1907.5	-0.500	0.014	100	1.00	21.82	22.00	1.042	0.015

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
2-n66 (BW: 20MHz)	1RB	Left Cheek	18900	1880.0	3.210	0.072	100	1.00	23.04	23.50	1.112	0.080
		Left Tilt	18900	1880.0	0.980	0.148	100	1.00	23.04	23.50	1.112	0.165
		Right Cheek	18900	1880.0	-1.540	0.109	100	1.00	23.04	23.50	1.112	0.121
		Right Tilt	18900	1880.0	-2.690	0.195	100	1.00	23.04	23.50	1.112	0.217
	50%RB	Left Cheek	18900	1880.0	-2.820	0.048	100	1.00	23.04	23.50	1.112	0.053
		Left Tilt	18900	1880.0	-4.880	0.089	100	1.00	23.04	23.50	1.112	0.099
		Right Cheek	18900	1880.0	1.790	0.065	100	1.00	23.04	23.50	1.112	0.072
		Right Tilt	18900	1880.0	-3.870	0.109	100	1.00	23.04	23.50	1.112	0.121
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
2-n66 (BW: 20MHz)	1RB	Front	18900	1880.0	4.950	0.059	100	1.00	23.04	23.50	1.112	0.066
		Back	18900	1880.0	3.980	0.082	100	1.00	23.04	23.50	1.112	0.091
		Left	18900	1880.0	-0.350	0.033	100	1.00	23.04	23.50	1.112	0.037
		Right	18900	1880.0	1.490	0.017	100	1.00	23.04	23.50	1.112	0.019
		Top	18900	1880.0	-0.690	0.045	100	1.00	23.04	23.50	1.112	0.050
		Bottom	18900	1880.0	-1.830	0.016	100	1.00	23.04	23.50	1.112	0.018
	50%RB	Front	18900	1880.0	2.730	0.037	100	1.00	23.04	23.50	1.112	0.041
		Back	18900	1880.0	-3.740	0.049	100	1.00	23.04	23.50	1.112	0.054
		Left	18900	1880.0	4.560	0.020	100	1.00	23.04	23.50	1.112	0.022
		Right	18900	1880.0	4.650	0.011	100	1.00	23.04	23.50	1.112	0.012
		Top	18900	1880.0	-2.200	0.026	100	1.00	23.04	23.50	1.112	0.029
		Bottom	18900	1880.0	-1.150	0.009	100	1.00	23.04	23.50	1.112	0.010

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
2-n78 (BW: 20MHz)	1RB	Left Cheek	18900	1880.0	3.960	0.895	100	1.00	22.76	23.00	1.057	0.946
		Left Tilt	18900	1880.0	-1.580	0.439	100	1.00	22.76	23.00	1.057	0.464
		Right Cheek	18900	1880.0	-4.060	0.964	100	1.00	22.76	23.00	1.057	1.019
		Right Tilt	18900	1880.0	-0.160	0.526	100	1.00	22.76	23.00	1.057	0.556
	50%RB	Left Cheek	18900	1880.0	1.390	0.623	100	1.00	22.76	23.00	1.057	0.658
		Left Tilt	18900	1880.0	-0.120	0.341	100	1.00	22.76	23.00	1.057	0.360
		Right Cheek	18900	1880.0	0.030	0.652	100	1.00	22.76	23.00	1.057	0.689
		Right Tilt	18900	1880.0	-0.200	0.386	100	1.00	22.76	23.00	1.057	0.408
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
2-n78 (BW: 20MHz)	1RB	Front	18900	1880.0	-1.570	0.297	100	1.00	22.76	23.00	1.057	0.314
		Back	18900	1880.0	-2.650	0.330	100	1.00	22.76	23.00	1.057	0.349
		Left	18900	1880.0	0.860	0.236	100	1.00	22.76	23.00	1.057	0.249
		Right	18900	1880.0	3.750	0.025	100	1.00	22.76	23.00	1.057	0.026
		Top	18900	1880.0	3.230	0.173	100	1.00	22.76	23.00	1.057	0.183
		Bottom	18900	1880.0	1.250	0.015	100	1.00	22.76	23.00	1.057	0.016
	50%RB	Front	18900	1880.0	3.830	0.195	100	1.00	22.76	23.00	1.057	0.206
		Back	18900	1880.0	-1.030	0.249	100	1.00	22.76	23.00	1.057	0.263
		Left	18900	1880.0	0.130	0.127	100	1.00	22.76	23.00	1.057	0.134
		Right	18900	1880.0	-3.310	0.017	100	1.00	22.76	23.00	1.057	0.018
		Top	18900	1880.0	-3.160	0.162	100	1.00	22.76	23.00	1.057	0.171
		Bottom	18900	1880.0	1.230	0.013	100	1.00	22.76	23.00	1.057	0.014

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
4-n7 (BW: 20MHz)	1RB	Left Cheek	20375	1752.5	-0.640	0.524	100	1.00	21.98	22.00	1.005	0.526
		Left Tilt	20375	1752.5	-3.440	0.873	100	1.00	21.98	22.00	1.005	0.877
		Right Cheek	20375	1752.5	-0.580	0.685	100	1.00	21.98	22.00	1.005	0.688
		Right Tilt	20375	1752.5	3.320	0.920	100	1.00	21.98	22.00	1.005	0.924
	50%RB	Left Cheek	20375	1752.5	4.760	0.267	100	1.00	21.98	22.00	1.005	0.268
		Left Tilt	20375	1752.5	0.860	0.445	100	1.00	21.98	22.00	1.005	0.447
		Right Cheek	20375	1752.5	-0.440	0.392	100	1.00	21.98	22.00	1.005	0.394
		Right Tilt	20375	1752.5	-3.930	0.537	100	1.00	21.98	22.00	1.005	0.539
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
4-n7 (BW: 20MHz)	1RB	Front	20375	1752.5	3.970	0.346	100	1.00	21.98	22.00	1.005	0.348
		Back	20375	1752.5	-0.530	0.518	100	1.00	21.98	22.00	1.005	0.520
		Left	20375	1752.5	-2.580	0.293	100	1.00	21.98	22.00	1.005	0.294
		Right	20375	1752.5	3.110	0.031	100	1.00	21.98	22.00	1.005	0.031
		Top	20375	1752.5	1.240	0.195	100	1.00	21.98	22.00	1.005	0.196
		Bottom	20375	1752.5	-4.680	0.017	100	1.00	21.98	22.00	1.005	0.017
	50%RB	Front	20375	1752.5	1.300	0.207	100	1.00	21.98	22.00	1.005	0.208
		Back	20375	1752.5	-4.950	0.345	100	1.00	21.98	22.00	1.005	0.347
		Left	20375	1752.5	-0.910	0.149	100	1.00	21.98	22.00	1.005	0.150
		Right	20375	1752.5	4.440	0.020	100	1.00	21.98	22.00	1.005	0.020
		Top	20375	1752.5	-3.560	0.117	100	1.00	21.98	22.00	1.005	0.118
		Bottom	20375	1752.5	0.400	0.013	100	1.00	21.98	22.00	1.005	0.013

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
4-n41 (BW: 20MHz)	1RB	Left Cheek	20175	1732.5	1.420	0.739	100	1.00	21.76	22.00	1.057	0.781
		Left Tilt	20175	1732.5	0.370	0.428	100	1.00	21.76	22.00	1.057	0.452
		Right Cheek	20175	1732.5	-1.320	0.884	100	1.00	21.76	22.00	1.057	0.934
		Right Tilt	20175	1732.5	0.190	0.466	100	1.00	21.76	22.00	1.057	0.492
	50%RB	Left Cheek	20175	1732.5	-3.910	0.393	100	1.00	21.76	22.00	1.057	0.415
		Left Tilt	20175	1732.5	-3.370	0.241	100	1.00	21.76	22.00	1.057	0.255
		Right Cheek	20175	1732.5	4.310	0.442	100	1.00	21.76	22.00	1.057	0.467
		Right Tilt	20175	1732.5	-0.570	0.295	100	1.00	21.76	22.00	1.057	0.312
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
4-n41 (BW: 20MHz)	1RB	Front	20175	1732.5	0.440	0.226	100	1.00	21.76	22.00	1.057	0.239
		Back	20175	1732.5	-1.680	0.289	100	1.00	21.76	22.00	1.057	0.305
		Left	20175	1732.5	4.810	0.151	100	1.00	21.76	22.00	1.057	0.160
		Right	20175	1732.5	-0.850	0.023	100	1.00	21.76	22.00	1.057	0.024
		Top	20175	1732.5	-0.530	0.102	100	1.00	21.76	22.00	1.057	0.108
		Bottom	20175	1732.5	0.110	0.017	100	1.00	21.76	22.00	1.057	0.018
	50%RB	Front	20175	1732.5	1.760	0.142	100	1.00	21.76	22.00	1.057	0.150
		Back	20175	1732.5	-4.100	0.195	100	1.00	21.76	22.00	1.057	0.206
		Left	20175	1732.5	-2.420	0.096	100	1.00	21.76	22.00	1.057	0.101
		Right	20175	1732.5	2.880	0.016	100	1.00	21.76	22.00	1.057	0.017
		Top	20175	1732.5	2.900	0.069	100	1.00	21.76	22.00	1.057	0.073
		Bottom	20175	1732.5	-4.510	0.013	100	1.00	21.76	22.00	1.057	0.014

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
4-n78 (BW: 20MHz)	1RB	Left Cheek	20175	1732.5	2.660	0.779	100	1.00	22.62	23.00	1.091	0.850
		Left Tilt	20175	1732.5	-3.380	0.652	100	1.00	22.62	23.00	1.091	0.712
		Right Cheek	20175	1732.5	2.300	0.834	100	1.00	22.62	23.00	1.091	0.910
		Right Tilt	20175	1732.5	1.270	0.669	100	1.00	22.62	23.00	1.091	0.730
	50%RB	Left Cheek	20175	1732.5	-3.510	0.439	100	1.00	22.62	23.00	1.091	0.479
		Left Tilt	20175	1732.5	0.430	0.314	100	1.00	22.62	23.00	1.091	0.343
		Right Cheek	20175	1732.5	-3.930	0.496	100	1.00	22.62	23.00	1.091	0.541
		Right Tilt	20175	1732.5	2.560	0.378	100	1.00	22.62	23.00	1.091	0.413
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
4-n78 (BW: 20MHz)	1RB	Front	20175	1732.5	-0.730	0.256	100	1.00	22.62	23.00	1.091	0.279
		Back	20175	1732.5	1.460	0.313	100	1.00	22.62	23.00	1.091	0.342
		Left	20175	1732.5	3.770	0.183	100	1.00	22.62	23.00	1.091	0.200
		Right	20175	1732.5	0.150	0.039	100	1.00	22.62	23.00	1.091	0.043
		Top	20175	1732.5	-0.980	0.130	100	1.00	22.62	23.00	1.091	0.142
		Bottom	20175	1732.5	1.460	0.025	100	1.00	22.62	23.00	1.091	0.027
	50%RB	Front	20175	1732.5	0.080	0.195	100	1.00	22.62	23.00	1.091	0.213
		Back	20175	1732.5	-0.700	0.239	100	1.00	22.62	23.00	1.091	0.261
		Left	20175	1732.5	1.040	0.127	100	1.00	22.62	23.00	1.091	0.139
		Right	20175	1732.5	-2.320	0.023	100	1.00	22.62	23.00	1.091	0.025
		Top	20175	1732.5	-4.920	0.089	100	1.00	22.62	23.00	1.091	0.097
		Bottom	20175	1732.5	0.720	0.016	100	1.00	22.62	23.00	1.091	0.017

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n7 (BW: 10MHz)	1RB	Left Cheek	20625	846.5	-3.240	0.041	100	1.00	23.16	23.50	1.081	0.044
		Left Tilt	20625	846.5	2.260	0.069	100	1.00	23.16	23.50	1.081	0.075
		Right Cheek	20625	846.5	1.930	0.046	100	1.00	23.16	23.50	1.081	0.050
		Right Tilt	20625	846.5	4.580	0.086	100	1.00	23.16	23.50	1.081	0.093
	50%RB	Left Cheek	20625	846.5	-4.230	0.034	100	1.00	23.16	23.50	1.081	0.037
		Left Tilt	20625	846.5	-1.250	0.051	100	1.00	23.16	23.50	1.081	0.055
		Right Cheek	20625	846.5	1.360	0.041	100	1.00	23.16	23.50	1.081	0.044
		Right Tilt	20625	846.5	-4.120	0.063	100	1.00	23.16	23.50	1.081	0.068
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n7 (BW: 10MHz)	1RB	Front	20625	846.5	-1.150	0.049	100	1.00	23.16	23.50	1.081	0.053
		Back	20625	846.5	4.800	0.052	100	1.00	23.16	23.50	1.081	0.056
		Left	20625	846.5	-3.530	0.025	100	1.00	23.16	23.50	1.081	0.027
		Right	20625	846.5	2.960	0.017	100	1.00	23.16	23.50	1.081	0.018
		Top	20625	846.5	-4.730	0.033	100	1.00	23.16	23.50	1.081	0.036
		Bottom	20625	846.5	2.400	0.011	100	1.00	23.16	23.50	1.081	0.012
	50%RB	Front	20625	846.5	1.150	0.041	100	1.00	23.16	23.50	1.081	0.044
		Back	20625	846.5	-4.800	0.043	100	1.00	23.16	23.50	1.081	0.047
		Left	20625	846.5	-3.520	0.017	100	1.00	23.16	23.50	1.081	0.018
		Right	20625	846.5	-1.210	0.011	100	1.00	23.16	23.50	1.081	0.012
		Top	20625	846.5	1.160	0.013	100	1.00	23.16	23.50	1.081	0.014
		Bottom	20625	846.5	-0.160	0.008	100	1.00	23.16	23.50	1.081	0.009

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n38 (BW: 10MHz)	1RB	Left Cheek	20625	846.5	-0.280	0.376	100	1.00	23.37	23.50	1.030	0.387
		Left Tilt	20625	846.5	2.290	0.247	100	1.00	23.37	23.50	1.030	0.255
		Right Cheek	20625	846.5	4.130	0.269	100	1.00	23.37	23.50	1.030	0.277
		Right Tilt	20625	846.5	1.070	0.215	100	1.00	23.37	23.50	1.030	0.222
	50%RB	Left Cheek	20625	846.5	0.540	0.259	100	1.00	23.37	23.50	1.030	0.267
		Left Tilt	20625	846.5	-2.510	0.167	100	1.00	23.37	23.50	1.030	0.172
		Right Cheek	20625	846.5	-2.280	0.224	100	1.00	23.37	23.50	1.030	0.231
		Right Tilt	20625	846.5	-0.670	0.118	100	1.00	23.37	23.50	1.030	0.122
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n38 (BW: 10MHz)	1RB	Front	20625	846.5	2.760	0.174	100	1.00	23.37	23.50	1.030	0.179
		Back	20625	846.5	-4.750	0.247	100	1.00	23.37	23.50	1.030	0.255
		Left	20625	846.5	0.840	0.128	100	1.00	23.37	23.50	1.030	0.132
		Right	20625	846.5	-1.130	0.015	100	1.00	23.37	23.50	1.030	0.015
		Top	20625	846.5	3.660	0.101	100	1.00	23.37	23.50	1.030	0.104
		Bottom	20625	846.5	-1.170	0.009	100	1.00	23.37	23.50	1.030	0.009
	50%RB	Front	20625	846.5	1.550	0.089	100	1.00	23.37	23.50	1.030	0.092
		Back	20625	846.5	0.310	0.131	100	1.00	23.37	23.50	1.030	0.135
		Left	20625	846.5	-0.980	0.065	100	1.00	23.37	23.50	1.030	0.067
		Right	20625	846.5	-1.550	1.510	0.009	100	1.00	23.37	23.50	1.030
		Top	20625	846.5	2.800	-2.790	0.057	100	1.00	23.37	23.50	1.030
		Bottom	20625	846.5	1.430	-3.800	0.004	100	1.00	23.37	23.50	1.030

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n41 (BW: 10MHz)	1RB	Left Cheek	20525	836.5	3.940	0.370	100	1.00	23.26	23.50	1.057	0.391
		Left Tilt	20525	836.5	-2.470	0.127	100	1.00	23.26	23.50	1.057	0.134
		Right Cheek	20525	836.5	1.410	0.451	100	1.00	23.26	23.50	1.057	0.477
		Right Tilt	20525	836.5	4.470	0.213	100	1.00	23.26	23.50	1.057	0.225
	50%RB	Left Cheek	20525	836.5	-1.150	0.329	100	1.00	23.26	23.50	1.057	0.348
		Left Tilt	20525	836.5	-0.080	0.118	100	1.00	23.26	23.50	1.057	0.125
		Right Cheek	20525	836.5	4.280	0.403	100	1.00	23.26	23.50	1.057	0.426
		Right Tilt	20525	836.5	-2.410	0.175	100	1.00	23.26	23.50	1.057	0.185
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n41 (BW: 10MHz)	1RB	Front	20525	836.5	-0.170	0.205	100	1.00	23.26	23.50	1.057	0.217
		Back	20525	836.5	-2.660	0.248	100	1.00	23.26	23.50	1.057	0.262
		Left	20525	836.5	1.350	0.136	100	1.00	23.26	23.50	1.057	0.144
		Right	20525	836.5	-3.600	0.036	100	1.00	23.26	23.50	1.057	0.038
		Top	20525	836.5	-1.300	0.102	100	1.00	23.26	23.50	1.057	0.108
		Bottom	20525	836.5	1.060	0.027	100	1.00	23.26	23.50	1.057	0.029
	50%RB	Front	20525	836.5	-3.400	0.107	100	1.00	23.26	23.50	1.057	0.113
		Back	20525	836.5	-0.300	0.143	100	1.00	23.26	23.50	1.057	0.151
		Left	20525	836.5	3.980	0.079	100	1.00	23.26	23.50	1.057	0.083
		Right	20525	836.5	0.520	0.018	100	1.00	23.26	23.50	1.057	0.019
		Top	20525	836.5	-1.560	0.020	100	1.00	23.26	23.50	1.057	0.021
		Bottom	20525	836.5	2.940	0.014	100	1.00	23.26	23.50	1.057	0.015

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n66 (BW: 10MHz)	1RB	Left Cheek	20525	836.5	3.490	0.475	100	1.00	23.32	23.50	1.042	0.495
		Left Tilt	20525	836.5	-0.640	0.673	100	1.00	23.32	23.50	1.042	0.701
		Right Cheek	20525	836.5	2.580	0.442	100	1.00	23.32	23.50	1.042	0.461
		Right Tilt	20525	836.5	-0.680	0.626	100	1.00	23.32	23.50	1.042	0.652
	50%RB	Left Cheek	20525	836.5	0.200	0.286	100	1.00	23.32	23.50	1.042	0.298
		Left Tilt	20525	836.5	-2.790	0.349	100	1.00	23.32	23.50	1.042	0.364
		Right Cheek	20525	836.5	2.600	0.243	100	1.00	23.32	23.50	1.042	0.253
		Right Tilt	20525	836.5	-3.170	0.307	100	1.00	23.32	23.50	1.042	0.320
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n66 (BW: 10MHz)	1RB	Front	20525	836.5	4.820	0.211	100	1.00	23.32	23.50	1.042	0.220
		Back	20525	836.5	1.010	0.274	100	1.00	23.32	23.50	1.042	0.286
		Left	20525	836.5	-0.880	0.163	100	1.00	23.32	23.50	1.042	0.170
		Right	20525	836.5	0.810	0.017	100	1.00	23.32	23.50	1.042	0.018
		Top	20525	836.5	-4.410	0.114	100	1.00	23.32	23.50	1.042	0.119
		Bottom	20525	836.5	4.430	0.012	100	1.00	23.32	23.50	1.042	0.013
	50%RB	Front	20525	836.5	1.220	0.113	100	1.00	23.32	23.50	1.042	0.118
		Back	20525	836.5	-1.970	0.165	100	1.00	23.32	23.50	1.042	0.172
		Left	20525	836.5	0.380	0.082	100	1.00	23.32	23.50	1.042	0.085
		Right	20525	836.5	-4.860	0.006	100	1.00	23.32	23.50	1.042	0.006
		Top	20525	836.5	1.950	0.054	100	1.00	23.32	23.50	1.042	0.056
		Bottom	20525	836.5	-0.260	0.005	100	1.00	23.32	23.50	1.042	0.005

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n77 (BW: 10MHz)	1RB	Left Cheek	20450	829.0	4.000	0.383	100	1.00	22.90	23.00	1.023	0.392
		Left Tilt	20450	829.0	-3.360	0.207	100	1.00	22.90	23.00	1.023	0.212
		Right Cheek	20450	829.0	1.000	0.286	100	1.00	22.90	23.00	1.023	0.293
		Right Tilt	20450	829.0	4.460	0.172	100	1.00	22.90	23.00	1.023	0.176
	50%RB	Left Cheek	20450	829.0	2.320	0.267	100	1.00	22.90	23.00	1.023	0.273
		Left Tilt	20450	829.0	-3.030	0.152	100	1.00	22.90	23.00	1.023	0.156
		Right Cheek	20450	829.0	-1.780	0.231	100	1.00	22.90	23.00	1.023	0.236
		Right Tilt	20450	829.0	0.480	0.119	100	1.00	22.90	23.00	1.023	0.122
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n77 (BW: 10MHz)	1RB	Front	20450	829.0	-1.960	0.216	100	1.00	22.90	23.00	1.023	0.221
		Back	20450	829.0	-4.010	0.247	100	1.00	22.90	23.00	1.023	0.253
		Left	20450	829.0	-2.360	0.188	100	1.00	22.90	23.00	1.023	0.192
		Right	20450	829.0	0.780	0.025	100	1.00	22.90	23.00	1.023	0.026
		Top	20450	829.0	2.100	0.136	100	1.00	22.90	23.00	1.023	0.139
		Bottom	20450	829.0	0.960	0.015	100	1.00	22.90	23.00	1.023	0.015
	50%RB	Front	20450	829.0	2.610	0.124	100	1.00	22.90	23.00	1.023	0.127
		Back	20450	829.0	1.920	0.182	100	1.00	22.90	23.00	1.023	0.186
		Left	20450	829.0	-0.900	0.106	100	1.00	22.90	23.00	1.023	0.108
		Right	20450	829.0	-0.610	0.011	100	1.00	22.90	23.00	1.023	0.011
		Top	20450	829.0	0.440	0.081	100	1.00	22.90	23.00	1.023	0.083
		Bottom	20450	829.0	-2.350	0.007	100	1.00	22.90	23.00	1.023	0.007

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n78 (BW: 10MHz)	1RB	Left Cheek	20450	829.0	-0.770	0.391	100	1.00	22.94	23.00	1.014	0.396
		Left Tilt	20450	829.0	3.350	0.194	100	1.00	22.94	23.00	1.014	0.197
		Right Cheek	20450	829.0	1.680	0.339	100	1.00	22.94	23.00	1.014	0.344
		Right Tilt	20450	829.0	4.610	0.175	100	1.00	22.94	23.00	1.014	0.177
	50%RB	Left Cheek	20450	829.0	4.070	0.269	100	1.00	22.94	23.00	1.014	0.273
		Left Tilt	20450	829.0	-2.970	0.117	100	1.00	22.94	23.00	1.014	0.119
		Right Cheek	20450	829.0	2.660	0.248	100	1.00	22.94	23.00	1.014	0.251
		Right Tilt	20450	829.0	3.100	0.095	100	1.00	22.94	23.00	1.014	0.096
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
5-n78 (BW: 10MHz)	1RB	Front	20450	829.0	1.880	0.201	100	1.00	22.94	23.00	1.014	0.204
		Back	20450	829.0	0.760	0.246	100	1.00	22.94	23.00	1.014	0.249
		Left	20450	829.0	-0.800	0.154	100	1.00	22.94	23.00	1.014	0.156
		Right	20450	829.0	0.260	0.030	100	1.00	22.94	23.00	1.014	0.030
		Top	20450	829.0	0.440	0.102	100	1.00	22.94	23.00	1.014	0.103
		Bottom	20450	829.0	-4.270	0.019	100	1.00	22.94	23.00	1.014	0.019
	50%RB	Front	20450	829.0	-2.740	0.082	100	1.00	22.94	23.00	1.014	0.083
		Back	20450	829.0	4.550	0.137	100	1.00	22.94	23.00	1.014	0.139
		Left	20450	829.0	-1.780	0.052	100	1.00	22.94	23.00	1.014	0.053
		Right	20450	829.0	0.310	0.017	100	1.00	22.94	23.00	1.014	0.017
		Top	20450	829.0	1.620	0.046	100	1.00	22.94	23.00	1.014	0.047
		Bottom	20450	829.0	-0.640	0.006	100	1.00	22.94	23.00	1.014	0.006

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
7-n7 (BW: 20MHz)	1RB	Left Cheek	21425	2567.5	4.850	0.873	100	1.00	22.64	23.00	1.086	0.948
		Left Tilt	21425	2567.5	-2.700	0.623	100	1.00	22.64	23.00	1.086	0.677
		Right Cheek	21425	2567.5	3.650	0.956	100	1.00	22.64	23.00	1.086	1.039
		Right Tilt	21425	2567.5	-1.320	0.679	100	1.00	22.64	23.00	1.086	0.738
	50%RB	Left Cheek	21425	2567.5	1.800	0.438	100	1.00	22.64	23.00	1.086	0.476
		Left Tilt	21425	2567.5	-4.190	0.324	100	1.00	22.64	23.00	1.086	0.352
		Right Cheek	21425	2567.5	-2.250	0.627	100	1.00	22.64	23.00	1.086	0.681
		Right Tilt	21425	2567.5	-3.630	0.395	100	1.00	22.64	23.00	1.086	0.429
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
7-n7 (BW: 20MHz)	1RB	Front	21425	2567.5	0.070	0.415	100	1.00	22.64	23.00	1.086	0.451
		Back	21425	2567.5	-3.320	0.469	100	1.00	22.64	23.00	1.086	0.510
		Left	21425	2567.5	1.100	0.263	100	1.00	22.64	23.00	1.086	0.286
		Right	21425	2567.5	-0.410	0.067	100	1.00	22.64	23.00	1.086	0.073
		Top	21425	2567.5	1.750	0.292	100	1.00	22.64	23.00	1.086	0.317
		Bottom	21425	2567.5	-3.030	0.046	100	1.00	22.64	23.00	1.086	0.050
	50%RB	Front	21425	2567.5	4.460	0.258	100	1.00	22.64	23.00	1.086	0.280
		Back	21425	2567.5	-1.370	0.349	100	1.00	22.64	23.00	1.086	0.379
		Left	21425	2567.5	4.510	0.164	100	1.00	22.64	23.00	1.086	0.178
		Right	21425	2567.5	-2.100	0.043	100	1.00	22.64	23.00	1.086	0.047
		Top	21425	2567.5	-1.750	0.207	100	1.00	22.64	23.00	1.086	0.225
		Bottom	21425	2567.5	2.710	0.026	100	1.00	22.64	23.00	1.086	0.028

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
7-n66 (BW: 20MHz)	1RB	Left Cheek	21100	2535.0	-3.430	0.755	100	1.00	21.11	21.50	1.094	0.826
		Left Tilt	21100	2535.0	2.170	0.429	100	1.00	21.11	21.50	1.094	0.469
		Right Cheek	21100	2535.0	-3.780	0.896	100	1.00	21.11	21.50	1.094	0.980
		Right Tilt	21100	2535.0	3.910	0.607	100	1.00	21.11	21.50	1.094	0.664
	50%RB	Left Cheek	21100	2535.0	-0.260	0.462	100	1.00	21.11	21.50	1.094	0.505
		Left Tilt	21100	2535.0	3.300	0.254	100	1.00	21.11	21.50	1.094	0.278
		Right Cheek	21100	2535.0	-2.200	0.627	100	1.00	21.11	21.50	1.094	0.686
		Right Tilt	21100	2535.0	1.000	0.395	100	1.00	21.11	21.50	1.094	0.432
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
7-n66 (BW: 20MHz)	1RB	Front	21100	2535.0	-1.880	0.495	100	1.00	21.11	21.50	1.094	0.542
		Back	21100	2535.0	4.040	0.607	100	1.00	21.11	21.50	1.094	0.664
		Left	21100	2535.0	-0.800	0.248	100	1.00	21.11	21.50	1.094	0.271
		Right	21100	2535.0	4.090	0.031	100	1.00	21.11	21.50	1.094	0.034
		Top	21100	2535.0	-0.370	0.296	100	1.00	21.11	21.50	1.094	0.324
		Bottom	21100	2535.0	2.190	0.022	100	1.00	21.11	21.50	1.094	0.024
	50%RB	Front	21100	2535.0	4.730	0.316	100	1.00	21.11	21.50	1.094	0.346
		Back	21100	2535.0	-2.100	0.457	100	1.00	21.11	21.50	1.094	0.500
		Left	21100	2535.0	-0.130	0.112	100	1.00	21.11	21.50	1.094	0.123
		Right	21100	2535.0	2.710	0.018	100	1.00	21.11	21.50	1.094	0.020
		Top	21100	2535.0	2.460	0.143	100	1.00	21.11	21.50	1.094	0.156
		Bottom	21100	2535.0	-2.540	0.011	100	1.00	21.11	21.50	1.094	0.012

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
7-n77 (BW: 20MHz)	1RB	Left Cheek	21100	2535.0	-0.490	0.896	100	1.00	22.78	23.00	1.052	0.943
		Left Tilt	21100	2535.0	4.720	0.469	100	1.00	22.78	23.00	1.052	0.493
		Right Cheek	21100	2535.0	4.840	0.953	100	1.00	22.78	23.00	1.052	1.003
		Right Tilt	21100	2535.0	-2.370	0.567	100	1.00	22.78	23.00	1.052	0.596
	50%RB	Left Cheek	21100	2535.0	4.390	0.569	100	1.00	22.78	23.00	1.052	0.599
		Left Tilt	21100	2535.0	4.950	0.371	100	1.00	22.78	23.00	1.052	0.390
		Right Cheek	21100	2535.0	-0.860	0.652	100	1.00	22.78	23.00	1.052	0.686
		Right Tilt	21100	2535.0	-0.660	0.432	100	1.00	22.78	23.00	1.052	0.454
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
7-n77 (BW: 20MHz)	1RB	Front	21100	2535.0	1.940	0.402	100	1.00	22.78	23.00	1.052	0.423
		Back	21100	2535.0	0.170	0.498	100	1.00	22.78	23.00	1.052	0.524
		Left	21100	2535.0	-0.130	0.195	100	1.00	22.78	23.00	1.052	0.205
		Right	21100	2535.0	3.390	0.037	100	1.00	22.78	23.00	1.052	0.039
		Top	21100	2535.0	4.170	0.274	100	1.00	22.78	23.00	1.052	0.288
		Bottom	21100	2535.0	-0.190	0.023	100	1.00	22.78	23.00	1.052	0.024
	50%RB	Front	21100	2535.0	2.350	0.246	100	1.00	22.78	23.00	1.052	0.259
		Back	21100	2535.0	-0.820	0.294	100	1.00	22.78	23.00	1.052	0.309
		Left	21100	2535.0	-4.700	0.117	100	1.00	22.78	23.00	1.052	0.123
		Right	21100	2535.0	2.820	0.025	100	1.00	22.78	23.00	1.052	0.026
		Top	21100	2535.0	-3.590	0.131	100	1.00	22.78	23.00	1.052	0.138
		Bottom	21100	2535.0	4.740	0.019	100	1.00	22.78	23.00	1.052	0.020

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
7-n78 (BW: 20MHz)	1RB	Left Cheek	20775	2502.5	-4.000	0.852	100	1.00	22.75	23.00	1.059	0.902
		Left Tilt	20775	2502.5	-0.020	0.498	100	1.00	22.75	23.00	1.059	0.528
		Right Cheek	20775	2502.5	4.390	0.986	100	1.00	22.75	23.00	1.059	1.044
		Right Tilt	20775	2502.5	3.990	0.674	100	1.00	22.75	23.00	1.059	0.714
	50%RB	Left Cheek	20775	2502.5	-4.760	0.469	100	1.00	22.75	23.00	1.059	0.497
		Left Tilt	20775	2502.5	-0.250	0.357	100	1.00	22.75	23.00	1.059	0.378
		Right Cheek	20775	2502.5	1.440	0.678	100	1.00	22.75	23.00	1.059	0.718
		Right Tilt	20775	2502.5	-4.900	0.412	100	1.00	22.75	23.00	1.059	0.436
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
7-n78 (BW: 20MHz)	1RB	Front	20775	2502.5	-1.570	0.396	100	1.00	22.75	23.00	1.059	0.419
		Back	20775	2502.5	3.820	0.479	100	1.00	22.75	23.00	1.059	0.507
		Left	20775	2502.5	-2.460	0.207	100	1.00	22.75	23.00	1.059	0.219
		Right	20775	2502.5	3.230	0.036	100	1.00	22.75	23.00	1.059	0.038
		Top	20775	2502.5	-3.890	0.285	100	1.00	22.75	23.00	1.059	0.302
		Bottom	20775	2502.5	4.370	0.024	100	1.00	22.75	23.00	1.059	0.025
	50%RB	Front	20775	2502.5	-2.040	0.253	100	1.00	22.75	23.00	1.059	0.268
		Back	20775	2502.5	0.360	0.348	100	1.00	22.75	23.00	1.059	0.369
		Left	20775	2502.5	-2.200	0.119	100	1.00	22.75	23.00	1.059	0.126
		Right	20775	2502.5	3.750	0.022	100	1.00	22.75	23.00	1.059	0.023
		Top	20775	2502.5	-4.010	0.154	100	1.00	22.75	23.00	1.059	0.163
		Bottom	20775	2502.5	-4.850	0.013	100	1.00	22.75	23.00	1.059	0.014

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
38-n78 (BW: 20MHz)	1RB	Left Cheek	37775	2572.5	0.710	0.407	100	1.00	22.65	23.00	1.084	0.441
		Left Tilt	37775	2572.5	4.230	0.250	100	1.00	22.65	23.00	1.084	0.271
		Right Cheek	37775	2572.5	2.820	0.477	100	1.00	22.65	23.00	1.084	0.517
		Right Tilt	37775	2572.5	-4.670	0.295	100	1.00	22.65	23.00	1.084	0.320
	50%RB	Left Cheek	37775	2572.5	-2.940	0.224	100	1.00	22.65	23.00	1.084	0.243
		Left Tilt	37775	2572.5	-2.150	0.165	100	1.00	22.65	23.00	1.084	0.179
		Right Cheek	37775	2572.5	-0.050	0.262	100	1.00	22.65	23.00	1.084	0.284
		Right Tilt	37775	2572.5	-4.090	0.207	100	1.00	22.65	23.00	1.084	0.224
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
38-n78 (BW: 20MHz)	1RB	Front	37775	2572.5	3.140	0.058	100	1.00	22.65	23.00	1.084	0.063
		Back	37775	2572.5	2.160	0.111	100	1.00	22.65	23.00	1.084	0.120
		Left	37775	2572.5	3.980	0.043	100	1.00	22.65	23.00	1.084	0.047
		Right	37775	2572.5	-2.800	0.019	100	1.00	22.65	23.00	1.084	0.021
		Top	37775	2572.5	-4.780	0.047	100	1.00	22.65	23.00	1.084	0.051
		Bottom	37775	2572.5	-3.760	0.013	100	1.00	22.65	23.00	1.084	0.014
	50%RB	Front	37775	2572.5	-2.520	0.046	100	1.00	22.65	23.00	1.084	0.050
		Back	37775	2572.5	-0.810	0.089	100	1.00	22.65	23.00	1.084	0.096
		Left	37775	2572.5	-3.220	0.024	100	1.00	22.65	23.00	1.084	0.026
		Right	37775	2572.5	3.250	0.011	100	1.00	22.65	23.00	1.084	0.012
		Top	37775	2572.5	-0.200	0.029	100	1.00	22.65	23.00	1.084	0.031
		Bottom	37775	2572.5	-2.210	0.010	100	1.00	22.65	23.00	1.084	0.011

Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
41-n41 (BW: 20MHz)	1RB	Left Cheek	40620	2593.0	2.120	0.258	100	1.00	23.88	24.00	1.028	0.265
		Left Tilt	40620	2593.0	-4.300	0.196	100	1.00	23.88	24.00	1.028	0.201
		Right Cheek	40620	2593.0	-3.350	0.375	100	1.00	23.88	24.00	1.028	0.386
		Right Tilt	40620	2593.0	3.190	0.285	100	1.00	23.88	24.00	1.028	0.293
	50%RB	Left Cheek	40620	2593.0	-2.690	0.173	100	1.00	23.88	24.00	1.028	0.178
		Left Tilt	40620	2593.0	4.820	0.159	100	1.00	23.88	24.00	1.028	0.163
		Right Cheek	40620	2593.0	-0.390	0.243	100	1.00	23.88	24.00	1.028	0.250
		Right Tilt	40620	2593.0	3.910	0.184	100	1.00	23.88	24.00	1.028	0.189
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)
41-n41 (BW: 20MHz)	1RB	Front	40620	2593.0	-2.190	0.086	100	1.00	23.88	24.00	1.028	0.088
		Back	40620	2593.0	-0.600	0.115	100	1.00	23.88	24.00	1.028	0.118
		Left	40620	2593.0	-0.350	0.067	100	1.00	23.88	24.00	1.028	0.069
		Right	40620	2593.0	-4.410	0.023	100	1.00	23.88	24.00	1.028	0.024
		Top	40620	2593.0	-4.850	0.069	100	1.00	23.88	24.00	1.028	0.071
		Bottom	40620	2593.0	0.310	0.015	100	1.00	23.88	24.00	1.028	0.015
	50%RB	Front	40620	2593.0	-3.370	0.043	100	1.00	23.88	24.00	1.028	0.044
		Back	40620	2593.0	-1.540	0.068	100	1.00	23.88	24.00	1.028	0.070
		Left	40620	2593.0	3.250	0.034	100	1.00	23.88	24.00	1.028	0.035
		Right	40620	2593.0	2.180	0.013	100	1.00	23.88	24.00	1.028	0.013
		Top	40620	2593.0	-2.770	0.037	100	1.00	23.88	24.00	1.028	0.038
		Bottom	40620	2593.0	3.490	0.010	100	1.00	23.88	24.00	1.028	0.010