

RF TEST REPORT



Report No.: 16070785-FCC-R

Supersede Report No.: N/A

Applicant	SHENZHEN BESTVIEW ELECTRONICS CO., LIMITED	
Product Name	DVD/MP3G/CDG KARAOKE & BLUETOOTH MEDIA PLAYER	
Model No.	GF842	
Serial No.	GF829S;GF839.GF839S;GF840;GF840S;GF842S;GF845; GF846;GF847;GF848.GF755;GF756;GF758;GF758S;GF759; GP975;GP978;GP979;GP980	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	July 02 to 17, 2016	
Issue Date	July 18, 2016	
Test Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only		
Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070785-FCC-R
Page	3 of 61

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT.....	9
6.2 CHANNEL SEPARATION	10
6.3 20DB BANDWIDTH.....	14
6.4 PEAK OUTPUT POWER.....	18
6.5 NUMBER OF HOPPING CHANNEL.....	22
6.6 TIME OF OCCUPANCY (DWELL TIME)	24
6.7 BAND EDGE.....	28
6.8 AC POWER LINE CONDUCTED EMISSIONS.....	36
6.9 RADIATED SPURIOUS EMISSIONS	42
ANNEX A. TEST INSTRUMENT.....	48
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	49
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	56
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	60
ANNEX E. DECLARATION OF SIMILARITY	61

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070785-FCC-R	NONE	Original	July 18, 2016

2. Customer information

Applicant Name	SHENZHEN BESTVIEW ELECTRONICS CO., LIMITED
Applicant Add	6th,1st Building,No.9 Shilong Road,No.2 Shuitian Industrial Zone, Shiyan Town ,Bao'an , Shenzhen,China
Manufacturer	SHENZHEN BESTVIEW ELECTRONICS CO., LIMITED
Manufacturer Add	6th,1st Building,No.9 Shilong Road,No.2 Shuitian Industrial Zone, Shiyan Town ,Bao'an , Shenzhen,China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: DVD/MP3G/CDG KARAOKE & BLUETOOTH MEDIA PLAYER

Main Model: GF842

GF829S;GF839.GF839S;GF840;GF840S;GF842S;GF845;

Serial Model: GF846;GF847;GF848.GF755;GF756;GF758;GF758S;GF759;
GP975;GP978;GP979;GP980

Date EUT received: July 01, 2016

Test Date(s): July 02 to 17, 2016

Equipment Category : DSS

Antenna Gain: 0dBi

Antenna Type: PCB antenna

Type of Modulation: GFSK,π /4DQPSK,8DPSK

RF Operating Frequency (ies): 2402-2480 MHz

Max. Output Power: 0.237dBm

Number of Channels: 79CH

Port: USB Port, Power Port, Microphone Port,Headphone Port,SD Card Port,Audio Port,DISC Port,AUX IN,CD Port

Test Report	16070785-FCC-R
Page	7 of 61

Power requirements: DC 12V/2A

Power Consumption: 25 Watts

Adapter:

Model: RS18-SP1202000

Input: 100-240V~50/60Hz, 0.6Max

Output: 12V,2000mA

Input Power:

Trade Name : Karaoke USA

FCC ID:

2A1ZSGF842

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:

A permanently attached PCB antenna for Bluetooth, the gain is 0dBi for Bluetooth.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	25°C
Relative Humidity	54%
Atmospheric Pressure	1012mbar
Test date :	July 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) \geq 1% of the span - Video (or Average) Bandwidth (VBW) \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot. 		


Remark		
Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail
Test Data	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> N/A
Test Plot	<input checked="" type="checkbox"/> Yes (See below)	<input type="checkbox"/> N/A





Channel Separation measurement result

Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.005	0.747	Pass
	Adjacency Channel	2403			
	Mid Channel	2440			
	Adjacency Channel	2441	1.005	0.772	Pass
	High Channel	2480			
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.005	0.971	Pass
	Adjacency Channel	2403			
	Mid Channel	2440			
	Adjacency Channel	2441	1.005	1.243	Pass
	High Channel	2480			
	Adjacency Channel	2479			
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.005	0.881	Pass
	Adjacency Channel	2403			
	Mid Channel	2440			
	Adjacency Channel	2441	1.005	0.908	Pass
	High Channel	2480			
	Adjacency Channel	2479			

Test Plots

Channel Separation measurement result






8DPSK - High Channel



6.3 20dB Bandwidth

Temperature	25°C
Relative Humidity	54%
Atmospheric Pressure	1012mbar
Test date :	July 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW \geq 1% of the 20 dB bandwidth - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference 		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A


Measurement result

Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.120	0.9470
	Mid	2441	1.158	0.9596
	High	2480	1.191	0.9911
$\pi/4$ DQPSK	Low	2402	1.456	1.2504
	Mid	2441	1.864	1.3177
	High	2480	1.878	1.4015
8DPSK	Low	2402	1.322	1.1994
	Mid	2441	1.362	1.2712
	High	2480	1.361	1.2557

Test Plots

20dB Bandwidth measurement result






6.4 Peak Output Power

Temperature	25°C
Relative Humidity	54%
Atmospheric Pressure	1012mbar
Test date :	July 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with \geq 75 channels: \leq 1 Watt	<input checked="" type="checkbox"/>
	b)	FHSS in 5725-5850MHz: \leq 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: \leq 0.125 Watt.	<input checked="" type="checkbox"/>
	d)	FHSS in 902-928MHz with \geq 50 channels: \leq 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with \geq 25 & $<$ 50 channels: \leq 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: \leq 1 Watt	<input type="checkbox"/>
Test Setup			
Test Procedure		<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW > the 20 dB bandwidth of the emission being measured - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. 	

	<p>- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A





Peak Output Power measurement result

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	-2.885	125	Pass
		Mid	2441	-1.715	125	Pass
		High	2480	-0.848	125	Pass
	$\pi/4$ DQPSK	Low	2402	-1.561	125	Pass
		Mid	2441	-0.683	125	Pass
		High	2480	0.131	125	Pass
	8DPSK	Low	2402	-1.535	125	Pass
		Mid	2441	-0.640	125	Pass
		High	2480	0.237	125	Pass

Test Plots

Output Power measurement result






8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	25°C
Relative Humidity	54%
Atmospheric Pressure	1012mbar
Test date :	July 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable	
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz \geq 15 channels	<input checked="" type="checkbox"/>	
Test Setup				
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <p>The EUT must have its hopping function enabled.</p> <ul style="list-style-type: none"> - Span = the frequency band of operation - RBW \geq 1% of the span - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s). 			
Remark				
Result	<input checked="" type="checkbox"/>	Pass	<input type="checkbox"/>	Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	25°C
Relative Humidity	54%
Atmospheric Pressure	1012mbar
Test date :	July 12, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable	
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	<input checked="" type="checkbox"/>	
Test Setup				
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer</u></p> <ul style="list-style-type: none"> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW \geq RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time 			
Remark				
Result	<input checked="" type="checkbox"/>	Pass	<input type="checkbox"/>	Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A


Dwell Time measurement result




Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	3.060	326.400	400	Pass
		Mid	3.060	326.400	400	Pass
		High	3.105	331.200	400	Pass
	$\pi/4$ DQPSK	Low	3.105	331.200	400	Pass
		Mid	3.082	328.747	400	Pass
		High	3.060	326.400	400	Pass
	8DPSK	Low	3.083	328.853	400	Pass
		Mid	3.060	326.400	400	Pass
		High	3.060	326.400	400	Pass

Note: Dwell time=Pulse Time (ms) \times (1600 \div 6 \div 79) \times 31.6

Test Plots

Dwell Time measurement result






6.7 Band Edge

Temperature	23°C
Relative Humidity	51%
Atmospheric Pressure	1018mbar
Test date :	July 18, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. A Turn Table is positioned on a Ground Plane. An EUT & Support Units is placed on the turn table. A vertical Ant. Tower is mounted on the turn table, with a 3m horizontal distance to the EUT. The Ant. Tower has a 1-4m Variable height adjustment. A Test Receiver is connected to the Ant. Tower to measure the signal. </p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ul style="list-style-type: none"> - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, 		


	<p>and make sure the instrument is operated in its linear range.</p> <ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Plots

GFSK Mode:








GFSK-Left Side-PK


Note: F1 is frequency 2400MHz

GFSK-Right Side-PK





Note: F1 is frequency 2483.5MHz





π /4 DQPSK Mode:

π /4 DQPSK-Hopping Left Side-PK
Note: F1 is frequency 2400MHz
π /4 DQPSK-Hopping Right Side-PK
Note: F1 is frequency 2483.5MHz




8DPSK Mode:


 <p>Test Report: 8DPSK Mode Left Side PK</p> <p>Test Parameters: * RBW 1 MHz, * VBW 3 MHz, SWT 2.5ms, Att 5 dB, Ref 102.0 dBμV</p> <p>Plot Title: M2[1]</p> <p>Plot Data: 46.82 dBμV at 2.377150000 GHz, 61.44 dBμV at 2.400000000 GHz</p> <p>Limit Check: Line Limit-L 74 (PASS), Line Limit-R 74 (PASS)</p> <p>Y-axis: 10 dBμV to 90 dBμV, X-axis: Start 2.31 GHz to Stop 2.44 GHz</p> <p>Date: 18.JUL.2016 20:36:50</p>	 <p>Test Report: 8DPSK Mode Right Side PK</p> <p>Test Parameters: * RBW 1 MHz, * VBW 3 MHz, SWT 2.5ms, Att 5 dB, Ref 102.0 dBμV</p> <p>Plot Title: M1[1]</p> <p>Plot Data: 47.00 dBμV at 2.492510000 GHz</p> <p>Limit Check: Line Limit-L 74 (PASS), Line Limit-R 74 (PASS)</p> <p>Y-axis: 10 dBμV to 90 dBμV, X-axis: Start 2.44 GHz to Stop 2.5 GHz</p> <p>Date: 18.JUL.2016 20:43:52</p>
<p>8DPSK-Hopping Left Side-PK</p> <p>Note: F1 is frequency 2400MHz</p>  <p>Test Report: 8DPSK Hopping Left Side PK</p> <p>Test Parameters: * RBW 1 MHz, * VBW 3 MHz, SWT 2.5ms, Att 5 dB, Ref 102.0 dBμV</p> <p>Plot Title: M2[1]</p> <p>Plot Data: 40.45 dBμV at 2.382340000 GHz, 53.28 dBμV at 2.400000000 GHz</p> <p>Limit Check: Line Limit-L 74 (PASS), Line Limit-R 74 (PASS)</p> <p>Y-axis: 10 dBμV to 90 dBμV, X-axis: Start 2.31 GHz to Stop 2.44 GHz</p> <p>Date: 18.JUL.2016 20:38:00</p>	<p>8DPSK--Hopping Right Side-PK</p> <p>Note: F1 is frequency 2483.5MHz</p>  <p>Test Report: 8DPSK Hopping Right Side PK</p> <p>Test Parameters: * RBW 1 MHz, * VBW 3 MHz, SWT 2.5ms, Att 5 dB, Ref 102.0 dBμV</p> <p>Plot Title: M1[1]</p> <p>Plot Data: 47.00 dBμV at 2.492510000 GHz</p> <p>Limit Check: Line Limit-L 74 (PASS), Line Limit-R 74 (PASS)</p> <p>Y-axis: 10 dBμV to 90 dBμV, X-axis: Start 2.44 GHz to Stop 2.5 GHz</p> <p>Date: 18.JUL.2016 20:43:52</p> <p>Note: (no need if PK value less than the AV limit)</p>
<p>8DPSK--Hopping Left-AV</p>	<p>8DPSK--Hopping Right-AV</p>



6.8 AC Power Line Conducted Emissions

Temperature	23°C
Relative Humidity	51%
Atmospheric Pressure	1018mbar
Test date :	July 18, 2016
Tested By :	Loren Luo


Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15. 207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB μ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB μ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup		 <p>The diagram illustrates the test setup for AC power line conducted emissions. It shows the EUT (Equipment Under Test) connected to a LISN (Line Impedance Stabilization Network) on the left. The LISN is connected to a vertical ground reference plane. The EUT is positioned 40 cm from this plane. To the right of the EUT, there is a horizontal ground reference plane. A test receiver is connected to the EUT via a cable, and its output is connected to the test receiver. The distance between the vertical ground reference plane and the horizontal ground reference plane is 80 cm. A note at the bottom specifies: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>															
Procedure		<ol style="list-style-type: none"> 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. 2. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. 3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss 															

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode : Bluetooth Mode

Test Data
Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	L1	0.1578	43.84	QP	10.03	53.87	65.58	-11.71
2	L1	0.1578	27.53	AVG	10.03	37.56	55.58	-18.02
3	L1	0.1929	38.27	QP	10.03	48.30	63.91	-15.61
4	L1	0.1929	27.89	AVG	10.03	37.92	53.91	-15.99
5	L1	0.2202	29.49	QP	10.03	39.52	62.81	-23.29
6	L1	0.2202	15.05	AVG	10.03	25.08	52.81	-27.73
7	L1	0.4035	29.79	QP	10.03	39.82	57.78	-17.96
8	L1	0.4035	16.74	AVG	10.03	26.77	47.78	-21.01
9	L1	1.0002	18.53	QP	10.03	28.56	56.00	-27.44
10	L1	1.0002	6.30	AVG	10.03	16.33	46.00	-29.67
11	L1	3.6903	19.30	QP	10.06	29.36	56.00	-26.64
12	L1	3.6903	7.75	AVG	10.06	17.81	46.00	-28.19


Test Mode : Bluetooth Mode



Test Data


Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.1578	42.92	QP	10.02	52.94	65.58	-12.64
2	N	0.1578	31.00	AVG	10.02	41.02	55.58	-14.56
3	N	0.1968	36.66	QP	10.02	46.68	63.74	-17.06
4	N	0.1968	26.57	AVG	10.02	36.59	53.74	-17.15
5	N	0.2865	25.75	QP	10.02	35.77	60.63	-24.86
6	N	0.2865	14.37	AVG	10.02	24.39	50.63	-26.24
7	N	0.3996	32.23	QP	10.02	42.25	57.86	-15.61
8	N	0.3996	21.71	AVG	10.02	31.73	47.86	-16.13
9	N	0.7272	21.64	QP	10.02	31.66	56.00	-24.34
10	N	0.7272	11.00	AVG	10.02	21.02	46.00	-24.98
11	N	3.8346	21.68	QP	10.06	31.74	56.00	-24.26
12	N	3.8346	9.98	AVG	10.06	20.04	46.00	-25.96

Test Mode : Bluetooth Mode

Test Data
Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	L1	0.1851	39.17	QP	10.03	49.20	64.25	-15.05
2	L1	0.1851	29.37	AVG	10.03	39.40	54.25	-14.85
3	L1	0.3918	30.77	QP	10.03	40.80	58.03	-17.23
4	L1	0.3918	19.69	AVG	10.03	29.72	48.03	-18.31
5	L1	0.7818	27.15	QP	10.03	37.18	56.00	-18.82
6	L1	0.7818	16.75	AVG	10.03	26.78	46.00	-19.22
7	L1	1.3122	26.30	QP	10.03	36.33	56.00	-19.67
8	L1	1.3122	15.12	AVG	10.03	25.15	46.00	-20.85
9	L1	1.7568	26.31	QP	10.04	36.35	56.00	-19.65
10	L1	1.7568	15.04	AVG	10.04	25.08	46.00	-20.92
11	L1	2.7747	25.28	QP	10.05	35.33	56.00	-20.67
12	L1	2.7747	14.87	AVG	10.05	24.92	46.00	-21.08

Test Mode : Bluetooth Mode



Test Data


Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.1874	40.26	QP	10.02	50.28	64.15	-13.87
2	N	0.1874	31.96	AVG	10.02	41.98	54.15	-12.17
3	N	0.2174	36.88	QP	10.02	46.90	62.92	-16.02
4	N	0.2174	28.20	AVG	10.02	38.22	52.92	-14.70
5	N	0.2553	34.67	QP	10.02	44.69	61.58	-16.89
6	N	0.2553	27.15	AVG	10.02	37.17	51.58	-14.41
7	N	0.2826	34.08	QP	10.02	44.10	60.74	-16.64
8	N	0.2826	23.88	AVG	10.02	33.90	50.74	-16.84
9	N	0.7584	28.00	QP	10.03	38.03	56.00	-17.97
10	N	0.7584	16.21	AVG	10.03	26.24	46.00	-19.76
11	N	1.7997	27.17	QP	10.04	37.21	56.00	-18.79
12	N	1.7997	16.64	AVG	10.04	26.68	46.00	-19.32

6.9 Radiated Spurious Emissions

Temperature	23°C
Relative Humidity	51%
Atmospheric Pressure	1018mbar
Test date :	July 18, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15. 205, §15.209, §15.247(d)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (μV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (μ V/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (μ V/m)												
30 – 88	100												
88 – 216	150												
216 960	200												
Above 960	500												
Test Setup	 <p>The diagram illustrates the test setup for radiated spurious emissions. A 'Turn Table' is positioned on a 'Ground Plane'. A 'EUT & Support Units' is mounted on the turn table. A 'Ant. Tower' is connected to the EUT and is height-adjustable, with a '1-4m Variable' height indicator. A 'Test Receiver' is connected to the tower and is shown with a waveform display. The distance between the EUT and the turn table is 0.8/1.5m, and the distance between the turn table and the antenna tower is 3m.</p>												
Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: 												

	<p>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</p> <p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</p> <p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode: Bluetooth Mode


Below 1GHz



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dBuV/ m)	Detector	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)
1	H	42.8998	37.82	peak	-9.53	28.29	40.00	-11.71	100	59
2	H	209.3129	44.45	peak	-8.82	35.63	43.50	-7.87	100	151
3	H	330.1949	44.24	QP	-6.04	38.20	46.00	-7.80	100	248
4	H	349.2500	46.40	QP	-5.48	40.92	46.00	-5.08	100	178
5	H	627.2738	38.66	peak	0.45	39.11	46.00	-6.89	100	195
6	H	766.0572	36.56	peak	2.67	39.23	46.00	-6.77	100	223

Below 1GHz

Test Data
Vertical Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dBuV/ m)	Detector	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree
1	V	97.7983	43.87	peak	-11.39	32.48	40.00	-7.52	100	156
2	V	151.0666	41.02	peak	-8.38	32.64	40.00	-7.36	100	259
3	V	202.8104	40.78	peak	-8.76	32.02	40.00	-7.98	100	53
4	V	349.2500	45.74	QP	-5.48	40.26	47.00	-6.74	100	238
5	V	487.3151	38.95	peak	-2.04	36.91	47.00	-10.09	100	180
6	V	629.4772	40.85	QP	0.47	41.32	47.00	-5.68	100	174

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel: 8DPSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4804	38.66	AV	V	33.67	6.86	32.66	46.53	54	-7.47
4804	38.51	AV	H	33.67	6.86	32.66	46.38	54	-7.62
4804	47.95	PK	V	33.67	6.86	32.66	55.82	74	-18.18
4804	47.38	PK	H	33.67	6.86	32.66	55.25	74	-18.75
17793	24.53	AV	V	45.03	11.21	32.38	48.39	54	-5.61
17793	24.29	AV	H	45.03	11.21	32.38	48.15	54	-5.85
17793	40.91	PK	V	45.03	11.21	32.38	64.77	74	-9.23
17793	40.65	PK	H	45.03	11.21	32.38	64.51	74	-9.49

Middle Channel: 8DPSK Mode (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4882	38.75	AV	V	33.71	6.95	32.74	46.67	54	-7.33
4882	38.63	AV	H	33.71	6.95	32.74	46.55	54	-7.45
4882	48.01	PK	V	33.71	6.95	32.74	55.93	74	-18.07
4882	47.67	PK	H	33.71	6.95	32.74	55.59	74	-18.41
17807	24.16	AV	V	45.15	11.18	32.41	48.08	54	-5.92
17807	24.02	AV	H	45.15	11.18	32.41	47.94	54	-6.06
17807	41.25	PK	V	45.15	11.18	32.41	65.17	74	-8.83
17807	40.79	PK	H	45.15	11.18	32.41	64.71	74	-9.29

High Channel: $\pi/4$ DQPSK Mode (Worst Case) (2480 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4960	38.59	AV	V	33.9	6.76	32.74	46.51	54	-7.49
4960	38.46	AV	H	33.9	6.76	32.74	46.38	54	-7.62
4960	48.12	PK	V	33.9	6.76	32.74	56.04	74	-17.96
4960	47.95	PK	H	33.9	6.76	32.74	55.87	74	-18.13
17795	24.72	AV	V	45.22	11.35	32.38	48.91	54	-5.09
17795	24.48	AV	H	45.22	11.35	32.38	48.67	54	-5.33
17795	41.35	PK	V	45.22	11.35	32.38	65.54	74	-8.46
17795	41.09	PK	H	45.22	11.35	32.38	65.28	74	-8.72

Note:

 1, The testing has been conformed to $10*2480\text{MHz}=24,800\text{MHz}$

2, All other emissions more than 30 dB below the limit


3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.


Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/19/2015	11/18/2016	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo





EUT - Bottom View

EUT - Left View





EUT - Right View




Adapter View

Annex B.ii. Photograph: EUT Internal Photo






MIC Connector 2- Rear View




Key Board 1- Front View




Key Board 1 - Rear View




Key Board 2- Front View




Key Board 2 - Rear View




Key Board 3- Front View




Key Board 3 - Rear View




BT board - Front View




BT board - Rear View




Main board- Front View




Main board- Rear View




Small board - Front View




Small board- Rear View



LCD - Front View



LCD - Rear View





BT – Antenna View

Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup – Front View

Conducted Emissions Test Setup – Side View



Radiated Spurious Emissions Test Setup Below 1GHz

Radiated Spurious Emissions Test Above 1GHz




Radiated Spurious Emissions Test Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emission (Below 1GHz).



Block Configuration Diagram for Radiated Emission (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Lenovo Laptop	E40	N3-F5022

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
Power Cable	Un-shielding	No	50cm	Y201301
USB Cable	Un-shielding	No	0.5m	S11021

Test Report	16070785-FCC-R
Page	60 of 61

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Annex E. DECLARATION OF SIMILARITY

BESTVIEW ELECTRONICS Technology Corp.

To: SIEMIC ,775 Montague Expressway, Milpitas, CA 95035,USA

Declaration Letter

Dear Sir,


For our business issue and marketing requirement, we would like to list 2 model numbers on the **Fcc id and CE notify body** certificates and reports, as following:

Model No.: GF842

We declare that the difference of these is listed as below:

Main Model No	Serial Model No	Difference
GF842	GF829S;GF839.GF839S;GF840;GF840S;GF842S;GF845;GF846;GF847;GF848.GF755;GF756;GF758;GF758S;GF759;GP975;GP978;GP979;GP980	Model and color difference pcb layout all same inside.

Thank you!

Signature: 

Printed name/title: Jake Jiang

Tel: 0755-29839666-806

Fax: 0755-29839080

Address: 6th,1st Building, No.9 Shilong Road, No.2 Shuitian Industrial Zone, Shitian Town, Bao'an, Shenzhen, China