

Product Number: AN2400W-174B230-IF-65

Product Name: Antenna

Specification For Approval

Date: 2025-02-15

File No.: 250215001

Version: 1.3

Customer : 北京疯景科技有限公司

Customer P/N :

JiuMao P/N : AN2400W-174B230-IF-65

Description : Antenna

JiuMao Checked By:

Customer Approved By:



东莞久茂电子有限公司

DongGuan JiuMao Electronics Co., Ltd

地址: 东莞市长安镇沙头社区龙泽路7号二楼208室

Address: Room 208, 2nd Floor, No. 7 Longze Road, Shatou Community, Chang'an Town, Dongguan

TEL:0769-88007494 FAX:0769-88007034

Product Number: AN2400W-174B230-IF-65

Product Name: Antenna

Index:

- 1. Revision History / Page 3**
- 2. Specification / Page 4**
- 3. Characteristics and Reliability Test / Page 5 ~ 6**
- 4. Antenna - S Parameter Test Data / Page 7**
- 5. Antenna - Radiation Pattern Test Data / Page 8**
- 6. Mechanical and Packing Drawing / Page 9 ~ 10**

Product Name: Antenna

1. Revision History

[illegible]

Product Number: AN2400W-174B230-IF-65

Product Name: Antenna

2. Specification

A. Electrical Characteristics	
Frequency	2400 ~ 2500 MHz
S.W.R.	≤ 2.0
Antenna Gain	$4.0 \pm 0.7\text{dBi}$
Polarization	Linear
Impedance	50 Ohm
B. Material & Mechanical Characteristics	
Material of Radiator	CU
Material of Plastic	Body: TPEE
Cable Type	RG-178/174PVC
Connector Type	IPEX
Connector Pull Test	$\geq 1\text{ Kg}$
C. Environmental	
Operation Temperature	- 40 °C ~ + 65 °C
Storage Temperature	- 40 °C ~ + 80 °C
Antenna Color Storage life	< 2 year

Product Number: AN2400W-174B230-IF-65

Product Name: Antenna

3. Characteristics and Reliability Test

Test Items 測試項目		Test Condition and Procedure 測試方法	Requirements 要求	Result 結果
C1	V.S.W.R. 電壓駐波比	Set DUT on Network Analyzer; make individual calibration to test 設置網路分析儀參數進行測試	Directive DUT specification 符合待測物規範	PASS
C2	Insertion Loss 插入損失	Set DUT on Network Analyzer; make individual calibration to test 設置網路分析儀參數進行測試	Directive DUT specification 符合待測物規範	N/A
C3	Antenna Gain 天線增益	Set DUT on Antenna Chamber; make individual calibration to test 設置天線暗室參數進行測試	Directive DUT specification 符合待測物規範	PASS
C4	Voltage Breakdown 耐電壓	Test voltage should be applied between insulated portions, or between ground as specified. 在绝缘部分测试电压,或指定接地面之间	Max Voltage $\geq$ 500 V or directive material specification 最大電壓 $\geq$ 500V 或符合材料規範	N/A
C5	Insulation Resistance 絕緣阻抗	Set Voltage: 500 $\pm$ 50V; between the insulated portions, or between ground as specified. 設置電壓 500 $\pm$ 50V,在绝缘部份測試或指定接地面之间	Resistance $\geq$ 500 M ohm or directive material specification 阻抗 $\geq$ 500M ohm 或符合材料規範	N/A
C6	Contact Resistance 接觸阻抗	Air Temp: 26°C; measured with test equipment 室溫 26°C, 指定量測設備	Directive material specification 符合材料規範	N/A
M1	Vibration 震動	GB / T2423.48-2008 Amplitude: 0.03 inch (1.5mm); Freq: 20 to 80 to 20 Hz 3 directions; 2 hours for each direction 振幅 1.5mm ; 頻率 20~80~20Hz ; 3 個方向各 2H	1. No Visual Damage 2. Frequency Tol. $\leq$ 5% 無明顯外觀不良;頻率偏移 $\leq$ 5%	PASS
M2	Random Drop 跌落	GB / T2423.8-1995 Single : Height: 1.0 Meter; 3 directions; 1 time for each direction 單支天線, 高 1m ; 3 個方向各 1 次	1. No parts separated 、 fracture 2. Frequency Tol. $\leq$ 5% 產品無脫落、斷裂;頻率偏移 $\leq$ 5%	PASS
		Packing : Height: 0.76 Meter; 1 corner, 3 edges, 6 surface 包裝 : 高 0.76m , 一角、三棱、六面各一次		PASS
		Antenna+Machine:Height: 0.76 Meter; 1 corner, 3 edges, 6 surface.整機 : 高 0.76m , 一角、三棱、六面各一次		N/A
M3	Solderability	GB / T2423.28-2005	Tin evenly on full	N/A

Product Number: AN2400W-174B230-IF-65


Product Name: Antenna

	可焊性	Temp: 260±5° C;Duration: 5 seconds 溫度 260±5° C;持續 5 秒	上錫均勻飽滿	
M4	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal .單獨定義產品端子拉力	1. Directive DUT specification 2. Frequency Tol.≤5% 符合待測物規範;頻率偏移≤5%	PASS
M5	Torque Test 扭力	Holding with individual specification; applied clockwise and counterclockwise to the axis of terminal 單獨定義產品端子之順時針及逆時針扭力	1. Directive DUT specification 2. Frequency Tol.≤ 5% 符合待測物規範;頻率偏移≤5%	N/A
M6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process.检查尺寸,颜色,材料,包装,表面處理	Directive DUT specification 符合待測物規範	PASS
E1	Waterproof 防水	With Reference to IEC 60529 // IP Code Definition 參考 IEC60529 IP 定義	Directive DUT specification 符合待測物規範	IP67
E2	Salt Spray 鹽霧	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 24H 溫度 35°C ; 濕度≥95%;鹽水濃度≥5% ; 測試 24H	1. No Visual Damage 2. Frequency Tol.≤5% 無明顯外觀不良;頻率偏移≤5%	PASS
E3	Temperature and Humidity Chamber 恒溫恒濕	GB / T 2423.3-2006 Temp: 80°C / 12 H; -40°C / 12H RH: ≥ 90%; Time: 24H 溫度 80°C 測試 12H 轉-40°C 測試 12H; 濕度≥ 90% ; 時間 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 恢復 2H 后, 無明顯外觀不良;頻率偏移≤5%	PASS
E4	Thermal Shock 冷熱衝擊	GB / T 2423.22 - 2008 - 40°C (30 minutes) to + 80°C (30 minutes) ; Cycles: 24 - 40°C 測試 30 分轉 80°C 測試 30 分爲一個週期; 共 24 週期	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 恢復 2H 后, 無明顯外觀不良;頻率偏移≤5%	PASS
E5	Aging test 老化	GB / T 2423.2 - 2008 Temp: 80°C; Time: 24 hours 溫度 80°C , 測試 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5% 無明顯外觀不良;頻率偏移≤5%	PASS
E6	High Temp. 高溫	Temp. 270±10°C ; Times : 120 seconds 溫度 270±10°C , 測試時間 120 秒	No Visual Damage 無明顯外觀不良	N/A
R1	RoHS	With Reference to IEC 62321:2008 with flow chart 參考 IEC 62321 測試流程	Directive RoHS 2011/65/EU 符合 RoHS 2011/65/EU 標準	PASS
R2	PFOS	With Reference to USA EPA 3550C:1996 by LC/MS 參考 USA EPA 3550C 測試流程	Directive RoHS 2006/122/EC 符合 RoHS 2011/65/EU 標準	PASS

Product Number: AN2400W-174B230-IF-65

Product Name: Antenna



4. Antenna - S Parameter Test Data



Product Number: AN2400W-174B230-IF-65

Product Name: Antenna

5.1 Antenna - Radiation Pattern Test Data



Product Number: AN2400W-174B230-IF-65

Product Name: Antenna

5.2 Antenna - Radiation Pattern Test Data


	1	2	3	4	5	6	7	8	9	10	11
Frequency	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
TRP (dBm)	-2.23	-2.07	-2.25	-2.24	-2.73	-2.6	-2.49	-2.41	-2.47	-2.61	-2.05
Peak EIRP (dBm)	3.82	3.73	3.63	3.77	3.15	3.13	3.26	3.52	3.52	3.6	4.16
NHPRP +/- 45 (degree)	-2.52	-2.36	-2.55	-2.54	-3.02	-2.89	-2.77	-2.71	-2.77	-2.9	-2.35
NHPRP +/- 30 (degree)	-2.95	-2.82	-3.02	-2.98	-3.46	-3.33	-3.24	-3.23	-3.28	-3.39	-2.83
E-Theta Peak Gain (dBi)	-7.9	-7.75	-6.95	-7.35	-7.52	-7.63	-7.73	-7.07	-8.1	-8.11	-7.43
E-Phi Peak Gain (dBi)	3.82	3.71	3.59	3.67	3.1	3.13	3.24	3.43	3.44	3.5	4.11
E-Total Peak Gain (dBi)	3.82	3.73	3.63	3.77	3.15	3.13	3.26	3.52	3.52	3.6	4.16
Directivity (dBi)	6.06	5.8	5.89	6.02	5.87	5.73	5.75	5.93	5.99	6.21	6.21
Efficiency (%)	59.78	62.08	59.53	59.65	53.38	54.96	56.41	57.4	56.61	54.78	62.36

RoHS

Compatible



SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			



5	AN12060-002-01	spring		brass	
4	AN068250	copper pipe		tinned copper	
3	CR-178	IPEX		Cu Au Plated	
2	YNX-AN61-01W			white	1
1	RG-178/174PVC	Cable		Black	1
No.	Part Number	Name	Material	Finish	Q'ty

 东莞久茂电子有限公司

TITLE: 2.4G Antenna					
PART NO.: AN2400W-174B230-IF-65				CUSTOMER P/N: /	
APP BY	CHK BY	RF BY	DES BY		Tolerance
LQ	DJC			UNITS: mm	X.X ±0.3
2025-02-15	2025-02-15			SCALE: 1/1	X.XX ±0.2
				REVISION: A	X° ±1

產品包裝規範
PACKING CRITERION




Date: 2025-02-15

Page: 1 of 1


Part Number : AN2400W-174B230-IF-65	Revision : A
Name: 2.4 GHz Antenna	Customer : ALL

一.




25pcs/扎

二.



R-PE-BAG-360290006 50pcs/袋


三.



规格：44*30*28CM 500pcs/箱




四.



SIDE

FRONT



APPROVED BY : LQ

CHECKED BY : DJC

DESIGNED BY : DJC