



FCC Part 15.247


TEST REPORT

For

Hangzhou Eboylamp Electronics Co., Ltd.

No.568 Huabao Street, Qianyuan Town, Deqing huzhou China

FCC ID: 2AJ3WEBEQPW25

Report Type: Original Report	Product Type: LED lamp
Report Producer : <u>Kaylee Chiang</u> 	
Report Number : <u>RXZ190604002-00A</u>	
Report Date : <u>2019-06-19</u>	
Reviewed By: <u>Jerry Chang</u> 	
Prepared By: Bay Area Compliance Laboratories Corp.(Taiwan) 70, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C. Tel: +886 (2) 2647 6898 Fax: +886 (2) 2647 6895 www.bacl.com.tw	

Revision History

Revision	No.	Report Number	Issue Date	Description	Author/ Revised by
1.0	RXZ190604002	RXZ190604002-00A	2019-06-19	Original Report	Kaylee Chiang

TABLE OF CONTENTS

1	General Information.....	5
1.1	Product Description for Equipment under Test (EUT)	5
1.2	Objective.....	5
1.3	Related Submittal(s)/Grant(s)	6
1.4	Test Methodology.....	6
1.5	Test Facility.....	6
2	System Test Configuration.....	7
2.1	Description of Test Configuration	7
2.2	Equipment Modifications.....	7
2.3	EUT Exercise Software	7
2.4	Test Mode	8
2.5	Support Equipment List and Details	8
2.6	External Cable List and Details	8
2.7	Block Diagram of Test Setup.....	9
2.8	Duty Cycle	11
3	Summary of Test Results.....	13
4	Test Equipment List and Details.....	14
5	FCC §15.247(i), §1.1310, § 2.1091 - Maximum Permissible Exposure (MPE)	16
5.1	Applicable Standard	16
5.2	RF Exposure Evaluation Result	16
6	FCC §15.203 – Antenna Requirements.....	17
6.1	Applicable Standard	17
6.2	Antenna List and Details.....	17
7	FCC §15.207(a) – AC Line Conducted Emissions.....	18
7.1	Applicable Standard	18
7.2	Measurement Uncertainty	18
7.3	EUT Setup.....	19
7.4	EMI Test Receiver Setup	19
7.5	Test Procedure.....	19
7.6	Corrected Factor & Margin Calculation	20
7.7	Environmental Conditions	20
7.8	Test Results	21
8	FCC §15.209, §15.205 , §15.247(d) – Spurious Emissions.....	23
8.1	Applicable Standard	23
8.2	Measurement Uncertainty	24
8.3	EUT Setup.....	25
8.4	EMI Test Receiver & Spectrum Analyzer Setup.....	25
8.5	Test Procedure.....	26
8.6	Corrected Factor & Margin Calculation	26
8.7	Test Results Summary	26
8.8	Environmental Conditions	26
8.9	Test Results	27
9	FCC §15.247(a)(2) – 6 dB Emission Bandwidth.....	39

9.1	Applicable Standard	39
9.2	Test Procedure.....	39
9.3	Environmental Conditions	39
9.4	Test Results	40
10	FCC §15.247(b)(3) – Maximum Output Power	45
10.1	Applicable Standard	45
10.2	Test Procedure.....	45
10.3	Environmental Conditions	45
10.4	Test Results	46
11	FCC§15.247(d) – 100 kHz Bandwidth of Frequency Band Edge.....	48
11.1	Applicable Standard	48
11.2	Test Procedure.....	48
11.3	Environmental Conditions	48
11.4	Test Results	49
12	FCC §15.247(e) – Power Spectral Density	53
12.1	Applicable Standard	53
12.2	Test Procedure.....	53
12.3	Environmental Conditions	53
12.4	Test Results	54

1 General Information

1.1 Product Description for Equipment under Test (EUT)

Applicant	Hangzhou Eboylamp Electronics Co., Ltd. No.568 Huabao Street,Qianyuan Town ,Deqing huzhou China
Manufacturer	Hangzhou Eboylamp Electronics Co., Ltd. No.568 Huabao Street,Qianyuan Town ,Deqing huzhou China
Brand(Trade) Name	eboy
Product (Equipment)	LED lamp
Main Model Name	EBE-QPW25
Series Model Name	N/A
Frequency Range	IEEE 802.11b/g / IEEE 802.11n HT20 Mode: 2412 ~ 2462 MHz
Transmit Power	IEEE 802.11b Mode: 16.59 dBm (0.046W) IEEE 802.11g Mode: 15.68 dBm (0.037W) IEEE 802.11n HT20 Mode: 14.69 dBm (0.030W)
Modulation Technique	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n HT20 Mode: OFDM
Transmit Data Rate	IEEE 802.11b Mode: 11, 5.5, 2, 1 Mbps IEEE 802.11g Mode: 54, 48, 36, 24, 18, 12, 11 , 9, 6Mbps IEEE 802.11n HT 20 Mode: MCS0~MCS7
Number of Channels	IEEE 802.11b/g / IEEE 802.11n HT20 Mode: 11 Channels
Antenna Specification	Metal antenna / 2 dBi
Power Operation (Voltage Range)	<input checked="" type="checkbox"/> AC 120V/60Hz <input type="checkbox"/> Adapter I/P: 100-240Vac,1.2A ; O/P: 12Vdc, 3A <input checked="" type="checkbox"/> By AC Power Cord <input type="checkbox"/> PoE <input type="checkbox"/> DC Type <input type="checkbox"/> Battery <input type="checkbox"/> DC Power Supply <input type="checkbox"/> External from USB Cable <input type="checkbox"/> External DC Adapter <input type="checkbox"/> Host System
Received Date	June 04, 2019
Date of Test	June 10, 2019 ~ June 13, 2019

*All measurement and test data in this report was gathered from production sample serial number: 190604002
(Assigned by BACL, Taiwan).

1.2 Objective

This report is prepared on behalf of *Hangzhou Eboylamp Electronics Co., Ltd.* in accordance with Part

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Taiwan)

2, Subpart J, Part 15, Subparts A and C of the Federal Communication Commission's rules. The objective is to determine compliance with FCC Part 15.247 rules for Output Power, Antenna Requirements, 6 dB Bandwidth, Power Spectral Density, 100 kHz Bandwidth of Band Edges Measurement, Conducted and Radiated Spurious Emissions.

1.3 Related Submittal(s)/Grant(s)

N/A.

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices KDB 558074 D01 DTS Meas Guidance v05r02

1.5 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Taiwan) to collect test data is located on

70, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.

68-3, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.

Bay Area Compliance Laboratories Corp. (Taiwan) Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3180) and the FCC designation No.TW3180 under the Mutual Recognition Agreement (MRA) in FCC Test. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 974454. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

2 System Test Configuration

2.1 Description of Test Configuration

For WIFI mode, there are totally 11 channels.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

For 802.11 b/g/n20 Modes were tested with channel 1, 6 and 11.

2.2 Equipment Modifications

No modification was made to the EUT.

2.3 EUT Exercise Software

Used “ESP_RF_test_tool_v1.1.0” software.

Test Frequency		Low	Mid	High
Power Level Setting	B Mode	0	0	0
	G Mode	24	24	24
	N20 Mode	24	24	24

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

802.11b: 1Mbps

802.11g: 6Mbps

802.11n ht20: MCS0

2.4 Test Mode

Pre-Scan

Mode 1: Full System (model: EBE-QPW25) for all test item.

Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available.

Final Test

Mode 1: Full System (model: EBE-QPW25) for all test item.

2.5 Support Equipment List and Details

Description	Manufacturer	Model Number	BSMI	FCC ID	S/N
NB	DELL	E6410	N/A	PD98260NG U	10912240367
FIX	N/A	N/A	N/A	N/A	N/A

2.6 External Cable List and Details


Cable Description	Length (m)	From	To
Micro USB Cable	1.5	NB	FIX

2.7 Block Diagram of Test Setup


See test photographs attached in setup photos for the actual connections between EUT and support equipment.


Radiation:

Below 1GHz:



Above 1GHz:



Conduction:

2.8 Duty Cycle

According to KDB 558074 D01 15.247 Meas Guidance v05r02 section 6.0:


All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x, and maximum power transmission duration, T, are required for each tested mode of operation.

Radio Mode	On Time (ms)	Period (ms)	Duty Cycle	Duty Cycle Correction Factor (dB)
802.11b	4.198	4.711	0.89	0.51
802.11g	0.689	0.793	0.87	0.60
802.11n20	0.649	0.777	0.84	0.76


Note: Duty Cycle Correction Factor = $10 \times \log(1/\text{duty cycle})$

Please refer to the following plots.


B Mode



Date: 13.JUN.2019 13:52:08

G Mode

Date: 13.JUN.2019 13:47:14

N20 Mode

Date: 13.JUN.2019 13:46:31

3 Summary of Test Results

FCC Rules	Description of Test	Results
§15.247(i), §1.1310, §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247(a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

4 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conduction Room (CON-A)					
LISN	Rohde & Schwarz	ENV216	101612	2019/02/21	2020/02/20
LISN	Rohde & Schwarz	ENV216	101248	2018/06/27	2019/06/26
EMI Test Receiver	Rohde & Schwarz	ESR7	101419	2018/10/23	2019/10/22
Pulse Limiter	Rohde & Schwarz	ESH3Z2	TXZEM104	2018/08/03	2019/08/02
RF Cable	EMEC	EM-CB5D	001	2018/07/02	2019/07/01
Software	AUDIX	E3	V9.150826k	N.C.R	N.C.R
Radiated Room (966-A)					
Bilog Antenna with 6 dB Attenuator	SUNOL SCIENCES & MINI-CIRCUITS	JB6/UNAT-6+	A050115/15542_01	2018/12/11	2019/12/10
Horn Antenna	EMCO	SAS-571	1020	2019/04/17	2020/04/16
Horn Antenna	ETS-Lindgren	3116	62638	2018/08/29	2019/08/28
Preamplifier	Sonoma	310N	130602	2018/07/04	2019/07/03
Preamplifier	EM Electronics Corp.	EM01G18G	060657	2018/12/07	2019/12/06
Microware Preamplifier	EM Electronics Corporation	EM18G40G	060656	2019/01/11	2020/01/10
EMI Test Receiver	Rohde & Schwarz	ESR7	101419	2018/10/23	2019/10/22
Spectrum Analyzer	Rohde & Schwarz	FSV40	101435	2019/02/13	2020/02/12
Micro flex Cable	UTIFLEX	FSCM 64639 / (2M)	93D0127	2018/07/31	2019/07/30
Micro flex Cable	UTIFLEX	UFA210A-1-3149-300300	MFR64639 226389-001	2018/11/16	2019/11/15
Micro flex Cable	ROSNOL	K1K50-UP0264-K1K50-450CM	160309-1	2019/03/04	2020/03/03
Micro flex Cable	ROSNOL	K1K50-UP0264-K1K50-80CM	160309-2	2019/01/16	2020/01/15
Turn Table	Champro	TT-2000	060772-T	N.C.R	N.C.R
Antenna Tower	Champro	AM-BS-4500-B	060772-A	N.C.R	N.C.R
Controller	Champro	EM1000	60772	N.C.R	N.C.R
Software	Farad	EZ_EMC	BACL-03A1	N.C.R	N.C.R

Description	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Room					
Spectrum Analyzer	Rohde & Schwarz	FSU26	200268	2019/05/10	2020/05/09
Cable	WOKEN	SFL402	S02-160323-07	2019/02/11	2020/02/10
Power Sensor	KEYSIGHT	U2021XA	MY54080018	2019/03/06	2020/03/05
Attenuator	MINI-CIRCUITS	BW-S10W5+	N/A	2019/03/07	2020/03/07

***Statement of Traceability:** BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to the SI System of Units via the R.O.C. Center for Measurement Standards of the Electronics Testing Center, Taiwan (ETC) or to another internationally recognized National Metrology Institute (NMI), and were compliant with the current Taiwan Accreditation Foundation (TAF) requirements

5 FCC §15.247(i), §1.1310, § 2.1091 - Maximum Permissible Exposure (MPE)

5.1 Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

5.2 RF Exposure Evaluation Result

MPE evaluation:

Mode	Frequency Range (MHz)	Antenna Gain		Target Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
2.4G WIFI	2412-2462	2	1.58	17	50.12	20	0.015	1.0

Note: the maximum antenna gain was used for evaluation.

Result: MPE evaluation meet 20 cm the requirement of standard.

6 FCC §15.203 – Antenna Requirements

6.1 Applicable Standard

According to § 15.203,

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna does not exceed 6dBi.

6.2 Antenna List and Details

Manufacturer	Type	Antenna Gain	Result
Dongguan RF Electronic Technology Co., Ltd	Metal Antenna	2 dBi	Compliance

The EUT has an internal antenna arrangement, which was permanently attached; fulfill the requirement of this section.

Result: Compliance

7 FCC §15.207(a) – AC Line Conducted Emissions

7.1 Applicable Standard

According to §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 2}
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency.

Note 2: A linear average detector is required


7.2 Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN/ISN and receiver, LISN/ISN voltage division factor, LISN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Taiwan) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Port	Expanded Measurement uncertainty
AC Mains	2.71 dB (k=2, 95% level of confidence)

7.3 EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

7.4 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations

Frequency Range	IF B/W
150kHz – 30MHz	9kHz

7.5 Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

7.6 Corrected Factor & Margin Calculation

The factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “Over Limit” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit Line}$$

7.7 Environmental Conditions


Temperature:	22.1 °C
Relative Humidity:	43 %
ATM Pressure:	1010 hPa

The testing was performed by Tom Hsu on 2019-06-10.

7.8 Test Results

Test Mode: Transmitting

Main: AC120 V, 60 Hz, Line




No.	Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB)	Result (dB μ V)	Limit (dB μ V)	Over limit (dB)	Remark
1	0.150	36.56	19.45	56.01	66.00	-9.99	QP
2	0.150	22.56	19.45	42.01	56.00	-13.99	Average
3	0.156	32.73	19.45	52.18	65.67	-13.49	QP
4	0.156	21.33	19.45	40.78	55.67	-14.89	Average
5	0.200	29.59	19.46	49.05	63.60	-14.55	QP
6	0.200	22.40	19.46	41.86	53.60	-11.74	Average
7	0.238	21.99	19.46	41.45	62.15	-20.70	QP
8	0.238	15.20	19.46	34.66	52.15	-17.49	Average
9	0.278	18.56	19.46	38.02	60.87	-22.85	QP
10	0.278	11.32	19.46	30.78	50.87	-20.09	Average
11	0.317	11.30	19.47	30.77	59.79	-29.02	QP
12	0.317	2.98	19.47	22.45	49.79	-27.34	Average

Note:

Level = Read Level + Factor

Over Limit = Level – Limit Line

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

Main: AC120 V, 60 Hz, Neutral

No.	Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB)	Result (dB μ V)	Limit (dB μ V)	Over limit (dB)	Remark
1	0.150	32.54	19.44	51.98	66.00	-14.02	QP
2	0.150	13.62	19.44	33.06	56.00	-22.94	Average
3	0.165	32.45	19.45	51.90	65.21	-13.31	QP
4	0.165	25.40	19.45	44.85	55.21	-10.36	Average
5	0.207	29.66	19.46	49.12	63.31	-14.19	QP
6	0.207	22.64	19.46	42.10	53.31	-11.21	Average
7	0.247	20.90	19.46	40.36	61.86	-21.50	QP
8	0.247	14.58	19.46	34.04	51.86	-17.82	Average
9	0.287	15.88	19.46	35.34	60.62	-25.28	QP
10	0.287	8.03	19.46	27.49	50.62	-23.13	Average
11	0.331	14.13	19.46	33.59	59.42	-25.83	QP
12	0.331	9.95	19.46	29.41	49.42	-20.01	Average

Note:

Level = Read Level + Factor

Over Limit = Level - Limit Line

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

8 FCC §15.209, §15.205 , §15.247(d) – Spurious Emissions

8.1 Applicable Standard

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1MHz.

As Per FCC §15.205(a) except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	960 – 1240	4. 5 – 5. 15
0.495 – 0.505	16.69475 – 16.69525	1300 – 1427	5. 35 – 5. 46
2.1735 – 2.1905	25.5 – 25.67	1435 – 1626.5	7.25 – 7.75
4.125 – 4.128	37.5 – 38.25	1645.5 – 1646.5	8.025 – 8.5
4.17725 – 4.17775	73 – 74.6	1660 – 1710	9.0 – 9.2
4.20725 – 4.20775	74.8 – 75.2	1718.8 – 1722.2	9.3 – 9.5
6.215 – 6.218	108 – 121.94	2200 – 2300	10.6 – 12.7
6.26775 – 6.26825	123 – 138	2310 – 2390	13.25 – 13.4
6.31175 – 6.31225	149.9 – 150.05	2483.5 – 2500	14.47 – 14.5
8.291 – 8.294	156.52475 – 156.52525	2690 – 2900	15.35 – 16.2
8.362 – 8.366	156.7 – 156.9	3260 – 3267	17.7 – 21.4
8.37625 – 8.38675	162.0125 – 167.17	3.332 – 3.339	22.01 – 23.12
8.41425 – 8.41475	167.72 – 173.2	3 3458 – 3 358	23.6 – 24.0
12.29 – 12.293	240 – 285	3.600 – 4.400	31.2 – 31.8
12.51975 – 12.52025	322 – 335.4		36.43 – 36.5
12.57675 – 12.57725	399.9 – 410		Above 38.6
13.36 – 13.41	608 – 614		

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

8.2 Measurement Uncertainty


All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Taiwan) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report.


Frequency	Measurement uncertainty
30 MHz~200 MHz	3.75 dB (k=2, 95% level of confidence)
200 MHz~1 GHz	4.21 dB (k=2, 95% level of confidence)
1 GHz~6 GHz	4.83 dB (k=2, 95% level of confidence)
6 GHz~18 GHz	5.18 dB (k=2, 95% level of confidence)
18 GHz~26 GHz	4.55 dB (k=2, 95% level of confidence)
26 GHz~40 GHz	4.67 dB (k=2, 95% level of confidence)

8.3 EUT Setup

Below 1 GHz:



Above 1 GHz:



Radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC Part 15.209 and FCC 15.247 Limits.

8.4 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 26.5 GHz. During the radiated emission test, the EMI test receiver was set with the following configurations measurement method 6.3 in ANSI C63.10.

Frequency Range	RBW	VBW	Detector	Duty cycle	Measurement method
30-1000 MHz	120 kHz	/	QP		QP
Above 1 GHz	1 MHz	3 MHz	PK		PK
	1 MHz	3 MHz	RMS	>98%	Ave
	1 MHz	1/T	PK	<98%	Ave

8.5 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

8.6 Corrected Factor & Margin Calculation

The Correct Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Correct Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Result} - \text{Limit}$$

8.7 Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

8.8 Environmental Conditions

Radiation		Conducted	
Temperature:	25 °C	Temperature:	21.5 °C
Relative Humidity:	55 %	Relative Humidity:	60.6 %
ATM Pressure:	1010 hPa	ATM Pressure:	1010 hPa

The Radiation Spurious Emissions testing was performed by Tom Hsu on 2019-06-13.

The Conducted Spurious Emissions testing was performed by Tom Hsu on 2019-06-13.


8.9 Test Results

Test Mode: Transmitting


(Pre-scan with three orthogonal axis, and worse case as X axis.)

Horizontal (worst case is Wi-Fi B mode high channel)


30MHz-1GHz:



1GHz-18GHz:




18GHz-26.5GHz:




Vertical (*worst case is Wi-Fi B mode high channel*)


30MHz-1GHz:



1GHz-18GHz:



18GHz-26.5GHz:



Below 1GHz**Horizontal**

Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
B Mode								
95.9600	48.28	-14.33	33.95	43.50	-9.55	100	178	QP
143.4900	49.75	-9.60	40.15	43.50	-3.35	100	257	QP
191.9900	52.79	-10.56	42.23	43.50	-1.27	100	263	QP
239.5200	50.70	-10.39	40.31	46.00	-5.69	100	141	QP
288.0200	47.59	-8.17	39.42	46.00	-6.58	100	124	QP
384.0500	47.92	-6.32	41.60	46.00	-4.40	100	113	QP
G Mode								
95.9600	47.99	-14.33	33.66	43.50	-9.84	100	182	QP
143.4900	49.42	-9.60	39.82	43.50	-3.68	100	251	QP
191.9900	52.37	-10.56	41.81	43.50	-1.69	100	271	QP
288.0200	47.51	-8.17	39.34	46.00	-6.66	100	124	QP
384.0500	48.06	-6.32	41.74	46.00	-4.26	100	116	QP
480.0800	42.50	-4.75	37.75	46.00	-8.25	100	360	QP
N20 Mode								
143.4900	49.38	-9.60	39.78	43.50	-3.72	100	247	QP
191.9900	52.30	-10.56	41.74	43.50	-1.76	100	259	QP
239.5200	49.90	-10.39	39.51	46.00	-6.49	100	122	QP
320.0300	46.72	-7.56	39.16	46.00	-6.84	100	124	QP
384.0500	47.53	-6.32	41.21	46.00	-4.79	100	119	QP
480.0800	42.59	-4.75	37.84	46.00	-8.16	100	7	QP

Result = Reading + Correct Factor

Margin = Result – Limit

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

Vertical

Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Degree ($^{\circ}$)	Remark
B Mode								
95.9600	42.00	-14.33	27.67	43.50	-15.83	100	121	QP
143.4900	40.33	-9.60	30.73	43.50	-12.77	100	150	QP
191.9900	39.89	-10.56	29.33	43.50	-14.17	100	157	QP
384.0500	36.29	-6.32	29.97	46.00	-16.03	100	181	QP
480.0800	35.67	-4.75	30.92	46.00	-15.08	100	216	QP
640.1300	34.08	-3.04	31.04	46.00	-14.96	100	200	QP
G Mode								
143.4900	41.42	-9.60	31.82	43.50	-11.68	100	117	QP
191.9900	39.66	-10.56	29.10	43.50	-14.40	100	165	QP
239.5200	39.91	-10.39	29.52	46.00	-16.48	100	92	QP
384.0500	36.48	-6.32	30.16	46.00	-15.84	100	196	QP
480.0800	36.13	-4.75	31.38	46.00	-14.62	100	201	QP
640.1300	33.74	-3.04	30.70	46.00	-15.30	100	244	QP
N20 Mode								
143.4900	40.31	-9.60	30.71	43.50	-12.79	100	118	QP
191.9900	40.10	-10.56	29.54	43.50	-13.96	100	171	QP
239.5200	39.35	-10.39	28.96	46.00	-17.04	100	106	QP
384.0500	35.98	-6.32	29.66	46.00	-16.34	100	184	QP
480.0800	36.84	-4.75	32.09	46.00	-13.91	100	99	QP
640.1300	34.32	-3.04	31.28	46.00	-14.72	100	204	QP

Result = Reading + Correct Factor

Margin = Result – Limit

Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

Above 1GHz**Horizontal**

Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
B Mode, Low channel								
2390.000	55.68	-3.87	51.81	74.00	-22.19	100	18	peak
2390.000	41.83	-3.87	37.96	54.00	-16.04	100	18	AVG
2412.000	102.33	-3.66	98.67	N/A	N/A	100	24	peak
2412.000	97.71	-3.66	94.05	N/A	N/A	100	24	AVG
4824.000	48.32	2.04	50.36	74.00	-23.64	100	297	peak
4824.000	44.34	2.04	46.38	54.00	-7.62	100	297	AVG
B Mode, Middle channel								
2437.000	101.96	-3.39	98.57	N/A	N/A	100	22	peak
2437.000	97.33	-3.39	93.94	N/A	N/A	100	22	AVG
4874.000	48.07	2.59	50.66	74.00	-23.34	100	296	peak
4874.000	45.34	2.59	47.93	54.00	-6.07	100	296	AVG
B Mode, High channel								
2462.000	100.98	-3.12	97.86	N/A	N/A	100	24	peak
2462.000	96.23	-3.12	93.11	N/A	N/A	100	24	AVG
2483.500	54.78	-2.88	51.90	74.00	-22.10	100	19	peak
2483.500	41.34	-2.88	38.46	54.00	-15.54	100	19	AVG
4924.000	49.20	2.81	52.01	74.00	-21.99	100	176	peak
4924.000	45.69	2.81	48.50	54.00	-5.50	100	176	AVG

Vertical

Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
B Mode, Low channel								
2390.000	53.01	-3.87	49.14	74.00	-24.86	100	80	peak
2390.000	40.13	-3.87	36.26	54.00	-17.74	100	80	AVG
2412.000	93.05	-3.66	89.39	N/A	N/A	100	285	peak
2412.000	88.18	-3.66	84.52	N/A	N/A	100	285	AVG
4824.000	48.76	2.04	50.80	74.00	-23.20	100	243	peak
4824.000	45.14	2.04	47.18	54.00	-6.82	100	243	AVG
B Mode, Middle channel								
2437.000	91.87	-3.39	88.48	N/A	N/A	100	271	peak
2437.000	86.93	-3.39	83.54	N/A	N/A	100	271	AVG
4874.000	48.81	2.59	51.40	74.00	-22.60	100	249	peak
4874.000	45.55	2.59	48.14	54.00	-5.86	100	249	AVG
B Mode, High channel								
2462.000	91.38	-3.12	88.26	N/A	N/A	100	285	peak
2462.000	86.76	-3.12	83.64	N/A	N/A	100	285	AVG
2483.500	54.25	-2.88	51.37	74.00	-22.63	100	46	peak
2483.500	40.22	-2.88	37.34	54.00	-16.66	100	46	AVG
4924.000	49.55	2.81	52.36	74.00	-21.64	100	247	peak
4924.000	46.21	2.81	49.02	54.00	-4.98	100	247	AVG

Result = Reading + Correct Factor

Margin = Result - Limit

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

Horizontal

Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
G Mode, Low channel								
2390.000	54.57	-3.87	50.70	74.00	-23.30	100	26	peak
2390.000	41.95	-3.87	38.08	54.00	-15.92	100	26	AVG
2412.000	99.84	-3.66	96.18	N/A	N/A	100	24	peak
2412.000	89.43	-3.66	85.77	N/A	N/A	100	24	AVG
4824.000	42.71	2.04	44.75	74.00	-29.25	100	29	peak
4824.000	29.41	2.04	31.45	54.00	-22.55	100	29	AVG
G Mode, Middle channel								
2437.000	102.46	-3.39	99.07	N/A	N/A	100	27	peak
2437.000	91.96	-3.39	88.57	N/A	N/A	100	27	AVG
4874.000	44.03	2.59	46.62	74.00	-27.38	100	298	peak
4874.000	30.31	2.59	32.90	54.00	-21.10	100	298	AVG
G Mode, High channel								
2462.000	101.42	-3.12	98.30	N/A	N/A	100	29	peak
2462.000	91.02	-3.12	87.90	N/A	N/A	100	29	AVG
2483.500	56.20	-2.88	53.32	74.00	-20.68	100	41	peak
2483.500	42.36	-2.88	39.48	54.00	-14.52	100	41	AVG
4924.000	43.75	2.81	46.56	74.00	-27.44	100	181	peak
4924.000	30.58	2.81	33.39	54.00	-20.61	100	181	AVG

Vertical

Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
G Mode, Low channel								
2390.000	53.67	-3.87	49.80	74.00	-24.20	100	288	peak
2390.000	40.70	-3.87	36.83	54.00	-17.17	100	288	AVG
2412.000	93.44	-3.66	89.78	N/A	N/A	100	286	peak
2412.000	82.78	-3.66	79.12	N/A	N/A	100	286	AVG
4824.000	43.84	2.04	45.88	74.00	-28.12	100	142	peak
4824.000	30.15	2.04	32.19	54.00	-21.81	100	142	AVG
G Mode, Middle channel								
2437.000	92.15	-3.39	88.76	N/A	N/A	100	271	peak
2437.000	81.45	-3.39	78.06	N/A	N/A	100	271	AVG
4874.000	43.89	2.59	46.48	74.00	-27.52	100	245	peak
4874.000	30.33	2.59	32.92	54.00	-21.08	100	245	AVG
G Mode, High channel								
2462.000	90.89	-3.12	87.77	N/A	N/A	100	289	peak
2462.000	80.81	-3.12	77.69	N/A	N/A	100	289	AVG
2483.500	54.23	-2.88	51.35	74.00	-22.65	100	108	peak
2483.500	40.72	-2.88	37.84	54.00	-16.16	100	108	AVG
4924.000	43.85	2.81	46.66	74.00	-27.34	100	240	peak
4924.000	30.89	2.81	33.70	54.00	-20.30	100	240	AVG

Result = Reading + Correct Factor

Margin = Result - Limit

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

Horizontal

Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
N20 Mode, Low channel								
2390.000	59.21	-3.87	55.34	74.00	-18.66	100	30	peak
2390.000	43.38	-3.87	39.51	54.00	-14.49	100	30	AVG
2412.000	101.79	-3.66	98.13	N/A	N/A	100	21	peak
2412.000	91.40	-3.66	87.74	N/A	N/A	100	21	AVG
4824.000	42.97	2.04	45.01	74.00	-28.99	100	34	peak
4824.000	29.64	2.04	31.68	54.00	-22.32	100	34	AVG
N20 Mode, Middle channel								
2437.000	102.13	-3.39	98.74	N/A	N/A	100	27	peak
2437.000	91.33	-3.39	87.94	N/A	N/A	100	27	AVG
4874.000	44.03	2.59	46.62	74.00	-27.38	100	129	peak
4874.000	30.08	2.59	32.67	54.00	-21.33	100	129	AVG
N20 Mode, High channel								
2462.000	101.28	-3.12	98.16	N/A	N/A	100	29	peak
2462.000	90.71	-3.12	87.59	N/A	N/A	100	29	AVG
2483.500	57.31	-2.88	54.43	74.00	-19.57	100	23	peak
2483.500	42.24	-2.88	39.36	54.00	-14.64	100	23	AVG
4924.000	44.41	2.81	47.22	74.00	-26.78	100	178	peak
4924.000	30.48	2.81	33.29	54.00	-20.71	100	178	AVG

Vertical

Frequency (MHz)	Reading (dB μ V)	Correct Factor(dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
N20 Mode, Low channel								
2390.000	53.52	-3.87	49.65	74.00	-24.35	100	309	peak
2390.000	40.63	-3.87	36.76	54.00	-17.24	100	309	AVG
2412.000	92.63	-3.66	88.97	N/A	N/A	100	285	peak
2412.000	81.98	-3.66	78.32	N/A	N/A	100	285	AVG
4824.000	43.69	2.04	45.73	74.00	-28.27	100	252	peak
4824.000	29.95	2.04	31.99	54.00	-22.01	100	252	AVG
N20 Mode, Middle channel								
2437.000	91.77	-3.39	88.38	N/A	N/A	100	274	peak
2437.000	81.19	-3.39	77.80	N/A	N/A	100	274	AVG
4874.000	43.52	2.59	46.11	74.00	-27.89	100	243	peak
4874.000	30.34	2.59	32.93	54.00	-21.07	100	243	AVG
N20 Mode, High channel								
2462.000	91.38	-3.12	88.26	N/A	N/A	100	151	peak
2462.000	80.22	-3.12	77.10	N/A	N/A	100	151	AVG
2483.500	54.84	-2.88	51.96	74.00	-22.04	100	144	peak
2483.500	40.84	-2.88	37.96	54.00	-16.04	100	144	AVG
4924.000	44.91	2.81	47.72	74.00	-26.28	100	238	peak
4924.000	30.21	2.81	33.02	54.00	-20.98	100	238	AVG

Result = Reading + Correct Factor


Margin = Result - Limit

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.


Conducted Spurious Emissions:

Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
B Mode				
Low	2412	49.81	≥ 20	PASS
Mid	2437	47.82	≥ 20	PASS
High	2462	49.10	≥ 20	PASS
G Mode				
Low	2412	42.48	≥ 20	PASS
Mid	2437	46.74	≥ 20	PASS
High	2462	46.06	≥ 20	PASS
N20 Mode				
Low	2412	43.88	≥ 20	PASS
Mid	2437	44.72	≥ 20	PASS
High	2462	40.48	≥ 20	PASS

B Mode
Low Channel


Date: 13.JUN.2019 13:58:55

Middle Channel



Date: 13.JUN.2019 14:04:00


High Channel



Date: 13.JUN.2019 14:07:51


G Mode

Low Channel




Date: 13.JUN.2019 14:10:38

Middle Channel




Date: 13.JUN.2019 14:14:51

High Channel




Date: 13.JUN.2019 14:24:57

N20 Mode Low Channel




Date: 13.JUN.2019 14:29:28

Middle Channel



Date: 13.JUN.2019 14:32:09

High Channel



Date: 13.JUN.2019 14:36:07

9 FCC §15.247(a)(2) – 6 dB Emission Bandwidth

9.1 Applicable Standard

According to FCC §15.247(a)(2).

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

9.2 Test Procedure

The steps for the first option are as follows:

- a) Set RBW = 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

9.3 Environmental Conditions

Temperature:	21.5 °C
Relative Humidity:	60.6 %
ATM Pressure:	1010 hPa


The testing was performed by Tom Hsu on 2019-06-13.

9.4 Test Results

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)	Result
B Mode				
Low	2412	8.52	> 500	PASS
Middle	2437	8.52	> 500	PASS
High	2462	8.52	> 500	PASS
G Mode				
Low	2412	15.80	> 500	PASS
Middle	2437	15.80	> 500	PASS
High	2462	15.84	> 500	PASS
N20 Mode				
Low	2412	16.04	> 500	PASS
Middle	2437	16.04	> 500	PASS
High	2462	16.04	> 500	PASS


Please refer to the following plots

B Mode Low Channel




Date: 13.JUN.2019 13:58:08

Middle Channel



Date: 13.JUN.2019 14:03:32


High Channel




Date: 13.JUN.2019 14:07:04

G Mode


Low Channel



Middle Channel




High Channel



Date: 13.JUN.2019 14:24:11


N20 Mode

Low Channel




Date: 13.JUN.2019 14:28:41

Middle Channel



Date: 13.JUN.2019 14:31:41

High Channel



Date: 13.JUN.2019 14:35:20

10 FCC §15.247(b)(3) – Maximum Output Power

10.1 Applicable Standard

According to FCC §15.247(b) (3).

Systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

10.2 Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to measuring equipment.

10.3 Environmental Conditions

Temperature:	21.5 °C
Relative Humidity:	60.6 %
ATM Pressure:	1010 hPa

The testing was performed by Tom Hsu on 2019-06-13.

10.4 Test Results

Conducted Peak Output Power

Channel	Frequency (MHz)	Power (dBm)	Power (W)	Limit (W)	Result
B Mode					
Low	2412	16.12	0.041	1	PASS
Middle	2437	16.59	0.046	1	PASS
High	2462	16.58	0.045	1	PASS
G Mode					
Low	2412	15.04	0.032	1	PASS
Middle	2437	15.68	0.037	1	PASS
High	2462	15.65	0.037	1	PASS
N20 Mode					
Low	2412	14.17	0.026	1	PASS
Middle	2437	14.69	0.029	1	PASS
High	2462	14.82	0.030	1	PASS

Conducted Average Output Power

Channel	Frequency (MHz)	Power (dBm)	Duty Factor (dB)	Power With Duty Factor (dBm)	Limit (dBm)	Result
B Mode						
Low	2412	12.20	0.51	12.71	30	PASS
Middle	2437	12.65	0.51	13.16	30	PASS
High	2462	12.66	0.51	13.17	30	PASS
G Mode						
Low	2412	6.16	0.6	6.76	30	PASS
Middle	2437	6.81	0.6	7.41	30	PASS
High	2462	6.76	0.6	7.36	30	PASS
N20 Mode						
Low	2412	5.12	0.76	5.88	30	PASS
Middle	2437	5.61	0.76	6.37	30	PASS
High	2462	5.77	0.76	6.53	30	PASS

11 FCC§15.247(d) – 100 kHz Bandwidth of Frequency Band Edge

11.1 Applicable Standard

According to FCC §15.247(d).

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

11.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.3 Environmental Conditions

Temperature:	21.5 °C
Relative Humidity:	60.6 %
ATM Pressure:	1010 hPa


The testing was performed by Tom Hsu on 2019-06-13.

11.4 Test Results


Channel	Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
B Mode				
Low	2412	44.67	≥ 20	PASS
High	2462	44.75	≥ 20	PASS
G Mode				
Low	2412	37.03	≥ 20	PASS
High	2462	36.25	≥ 20	PASS
N20 Mode				
Low	2412	36.17	≥ 20	PASS
High	2462	36.43	≥ 20	PASS

Please refer to the following plots.


B Mode Band Edge, Left Side




Date: 13.JUN.2019 13:58:36

Band Edge, Right Side


Date: 13.JUN.2019 14:07:33

G Mode
Band Edge, Left Side

Date: 13.JUN.2019 14:10:20


Band Edge, Right Side

Date: 13.JUN.2019 14:24:39

N20 Mode
Band Edge, Left Side

Date: 13.JUN.2019 14:29:10

Band Edge, Right Side



Date: 13.JUN.2019 14:35:49

12 FCC §15.247(e) – Power Spectral Density

12.1 Applicable Standard

According to FCC §15.247(e).

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

12.2 Test Procedure

According to ANSI C63.10-2013

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat

12.3 Environmental Conditions


Temperature:	21.5 °C
Relative Humidity:	60.6 %
ATM Pressure:	1010 hPa

The testing was performed by Tom Hsu on 2019-06-13.


12.4 Test Results

Channel	Frequency (MHz)	Power Spectral Density (dBm/3 kHz)	Limit (dBm/3 kHz)	Result
B Mode				
Low	2412	-11.05	8	PASS
Middle	2437	-10.16	8	PASS
High	2462	-9.25	8	PASS
G Mode				
Low	2412	-17.69	8	PASS
Middle	2437	-17.75	8	PASS
High	2462	-17.09	8	PASS
N20 Mode				
Low	2412	-18.89	8	PASS
Middle	2437	-19.43	8	PASS
High	2462	-18.49	8	PASS

Please refer to the following plots




Middle Channel



Date: 13.JUN.2019 14:03:41


High Channel




Date: 13.JUN.2019 14:07:14


G Mode

Low Channel




Middle Channel




High Channel

Date: 13.JUN.2019 14:24:21

**N20 Mode
Low Channel**


Date: 13.JUN.2019 14:28:51

Middle Channel



Date: 13.JUN.2019 14:31:51

High Channel



Date: 13.JUN.2019 14:35:30

***** END OF REPORT *****