



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

198 Kezhu Road, Scientechn Park, Guangzhou Economic & Technological
Development District, Guangzhou, China 510663
Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM161000681102
Page: 1 of 52
FCC ID: 2AJ8KB0029RA

TEST REPORT

The following sample(s) was/were submitted and identified on behalf of the client as:

Application No.:	GZEM1610006811AV
Applicant:	BRIGHT INDUSTRIES COMPANY LIMITED
Manufacturer:	Dong Guan Jia Sheng Lighting Technology Co., Ltd.
Factory:	Dong Guan Jia Sheng Lighting Technology Co., Ltd.
FCC ID:	2AJ8KB0029RA
Product Description:	Low Voltage Outdoor Speaker
Model No.:	B0029RA
Trade Mark:	Hampton Bay
Standards:	CFR 47 FCC PART 15 Subpart C: 2015 section 15.247
Date of Receipt:	2016-10-25
Date of Test:	2016-12-05 to 2016-12-07
Date of Issue:	2016-12-26
Test Result :	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.



Authorized Signature:

Ricky Liu
Manager


The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2016-12-26		Original Report

Authorized for issue by:			
Tested By		 (Vico Cui) /Project Engineer	2016-12-05 to 2016-12-07
Prepared By		 (Millie Li) / Clerk	2016-12-24
Checked By		 (Ricky Liu) / Reviewer	2016-12-26

3 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
6 dB Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10: Clause 11.8	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	ANSI C63.10: Clause 11.9	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10: Clause 11.10	PASS
Conducted Spurious Emission	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 11.11	PASS
Radiated Spurious Emission	FCC PART 15 C section 15.209	ANSI C63.10: Clause 11.12,6.3,6.5 and 6.6	PASS
Radiated Emissions which fall in the restricted bands	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 11.12,6.3,6.5 and 6.6	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	ANSI C63.10: Clause 11.13	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS

Remark1:

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report.

Conducted testing use a direct connection between the antenna port of the device and the spectrum analyzer, may through suitable attenuator, all the attenuation in the conducted RF path, include cable loss or external attenuation will be offset to the spectrum analyzer during testing. Detailed offset value, please refer to the corresponding test plot.

4 Contents

1	Cover Page	1
2	Version	2
3	Test Summary	3
4	Contents	4
5	General Information	5
5.1	Client Information	5
5.2	General Description of E.U.T.	5
5.3	Details of E.U.T.	5
5.4	Description of Support Units	6
5.5	Deviation from Standards	6
5.6	Abnormalities from Standard Conditions	6
5.7	Other Information Requested by the Customer	6
5.8	Test Location	6
5.9	Measurement Uncertainty	6
5.10	Test Facility	7
6	Equipment List	8
7	Test Results	9
7.1	E.U.T. test conditions	9
7.2	Antenna Requirement	12
7.3	6 dB Bandwidth	13
7.4	Maximum Peak Output Power	16
7.5	Peak Power Spectral Density	20
7.6	Conducted Spurious Emissions	23
7.7	Radiated Spurious Emissions	29
7.8	Radiated Emissions which fall in the restricted bands	38
7.9	Band Edges Requirement	45
7.10	Conducted Emissions at Mains Terminals 150 kHz to 30 MHz	49

5 General Information

5.1 Client Information

Applicant:	BRIGHT INDUSTRIES COMPANY LIMITED
Address of Applicant:	UNIT 16 17F GOLDEN ERA PLAZA NO 39-55 SAI YEE STREET MONG KOK HONG KONG
Manufacturer:	Dong Guan Jia Sheng Lighting Technology Co., Ltd.
Address of Manufacturer:	Shutian Manage District, Humen Town, Dongguan City, China, 523929
Factory:	Dong Guan Jia Sheng Lighting Technology Co., Ltd.
Address of Factory:	Shutian Manage District, Humen Town, Dongguan City, China, 523929

5.2 General Description of E.U.T.

Product Description:	Low Voltage Outdoor Speaker
Model No.:	B0029RA

5.3 Details of E.U.T.

Operating Frequency	2404 MHz to 2479 MHz
Type of Modulation:	GFSK
Equipment Types:	DSSS with Adaptive (Only one adaptive mode is implemented and could not operate in a non-adaptive mode.)
Number of Channels	16 Channels
Channel Separation:	5 MHz
Duty Cycle:	Continuous operation possible for testing purposes
Antenna Type	Integral antenna
Antenna gain:	3.5 dBi
Power Supply:	DC 3.7V (internal rechargeable battery operated) AC/DC 12V for charging
Power Cord:	N/A

5.4 Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by SGS:

Description	Manufacturer	Model No.	SN/Certificate NO
NoteBook	IBM	T30	S/N78-3VMLX 06/01
DC Power supply (EMC 0009)	Insteek	PS-3030	L9905E037.34

Using the special software and development board we can enter the product for engineer mode then we can control the EUT to select the wanted channel for test. The test board and PC are only to configure the engineer mode and not used to final test.

5.5 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

5.6 Abnormalities from Standard Conditions

None.

5.7 Other Information Requested by the Customer

None.

5.8 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

5.9 Measurement Uncertainty

No.	Item	Measurement uncertainty
1	Conducted emission	1.02dB(9kHz to 150kHz)
		1.05dB(150kHz to 30MHz)
2	Radiated emission	5.06dB(30MHz to 1GHz)
		5.06dB(1GHz to 26GHz)

5.10 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

6 Equipment List

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2016-12-04	2019-12-03
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2016-02-01	2017-01-31
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2016-02-01	2017-01-31
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2016-04-19	2018-04-18
EMC2025	Trilog Broadband Antenna 30-1000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9160	9160-3372	2016-09-08	2019-09-07
SEM003-18	Trilog Broadband Antenna 25-2000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	665	2016-06-29	2019-06-28
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2016-09-08	2019-09-07
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2014-05-04	2017-05-03
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	9120D-841	2016-09-09	2019-09-08
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2016-01-25	2017-01-24
EMC2065	Amplifier	HP	8447F	N/A	2016-07-04	2017-07-03
EMC2086	PRE AMPLIFIER MH648A	ANRITSU CORP	MH648A	N/A	2016-12-02	2017-12-01
EMC2063	Pre-amplifier 1GHz-26GHz	Compliance Direction Systems Lnc.	PAP-1G26-48	6279.628	2016-12-02	2017-12-01
EMC0523	Active Loop Antenna	EMCO	6502	42963	2016-02-27	2018-02-26
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2014-05-26	2017-05-25
EMC2079	High Pass Filter(915MHz)	FSY MICROWAVE	HM1465-9SS	009	2016-01-25	2017-01-24
EMC2069	2.4GHz Filter	Micro-Tronics	BRM 50702	149	2016-01-25	2017-01-24
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2016-04-30	2018-04-29

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0006	DMM	Fluke	73	70681569	2016-09-01	2017-08-31
EMC0007	DMM	Fluke	73	70671122	2016-08-22	2017-08-21

7 Test Results

7.1 E.U.T. test conditions

Test Voltage:	DC 3.7V (battery operated) AC/DC 12V for charging
Temperature:	20.0 -25.0 °C
Humidity:	38-50 % RH
Atmospheric Pressure:	1000 -1010 mbar
Requirements:	<p>15.31(e): For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.</p> <p>15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.</p>
Test frequencies and frequency range:	<p>According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:</p> <p>According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:</p>

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2404.00	4	2424.00	8	2444.00	12	2464.00
1	2409.00	5	2429.00	9	2449.00	13	2469.00
2	2414.00	6	2434.00	10	2454.00	14	2474.00
3	2419.00	7	2439.00	11	2459.00	15	2479.00

Using the special software and development board we can enter the product for engineer mode then we can control the EUT to select the wanted channel for test as above list.

Test frequencies are the lowest channel: 0 channel(2404MHz), middle channel: 8 channel(2444 MHz) and highest channel: 15 channel(2479 MHz)

7.2 Antenna Requirement

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed.

Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna

The antenna is PCB Layout antenna and no consideration of replacement. The best case gain of the antenna is 3.5dBi.



Test result: The unit does meet the FCC requirements.


7.3 6 dB Bandwidth

Test Requirement: FCC Part 15 C section 15.247
(a)(2)Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Method: ANSI C63.10: Clause 11.8

Test Status: Enter test mode for the product. Test in Channel lowest (2404MHz), middle (2444MHz) and highest (2479MHz), keep in continuously transmitting status.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW=100 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Set span to encompass the entire emission bandwidth of the signal.
3. Mark the peak power frequency and -6dB (upper and lower) power frequency.
4. Repeat until all the test status is investigated.
5. Report the worse case.


Test result:



0	2404	GFSK	761.5	≥500KHz	Pass
8	2444		721.4		Pass
15	2479		761.5		Pass

The unit does meet the FCC requirements.

Result plot as follows:

Channel 0: 2.404GHz:



Channel 8: 2.444GHz:

Channel 15: 2.479GHz:



7.4 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247
(b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Method: ANSI C63.10: Clause 11.9

Test Status: Enter test mode for the product. Test in Channel lowest (2404MHz), middle (2444MHz) and highest (2479MHz), keep in continuously transmitting status.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable from the antenna port to the spectrum.
2. Set the $RBW \geq DTS$. bandwidth.
3. Set the $VBW \geq 3 \times RBW$
4. Set the span $\geq 3 \times RBW$
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use peak marker function to determine the peak amplitude level.

Report the worse case.

Test result:


Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Channel Power (dBm)	Limit	Result
0	2404	GFSK	1Mbps	7.22	1W(30dBm)	Pass
8	2444		1Mbps	6.93		Pass
15	2479		1Mbps	5.73		Pass

Remark: Level = Read Level + Cable Loss


The unit does meet the FCC requirements.

Result plot as follows:


Channel 0: 2.404GHz:



Channel 8: 2.444GHz:



Channel 15: 2.479GHz:



7.5 Peak Power Spectral Density

Test Requirement:

FCC Part 15 C section 15.247

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


Test Method:

ANSI C63.10: Clause 11.10

Test Status:

Enter test mode for the product. Test in lowest Channel 2404MHz, middle Channel 2444MHz and highest Channel 2479MHz, keep in continuously transmitting status.

Test Configuration:






Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=3 kHz.
3. VBW \geq 3 x RBW sweep= Auto couple; Set the span to 1.5 times the DTS bandwidth.
4. Detector Function = Peak. Trace = Max Hold, Centre = the Peak Power of the signal.
5. Measure the Power Spectral Density of the test frequency with special test status.
6. Repeat until all the test status is investigated.
7. Report the worse case.

Test result:

Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Peak Power Spectral Density (dBm/3KHz)	Limit	Result
0	2404	GFSK	1 Mbps	6.89	8dBm/3KHz	Pass
8	2444		1 Mbps	6.26		Pass
15	2479		1 Mbps	5.32		Pass

Level = Read Level + Cable Loss.
The unit does meet the FCC requirements.
Result plot as follows:
Channel 0: 2.404 GHz:


Channel 8:2.444 GHz:

Channel 15:2.479 GHz:


7.6 Conducted Spurious Emissions

Test Requirement: FCC Part 15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 11.11

Test Status: Enter test mode for the product. Test in lowest Channel 2404MHz, middle Channel 2444MHz and highest Channel 2479MHz, keep in continuously transmitting status.



Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode was worse case



Test Configuration:







Test Procedure:


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.

Result plot as follows:
Channel 0: 2.404 GHz
30 MHz to 1GHz

1GHz to 5GHz


5GHz to 25GHz

Channel 8: 2.444GHz
30 MHz to 1GHz


1GHz to 5GHz

5GHz to 25GHz


Channel 15: 2.479GHz
30 MHz to 1GHz

1GHz to 5GHz


5GHz to 25GHz

7.7 Radiated Spurious Emissions

Test Requirement: 47 CFR Part 15C Section 15.209 and 15.205

Test Method: ANSI C63.10: 2013

Test Site: Measurement Distance:3m

(Semi-Anechoic Chamber below 1GHz, Full Anechoic Chamber above 1GHz)

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 and 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degree to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel (2404MHz), the middle channel (2444MHz), the Highest channel (2479MHz)
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Exploratory Test Mode: Transmitting with GFSK modulation.
a. Charge + Transmitting mode.
b. Transmitting mode.

Final Test Mode: Transmitting with GFSK modulation.
Pretest the EUT at Charge + Transmitting mode and Transmitting mode
For below 1GHz part, through pre-scan, the worst case is the lowest
channel Charge + Transmitting mode
Only the worst case is recorded in the report.

Instruments Used: Refer to section 6 for details


Test Results: Pass

Test Result:**9KHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement**

The measurements with Loop antenna and the amplitude of spurious emissions from the radiator are attenuated more than 20dB below the limit, so the test data were not recorded in the test report.

30MHz~1GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with Log antenna.

Lowest channel/ Vertical:

Trace: (Discrete)

Site : SGS
Condition : FCC PART15 C (3M) 3m VUBL9168(3M) VERTICAL

Job :

Application:

Test Mode : DSSS 2404


Product :

Model :

Engineer :

Remark : Level=Read Level + Cable loss
: + Antenna Factor - Preamp factor

Freq	ReadAntenna		Cable		Preamp		Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	62.651	37.99	13.82	1.45	27.00	26.26	40.00	-13.74	QP
2	69.600	40.78	12.74	1.50	27.00	28.02	40.00	-11.98	QP
3	140.835	36.19	13.02	2.24	26.82	24.63	43.50	-18.87	QP
4	191.745	42.59	11.74	2.66	26.62	30.37	43.50	-13.13	QP
5	223.733	43.15	11.40	2.86	26.51	30.90	46.00	-15.10	QP
6	385.281	34.33	16.12	3.82	27.04	27.23	46.00	-18.77	QP

Lowest channel /Horizontal:

Freq	ReadAntenna		Cable		Preamp	Limit	Over	Remark
	Level	Factor	Loss	Factor				
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	68.631	39.09	12.82	1.50	27.00	26.41	40.00	-13.59 QP
2	138.874	43.64	12.94	2.23	26.83	31.98	43.50	-11.52 QP
3	189.739	47.73	11.95	2.65	26.62	35.71	43.50	-7.79 QP
4	223.733	44.30	11.40	2.86	26.51	32.05	46.00	-13.95 QP
5	324.456	36.80	14.32	3.55	26.57	28.10	46.00	-17.90 QP
6	440.196	33.52	16.99	4.10	27.45	27.16	46.00	-18.84 QP

Above 1GHz Field Strength of Unwanted Emissions. Peak & Average Measurement**Lowest channel: Peak Measurement**

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Antenna polarization
4808.000	51.24	30.79	9.95	40.21	51.77	74.00	-22.23	V
7212.000	38.73	35.50	12.76	39.25	47.74	74.00	-26.26	V
9616.000	33.64	37.51	14.48	37.97	47.66	74.00	-26.34	V
12020.000	33.36	39.50	15.80	38.08	50.58	74.00	-23.42	V
4804.110	49.13	30.79	9.95	40.21	49.66	74.00	-24.34	H
7212.000	38.80	35.50	12.76	39.25	47.81	74.00	-26.19	H
9616.000	33.45	37.51	14.48	37.97	47.47	74.00	-26.53	H
12020.000	32.54	39.50	15.80	38.08	49.76	74.00	-24.24	H

Lowest channel: Average Measurement

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Antenna polarization
4808.000	36.28	30.79	9.95	40.21	36.81	54.00	-17.19	V
7212.000	31.00	35.50	12.76	39.25	40.01	54.00	-13.99	V
9616.000	26.83	37.51	14.48	37.97	40.85	54.00	-13.15	V
12020.000	24.78	39.50	15.80	38.08	42.00	54.00	-12.00	V
4804.110	38.27	30.79	9.95	40.21	38.80	54.00	-15.20	H
7212.000	29.25	35.50	12.76	39.25	38.26	54.00	-15.74	H
9616.000	24.54	37.51	14.48	37.97	38.56	54.00	-15.44	H
12020.000	25.35	39.50	15.80	38.08	42.57	54.00	-11.43	H

Above 1GHz Field Strength of Unwanted Emissions. Peak & Average Measurement**Middle channel: Peak Measurement**

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Antenna polarization
4888.000	49.85	30.95	10.02	40.22	50.60	74.00	-23.40	V
7332.000	37.91	35.74	12.93	39.22	47.36	74.00	-26.64	V
9776.000	33.55	37.74	14.44	37.90	47.83	74.00	-26.17	V
12220.000	33.83	39.21	16.05	38.10	50.99	74.00	-23.01	V
4888.000	52.00	30.95	10.02	40.22	52.75	74.00	-21.25	H
7332.000	38.30	35.74	12.93	39.22	47.75	74.00	-26.25	H
9776.000	33.70	37.74	14.44	37.90	47.98	74.00	-26.02	H
12220.000	33.63	39.21	16.05	38.10	50.79	74.00	-23.21	H

Middle channel: Average Measurement

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Antenna polarization
4888.000	37.81	30.95	10.02	40.22	38.56	54.00	-15.44	V
7332.000	29.16	35.74	12.93	39.22	38.61	54.00	-15.39	V
9776.000	22.14	37.74	14.44	37.90	36.42	54.00	-17.58	V
12220.000	25.47	39.21	16.05	38.10	42.63	54.00	-11.37	V
4888.000	39.02	30.95	10.02	40.22	39.77	54.00	-14.23	H
7332.000	30.89	35.74	12.93	39.22	40.34	54.00	-13.66	H
9776.000	22.39	37.74	14.44	37.90	36.67	54.00	-17.33	H
12220.000	24.86	39.21	16.05	38.10	42.02	54.00	-11.98	H

Above 1GHz Field Strength of Unwanted Emissions. Peak & Average Measurement**Highest channel: Peak Measurement**



Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Antenna polarization
4958.000	46.32	31.05	10.07	40.23	47.21	74.00	-26.79	V
7437.000	37.42	35.92	13.04	39.20	47.18	74.00	-26.82	V
9916.000	35.27	37.92	14.41	37.84	49.76	74.00	-24.24	V
12395.000	33.19	38.93	16.29	38.12	50.29	74.00	-23.71	V
4958.000	49.72	31.05	10.07	40.23	50.61	74.00	-23.39	H
7437.000	37.77	35.92	13.04	39.20	47.53	74.00	-26.47	H
9916.000	33.44	37.92	14.41	37.84	47.93	74.00	-26.07	H
12395.000	33.31	38.93	16.29	38.12	50.41	74.00	-23.59	H

Highest channel: Average Measurement

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Antenna polarization
4958.000	35.72	31.05	10.07	40.23	36.61	54.00	-17.39	V
7437.000	29.89	35.92	13.04	39.20	39.65	54.00	-14.35	V
9916.000	23.03	37.92	14.41	37.84	37.52	54.00	-16.48	V
12395.000	23.95	38.93	16.29	38.12	41.05	54.00	-12.95	V
4958.000	37.76	31.05	10.07	40.23	38.65	54.00	-15.35	H
7437.000	29.35	35.92	13.04	39.20	39.11	54.00	-14.89	H
9916.000	24.48	37.92	14.41	37.84	38.97	54.00	-15.03	H
12395.000	24.42	38.93	16.29	38.12	41.52	54.00	-12.48	H

7.8 Radiated Emissions which fall in the restricted bands

Test Requirement:	FCC Part 15 C section 15.247																						
	(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).																						
Test Method:	ANSI C63.10.2013																						
Test Status:	Enter test mode for the product. Test in lowest channel 2404 MHz and highest channel 2479 MHz, keep in continuously transmitting status with GFSK modulation. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode was worse case.																						
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																						
Limit:	<table border="1"><thead><tr><th>Frequency</th><th>Limit (dBuV/m @3m)</th><th>Remark</th></tr></thead><tbody><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td></td><td>54.0</td><td>Average Value</td></tr><tr><td>Above 1GHz</td><td>74.0</td><td>Peak Value</td></tr></tbody></table>		Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value		54.0	Average Value	Above 1GHz	74.0	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																					
30MHz-88MHz	40.0	Quasi-peak Value																					
88MHz-216MHz	43.5	Quasi-peak Value																					
216MHz-960MHz	46.0	Quasi-peak Value																					
960MHz-1GHz	54.0	Quasi-peak Value																					
	54.0	Average Value																					
Above 1GHz	74.0	Peak Value																					
Detector:	For PK value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW \geq RBW Sweep = auto Detector function = peak Trace = max hold																						
	For AV value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW = 10Hz Sweep = auto Detector function = peak Trace = max hold																						

Test Configuration:1). 30 MHz to 1 GHz emissions:2). Above 1 GHz emissions:

Test Procedure:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2010 was used to perform radiated emission test above 1 GHz.

The receiver scanned from the lowest frequency generated within the EUT to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

From 30MHz to 1GHz, read the Quasi-Peak field strength of the emissions with receiver QP detector RBW=120KHz.

Above 1GHz, read the Peak field strength and Average field strength.

Read the Peak field strength through RBW=1MHz, VBW=3MHz in spectrum analyzer setting;

Read the Average field strength through RBW=1MHz, VBW=10Hz in spectrum analyzer setting;

While maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the average field strength reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

Test Result:**Above 1GHz Radiated Emissions. Peak & Average Measurement**

Lowest channel: Peak Measurement								
Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit	Antenna polarization
2310.000	41.36	26.25	6.80	39.07	35.34	74.00	-38.66	V
2390.000	43.81	26.43	6.87	39.10	38.01	74.00	-35.99	V
2483.500	41.64	26.58	7.07	39.14	36.15	74.00	-37.85	V
2500.000	41.86	26.60	7.10	39.14	36.42	74.00	-37.58	V
2310.000	42.48	26.25	6.80	39.07	36.46	74.00	-37.54	H
2390.000	42.10	26.43	6.87	39.10	36.30	74.00	-37.70	H
2483.500	42.15	26.58	7.07	39.14	36.66	74.00	-37.34	H
2500.000	42.75	26.60	7.10	39.14	37.31	74.00	-36.69	H

Lowest channel: Average Measurement

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit	Antenna polarization
2310.000	32.40	26.25	6.80	39.07	26.38	54.00	-27.62	V
2390.000	31.19	26.43	6.87	39.10	25.39	54.00	-28.61	V
2483.500	33.46	26.58	7.07	39.14	27.97	54.00	-26.03	V
2500.000	33.80	26.60	7.10	39.14	28.36	54.00	-25.64	V
2310.000	33.78	26.25	6.80	39.07	27.76	54.00	-26.24	H
2390.000	32.38	26.43	6.87	39.10	26.58	54.00	-27.42	H
2483.500	30.16	26.58	7.07	39.14	24.67	54.00	-29.33	H
2500.000	34.19	26.60	7.10	39.14	28.75	54.00	-25.25	H

Above 1GHz Radiated Emissions. Peak & Average Measurement

Middle channel: Peak Measurement								
Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit	Antenna polarization
2310.000	41.31	26.25	6.80	39.07	35.29	74.00	-38.71	V
2390.000	40.65	26.43	6.87	39.10	34.85	74.00	-39.15	V
2483.500	41.24	26.58	7.07	39.14	35.75	74.00	-38.25	V
2500.000	40.96	26.60	7.10	39.14	35.52	74.00	-38.48	V
2310.000	40.29	26.25	6.80	39.07	34.27	74.00	-39.73	H
2390.000	40.07	26.43	6.87	39.10	34.27	74.00	-39.73	H
2483.500	40.25	26.58	7.07	39.14	34.76	74.00	-39.24	H
2500.000	40.35	26.60	7.10	39.14	34.91	74.00	-39.09	H

Middle channel: Average Measurement

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit	Antenna polarization
2310.000	33.86	26.25	6.80	39.07	27.84	54.00	-26.16	V
2390.000	29.97	26.43	6.87	39.10	24.17	54.00	-29.83	V
2483.500	32.87	26.58	7.07	39.14	27.38	54.00	-26.62	V
2500.000	32.06	26.60	7.10	39.14	26.62	54.00	-27.38	V
2310.000	31.47	26.25	6.80	39.07	25.45	54.00	-28.55	H
2390.000	33.06	26.43	6.87	39.10	27.26	54.00	-26.74	H
2483.500	30.29	26.58	7.07	39.14	24.80	54.00	-29.20	H
2500.000	31.38	26.60	7.10	39.14	25.94	54.00	-28.06	H

Above 1GHz Radiated Emissions. Peak & Average Measurement**Highest channel: Peak Measurement**

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Antenna polarization
2310.000	42.53	26.25	6.80	39.07	36.51	74.00	-37.49	V
2390.000	42.32	26.43	6.87	39.10	36.52	74.00	-37.48	V
2483.500	75.05	26.58	7.07	39.14	69.56	74.00	-4.44	V
2500.000	43.82	26.60	7.10	39.14	38.38	74.00	-35.62	V
2310.000	43.19	26.25	6.80	39.07	37.17	74.00	-36.83	H
2390.000	41.76	26.43	6.87	39.10	35.96	74.00	-38.04	H
2483.500	74.25	26.58	7.07	39.14	68.76	74.00	-5.24	H
2500.000	42.01	26.60	7.10	39.14	36.57	74.00	-37.43	H

Highest channel: Average Measurement

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Over limit	Antenna polarization
2310.000	33.32	26.25	6.80	39.07	27.30	54.00	-26.70	V
2390.000	34.34	26.43	6.87	39.10	28.54	54.00	-25.46	V
2483.500	45.25	26.58	7.07	39.14	39.76	54.00	-14.24	V
2500.000	34.30	26.60	7.10	39.14	28.86	54.00	-25.14	V
2310.000	32.69	26.25	6.80	39.07	26.67	54.00	-27.33	H
2390.000	32.34	26.43	6.87	39.10	26.54	54.00	-27.46	H
2483.500	44.57	26.58	7.07	39.14	39.08	54.00	-14.92	H
2500.000	33.11	26.60	7.10	39.14	27.67	54.00	-26.33	H

7.9 Band Edges Requirement

Test Requirement: FCC Part 15 C section 15.247


(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: ANSI C63.10: Clause 11.13

Test Status: Enter test mode for the product. Test in lowest channel 2404 MHz and highest channel 2479 MHz, keep in continuously transmitting status with GFSK modulation.
Pre-test the EUT in B/O mode and charging mode find the worst case is B/O Mode.

Test Configuration:



Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set instrument center frequency to the frequency of the emission to be measured(must be within 2MHz of the authorized band edge).
3. Set span (wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.),
4. RBW=100kHz,
5. $VBW \geq 3 \times RBW$
6. Detector=peak
7. Sweep time =auto,
8. Trace mode=max hold.
9. Allow sweep to continue until the trace stabilizes(required measurement time may increase for low duty cycle applications)
10. Compute the power by integrating the spectrum over 1MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency(f_{emission}) $\pm 0.5\text{MHz}$.If the instrument does not have a band power function,the sum the amplitude levels(in power units) at 100kHz intervals extending across the 1MHz spectrum defined by $f_{\text{emission}}\pm 0.5\text{MHz}$.


Test result:

Compare with the output power of the lowest frequency, the Lower Edges attenuated more than 20dB
Compare with the output power of the highest frequency, the Upper Edges attenuated more than 20dB.

Result plot as follows:

Channel 0: 2.404 GHz



Channel 15: 2.479GHz


7.10 Conducted Emissions at Mains Terminals 150 kHz to 30 MHz


Test Requirement: FCC Part 15 C section 15.207
Test Method: ANSI C63.10: Clause 6.2
Frequency Range: 150 kHz to 30 MHz
Detector: Peak for pre-scan (9 kHz Resolution Bandwidth)

Test Limit**Limits for conducted disturbance at the mains ports of class B**

Frequency Range (MHz)	Class B Limit dB(µV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

EUT Operation: Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.
Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Test Configuration:**Test procedure:**


1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.


Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected. For EUT the communicating was worst case mode.

The following Quasi-Peak and Average measurements were performed on the EUT:

Neutral LineLevel(dB μ V)

Measure data:

Frequency MHz	read level dB μ V	Cable Loss dB	LISN Factor dB	Measured level dB μ V	Limit Line dB μ V	Over limit dB	Remark
0.179	21.21	0.10	9.56	30.87	54.55	-23.68	AVERAGE
0.179	32.41	0.10	9.56	42.07	64.55	-22.48	QP
0.456	21.94	0.19	9.55	31.68	46.76	-15.08	AVERAGE
0.456	34.28	0.19	9.55	44.02	56.76	-12.74	QP
0.595	23.68	0.23	9.54	33.45	46.00	-12.55	AVERAGE
0.595	36.26	0.23	9.54	46.03	56.00	-9.97	QP
4.622	27.49	0.67	9.61	37.77	56.00	-18.23	QP
4.622	26.54	0.67	9.61	36.82	46.00	-9.18	AVERAGE
7.466	31.34	0.64	9.67	41.65	50.00	-8.35	AVERAGE
7.466	34.44	0.64	9.67	44.75	60.00	-15.25	QP
19.895	31.55	0.70	10.01	42.26	60.00	-17.74	QP
19.895	25.14	0.70	10.01	35.85	50.00	-14.15	AVERAGE

Live LineLevel(dB μ V)

Measure data:

Frequency MHz	read level dB μ V	Cable Loss dB	LISN Factor dB	Measured level dB μ V	Limit Line dB μ V	Over limit dB	Remark
0,169	34,23	0,10	9,69	44,02	64,99	-20,97	QP
0,169	22,80	0,10	9,69	32,59	54,99	-22,40	AVERAGE
0,502	26,59	0,20	9,71	36,50	46,00	-9,50	AVERAGE
0,502	37,93	0,20	9,71	47,84	56,00	-8,16	QP
0,573	37,27	0,22	9,70	47,19	56,00	-8,81	QP
0,573	23,32	0,22	9,70	33,24	46,00	-12,76	AVERAGE
4,622	26,87	0,67	9,74	37,28	46,00	-8,72	AVERAGE
4,622	29,46	0,67	9,74	39,87	56,00	-16,13	QP
7,479	32,45	0,64	9,79	42,88	50,00	-7,12	AVERAGE
7,479	35,25	0,64	9,79	45,68	60,00	-14,32	QP
20,295	33,42	0,70	10,04	44,16	60,00	-15,84	QP
20,295	30,18	0,70	10,04	40,92	50,00	-9,08	AVERAGE

--End of Report--