

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640 Fay: +86-755-26648637

Website: www.cga-cert.com

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No.: CQASZ20180800067E-03

Applicant: BRIGHT INDUSTRIES COMPANY LIMITED

Address of Applicant: UNIT 16 17F GOLDEN ERA PLAZA NO 39-55 SAI YEE STREET MONG KOK

HONG KONG

Manufacturer: DONG GUAN JIA SHENG LIGHTING TECHNOLOGY CO.,LTD

Address of Manufacturer: Shutian Village, Humen Town, Dongguan City, Guangdong Province, China

Equipment Under Test (EUT):

Product: LED Lighting speaker All Model No.: FWS-17, FLM-17

Test Model No.: FWS-17 Brand Name: MoriMori FCC ID: 2AJ8KSP1701

47 CFR Part 1.1307 Standards:

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-08-17 to 2018-08-22

Date of Issue: 2018-08-22 Test Result: PASS*

Tested By:

(Daisy Qin)

Reviewed By:

Approved By:

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: CQASZ20180800067E-03

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20180800067E-03	Rev.01	Initial report	2018-08-22



Report No.: CQASZ20180800067E-03

2 Contents

		Page
1	TOVER PAGE错误!	未定义书签。
2	2 VERSION	2
3	3 CONTENTS	3
4	4 GENERAL INFORMATION	4
	4.1 CLIENT INFORMATION	4
	4.2 GENERAL DESCRIPTION OF EUT	
	5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
	5.1.1 Standard Requirement	5
	5.1.2 Limits	5
	5.1.3 FUT RF Exposure	



Report No.: CQASZ20180800067E-03

3 General Information

3.1 Client Information

Applicant:	BRIGHT INDUSTRIES COMPANY LIMITED	
Address of Applicant:	UNIT 16 17F GOLDEN ERA PLAZA NO 39-55 SAI YEE STREET MONG KOK HONG KONG	
Manufacturer:	DONG GUAN JIA SHENG LIGHTING TECHNOLOGY CO.,LTD	
Address of Manufacturer:	Shutian Village, Humen Town, Dongguan City, Guangdong Province, China	

3.2 General Description of EUT

Product Name:	LED Lighting speaker
All Model No.:	FWS-17, FLM-17
Test Model No.:	FWS-17
Trade Mark:	MoriMori
Hardware Version:	V2.1
Software Version:	V0.1
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
Modulation Type:	BT classic: GFSK, π/4DQPSK BLE: GFSK
Number of Channel:	BT classic:79 BLE:40
Sample Type:	portable production
Test Software of EUT:	FCCAssist 2.4 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	-0.58dBi
Power Supply:	lithium battery:DC3.7V, 1700mAh, Charge by DC5.0V



Report No.: CQASZ20180800067E-03

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation 17

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

For BT: Measurement Data

GFSK mode		
Test channel	Peak Output Power (dBm)	
Lowest	-2.110	
Middle	-1.870	
Highest	-2.110	
π/4DQPSK mode		
Test channel	Peak Output Power (dBm)	
Lowest	-1.090	
Middle	-0.950	
Highest	-1.220	

Remark: The Conducted Peak Output Power data refer to report Report No.: CQASZ20180800067E-01



Report No.: CQASZ20180800067E-03

For BLE:

Measurement Data

	GFSK mode	
Test channel	Peak Output Power (dBm)	
Lowest	0.82	
Middle	0.9	
Highest	0.57	

Remark: The Conducted Peak Output Power data refer to report Report No.: CQASZ20180800067E-02

BDR, EDR and BLE can not simultaneous transmitting at same time.

The worst case data: BLE_GFSK_middle channel

The Max Conducted Peak Output Power is 0.9dBm in middle channel(2.441GHz);

The best case gain of the antenna is -0.58dBi.

EIRP= 0.9dBm - 0.58dBm= 0.32dBm

0.32dBm logarithmic terms convert to numeric result is nearly 1.1mW

According to the formula. calculate the EIRP test result:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}]$

General RF Exposure = $(1.1 \text{mW} / 5 \text{ mm}) \times \sqrt{2.441 \text{GHz}} = 0.34$ ①

SAR requirement:

S= 3.0 ②;

1 < 2.

So the SAR report is not required.