

TEST REPORT

Product Name : Smart Identification Terminal
Model Number : M1, SenseFP M1, TR1
FCC ID : 2AJ9T-10605

Prepared for : ZKTECO CO., LTD.
Address : No.32, Pingshan Industrial Avenue, Tangxia Town, Dongguan City, Guangdong Province, China 523728

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2504110195W00701R
Date(s) of Tests : April 24, 2025 to May 27, 2025
Date of issue : May 28, 2025

TABLE OF CONTENTS

TEST REPORT	1
1 EUT TECHNICAL DESCRIPTION	5
2 SUMMARY OF TEST RESULT	6
3 TEST METHODOLOGY	7
3.1 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.2 MEASUREMENT EQUIPMENT USED	7
3.3 DESCRIPTION OF TEST MODES	9
4 FACILITIES AND ACCREDITATIONS	10
4.1 FACILITIES	10
4.2 EQUIPMENT	10
4.3 LABORATORY ACCREDITATIONS AND LISTINGS	10
5 TEST SYSTEM UNCERTAINTY	11
6 SETUP OF EQUIPMENT UNDER TEST	12
6.1 RADIO FREQUENCY TEST SETUP 1	12
6.2 RADIO FREQUENCY TEST SETUP 2	12
6.3 CONDUCTED EMISSION TEST SETUP	13
6.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	14
6.5 SUPPORT EQUIPMENT	14
7 TEST REQUIREMENTS	15
7.1 OCCUPIED BANDWIDTH	15
7.2 FREQUENCY STABILITY	17
7.3 RADIATED SPURIOUS EMISSION	19
7.4 CONDUCTED EMISSION TEST	32
8 ANTENNA APPLICATION	35
8.1 ANTENNA REQUIREMENT	35
8.2 RESULT	35

TEST RESULT CERTIFICATION

Applicant : ZKTECO CO., LTD.
Address : No.32, Pingshan Industrial Avenue, Tangxia Town, Dongguan City, Guangdong Province, China 523728
Manufacturer : ZKTECO CO., LTD.
Address : No.32, Pingshan Industrial Avenue, Tangxia Town, Dongguan City, Guangdong Province, China 523728
EUT : Smart Identification Terminal
Model Name : M1, SenseFP M1, TR1
Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.225.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : April 24, 2025 to May 27, 2025
Prepared by : 
Guangjun Zhu/Editor
Reviewer : 
Joe Xia/Supervisor
Approved & Authorized Signer : 
Lisa Wang/Manager

Modified Information

Version	Report No.	Revision Date	Summary
Ver.1.0	ENS2504110195W00701R	/	Original Report



1 EUT TECHNICAL DESCRIPTION

Product:	Smart Identification Terminal
Model Number:	M1, SenseFP M1, TR1
Power Supply:	DC 5V from adapter
Adapter1:	MODEL:ADS-12FB-06 05010EPCU INPUT: 100-240V~, 50Hz/60Hz, Max 0.3A OUTPUT:5.0V, 2.0A
Adapter2:	MODEL:FJ-SW1260502000DE INPUT: 100-240V~, 50Hz/60Hz, Max 0.4A OUTPUT:5.0V, 2.0A,10.0W
Test Voltage:	AC 120V/60Hz
Modulation:	ASK
Frequency Range:	13.56MHz
Antenna Type:	Induction coil antenna
Antenna Gain:	0 dBi Note: The antenna information provided by the manufacturer will have a certain impact on the test results.
Temperature Range:	0°C~+45°C

Note: For more details, please refer to the user's manual of the EUT.

2 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
2.1049	Occupied Bandwidth	PASS	
15.225(e)	Frequency stability	PASS	
15.225(d) 15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	PASS	
NOTE: N/A (Not Applicable)			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for **FCC ID: 2AJ9T-10605** filing to comply with Section 15.225 of the FCC Part 15, Subpart C Rules.



3 TEST METHODOLOGY

3.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
FCC 47 CFR Part 2, Subpart J
FCC 47 CFR Part 15, Subpart C

3.2 MEASUREMENT EQUIPMENT USED

Conducted Emission Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESCI	101045	2024/5/10	1Year
PULSE LIMITER	Rohde & Schwarz	ESH3-Z2	100107	2024/5/10	1Year
AMN	Rohde & Schwarz	ESH3-Z5	100191	2024/5/10	1Year
AMN	Schwarzbeck	NNLK 8129	8129203	2024/5/11	1Year
V-Network	Rohde & Schwarz	ESH3-Z6	100011	2024/5/11	1Year
V-Network	Rohde & Schwarz	ESH3-Z6	100253	2024/5/11	1Year

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESCI	101045	2025/5/9	1Year
PULSE LIMITER	Rohde & Schwarz	ESH3-Z2	100107	2025/5/9	1Year
AMN	Rohde & Schwarz	ESH3-Z5	100191	2025/5/9	1Year
AMN	Schwarzbeck	NNLK 8129	8129203	2025/5/9	1Year
V-Network	Rohde & Schwarz	ESH3-Z6	100011	2025/5/9	1Year
V-Network	Rohde & Schwarz	ESH3-Z6	100253	2025/5/9	1Year

For Spurious Emissions Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Pre-Amplifier	HP	8447F	2944A07999	2024/5/11	1Year
EMI Test Receiver	Rohde & Schwarz	ESCI	101414	2024/5/11	1Year
Bilog Antenna	Schwarzbeck	VULB9163	712	2023/7/5	2 Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1178	2023/8/28	2 Year
Pre-Amplifier	Bonn	BLMA 0118-5G	2213967B-01	2024/10/23	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2024/5/10	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2023/5/12	2 Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2023/5/12	2 Year

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Pre-Amplifier	HP	8447F	2944A07999	2025/5/9	1Year
EMI Test Receiver	Rohde & Schwarz	ESCI	101414	2025/5/9	1Year
Bilog Antenna	Schwarzbeck	VULB9163	712	2024/6/15	2 Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1178	2025/5/17	2 Year
Pre-Amplifier	Bonn	BLMA 0118-5G	2213967B-01	2024/10/18	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2025/5/9	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2025/5/13	2 Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2025/5/13	2 Year

Cable:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Coaxial Cable	TIMES	NmNm-7-C1570 2	N/A	2024/5/23	1Year
Coaxial Cable	TIMES	HF290-NMSM-6. 5M	N/A	2024/5/23	1Year
Coaxial Cable	TIMES	LMR-240 N-N	N/A	2024/5/23	1Year

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Coaxial Cable	TIMES	NmNm-7-C1570 2	N/A	2025/5/22	1Year
Coaxial Cable	TIMES	HF290-NMSM-6. 5M	N/A	2025/5/22	1Year
Coaxial Cable	TIMES	LMR-240 N-N	N/A	2025/5/22	1Year

For other test items:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Wideband Radio Communication Tester	R&S	CMW500	171168	2024/9/18	1 Year
Frequency Extender	R&S	CMW-Z800A	100430	2024/9/18	1 Year
Spectrum Analyzer	R&S	FSV3044	101290	2024/10/18	1 Year
Analog Signal Generator	R&S	SMB100A	183237	2024/9/18	1 Year
Vector Signal Generator	R&S	SMM100A	101808	2024/9/18	1 Year
RF Control Unit	Tonscend	JS0806-2	22C8060567	2024/9/18	N/A
Temperature&Hum idity Chamber	ESPEC	EL-02KA	12107166	2024/5/10	1 Year

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Wideband Radio Communication Tester	R&S	CMW500	171168	2024/9/18	1 Year
Frequency Extender	R&S	CMW-Z800A	100430	2024/9/18	1 Year
Spectrum Analyzer	R&S	FSV3044	101290	2024/10/18	1 Year
Analog Signal Generator	R&S	SMB100A	183237	2024/9/18	1 Year
Vector Signal Generator	R&S	SMM100A	101808	2024/9/18	1 Year
RF Control Unit	Tonscend	JS0806-2	22C8060567	2024/9/18	N/A
Temperature&Hum idity Chamber	ESPEC	EL-02KA	12107166	2025/5/10	1 Year

3.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting mode is programmed.



4 FACILITIES AND ACCREDITATIONS

4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

EMTEK (Shenzhen) Co., Ltd.

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

4.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

4.3 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description
EMC Lab.

Accredited by CNAS

The Certificate Registration Number is L2291

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA

The Certificate Number is 4321.01

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008

Name of Firm

: EMTEK (SHENZHEN) CO., LTD.

Site Location

: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

5 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%



6 SETUP OF EQUIPMENT UNDER TEST

6.1 RADIO FREQUENCY TEST SETUP 1

The component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



6.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.


Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

(a) Radiated Emission Test Set-Up, Frequency Below 30MHz




(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz




6.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN. Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



6.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



6.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment

7 TEST REQUIREMENTS

7.1 OCCUPIED BANDWIDTH

7.1.1 Applicable Standard

According to FCC Part 2.1049

7.1.2 Conformance Limit

No limit requirement.

7.1.3 Test Configuration

Test according to clause 6.1 radio frequency test setup 1

7.1.4 Test Procedure

The EUT was operating in transmit mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1% occupied bandwidth(30Hz).

Set the video bandwidth (VBW) =3 times RBW .

Set Span= approximately 2 to 3 times the occupied bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 99% down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 99% bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.

7.1.5 Test Results


Temperature :	25°C	Test Date :	May 15,2025
Humidity :	65 %	Test By:	GJ

Modulation Mode	Channel Number	Channel Frequency (MHz)	-20dB Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
ASK	0	13.56	0.519	N/A	PASS
Note: N/A (Not Applicable)					

Test Model

Occupied Bandwidth
Channel 0: 13.56MHz

ASK Modulation



11:58:40 AM 05/15/2025

7.2 FREQUENCY STABILITY

7.2.1 Applicable Standard

According to FCC Part 2.1055

7.2.2 Conformance Limit

According to part 15.225(e), The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

7.2.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

7.2.4 Test Procedures

Connect the EUT to frequency analyzer via the antenna connector.
EUT was placed at temperature chamber and connected to an external power supply.
Temperature and voltage condition shall be tested to confirm frequency stability.

(a) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(b) The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point, which shall be specified by the manufacturer.

7.2.5 Test Results

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (°C)				
ASK	CH1	Vnom	-20	13.559871	-129.0	-9.51	100
			-10	13.559909	-89.0	-6.56	100
			0	13.559996	-1.0	-0.07	100
			10	13.559758	-242.0	-17.85	100
			20	13.560026	22.0	1.62	100
			30	13.559919	-85.0	-6.27	100
			40	13.559874	-126.0	-9.29	100
			50	13.559981	-17.0	-1.25	100
		85% Vnom	20	13.559929	-76.0	-5.60	100
		115% Vnom	20	13.559918	-82.0	-6.05	100
VERDICT				PASS			

7.3 RADIATED SPURIOUS EMISSION

7.3.1 Applicable Standard

According to FCC Part 15.225 and 15.209

7.3.2 Conformance Limit

Field Strength of Fundamental Emissions and Spectrum Mask					
Emissions	($\mu\text{V/m}$)@30m	(dB $\mu\text{V/m}$)@30m	(dB $\mu\text{V/m}$)@10m	(dB $\mu\text{V/m}$)@3m	(dB $\mu\text{V/m}$)@1m
Fundamental	15848	84.0	103.1	124.0	143.1
Quasi peak measurement of the fundamental.					

Spectrum Mask					
Freq. of Emission (MHz)	($\mu\text{V/m}$)@30m	(dB $\mu\text{V/m}$)@30m	(dB $\mu\text{V/m}$)@10m	(dB $\mu\text{V/m}$)@3m	(dB $\mu\text{V/m}$)@1m
1.705~13.110	30	29.5	48.6	69.5	88.6
13.110~13.410	106	40.5	59.6	80.5	99.6
13.410~13.553	334	50.5	69.6	90.5	109.6
13.553~13.567	15848	84.0	103.1	124.0	143.1
13.567~13.710	334	50.5	69.6	90.5	109.6
13.710~14.010	106	40.5	59.6	80.5	99.6
14.010~30.000	30	29.5	48.6	69.5	88.6

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	48.5 - 13.8	300
0.490-1.705	24000/F(KHz)	33.8 - 23.0	30
1.705-30	30	29.5	30
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

7.3.3 Test Configuration

Test according to clause 6.2 radio frequency test setup 2

7.3.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for $f < 1$ GHz (30MHz to 1GHz), 200Hz for $f < 150$ KHz (9KHz to 150KHz), 9KHz for $f < 30$ MHz (150KHz to 30KHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.


Repeat above procedures until all frequency measured was complete.

7.3.5 Test Results

Field Strength of Fundamental Emissions and Spectrum Mask



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11.5260	14.94	19.77	34.71	69.50	-34.79	peak		
2		12.3720	15.04	19.56	34.60	69.50	-34.90	peak		
3		13.0620	15.18	19.40	34.58	69.50	-34.92	peak		
4		13.5600	28.07	19.43	47.50	124.00	-76.50	peak		
5		14.6460	14.65	19.48	34.13	69.50	-35.37	peak		
6	*	14.9700	15.77	19.50	35.27	69.50	-34.23	peak		
7		16.0380	15.12	19.45	34.57	69.50	-34.93	peak		



Site 3m Chamber #2

Polarization: Y

Temperature: 23.1 C

Limit: (RE)FCC PART 15.225(Mask)


Power:

Humidity: 50 %

Mode: 13.56M

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	11.6640	14.36	19.73	34.09	69.50	-35.41	peak		
2		12.4620	13.43	19.53	32.96	69.50	-36.54	peak		
3		12.9300	13.96	19.42	33.38	69.50	-36.12	peak		
4		13.5600	26.36	19.43	45.79	124.00	-78.21	peak		
5		14.5380	13.91	19.48	33.39	69.50	-36.11	peak		
6		15.3960	14.13	19.48	33.61	69.50	-35.89	peak		
7		16.1760	13.80	19.44	33.24	69.50	-36.26	peak		



Site 3m Chamber #2

Polarization: Z

Temperature: 23.1 C

Limit: (RE)FCC PART 15.225(Mask)

Power:

Humidity: 50 %


Mode: 13.56M

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		11.5560	13.48	19.76	33.24	69.50	-36.26	peak		
2		12.7260	13.68	19.47	33.15	69.50	-36.35	peak		
3	*	12.9120	14.08	19.42	33.50	69.50	-36.00	peak		
4		13.5600	24.80	19.43	44.23	124.00	-79.77	peak		
5		13.8660	14.17	19.44	33.61	80.50	-46.89	peak		
6		15.1440	13.68	19.49	33.17	69.50	-36.33	peak		
7		15.6780	13.34	19.47	32.81	69.50	-36.69	peak		

■ Spurious Emission below 150kHz (9KHz to 150kHz)

All mode have been tested, and the worst result was report as below:



Site 3m Chamber #2

Polarization: X

Temperature: 23.1 C

Limit: (RE)FCC PART 15.209(9K-30M)


Power:

Humidity: 50 %

Mode: 13.56M

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		0.0111	32.01	20.29	52.30	126.68	-74.38	peak			
2		0.0221	27.14	20.18	47.32	120.70	-73.38	peak			
3		0.0284	25.51	20.12	45.63	118.52	-72.89	peak			
4		0.0533	26.73	20.62	47.35	113.06	-65.71	peak			
5		0.0777	23.49	20.58	44.07	109.79	-65.72	peak			
6	*	0.0998	22.12	20.40	42.52	107.61	-65.09	peak			



Site 3m Chamber #2

Polarization: **Y**

Temperature: 23.1 C

Limit: (RE)FCC PART 15.209(9K-30M)


Power:

Humidity: 50 %

Mode: 13.56M

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		0.0111	29.87	20.29	50.16	126.68	-76.52	peak		
2		0.0267	28.29	20.13	48.42	119.06	-70.64	peak		
3		0.0533	26.76	20.62	47.38	113.06	-65.68	peak		
4		0.0781	21.76	20.58	42.34	109.74	-67.40	peak		
5		0.0885	19.48	20.42	39.90	108.66	-68.76	peak		
6	*	0.1215	20.15	20.52	40.67	105.91	-65.24	peak		



Site 3m Chamber #2

Polarization: **Z**

Temperature: 23.1 C

Limit: (RE)FCC PART 15.209(9K-30M)

Power:

Humidity: 50 %


Mode: 13.56M

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.0111	30.52	20.29	50.81	126.68	-75.87	peak		
2		0.0221	24.29	20.18	44.47	120.70	-76.23	peak		
3		0.0267	29.51	20.13	49.64	119.06	-69.42	peak		
4		0.0444	22.44	20.46	42.90	114.64	-71.74	peak		
5	*	0.0533	26.41	20.62	47.03	113.06	-66.03	peak		
6		0.0777	21.03	20.58	41.61	109.79	-68.18	peak		

■ Spurious Emission below 30MHz (150KHz to 30MHz)

All mode have been tested, and the worst result was report as below:



Site 3m Chamber #2

Polarization: X

Temperature: 23.1 C

Limit: (RE)FCC PART 15.209(9K-30M)


Power:

Humidity: 50 %


Mode:13.56M

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		0.1864	25.49	20.45	45.94	102.19	-56.25	peak			
2		0.4020	19.56	20.76	40.32	95.52	-55.20	peak			
3		1.6276	14.29	20.54	34.83	63.40	-28.57	peak			
4		3.2930	14.78	20.43	35.21	69.50	-34.29	peak			
5	*	13.5510	31.33	19.43	50.76	69.50	-18.74	peak			
6		19.5316	14.53	19.83	34.36	69.50	-35.14	peak			




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.2267	22.18	20.51	42.69	100.49	-57.80	peak		
2		1.7530	13.49	20.52	34.01	69.50	-35.49	peak		
3		3.2410	13.42	20.42	33.84	69.50	-35.66	peak		
4		5.5346	12.19	20.49	32.68	69.50	-36.82	peak		
5	*	13.5508	26.01	19.43	45.44	69.50	-24.06	peak		
6		22.2978	14.01	20.09	34.10	69.50	-35.40	peak		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		0.2267	22.68	20.51	43.19	100.49	-57.30	peak		
2		0.5020	18.27	20.90	39.17	73.59	-34.42	peak		
3		0.7160	15.10	20.77	35.87	70.51	-34.64	peak		
4		3.2410	13.42	20.42	33.84	69.50	-35.66	peak		
5		3.9640	12.42	20.50	32.92	69.50	-36.58	peak		
6	*	13.5508	23.51	19.43	42.94	69.50	-26.56	peak		

■ Spurious Emission Above 30MHz (30MHz to 1GHz)

Mode:	13.56MHz
-------	----------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	40.6807	49.69	-23.36	26.33	PK	40.00	13.67	Vertical
2	47.4775	55.07	-22.39	32.68	PK	40.00	7.32	Vertical
3	54.2743	58.97	-22.60	36.37	PK	40.00	3.63	Vertical
4	60.1001	52.27	-23.41	28.86	PK	40.00	11.14	Vertical
5	80.4905	51.99	-26.20	25.79	PK	40.00	14.21	Vertical
6	112.5325	53.47	-24.06	29.41	PK	43.50	14.09	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	40.6807	-23.36	26.25	40.00	13.75
2	47.4775	-22.39	32.60	40.00	7.40
3	54.2743	-22.60	35.93	40.00	4.07
4	60.1001	-23.41	28.42	40.00	11.58
5	80.4905	-26.20	24.99	40.00	15.01
6	112.5325	-24.06	28.78	43.50	14.72

Mode:	13.56MHz
-------	----------



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	54.2743	47.79	-22.60	25.19	PK	40.00	14.81	Horizontal
2	67.8679	43.49	-24.48	19.01	PK	40.00	20.99	Horizontal
3	70.7808	43.14	-24.88	18.26	PK	40.00	21.74	Horizontal
4	225.1652	46.39	-22.19	24.20	PK	46.00	21.80	Horizontal
5	825.2252	41.48	-10.65	30.83	PK	46.00	15.17	Horizontal
6	900.961	40.08	-8.94	31.14	PK	46.00	14.86	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	54.2743	-22.60	24.35	40.00	15.65
2	67.8679	-24.48	19.00	40.00	21.00
3	70.7808	-24.88	17.61	40.00	22.39
4	225.1652	-22.19	23.55	46.00	22.45
5	825.2252	-10.65	30.54	46.00	15.46
6	900.961	-8.94	30.85	46.00	15.15

7.4 CONDUCTED EMISSION TEST

7.4.1 Applicable Standard

According to FCC Part 15.207(a)

7.4.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50
Note: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.		

7.4.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


7.4.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

7.4.5 Test Results

Pass

The 120V & 240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #1

Phase: **N**

Temperature: 24.2

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 56 %

Mode: RF ID 13.56MHz

Note: 13.56MHz

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	42.40	9.93	52.33	66.00	-13.67	QP	
2		0.1500	22.73	9.93	32.66	56.00	-23.34	AVG	
3		0.3300	29.66	9.91	39.57	59.45	-19.88	QP	
4		0.3300	15.44	9.91	25.35	49.45	-24.10	AVG	
5		5.1940	20.45	10.06	30.51	60.00	-29.49	QP	
6		5.1940	6.37	10.06	16.43	50.00	-33.57	AVG	
7	*	13.5620	43.29	10.37	53.66	60.00	-6.34	peak	
8		14.8380	25.71	10.42	36.13	60.00	-23.87	QP	
9		14.8380	2.56	10.42	12.98	50.00	-37.02	AVG	
10		23.1820	32.99	10.75	43.74	60.00	-16.26	QP	
11		23.1820	6.35	10.75	17.10	50.00	-32.90	AVG	
12		27.1260	34.24	10.89	45.13	60.00	-14.87	QP	
13		27.1260	28.78	10.89	39.67	50.00	-10.33	AVG	



Site Conduction #1

Phase: **L1**

Temperature: 24.2

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 56 %

Mode: RF ID 13.56MHz

Note: 13.56MHz

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	41.78	9.93	51.71	65.57	-13.86	QP	
2		0.1580	19.06	9.93	28.99	55.57	-26.58	AVG	
3		0.1780	40.17	9.91	50.08	64.58	-14.50	QP	
4		0.1780	21.21	9.91	31.12	54.58	-23.46	AVG	
5		0.3220	31.49	9.92	41.41	59.66	-18.25	QP	
6		0.3220	13.54	9.92	23.46	49.66	-26.20	AVG	
7		5.2900	15.83	10.06	25.89	60.00	-34.11	QP	
8		5.2900	0.37	10.06	10.43	50.00	-39.57	AVG	
9	*	13.5620	42.78	10.37	53.15	60.00	-6.85	peak	
10		14.8300	23.85	10.42	34.27	60.00	-25.73	QP	
11		14.8300	0.86	10.42	11.28	50.00	-38.72	AVG	
12		27.1260	33.88	10.89	44.77	60.00	-15.23	QP	
13		27.1260	26.77	10.89	37.66	50.00	-12.34	AVG	

8 ANTENNA APPLICATION

8.1 ANTENNA REQUIREMENT

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.2 RESULT

The EUT is Induction coil antenna, the antenna's gain is 0 dBi and meets the requirement, and the antenna can't be replaced by the user, which in accordance to section 15.203.

--- End of Report ---