

Company Name:Dongguan Youbi Electronics Co.,LTD
Company Address:Room 101,Building 2,No.9,Xinfa Road,Lin Village,Tangxia Town,
Dongguan City,Guangdong Province,China


WIFI Antenna Model:UB01C

1. Electrical Specification:

Characteristics	Specifications	Unit
Outline Dimensions	17.5x18.3,L125	mm
Frequency	2400-2500	MHz
Impedance	50	Ω
VSWR	< 2.0	
Polarization	Linear Polarization	
Gain	2.05	dBi
Efficiency	>40	%
Connector Type	MHF-1-Plug	
Operating temperature	-20℃~+85℃	
Storage Temp	-20℃~+50℃	

2.Test Items and Equipment

	Test items	Test equipment
S Parameter	1.Return Loss 2.VSWR	Network analyzer (Agilent E5071B)
The whole machine of Passive parameters	1.Frequency 2.Gain 3.Radiation Pattern	1.3D microwave darkroom (5m*5m*5m) 2.Network analyzer (Agilent E5071B)
The whole machine of Active parameters	1.TRP 2.TIS	1.3D microwave darkroom (5m*5m*5m) 2.Comprehensive test instrument (CMW500)




3. S Parameter

Frequency (MHz)	Return Loss (dB)	VSWR
2400	-19.16	1.24
2450	-23.61	1.14
2500	-17.50	1.30

* Voltage Standing Wave Ratio(VSWR)



Return Loss(RL)

$$RL=20*\log_{10}[(VSWR+1)/(VSWR-1)]$$




4. Efficiency and Gain

Frequency (MHz)	2400	2450	2500
Efficiency (%)	46.03	46.45	47.32
Gain (dBi)	1.63	1.44	2.05




5. Radiation Pattern


5-1 Antenna 3D Radiation Pattern



2400MHz




2450MHz




2500MHz


5-2 Antenna 2D Radiation Pattern



Phi 0 2D



Phi 90 2D



Theta 90 2D

