

## FCC 47 CFR MPE REPORT

Snap One, LLC

ACI Snap One SUB

Model Number: SUB-8

FCC ID: 2AJAC-BLKSUB8

|               |   |
|---------------|---|
| Prepared for: | Snap One, LLC   |
|               | 1800 Continental Blvd Suite 200-300 Charlotte, North Carolina 28273 USA |
|               |   |
| Prepared By:  | EST Technology Co., Ltd.  |
|               | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China     |
|               | Tel: 86-769-83081888-808  |

|                 |                       |
|-----------------|-----------------------|
| Report Number:  | ESTE-R2110014         |
| Date of Test:   | Aug. 12~Sep. 30, 2021 |
| Date of Report: | Oct. 08, 2021         |



## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6  |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f)*                                | 6  |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6  |
| 300-1500              |                                   |                                   | F/300                                   | 6  |
| 1500-10000            |                                   |                                   | 5                                       | 6  |

##### (b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30   |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                | 30   |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30   |
| 300-1500              |                                   |                                   | F/1500                                  | 30   |
| 1500-10000            |                                   |                                   | 1.0                                     | 30   |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 2. Calculated Result and Limit

For 2.4G SRD

Ant gain= -4.50dBi

Ant numeric gain= 0.3548

Field strength = 99.15 dBuV/m@3m

$P = \{ [10^{(99.15/20)} / 10^6 * 3]^2 / (30 * 0.3548) \} * 1000 \text{mW} = 6.9524 \text{mW}$

$P_d = (30 * 6.9524 * 0.3548) / (377 * 20^2) = 0.00049 < 1$

**End of Test Report**