

Nemko Korea Co., Ltd.

155 & 159, Osan-Ro, Mohyeon-Myeon, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, 16885 KOREA, REPUBLIC OF

TEL:+82 31 330 1700 FAX:+82 31 330 2332

FCC and IC EVALUATION REPORT FOR CERTIFICATION

Applicant :

HMLink Co., Ltd.

#1715, 126, Beolmal-ro, Dongan-gu,
Anyang-si, Gyeonggi-do, Korea
(Post code : 14057)
Attn. : Leeg-hyun Jo

Dates of Issue : August 22, 2016

Test Report No. : NK-16-R-085

Test Site : Nemko Korea Co., Ltd.

FCC

2AJAZHM225

Contact Person

HMLink Co., Ltd.
#1715, 126, Beolmal-ro, Dongan-gu,
Anyang-si, Gyeonggi-do, Korea, 14057.
Leeg-hyun Jo
Telephone No. : +82-31-450-3578

Applied Standard: FCC 47 CFR Part 15.247 and IC RSS-247 Issue 1

Classification: FCC Part 15 Spread Spectrum Transmitter (DSS)

EUT Type: Bluepot

The device bearing the brand name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Aug 22, 2016

Tested By : Wonho Son
Engineer



Aug 22, 2016

Reviewed By : Deokha Ryu
Technical Manager

HMLink Co., Ltd.

Page 1 of 60

TABLE OF CONTENTS

| | |
|---|-----------|
| 1. Scope | 4 |
| 2. Introduction (Site Description) | 5 |
| 2.1 Test facility | 5 |
| 2.2 Accreditation and listing | 6 |
| 3. Test Conditions & EUT Information | 7 |
| 3.1 Operation During Test | 7 |
| 3.1.1 Table of test power setting | 7 |
| 3.1.2 Table of test channels | 7 |
| 3.1.3 Antenna TX mode information | 7 |
| 3.1.4 Additional Information Related to testing | 7 |
| 3.2 Support Equipment | 8 |
| 3.3 Setup Drawing | 8 |
| 3.4 EUT Information | 9 |
| 4. Summary of Test Results | 10 |
| 5. Recommendation / Conclusion | 11 |
| 6. Antenna Requirements | 11 |
| 7. Description of Test | 12 |
| 7.1 Conducted Emissions | 12 |
| 7.2 Radiated Emissions | 13 |
| 7.3 20 dB Bandwidth | 14 |
| 7.4 Carrier Frequency Separation | 14 |
| 7.5 Transmitter Average Time of Occupancy | 15 |
| 7.6 Number of Hopping Channels | 15 |
| 7.7 Maximum Peak Output Power | 16 |
| 7.8 Conducted Spurious Emissions | 16 |

| | |
|---|-----------|
| 8. Test Data | 17 |
| 8.1 Radiated Emissions | 17 |
| 8.2 Radiated Emissions | 20 |
| 8.3 20 dB Modulated Bandwidth | 22 |
| 8.4 Carrier Frequency Separation | 28 |
| 8.5 Transmitter Average Time of Occupancy | 31 |
| 8.6 Number of Hopping Channels | 33 |
| 8.7 Peak Output Power and E.I.R.P | 34 |
| 8.8 Conducted Spurious Emissions | 40 |
| 8.9 Radiated Spurious Emissions | 52 |
| 8.10 Radiated Bandedge | 55 |
| 9. Test Equipment | 58 |
| 10 Accuracy of Measurement | 59 |

1. SCOPE

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 15

Responsible Party : HMLink Co., Ltd.

Contact Person : Leeg-hyun Jo

Manufacturer : #1715, 126, Beolmal-ro, Dongan-gu, Anyang-si, Gyeonggi-do, Korea, 14057

- FCC ID: 2AJAZHM225
- Model: HM-225
- EUT Type: Bluepot
- Classification: Part 15 Spread Spectrum Transmitter
- Applied Standard: FCC 47 CFR Part 15 subpart C
- Test Procedure(s): ANSI C63.10-2013
- Dates of Test: July 04, 2016 ~ August 11, 2016
- Place of Tests: Nemko Korea Co., Ltd.

2. INTRODUCTION

2.1 Test facility

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2014), the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013) was used in determining radiated and conducted emissions emanating from **HMLink Co., Ltd. FCC ID : 2AJAZHM225**.

These measurement tests were conducted at **Nemko Korea Co., Ltd. EMC Laboratory**.

The site address 155 & 159, Osan-Ro, Mohyeon-Myeon, Cheoin-Gu, Yongin-Si, Gyeonggi-Do 16885 KOREA, REPUBLIC OF.

The area of Nemko Korea Corporation Ltd. EMC Test Site is located in a mountain area at 80 km (48 miles) southeast and Incheon International Airport (Incheon Airport), 30 km (18miles) south-southeast from central Seoul.

It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures.

The detailed description of the measurement facility was found to be in compliance with the requirements of ANSI C63.4-2014 according to §2.948.



Nemko Korea Co., Ltd.
EMC Lab.
155 & 159, Osan-Ro, Mohyeon-Myeon,
Cheoin-Gu, Yongin-Si, Gyeonggi-Do
16885 KOREA, REPUBLIC OF
Tel)+82-31-330-1700
Fax)+82-31-322-2332

Fig. 1. The map above shows the Seoul in Korea vicinity area.

The map also shows Nemko Korea Corporation Ltd. EMC Lab. and Incheon Airport.

2.2 Accreditation and listing

| Accreditation type | Accreditation number |
|---|--|
|  | CAB Accreditation for DOC Designation No. KR0026 |
|  | KOLAS Accredited Lab. (Korea Laboratory Accreditation Scheme) Registration No. 155 |
|  Industry Canada | Canada IC Registered site Site No. 2040E |
|  | VCCI registration site(RE/CE/Telecom CE) Member No. 2118 |
|  | EMC CBTL - |
|  | KCC(RRL)Designated Lab. Registration No. KR0026 |

3. TEST CONDITIONS & EUT INFORMATION

3.1 Operation During Test

The EUT is the transceiver which is the Bluetooth 4.0 module supporting BDR/EDR mode.

The Laptop was used to control the EUT to transmit the wanted TX channel by the testing program (Bluetest) which manufacturer supported. The EUT was tested at the lowest channel, middle channel and the highest channel with the maximum output power in accordance with the manufacturer's specifications. The worst data were recorded in the report.

3.1.1 Table of test power setting

| Mode | Frequency Band | Power Setting Level | |
|----------------------------------|---------------------|---------------------|----|
| GFSK/ $\pi/4$ DQPSK/ 8DPSK | 2402 MHz ~ 2480 MHz | Ext. Power | 0 |
| | | Int. Power | 50 |

3.1.2 Table of test channels

| Frequency band | Mode | Test Channel (CH) | Frequency (MHz) |
|----------------|----------------------------|-------------------|-----------------|
| 2.4 GHz | GFSK, $\pi/4$ DQPSK, 8DPSK | 0 | 2402 |
| | | 39 | 2441 |
| | | 78 | 2480 |

3.1.3 Antenna TX mode information:

| Frequency band | Mode | Antenna TX mode | Support MIMO |
|----------------|----------------------------|---|--|
| 2.4 GHz | GFSK, $\pi/4$ DQPSK, 8DPSK | <input checked="" type="checkbox"/> 1TX, <input type="checkbox"/> 2TX | <input type="checkbox"/> Yes, <input checked="" type="checkbox"/> No |


3.1.4. Additional Information Related to Testing

The cable and attenuator loss from 30MHz to 25GHz was reflected in spectrum analyzer with correction factor for all conducted testing.

3.2 Support Equipment

| | | |
|-----------------|--|---|
| EUT | HMLink Co., Ltd. Model : HM-225 | S/N: N/A |
| Laptop Computer | Samsung Electronics Co., Ltd. Model : NT-R580 1.5 m shielded pin connector cable | FCC DOC S/N : ZNU793BZ200566M |
| AC/DC Adapter | Chicony Power Technology Co., Ltd. Model : CPA09-004A 1.5 m unshielded power cable | FCC DOC S/N : CNBA4400242ADON81CD 0B9U |

3.3 Setup Drawing



3.4 EUT Information

The EUT is the **HMLink Co., Ltd.** FCC ID : **2AJAZHM225** This unit supports full qualified Bluetooth 4.0 with EDR standard system.

Specifications:

| | |
|-------------------------------|---|
| EUT Type | Smart Control |
| Model Name | HM-225 |
| RF Frequency | 2402 MHz ~ 2480 MHz |
| Peak Power Output (Conducted) | 2.19 dBm |
| FCC Classification | FCC Part 15 Spread Spectrum Transmitter (DSS) |
| Method/System | Frequency Hopping Spread Spectrum (FHSS) |
| Channel Number | 79 |
| Modulation | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Antenna Gain | -0.61 dBi (Peak) |
| Power | 5 Vdc (Charging), 3.7 Vdc (Battery) |
| Size (W x H x D) | About 13.6 cm x 7.2 cm X 2.5 cm |
| Weight | About 260 g |
| H/W Status | |
| S/W Status | |
| Remarks | - |

4. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specification:

| Name of Test | FCC Paragraph No. | Result | Remark |
|---|-------------------|----------|--------|
| Radiated Emission | 15.209 | Complies | |
| 20dB Bandwidth | 15.247(a)(1) | Complies | |
| Carrier Frequency Separation | 15.247(a)(1) | Complies | |
| Transmitter Average Time of Occupancy | 15.247(a)(1)(iii) | Complies | |
| Maximum Peak Conducted Output Power and E.I.R.P | 15.247(b)(1) | Complies | |
| Conducted Spurious Emission | 15.247(d) | Complies | |
| Radiated Spurious Emission | 15.247(d) | Complies | |
| Number of Hopping channels | 15.247(a)(1)(iii) | Complies | |

5. RECOMMENDATION/CONCLUSION

The data collected shows that the **HMLink Co., Ltd. FCC ID : 2AJAZHM225** is in compliance with Part 15.247 of the FCC Rule.

6. ANTENNA REQUIREMENTS

§15.203 of the FCC Rules part 15 Subpart C

: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The antenna of the **HMLink Co., Ltd. FCC ID : 2AJAZHM225** is **permanently attached** and there are no provisions for connection to an external antenna. It complies with the requirement of §15.203.

7. DESCRIPTION OF TESTS

7.1 Conducted Emissions

The Line conducted emission test facility is located inside a 4 x 7 x 2.5 meter shielded enclosure. It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6. A 1 m x 1.5 m wooden table 0.8 m height is placed 0.4 m away from the vertical wall and 1.5 m away from the side of wall of the shielded room. Rohde & Schwarz (ESH3-Z5) and (ESH2-Z5) of the 50 ohm/50 μ H Line Impedance Stabilization Network (LISN) are bonded to the shielded room. The EUT is powered from the Rohde & Schwarz LISN (ESH3-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH2-Z5). Power to the LISNs are filtered by high-current high insertion loss Power line filters. The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure. All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1 / 2 ". If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISNs. All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentinefashion) to a 1 meter length. Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 150 kHz to 30 MHz with 200 msec sweep time. The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCS30). The detector functions were set to CISPR quasi-peak mode & average mode. The bandwidth of receiver was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by; switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; whichever determined the worst case emission.

Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

7.2 Radiated Emissions

The measurement was performed at the test site that is specified in accordance with ANSI C63.10-2013.

The spurious emission was scanned from 9 kHz to 30 MHz using Loop Antenna(Rohde&Schwarz, HFH2-Z2) and 30 to 1000 MHz using Trilog broadband test antenna(Schwarzbeck, VULB 9163). Above 1 GHz, Horn antenna (Schwarzbeck BBHA 9120D: up to 18 GHz, Q-par Angus QSH20S20 : 18 to 26.5 GHz, QSH22K20: up to 40 GHz) was used.

For emissions testing at below 1GHz, The test equipment was placed on turntable with 0.8 m above ground. For emission measurements above 1 GHz, The test equipment was placed on turntable with 1.5 m above ground. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The EUT, cable, wire arrangement and mode of operation that has the highest amplitude relative to the limit was selected. Then, the turn table was rotated from 0° to 360° and an antenna mast was moved from 1 m to 4 m height to maximize the suspected highest amplitude signal. The final maximized level was recorded.


At frequencies below 1000 MHz, measurements performed using the CISPR quasi-peak detection. At frequencies above 1000 MHz, measurements performed using the peak and average measurement procedures described in ANSI C63.10-2013. Peak emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Trace mode = max hold. Average emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 1 kHz, Detector = Peak, Trace mode = max hold.

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009–0.490 | 2400/F(kHz) | 300 |
| 0.490–1.705 | 24000/F(kHz) | 30 |
| 1.705–30.0 | 30 | 30 |
| 30–88 | 100 | 3 |
| 88–216 | 150 | 3 |
| 216–960 | 200 | 3 |
| Above 960 | 500 | 3 |

Radiated Emissions Limits per 47 CFR 15.209(a) and Radiated Emissions Limits per RSS-GEN Issue 4 8.9

7.3 20 dB Bandwidth

Test Setup



Test Procedure

The transmitter is set to the Low, Middle, High channels is connected to the spectrum analyzer.

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 1% to 5% of the OBW

VBW = approximately 3 x RBW


Sweep = auto

Detector function = peak

Trace = max hold

7.4 Carrier Frequency Separation

Test Setup



Test Procedure

The EUT must have its hopping function enabled. The following spectrum analyzer setting is used.

Span = wide enough to capture the peaks of two adjacent channels

RBW \geq approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel

VBW \geq RBW

Sweep = auto


Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

7.5 Transmitter Average Time of Occupancy

Test Setup



Test Procedure

The transmitter output is connected to a spectrum analyzer. The following spectrum analyzer setting is used.

Span = Zero span, centered on a hopping channel

RBW $\gg 1 / T$, where T is the expected dwell time per channel.

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel


Detector function = Peak

Trace = Single sweep

Use the marker-delta function to determine the width of pulse

7.6 Number of Hopping Channels

Test Setup



Test Procedure

Span = The frequency band of operation.

RBW = less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW \geq RBW


Sweep = Auto

Detector function = Peak

Trace = Max hold

7.7 Maximum Peak Output Power

Test Setup



Test Procedure

The transmitter is set to the Low, Middle, High channels is connected to the spectrum analyzer.

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 20 dB bandwidth of the emission being measured

VBW \geq RBW


Sweep = auto

Detector function = peak

Trace = max hold

7.8 Conducted Spurious Emission

Test Setup



Test Procedure

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the Lowest, middle and highest channels.

RBW = 100kHz

VBW = 300kHz

Sweep = auto

Detector function = peak

Trace = max hold

8. TEST DATA

8.1 Conducted Emissions

FCC §15.207

Result

| Frequency (MHz) | Level (dB μ V) | | *) Factor (dB) | **) Line | Limit (dB μ V) | | Margin (dB) | |
|--------------------|--------------------|---------|-------------------|----------|--------------------|---------|-------------|---------|
| | Q-Peak | Average | | | Q-Peak | Average | Q-Peak | Average |
| 0.17 | 46.5 | 34.9 | 10.80 | L | 65.0 | 55.0 | 18.5 | 20.1 |
| 0.24 | 39.2 | 29.8 | 10.69 | N | 62.1 | 52.1 | 22.9 | 22.3 |
| 0.30 | 39.5 | 30.1 | 10.53 | L | 60.2 | 50.2 | 20.7 | 20.1 |
| 0.43 | 39.3 | 27.8 | 10.28 | L | 57.3 | 47.3 | 18.0 | 19.5 |
| 0.49 | 41.0 | 29.2 | 10.21 | N | 56.2 | 46.2 | 15.2 | 17.0 |
| 0.53 | 39.4 | 25.9 | 10.14 | L | 56.0 | 46.0 | 16.6 | 20.1 |

Line Conducted Emissions Tabulated Data

Notes:

1. Measurements using CISPR quasi-peak mode & average mode.
2. All modes of operation were investigated and the worst -case emission were reported.
See attached Plots.
3. *) Factor = LISN + Cable Loss
4. **) LINE : L = Line , N = Neutral
5. The limit is on the FCC Part section 15.207(a) and IC RSS-GEN issue4 8.8.

PLOTS OF EMISSIONS

- Conducted Emission at the Mains port (Line)

Nemko Korea (NK-16-R-085)

28 Jul 2016 15:13


Conducted Emissions

EUT: Bluepot
 Manuf: HMLink Co.,Ltd.
 Op Cond: a.c. 120 V, 60 Hz (BT)
 Operator: Wonho.Son
 Test Spec: FCC Part 15
 Comment: MODEL : HM-225
 LINE : Line - PE
 Result File: r086_I.dat :

| Scan Settings | | (1 Range) Frequencies | | | Receiver Settings | | | | |
|---------------|-------|-----------------------|-------|----------|-------------------|-------|--------|-------|--|
| Start | Stop | Step | IF BW | Detector | M-Time | Atten | Preamp | OpRge | |
| 150kHz | 30MHz | 3.9063kHz | 9kHz | PK+AV | 20msec | 20 dB | OFF | 60dB | |

| Transducer | No. | Start | Stop | Name |
|------------|-----|--------|-------|--------------|
| | 1 | 150kHz | 30MHz | ESH3_Z5_Line |

Final Measurement: Detectors: X QP / + AV
 Meas Time: 1sec
 Subranges: 8
 Acc Margin: 60 dB



PLOTS OF EMISSIONS

- Conducted Emission at the Mains port (Neutral)

Nemko Korea (NK-16-R-085)

28 Jul 2016 15:27


Conducted Emissions

EUT: Bluepot
 Manuf: HMLink Co.,Ltd.
 Op Cond: a.c. 120 V, 60 Hz (BT)
 Operator: Wonho.Son
 Test Spec: FCC Part 15
 Comment: MODEL : HM-225
 LINE : Neutral - PE
 Result File: r086_n.dat :

| Scan Settings | | (1 Range) | | | Receiver Settings | | | | |
|---------------|-------|-----------|-------|----------|-------------------|-------|--------|-------|--|
| Start | Stop | Step | IF BW | Detector | M-Time | Atten | Preamp | OpRge | |
| 150kHz | 30MHz | 3.9063kHz | 9kHz | PK+AV | 20msec | 20 dB | OFF | 60dB | |

| Transducer | No. | Start | Stop | Name |
|------------|-----|--------|-------|-----------------|
| | 1 | 150kHz | 30MHz | ESH3_Z5_Neutral |

Final Measurement: Detectors: X QP / + AV
 Meas Time: 1sec
 Subranges: 8
 Acc Margin: 60 dB



8. TEST DATA

8.2 Radiated Emissions

FCC §15.209

Result

| Frequency (MHz) | Reading (dB μ V/m) | Pol* (H/V) | Antenna Heights (cm) | Turntable Angles (°) | AF+CL+Amp (dB)** | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|--------------------|---------------------------|---------------|-------------------------|-------------------------|---------------------|--------------------------|-------------------------|----------------|
| 256.01 | 52.90 | H | 118 | 46 | -20.8 | 32.1 | 46.0 | 13.9 |
| 259.99 | 54.00 | H | 100 | 0 | -20.7 | 33.3 | 46.0 | 12.7 |
| 264.01 | 55.50 | H | 100 | 0 | -20.6 | 34.9 | 46.0 | 11.1 |
| 267.99 | 56.30 | H | 118 | 23 | -20.5 | 35.8 | 46.0 | 10.2 |
| 272.02 | 53.50 | H | 100 | 11 | -20.4 | 33.1 | 46.0 | 12.9 |
| 275.99 | 53.40 | H | 100 | 193 | -20.3 | 33.1 | 46.0 | 12.9 |

Radiated Measurements at 3 meters





Fig. 3. Limits at 3 meters

Notes:

1. All modes were measured and the worst-case emission was reported.
- 2 The radiated limits are shown on Figure 3. Above 1GHz the limit is 500 μ V /m.
3. *Pol. H = Horizontal, V = Vertical
4. **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
5. Measurements using CISPR quasi-peak mode below 1 GHz.
6. The radiated emissions testing were made by rotating the receive antenna with horizontal, Vertical polarization. The worst date was recorded.
7. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

PLOTS OF EMISSIONS

Worst Case : 2480 MHz (below 1GHz) GFSK modulation



TEST DATA

8.3 20 dB Modulated Bandwidth

FCC §15.247(a)(1)(iii)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

| Modulation Mode | Frequency (MHz) | Result (kHz) | Limit (kHz) |
|-----------------|-----------------|--------------|---------------|
| GFSK | 2402 | 941.6 | Non specified |
| GFSK | 2441 | 937.8 | Non specified |
| GFSK | 2480 | 937.9 | Non specified |
| $\pi/4$ DQPSK | 2402 | 1275.0 | Non specified |
| $\pi/4$ DQPSK | 2441 | 1247.0 | Non specified |
| $\pi/4$ DQPSK | 2480 | 1250.0 | Non specified |
| 8DPSK | 2402 | 1293.0 | Non specified |
| 8DPSK | 2441 | 1277.0 | Non specified |
| 8DPSK | 2480 | 1269.0 | Non specified |

PLOTS OF EMISSIONS

20 dB Bandwidth, Lowest Channel (2402 MHz, GFSK Mode)



20 dB Bandwidth, Middle Channel (2441 MHz, GFSK Mode)




PLOTS OF EMISSIONS

20 dB Bandwidth, Highest Channel (2480 MHz, GFSK Mode)




20 dB Bandwidth, Lowest Channel (2402 MHz, π/4DQPSK Mode)




PLOTS OF EMISSIONS

20 dB Bandwidth, Middle Channel (2441 MHz, $\pi/4$ DQPSK Mode)



20 dB Bandwidth, Highest Channel (2480 MHz, $\pi/4$ DQPSK Mode)



PLOTS OF EMISSIONS


20 dB Bandwidth, Lowest Channel (2402 MHz, 8DPSK Mode)



20 dB Bandwidth, Middle Channel (2441 MHz, 8DPSK Mode)



PLOTS OF EMISSIONS



TEST DATA

8.4 Carrier Frequency Separation

FCC §15.247(a)(1)

Test Mode : Set to Hopping mode

Result


| Modulation Mode | Carrier Frequency Separation (kHz) | Limit (2 / 3 of 20dB Bandwidth) (kHz) | Margin (kHz) |
|-----------------|------------------------------------|---------------------------------------|--------------|
| GFSK | 1020 | 627.7 | 392.3 |
| $\pi/4$ DQPSK | 1010 | 850.0 | 160.0 |
| 8DPSK | 1000 | 862 | 138.0 |

Note:


The EUT complies with the minimum channel separation requirement when it is operating **1x/EDR mode using 79 channels** and when operating in **AFH mode using 20 channels**.


PLOTS OF EMISSIONS

Carrier Frequency Separation (GFSK Mode)



Carrier Frequency Separation ($\pi/4$ DQPSK Mode)



PLOTS OF EMISSIONS**Carrier Frequency Separation (8DPSK Mode)**

TEST DATA


8.5 Transmitter Average Time of Occupancy

FCC §15.247(a)(1)

Test mode : Set to Hopping mode

Result

| Mode | Pulse width (ms) | ^{*)} Numbers of slots | ^{**) Average time of Occupancy (ms)} | Limit (ms) | Margin (ms) |
|--------|------------------|--------------------------------|---|------------|-------------|
| 1x/EDR | 2.90 | 106.7 | 309.4 | ≤400 | 90.6 |
| AFH | 2.90 | 53.3 | 154.7 | ≤400 | 245.3 |



1x/EDR mode

- 1) This result was measured at DH5 mode in **1x/EDR mode**, which has longest time in one transmission burst.
- 2) Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s and 79 hopping channels.
- 3) The average time of occupancy in the specified 31.6 second period (79 channels x 0.4 s) is equal to pulse width x (hopping rate / 6) / 79 x (0.4 x hopping channels).
- 4) *) Numbers of slots in 31.6 sec = $(1600 / 6) / 79 \times 31.6$
- 5) **) Average time of Occupancy = $2.89 \text{ ms} \times 106.7 = 309.4 \text{ ms}$

AFH mode

- 1) This result was measured at DH5 mode in **AFH mode**, which has longest time in one transmission burst.
- 2) Bluetooth AFH mode has a channel hopping rate of 800 hops/s and 20 hopping channels.
- 3) The average time of occupancy in the specified 8 second period (20 channels x 0.4 s) is equal to pulse width x (hopping rate / 6) / 20 x (0.4 x hopping channels).
- 4) *) Numbers of slots in 20 sec = $(800 / 6) / 20 \times 8$
- 5) **) Average time of Occupancy = $2.90 \text{ ms} \times 53.33 = 154.7 \text{ ms}$

TEST DATA

8.6 Number of Hopping Channels


FCC §15.247(a)(1)(iii)

Test mode : Set to Hopping mode


Result

The EUT complies with the minimum number of hopping channels when it is operating **1x/EDR mode using 79 channels** and when operating in **AFH mode using 20 channels**.

Top half of Authorized band(1x mode)



Bottom half of Authorized band(1x mode)



TEST DATA

8.7 Peak Output Power and E.I.R.P

FCC §15.247(b)(1), IC RSS-247 Issue 1, 5.4(2)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

| Modulation | Frequency (MHz) | Peak Power (dBm) | Limit (dBm) | E.I.R.P* (dBm) | E.I.R.P Limit (dB) | Result |
|---------------|-----------------|------------------|-------------|----------------|--------------------|----------|
| GFSK | 2402 | -2.29 | 30.00 | -2.90 | 36.00 | Complies |
| GFSK | 2441 | 1.53 | 30.00 | 0.92 | 36.00 | Complies |
| GFSK | 2480 | 2.19 | 30.00 | 1.58 | 36.00 | Complies |
| $\pi/4$ DQPSK | 2402 | -2.82 | 30.00 | -3.43 | 36.00 | Complies |
| $\pi/4$ DQPSK | 2441 | 0.97 | 30.00 | 0.36 | 36.00 | Complies |
| $\pi/4$ DQPSK | 2480 | 1.64 | 30.00 | 1.03 | 36.00 | Complies |
| 8DPSK | 2402 | -2.81 | 30.00 | -3.42 | 36.00 | Complies |
| 8DPSK | 2441 | 1.03 | 30.00 | 0.42 | 36.00 | Complies |
| 8DPSK | 2480 | 1.69 | 30.00 | 1.08 | 36.00 | Complies |

Note:

The following formula was used for spectrum offset:

Spectrum offset (dB) = Attenuator (dB) + Cable Loss (dB) + SMA Type Connector Loss (dB)

*) E.I.R.P was calculated by following equation according to KDB412172 D01 Determining ERP and EIRP
v01

$$E.I.R.P = P_T + G_T - L_c$$


P_T = Peak output power (dBm)

G_T = Gain of the transmitting antenna in dB, Peak antenna gain is -0.61 dB.


L_c = Signal attenuation in the connecting cable between the transmitter and antenna in dB. This factor of an integral antenna is negligible.

PLOT OF TEST DATA

Maximum Peak Output Power, Lowest channel (2402 MHz, GFSK mode)




Maximum Peak Output Power, Middle channel (2441 MHz, GFSK mode)




PLOT OF TEST DATA

Maximum Peak Output Power, Highest channel (2480 MHz, GFSK mode)




Maximum Peak Output Power, Lowest channel (2402 MHz, $\pi/4$ DQPSK)




PLOT OF TEST DATA

Maximum Peak Output Power, Middle channel (2441 MHz, $\pi/4$ DQPSK)




Maximum Peak Output Power, Highest channel (2480 MHz, $\pi/4$ DQPSK)




PLOT OF TEST DATA


Maximum Peak Output Power, Lowest channel (2402 MHz, 8DPSK)



Maximum Peak Output Power, Middle channel (2441 MHz, 8DPSK)



PLOT OF TEST DATA



TEST DATA

8.8 Conducted Spurious Emission

FCC §15.247(d), IC RSS-247 Issue 1, 5.5

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result


| Modulation Mode | Frequency (MHz) | Result | Limit (dBc) |
|-----------------|-----------------|------------------|-------------|
| GFSK | 2402 | More than 20 dBc | 20 |
| GFSK | 2441 | More than 20 dBc | 20 |
| GFSK | 2480 | More than 20 dBc | 20 |
| $\pi/4$ DQPSK | 2402 | More than 20 dBc | 20 |
| $\pi/4$ DQPSK | 2441 | More than 20 dBc | 20 |
| $\pi/4$ DQPSK | 2480 | More than 20 dBc | 20 |
| 8DPSK | 2402 | More than 20 dBc | 20 |
| 8DPSK | 2441 | More than 20 dBc | 20 |
| 8DPSK | 2480 | More than 20 dBc | 20 |

Note:


The cable and attenuator loss from 30 MHz to 25 GHz was reflected in spectrum analyzer with correction factor for the spurious emissions test.

PLOT OF TEST DATA

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2402 MHz, GFSK Mode)




Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2441 MHz, GFSK Mode)




PLOT OF TEST DATA

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2480 MHz, GFSK Mode)




Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2402 MHz, π/4DQPSK Mode)




PLOT OF TEST DATA

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz(2441 MHz, π/4DQPSK Mode)




Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz(2480 MHz, π/4DQPSK Mode)




PLOT OF TEST DATA


Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2402 MHz, 8DPSK Mode)



Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2441 MHz, 8DPSK Mode)




PLOT OF TEST DATA




PLOT OF TEST DATA

Band Edge Lowest Channel (2402 MHz, GFSK, Non-hopping mode)




Band Edge Lowest Channel (2402 MHz, GFSK, Hopping mode)




PLOT OF TEST DATA

Band Edge Highest Channel (2480 MHz, GFSK, Non-hopping mode)




Band Edge Highest Channel (2480 MHz, GFSK, Hopping mode)




PLOT OF TEST DATA

Band Edge Lowest Channel(2402 MHz, $\pi/4$ DQPSK, Non-hopping mode)




Band Edge Lowest Channel(2402 MHz, $\pi/4$ DQPSK, Hopping mode)




PLOT OF TEST DATA

Band Edge Highest Channel(2480 MHz, $\pi/4$ DQPSK, Non-hopping mode)




Band Edge Highest Channel(2480 MHz, $\pi/4$ DQPSK, Hopping mode)




PLOT OF TEST DATA

Band Edge Lowest Channel(2402 MHz, 8DPSK, Non-hopping mode)




Band Edge Lowest Channel(2402 MHz, 8DPSK, Hopping mode)




PLOT OF TEST DATA

Band Edge Highest Channel(2480 MHz, 8DPSK, Non-hopping mode)



Band Edge Highest Channel(2480 MHz, 8DPSK, Hopping mode)



TEST DATA

8.9 Radiated Spurious Emission

FCC §15.247(d)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result

Lowest Channel

| Frequency (MHz) | Reading (dB μ V) | Pol* (H/V) | mode | AF+CL+Amp (dB)** | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------------|------------|---------|------------------|-----------------------|----------------------|-------------|
| 4804.38 | 41.3 | H | peak | 9.4 | 50.7 | 74.0 | 23.3 |
| 4804.38 | 32.0 | H | average | 9.4 | 41.4 | 54.0 | 12.6 |

Middle Channel


| Frequency (MHz) | Reading (dB μ V) | Pol* (H/V) | mode | AF+CL+Amp (dB)** | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------------|------------|---------|------------------|-----------------------|----------------------|-------------|
| 4881.88 | 40.7 | H | peak | 9.7 | 50.4 | 74.0 | 23.6 |
| 4881.88 | 32.6 | H | average | 9.7 | 42.3 | 54.0 | 11.7 |

Highest Channel

| Frequency (MHz) | Reading (dB μ V) | Pol* (H/V) | mode | AF+CL+Amp (dB)** | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------------|------------|---------|------------------|-----------------------|----------------------|-------------|
| 4959.38 | 41.2 | H | peak | 9.9 | 51.1 | 74.0 | 22.9 |
| 4959.38 | 32.4 | H | average | 9.9 | 42.3 | 54.0 | 11.7 |

Notes:

1. *Pol. H = Horizontal V = Vertical
2. **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Other spurious was under 20 dB below Fundamental.
4. GFSK modulation mode was the worst condition.
5. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization. The worst data was recorded.
6. Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.
7. Average emissions were measured using RBW = 1 MHz, VBW = 1 kHz, Detector = Peak.
8. The spectrum was measured from 9 kHz to 10th harmonic and the worst-case emissions were reported. No significant emissions were found beyond the 2nd harmonic for this device.

PLOTS OF EMISSIONS**Worst Case : 2480 MHz GFSK modulation : 1 GHz to 8 GHz**

TEST DATA

8.10 Radiated Bandedge

FCC §15.247(d), IC RSS-247 Issue 1, 5.5

Test Mode : Set to Lowest channel, Highest channel

Result

Lowest and Highest Channels


| Frequency (MHz) | Reading (dB μ V) | Pol* (H/V) | mode | AF+CL+Amp (dB)** | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------------|------------|---------|------------------|-----------------------|----------------------|-------------|
| 2390.00 | 45.2 | H | peak | 0.4 | 45.6 | 74.0 | 28.4 |
| 2390.00 | 34.3 | H | average | 0.4 | 34.7 | 54.0 | 19.3 |
| 2483.50 | 64.6 | H | peak | 0.8 | 65.4 | 74.0 | 8.6 |
| 2483.50 | 64.2 | H | average | 0.8 | ***33.9 | 54.0 | 20.1 |

Note:


1. *Pol. H = Horizontal V = Vertical
2. **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Other spurious was under 20 dB below Fundamental.
4. *** Duty Cycle Correction Factor Calculation (Worst case : AFH mode)
 - Channel hop rate = 800 hops/second
 - Adjusted channel hop rate for DH5 mode = 133.33 hops/second
 - Time per channel hop = 1/133.33 hops/second = 7.50 ms
 - Time to cycle through all channels = 7.50 x 20 channels = 150 ms
 - Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s)
 - Worst case dwell time = 7.50 ms
 - Duty cycle correction factor = $20\log_{10}(7.50\text{ms}/100\text{ms}) = -22.5 \text{ dB}$
5. GFSK modulation mode was the worst condition.
6. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization. The worst data was recorded.
7. Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.
8. Average emissions were measured using RBW = 1 MHz, VBW = 1kHz, Detector = Peak



PLOT OF TEST DATA

Restricted Band Spurious Emissions, Lowest channel(GFSK, Peak)



Restricted Band Spurious Emissions, Lowest channel(GFSK, Average)



PLOT OF TEST DATA**Restricted Band Spurious Emissions, Highest channel (GFSK, Peak)****Restricted Band Spurious Emissions, Highest channel (GFSK, Average)*****

9. TEST EQUIPMENT

| No. | Instrument | Manufacturer | Model | Serial No. | Calibration Date | Calibration Interval |
|-----|-------------------------------|---------------|-----------|-----------------------|------------------|----------------------|
| 1 | *Test Receiver | R & S | ESU 40 | 100202 | Apr. 04 2016 | 1 year |
| 2 | *Test Receiver | R & S | ESCS30 | 100302 | Oct. 06 2015 | 1 year |
| 3 | *Attenuator | PASTERNACK | PE7395-10 | 1441 | Jan. 19 2016 | 1 year |
| 4 | *Attenuator | FAIRVIEW | SA3N5W-06 | N/A | Apr. 04 2016 | 1 year |
| 5 | *Attenuator | FAIRVIEW | SA3N5W-10 | N/A | Apr. 04 2016 | 1 year |
| 6 | Attenuator | WEINSCHEL | 56-10 | 58765 | Oct. 02 2015 | 1 year |
| 7 | *Amplifier | R & S | SCU 01 | 10030 | Apr. 04 2016 | 1 year |
| 8 | *Amplifier | R & S | SCU18 | 10065 | Apr. 04 2016 | 1 year |
| 9 | *Amplifier | R & S | SCU26 | 10011 | Jul. 15 2016 | 1 year |
| 10 | Amplifier | R & S | SCU40 | 10008 | Jul. 15 2016 | 1 year |
| 11 | *Pre Amplifier | HP | 8449B | 3008A00107 | Jan. 07 2016 | 1 year |
| 12 | Spectrum Analyzer | R & S | FSW43 | 100732 | Apr. 05 2016 | 1 year |
| 13 | *Spectrum Analyzer | Agilent | N9020A | MY51110087 | Oct. 15 2015 | 1 year |
| 14 | *Spectrum Analyzer | R&S | FSP40 | 100361 | Jul. 15 2016 | 1 year |
| 15 | *Loop Antenna | R & S | HFH2-Z2 | 100279 | Feb. 22 2016 | 2 year |
| 16 | *Horn Antenna | SCHWARZBECK | BBHA9120D | 9120D-474 | Sep. 01 2014 | 2 year |
| 17 | *Horn Antenna | Q-par Angus | QSH20S20 | 8179 | Apr. 30 2015 | 2 year |
| 18 | Horn Antenna | Q-par Angus | QSH22K20 | 8180 | Apr. 30 2015 | 2 year |
| 19 | *Trilog-Broadband Antenna | SCHWARZBECK | VULB 9163 | 9163-423 | Nov. 04 2015 | 2 year |
| 20 | *LISN | R & S | ESH3-Z5 | 833874/006 | Oct. 06 2015 | 1 year |
| 21 | *Controller | INNCO | CO2000-G | CO2000/562/23890210/L | N/A | N/A |
| 22 | *Turn Table | INNCO | DT3000-3T | N/A | N/A | N/A |
| 23 | *Antenna Mast | INNCO | MA4000-EP | N/A | N/A | N/A |
| 24 | *Open Switch And Control Unit | R & S | OSP-120 | 100015 | N/A | N/A |
| 25 | *Anechoic Chamber | Seo-Young EMC | N/A | N/A | N/A | N/A |
| 26 | *Position Controller | INNCO | CO2000 | 12480406/L | N/A | N/A |
| 27 | *Turn Table | INNCO | DS1200S | N/A | N/A | N/A |
| 28 | *Antenna Mast | INNCO | MA4000 | N/A | N/A | N/A |
| 29 | *Anechoic Chamber | Seo-Young EMC | N/A | N/A | N/A | N/A |
| 30 | Shielded Room | Seo-Young EMC | N/A | N/A | N/A | N/A |
| 31 | *Open Switch And Control Unit | R & S | OSP-120 | 100081 | N/A | N/A |

*) Test equipment used during the test

10. ACCURACY OF MEASUREMENT

The Measurement Uncertainties stated were calculated in accordance with the requirements of measurement uncertainty contained in CISPR 16-4-2 with the confidence level of 95%

1. Conducted Uncertainty Calculation

| Source of Uncertainty | Xi | Uncertainty of Xi | | Coverage factor k | $u(Xi)$ (dB) | Ci | $Ci u(Xi)$ (dB) |
|----------------------------------|--|---------------------|--------------------------|------------------------|--------------|------|-----------------|
| | | Value (dB) | Probability Distribution | | | | |
| Receiver reading | RI | ± 0.1 | normal 1 | 1.000 | 0.1 | 1 | 0.1 |
| Attenuation AMN-Receiver | LC | ± 0.08 | normal 2 | 2.000 | 0.04 | 1 | 0.04 |
| AMN Voltage division factor | $LAMN$ | ± 0.8 | normal 2 | 2.000 | 0.4 | 1 | 0.4 |
| Sine wave voltage | $dVSW$ | ± 2.00 | normal 2 | 2.000 | 1.00 | 1 | 1.00 |
| Pulse amplitude response | $dVPA$ | ± 1.50 | rectangular | 1.732 | 0.87 | 1 | 0.87 |
| Pulse repetition rate response | $dVPR$ | ± 1.50 | rectangular | 1.732 | 0.87 | 1 | 0.87 |
| Noise floor proximity | $dVNF$ | ± 0.00 | - | - | 0.00 | 1 | 0.00 |
| AMN Impedance | dZ | ± 1.80 | triangular | 2.449 | 0.73 | 1 | 0.73 |
| ⓐ Mismatch | M | $+ 0.70$ | U-Shaped | 1.414 | 0.49 | 1 | 0.49 |
| ⓑ Mismatch | M | $- 0.80$ | U-Shaped | 1.414 | - 0.56 | 1 | - 0.56 |
| Measurement System Repeatability | RS | 0.05 | normal 1 | 1.000 | 0.05 | 1 | 0.05 |
| Remark | ⓐ: AMN-Receiver Mismatch : + ⓑ: AMN-Receiver Mismatch : - | | | | | | |
| Combined Standard Uncertainty | Normal | | | ± 1.88 | | | |
| Expended Uncertainty U | Normal ($k = 2$) | | | ± 3.76 | | | |

2. Radiation Uncertainty Calculation

| Source of Uncertainty | Xi | Uncertainty of Xi | | Coverage factor k | u(Xi) (dB) | Ci | Ci u(Xi) (dB) |
|--|----------------|-------------------|--------------------------|-------------------|------------|----|---------------|
| | | Value (dB) | Probability Distribution | | | | |
| Measurement System Repeatability | RI | 0.34 | normal 1 | 1.00 | 0.34 | 1 | 0.34 |
| Receiver reading | dVsw | ± 0.02 | normal 2 | 2.00 | 0.01 | 1 | 0.01 |
| Sine wave voltage | dVpa | ± 0.17 | normal 2 | 2.00 | 0.09 | 1 | 0.09 |
| Pulse amplitude response | dVpr | ± 0.92 | normal 2 | 2.00 | 0.46 | 1 | 0.46 |
| Pulse repetition rate response | dVnf | ± 0.35 | normal 2 | 2.00 | 0.18 | 1 | 0.18 |
| Noise floor proximity | AF | ± 0.50 | normal 2 | 2.00 | 0.25 | 1 | 0.25 |
| Antenna Factor Calibration | CL | ± 2.00 | rectangular | $\sqrt{3}$ | 1.15 | 1 | 1.15 |
| Cable Loss | AD | ± 1.00 | normal 2 | 2.00 | 0.50 | 1 | 0.50 |
| Antenna Directivity | AH | ± 0.00 | rectangular | $\sqrt{3}$ | 0.00 | 1 | 0.00 |
| Antenna Factor Height Dependence | AP | ± 2.00 | rectangular | $\sqrt{3}$ | 1.15 | 1 | 1.15 |
| Antenna Phase Centre Variation | AI | ± 0.20 | rectangular | $\sqrt{3}$ | 0.12 | 1 | 0.12 |
| Antenna Factor Frequency Interpolation | SI | ± 0.25 | rectangular | $\sqrt{3}$ | 0.14 | 1 | 0.14 |
| Site Imperfections | DV | ± 4.00 | triangular | $\sqrt{6}$ | 1.63 | 1 | 1.63 |
| Measurement Distance Variation | Dbal | ± 0.60 | rectangular | $\sqrt{3}$ | 0.35 | 1 | 0.35 |
| Antenna Balance | DCross | ± 0.90 | rectangular | $\sqrt{3}$ | 0.52 | 1 | 0.52 |
| Cross Polarisation | M | ± 0.00 | rectangular | $\sqrt{3}$ | 0.00 | 1 | 0.18 |
| Mismatch | M | + 0.98 - 1.11 | U-Shaped | $\sqrt{2}$ | 0.74 | 1 | 0.74 |
| EUT Volume Diameter | M | 0.33 | normal 1 | 1.00 | 0.33 | 1 | 0.11 |
| Remark | | | | | | | |
| Combined Standard Uncertainty | Normal | | | | | | |
| Expended Uncertainty U | Normal (k = 2) | | | | | | |