

Report No. : BLA-EMC-201907-A24-01

# FCC Report (Bluetooth)

Product Name : Basic Pro

Trade mark : N/A : PBT

FCC ID : 2AJDL-PBT

Report Number : BLA-EMC-201907-A24-01

Date of sample receipt : July 10, 2019

**Date of Test** : July 10, 2019 - July 23, 2019

Date of Issue : July 31, 2019

Test standard : FCC CFR Title 47 Part 15 Subpart C Section

15.247

Test result : PASS

### Prepared for:

Innate Devices, LLC. (DBA Plugfones) 2057 W 700 S, Suite 200, Springville, UT 84663, USA

Prepared by:

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.
IOT Test Centre of BlueAsia
No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen,
China

TEL: +86-755-28682673

FAX: +86-755-28682673

Compiled by:

ZUSON

Review by: Dramel - Wei

Approved by:

Date: July 31, 201



Report No. : BLA-EMC-201907-A24-01 Page 2 of 40

## 2 Version

Version No.	Date	Description
00	July 31, 2019	Original

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd. IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01

## Page 3 of 40

## 3 Contents

	raye
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	
5.1 GENERAL DESCRIPTION OF EUT	5 7 7 7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT. 7.2 CONDUCTED EMISSIONS. 7.3 CONDUCTED PEAK OUTPUT POWER. 7.4 20DB EMISSION BANDWIDTH. 7.5 CARRIER FREQUENCIES SEPARATION. 7.6 HOPPING CHANNEL NUMBER. 7.7 DWELL TIME. 7.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE. 7.9 BAND EDGE 7.9.1 Conducted Emission Method. 7.9.2 Radiated Emission Method. 7.10 SPURIOUS EMISSION 7.10.1 Conducted Emission Method. 7.10.2 Radiated Emission Method.	
8 TEST SETUP PHOTO	
9 EUT CONSTRUCTIONAL DETAILS	34
40 ADDENDIY	40

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No. : BLA-EMC-201907-A24-01 Page 4 of 40

### 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(iii)	Pass
Dwell Time	15.247 (a)(iii)	Pass
Pseudorandom Frequency Hopping Sequence	15.247(a)(1)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according ANSI C63.10:2013

### **Measurement Uncertainty**

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 5 of 40

## 5 General Information

## 5.1 General Description of EUT

Product Name:	Basic Pro
Model No.:	PBT
Test Model No.:	PBT
	are identical in the same PCB layout, interior structure and electrical circuits. name for commercial purpose.
Serial No.:	N/A
Sample(s) Status	Engineer sample
Hardware:	V1.1
Software:	V1.5
Operation Frequency:	2402MHz-2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, π/4-DQPSK, 8-DPSK
Antenna Type:	Internal Antenna
Antenna gain:	5.0dBi
Power supply:	DC 3.7V

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 6 of 40

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 7 of 40

#### 5.2 Test mode

Transmitting mode Keep the EUT in continuously transmitting mode.

Remark: Full battery is used during all test except ac conducted emission, DH1, DH3, DH5 all have been tested, only worse case is reported.

#### 5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • FCC — Designation No.: CN1252

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Designation CN1252.

#### •ISED — CAB identifier No.: CN0028

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd has been registered by Certification and Engineering Bureau of ISED for radio equipment testing with CAB identifier CN0028

#### 5.4 Test Location

All tests were performed at:

All tests were performed at:

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.

#### 5.5 Other Information Requested by the Customer

None

### 5.6 Description of Support Units

Manufacturer	Description	Model	Serial Number
UGREEN	Adapter	CD112	20358
Lenovo Notebook computer		E470C	PF-10FB5C

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 8 of 40

## 6 Test Instruments list

Radi	Radiated Emission:							
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)		
1	3m SAC	SKET	9m*6 m*6m	966	06-10-2018	06-09-2023		
2	Broadband Antenna	SCHWARZBECK	VULB9168	00836	07-14-2018 07-14-2019	07-13-2019 07-13-2020		
				P:00227 01892	07-14-2019	07-13-2020		
3	Horn Antenna	SCHWARZBECK	9120D	P:00331	07-14-2019	07-13-2020		
4	EMI Test Software	EZ	EZ	N/A	N/A	N/A		
5	Pre-amplifier	SKET	N/A	N/A	07-19-2018 07-19-2019	07-18-2019 07-18-2020		
6	Spectrum analyzer	Rohde & Schwarz	FSP40	100817	05-24-2019	05-23-2020		
7	EMI Test Receiver	Rohde & Schwarz	ESR7	101199	03-21-2019	03-20-2020		
8	Controller	SKET	N/A	N/A	N/A	N/A		
9	Vector Signal Generator	Agilent	E4438C	MY45092582	05-24-2019	05-23-2020		
10	Signal Generator	Agilent	E8257D	MY44320250	05-24-2019	05-23-2020		
11	Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A		
12	Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A		
13	Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A		

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd. IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 9 of 40

Conduc	Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)	
1	EMI Test Receiver	Rohde & Schwarz	ESPI3	101082	06-10-2019	06-09-2020	
2	LISN	CHASE	MN2050D	1447	12-18-2018	12-17-2019	
3	LISN	Rohde & Schwarz	ENV216	3560.6550.15	07-19-2018 07-19-2019	07-18-2019 07-18-2020	
4	EMI Test Software	EZ	EZ	N/A	N/A	N/A	
5	Temperature Humidity Chamber	Mingle	TH101B	N/A	07-19-2018 07-19-2019	07-18-2019 07-18-2020	
6	Coaxial Cable	BlueAsia	BLA-XC-05	N/A	N/A	N/A	

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Spectrum Analyzer	Agilent	N9030A	MY50510123	05-24-2019	05-23-2020
2	Spectrum analyzer	Rohde & Schwarz	FSP40	100817	05-24-2019	05-23-2020
3	MXA Signal Analyzer	Agilent	N9020A	MY49100060	12-18-2018	12-17-2019
4	Vector Signal Generator	Agilent	N5182A	MY49060650	12-18-2018	12-17-2019
5	Vector Signal Generator	Agilent	E4438C	MY45092582	05-24-2019	05-23-2020
6	Signal Generator	Agilent	E8257D	MY44320250	05-24-2019	05-23-2020
7	Power Sensor	D.A.R.E	RPR3006W	17I00015SNO27	05-24-2019	05-23-2020
8	Power Sensor	D.A.R.E	RPR3006W	17I00015SNO28	05-24-2019	05-23-2020
9	DC Power Supply	LODESTAR	LP305DE	N/A	07-19-2018 07-19-2019	07-18-2019 07-18-2020
10	Temperature Humidity Chamber	Mingle	TH101B	N/A	07-19-2018 07-19-2019	07-18-2019 07-18-2020

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 10 of 40

#### 7 Test results and Measurement Data

#### 7.1 Antenna requirement

Standard requirement: FCC Part15 C Section 15.203 /247(c)

#### 15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### 15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### E.U.T Antenna:

The antenna is chip antenna, the best case gain of the antenna is 5.0dBi



Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 11 of 40

### 7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	150KHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sv	veep time=auto					
Limit:	Limit (dRuV)						
	Prequency range (MHZ)  Quasi-peak  Average						
	0.15-0.5 66 to 56* 56 to 46*						
	0.5-5 56 46						
	5-30	60	50				
Test setup.	* Decreases with the logarithm	i of the frequency.					
Test setup:	Reference Plane		_				
	AUX Equipment E.U.T  Test table/Insulation plane  Remark: E.U.T. Equipment Under Test LISN: Line Impedence Stabilization Network Test table height=0.8m	Filter — AC pow					
Test procedure:	<ol> <li>The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</li> </ol>						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test results:	Pass						

#### Measurement data:

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 12 of 40


Line:

EUT: Basic Pro Probe: L1

Model: PBT Power Source: AC120V/60Hz

Mode: BT mode Test by: Lucas

**Temp./Hum.(%H)**: 26°C/60%RH



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	0.4500	27.31	9.70	37.01	56.88	-19.87	QP
2	0.4500	19.40	9.70	29.10	46.88	-17.78	AVG
3	0.5820	27.86	9.74	37.60	56.00	-18.40	QP
4	0.5820	20.04	9.74	29.78	46.00	-16.22	AVG
5	0.6260	31.87	9.72	41.59	56.00	-14.41	QP
6 *	0.6260	23.78	9.72	33.50	46.00	-12.50	AVG
7	0.8820	27.51	9.75	37.26	56.00	-18.74	QP
8	0.8820	19.56	9.75	29.31	46.00	-16.69	AVG
9	2.4580	21.35	9.81	31.16	56.00	-24.84	QP
10	2.4580	12.15	9.81	21.96	46.00	-24.04	AVG
11	7.4380	24.59	9.87	34.46	60.00	-25.54	QP
12	7.4380	13.77	9.87	23.64	50.00	-26.36	AVG

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 13 of 40


#### Neutral:

EUT: Basic Pro Probe: N

Model: PBT Power Source: AC120V/60Hz

Mode: BT mode Test by: Lucas

**Temp./Hum.(%H):** 26 °C/60%RH



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.4820	19.97	9.72	29.69	56.30	-26.61	QP
2		0.4820	13.52	9.72	23.24	46.30	-23.06	AVG
3		0.6340	25.01	9.74	34.75	56.00	-21.25	QP
4	*	0.6340	15.84	9.74	25.58	46.00	-20.42	AVG
5		0.8460	21.26	9.75	31.01	56.00	-24.99	QP
6		0.8460	13.62	9.75	23.37	46.00	-22.63	AVG
7		2.1300	18.91	9.86	28.77	56.00	-27.23	QP
8		2.1300	9.37	9.86	19.23	46.00	-26.77	AVG
9		7.5180	24.09	9.85	33.94	60.00	-26.06	QP
10		7.5180	12.02	9.85	21.87	50.00	-28.13	AVG
11		15.9940	12.92	10.00	22.92	60.00	-37.08	QP
12		15.9940	4.89	10.00	14.89	50.00	-35.11	AVG

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 14 of 40

#### Notes:

- 1. An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3. Final Level =Receiver Read level +Correct Factor
- 4. Correct Factor = LISN Factor + Cable Loss

### 7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013
Limit:	21dBm(for GFSK),21dBm(for EDR)
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

#### **Measurement Data**

Reference to the AppendixC: Maximum conducted output power

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 15 of 40

#### 7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)	
Test Method:	ANSI C63.10:2013	
Limit:	N/A	
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane	
Test Instruments:	Refer to section 6.0 for details	
Test mode:	Refer to section 5.2 for details	
Test results:	Pass	

#### **Measurement Data**

Reference to the AppendixA: 20dBEmission Bandwidth

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No. : BLA-EMC-201907-A24-01 Page 16 of 40

## 7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)				
Test Method:	ANSI C63.10:2013				
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak				
Limit:	GFSK & Pi/4QPSK & 8-DPSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)				
Test setup:	Spectrum Analyzer  Non-Conducted Table  Ground Reference Plane				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

#### **Measurement Data**

Reference to the AppendixD: Carrier frequency separation

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 17 of 40

## 7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)		
Test Method:	ANSI C63.10:2013		
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz,		
	Detector=Peak		
Limit:	15 channels		
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane		
Test Instruments:	Refer to section 6.0 for details		
Test mode:	Refer to section 5.2 for details		
Test results:	Pass		

### **Measurement Data:**

Reference to the AppendixF: Number of hopping channels

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 18 of 40

### 7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)				
Test Method:	ANSI C63.10:2013				
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak				
Limit:	0.4 Second				
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

#### **Measurement Data**

Reference to the AppendixE: Time of occupancy

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 19 of 40

### 7.8 Pseudorandom Frequency Hopping Sequence

#### Test Requirement: FCC Part15 C Section 15.247 (a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

#### **EUT Pseudorandom Frequency Hopping Sequence**


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29-1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 20 of 40

## 7.9 Band Edge

#### 7.9.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)				
Test Method:	ANSI C63.10:2013				
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak				
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.				
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

#### **Measurement Data**

Reference to the AppendixG:Band edge measurements

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 21 of 40

#### 7.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	All restriction band have been tested, and 2310MHz to 2390MHz, 2483.5MHz to 2500MHz band is the worse case					
Test site:	Measurement Distance: 3m					
Receiver setup:	Frequency Detector		RBW	VBW	Remark	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
	Above 1G112	Peak	1MHz	10Hz	Average Value	
Limit:	Freque	ency	Limit (dBuV/m @3m)		Remark	
	Above 1	IGHz	54.0 74.0		Average Value Peak Value	
Test setup:	Tum Table < lm 4m > v      Company   Receiver   Preamplifier      Receiver   Preamplifier     Receiver   Preamplifier     Receiver   Preamplifier     Preamplifier   Preamplifier     Prea					
Test Procedure:	<ol> <li>The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or</li> </ol>					
Test Instruments:	average method as specified and then reported in a data sheet.  Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01

Page 22 of 40

#### Remark:

1. During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the 8-DPSK modulation which it is worse case.

Test channel: Lowest

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	57.38	-14.56	42.82	74.00	-31.18	Horizontal
2390.00	57.82	-14.19	43.63	74.00	-30.37	Horizontal
2310.00	56.81	-14.85	41.96	74.00	-32.04	Vertical
2390.00	60.19	-14.52	45.67	74.00	-28.33	Vertical

#### Average value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	45.26	-14.56	30.70	54.00	-23.30	Horizontal
2390.00	48.65	-14.19	34.46	54.00	-19.54	Horizontal
2310.00	42.74	-14.85	27.89	54.00	-26.11	Vertical
2390.00	44.92	-14.52	30.40	54.00	-23.60	Vertical

Tost channel:	Lighoot
Test channel:	Hignest
	1

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	72.10	-13.66	58.44	74.00	-15.56	Horizontal
2500.00	56.97	-13.57	43.40	74.00	-30.60	Horizontal
2483.50	69.89	-14.05	55.84	74.00	-18.16	Vertical
2500.00	69.24	-13.97	55.27	74.00	-18.73	Vertical

#### Average value:

Average value						
Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	45.96	-13.66	32.30	54.00	-21.70	Horizontal
2500.00	45.50	-13.57	31.93	54.00	-22.07	Horizontal
2483.50	43.05	-14.05	29.00	54.00	-25.00	Vertical
2500.00	42.87	-13.97	28.90	54.00	-25.10	Vertical

#### Remark:

- 1. Final Level =Receiver Read level + Correct factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3. Correct factor= Antenna Factor + Cable Loss Preamplifier Factor

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 23 of 40

## 7.10 Spurious Emission

#### 7.10.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)					
Test Method:	ANSI C63.10:2013					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					

#### **Measurement Data**

Reference to the AppendixH:Conducted SpuriousEmission

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No. : BLA-EMC-201907-A24-01 Page 24 of 40


#### 7.10.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209								
Test Method:	ANSI C63.10:2013								
Test Frequency Range:	9kHz to 25GHz								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Frequency D		Detector RB\		VBW	'	Value	
	9KHz-150KHz Quasi-		ıasi-peak	200	Hz	600H:	z	Quasi-peak	
	150KHz-30MHz	Qι	ıasi-peak	9KF	Ιz	30KH	z	Quasi-peak	
	30MHz-1GHz	Qι	ıasi-peak	120k	Ήz	300KH	lz	Quasi-peak	
	Above 1GHz		Peak	1Mł	Τz	3MHz	<u>z</u>	Peak	
	Above 1912		Peak	1MF	Ηz	10Hz	. \	Average	
Limit: (Spurious Emissions)	Frequency		Limit (uV/m)		Value		ľ	Measurement Distance	
	0.009MHz-0.490M	lHz	2400/F(k	2400/F(KHz)		QP		300m	
	0.490MHz-1.705M	lHz	24000/F(KHz)		(Hz) QP			30m	
	1.705MHz-30MH	lz	30			QP		30m	
	30MHz-88MHz		100	QP					
	88MHz-216MHz	<u>z</u>	150		QP				
	216MHz-960MH	z	200			QP		3m	
	960MHz-1GHz		500			QP		Sili	
	Above 1GHz		500		Αv	erage			
	Above IGHZ 5000			)	F	Peak			
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.								

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd. IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China

Report No.: BLA-EMC-201907-A24-01 Page 25 of 40



Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 26 of 40

	3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
	4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
	<ol><li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li></ol>
	6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

#### Measurement data:

#### Remark:

- 1. During the test, pre-scan the GFSK, Pi/4QPSK, 8-DPSK modulation, and found the 8-DPSK modulation which it is worse case.
- 2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

#### ■ 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 27 of 40

#### ■ Below 1GHz


EUT: Basic Pro Polarziation: Horizontal

Model: PBT Power Source: AC120V/60Hz

Mode: BT mode Test by: Lucas

Temp./Hum.(%H): 26°C/60%RH

Note:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		63.7588	11.07	12.10	23.17	40.00	-16.83	QP
2		98.8326	11.46	10.20	21.66	43.50	-21.84	QP
3		137.9028	14.50	12.98	27.48	43.50	-16.02	QP
4		226.0994	11.55	11.72	23.27	46.00	-22.73	QP
5		377.2591	17.31	15.84	33.15	46.00	-12.85	QP
6	*	607.7867	12.15	21.04	33.19	46.00	-12.81	QP

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01

Page 28 of 40

EUT:

Basic Pro

**Polarziation:** 

Vertical

Model:

PBT

**Power Source:** 

AC120V/60Hz

Mode:

BT mode


Test by:

Alex

Temp./Hum.(%H):

26°C/60%RH

Note:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	59.2325	18.23	13.02	31.25	40.00	-8.75	QP
2		98.1419	10.71	10.13	20.84	43.50	-22.66	QP
3		191.0738	18.27	10.23	28.50	43.50	-15.00	QP
4		327.8873	11.60	14.29	25.89	46.00	-20.11	QP
5		547.0977	11.77	19.85	31.62	46.00	-14.38	QP
6		739.6604	11.87	23.05	34.92	46.00	-11.08	QP

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01

**Above 1GHz** 

Test channel: Lowest

Page 29 of 40

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	54.56	-7.43	47.13	74.00	-26.87	Vertical
7206.00	56.04	-2.42	53.62	74.00	-20.38	Vertical
9608.00	55.22	-2.38	52.84	74.00	-21.16	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	54.32	-7.43	46.89	74.00	-27.11	Horizontal
7206.00	55.71	-2.42	53.29	74.00	-20.71	Horizontal
9608.00	53.88	-2.38	51.50	74.00	-22.50	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal

### Average value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	44.35	-7.43	36.92	54.00	-17.08	Vertical
7206.00	43.46	-2.42	41.04	54.00	-12.96	Vertical
9608.00	43.87	-2.38	41.49	54.00	-12.51	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	43.71	-7.43	36.28	54.00	-17.72	Horizontal
7206.00	42.04	-2.42	39.62	54.00	-14.38	Horizontal
9608.00	44.92	-2.38	42.54	54.00	-11.46	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal

#### Remark:

- 1. Final Level =Receiver Read level + Correct factor
- 2. Correct factor = Antenna Factor + Cable Loss Preamplifier Factor
- 3. "\*", means this data is the too weak instrument of signal is unable to test.
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 30 of 40

Test channel:	Middle
1 Cot Griannici.	Middle

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	53.39	-7.49	45.90	74.00	-28.10	Vertical
7323.00	54.56	-2.40	52.16	74.00	-21.84	Vertical
9764.00	55.47	-2.38	53.09	74.00	-20.91	Vertical
12205.00	*			74.00		Vertical
14646.00	*			74.00		Vertical
4882.00	52.72	-7.49	45.23	74.00	-28.77	Horizontal
7323.00	53.78	-2.40	51.38	74.00	-22.62	Horizontal
9764.00	51.66	-2.38	49.28	74.00	-24.72	Horizontal
12205.00	*			74.00		Horizontal
14646.00	*			74.00		Horizontal

#### Average value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	42.25	-7.49	34.76	54.00	-19.24	Vertical
7323.00	44.78	-2.40	42.38	54.00	-11.62	Vertical
9764.00	43.95	-2.38	41.57	54.00	-12.43	Vertical
12205.00	*			54.00		Vertical
14646.00	*			54.00		Vertical
4882.00	44.51	-7.49	37.02	54.00	-16.98	Horizontal
7323.00	45.66	-2.40	43.26	54.00	-10.74	Horizontal
9764.00	42.39	-2.38	40.01	54.00	-13.99	Horizontal
12205.00	*			54.00		Horizontal
14646.00	*			54.00		Horizontal

#### Remark:

- 1. Final Level =Receiver Read level + Correct facto
- 2. Correct factor = Antenna Factor + Cable Loss Preamplifier Factor
- 3. "\*", means this data is the too weak instrument of signal is unable to test.
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01 Page 31 of 40

Test channel:	Highest

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	52.05	-7.47	44.58	74.00	-29.42	Vertical
7440.00	54.13	-2.45	51.68	74.00	-22.32	Vertical
9920.00	55.61	-2.37	53.24	74.00	-20.76	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	51.87	-7.47	44.40	74.00	-29.60	Horizontal
7440.00	52.84	-2.45	55.38	74.00	-18.62	Horizontal
9920.00	52.16	-2.37	49.79	74.00	-24.21	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal

#### Average value:

7 trorago raid						
Frequency (MHz)	Read Level (dBuV)	Correct factor (dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	41.69	-7.47	32.22	54.00	-19.78	Vertical
7440.00	43.36	-2.45	40.91	54.00	-13.09	Vertical
9920.00	46.87	-2.37	44.50	54.00	-9.50	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	40.49	-7.47	33.02	54.00	-20.98	Horizontal
7440.00	42.58	-2.45	40.13	54.00	-13.87	Horizontal
9920.00	44.77	-2.37	42.40	54.00	-11.60	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

#### Remark:

- 1. Final Level =Receiver Read level + Correct factor
- 2. Correct factor = Antenna Factor + Cable Loss Preamplifier Factor
- 3. "\*", means this data is the too weak instrument of signal is unable to test.
- 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China




Report No.: BLA-EMC-201907-A24-01 Page 32 of 40

## 8 Test Setup Photo

Radiated Emission





Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No. : BLA-EMC-201907-A24-01 Page 33 of 40

## Conducted Emission




Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd. IOT Test Centre of BlueAsia,


No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No. : BLA-EMC-201907-A24-01 Page 34 of 40

## 9 EUT Constructional Details





Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,


No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China



Report No.: BLA-EMC-201907-A24-01



Page 35 of 40



Qianhai BlueAsia of Technical Services(Shenzhen) Co., Ltd.

IOT Test Centre of BlueAsia,

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China