



Test Model

 Unwanted Emissions In Non-Restricted Frequency Bands
 Bluetooth DTS
 Channel 19: 2440MHz



Date: 31.DEC.2006 23:42:36

Test Model

 PSD(Power Spectral Density) RBW=100kHz
 Bluetooth DTS
 Channel 19: 2480MHz



Date: 31.DEC.2006 23:43:27

Test Model

 Unwanted Emissions In Non-Restricted Frequency Bands
 Bluetooth DTS
 Channel 39: 2480MHz


Date: 31.DEC.2006 23:45:50

Test Model

 Band edge
 Bluetooth DTS
 Channel 39: 2480MHz


Date: 31.DEC.2006 23:44:51


2M

Test Model

PSD(Power Spectral Density) RBW=100kHz

Bluetooth DTS

Channel 0: 2402MHz




Date: 31.DEC.2006 23:54:22

Test Model

Unwanted Emissions in non-restricted frequency bands

Bluetooth DTS

Channel 0: 2402MHz




Date: 1.JAN.2007 00:17:30

Test Model

 Band edge
Bluetooth DTS

Channel 0: 2402MHz




Date: 31.DEC.2006 23:55:49

Test Model


 PSD(Power Spectral Density) RBW=100kHz
 Bluetooth DTS

Channel 19: 2440MHz




Date: 1.JAN.2007 00:18:05

Test Model

 Unwanted Emissions In Non-Restricted Frequency Bands
 Bluetooth DTS
 Channel 19: 2440MHz



Date: 1.JAN.2007 00:19:00

Test Model


 PSD(Power Spectral Density) RBW=100kHz
 Bluetooth DTS
 Channel 19: 2480MHz


Date: 1.JAN.2007 00:19:38

Test Model

 Unwanted Emissions In Non-Restricted Frequency Bands
 Bluetooth DTS
 Channel 39: 2480MHz


Test Model

 Band edge
 Bluetooth DTS
 Channel 39: 2480MHz


8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μ V/m)	Field Strength ($\text{dB}\mu$ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (μ V/m)	300
0.490-1.705	24000/F(KHz)	20 log (μ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz(1GHz to 25GHz), 100 kHz for $f < 1$ GHz(30MHz to 1GHz)

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})(\text{dB})$;

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth DTS mode have been tested, and the worst result was report as below:

Test mode: BLE Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
5773.621	V	46.79	28.6	74	54	-27.21	-25.4
7299.845	V	48.36	30.1	74	54	-25.64	-23.9
13388.52	V	50.28	35.6	74	54	-23.72	-18.4
7333.682	H	50.64	32.5	74	54	-23.36	-21.5
12105.6	H	52.98	34.2	74	54	-21.02	-19.8
17981.8	H	55.68	37.3	74	54	-18.32	-16.7

Test mode: BLE Frequency: Channel 19: 2440MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
7328.385	V	50.74	32.4	74	54	-23.26	-21.6
11148.36	V	55.09	37.2	74	54	-18.91	-16.8
17981.8	V	64.78	46.5	74	54	-9.22	-7.5
11225.96	H	55.27	37.2	74	54	-18.73	-16.8
15263.67	H	55.64	37.5	74	54	-18.36	-16.5
17896.24	H	64.18	46.3	74	54	-9.82	-7.7

Test mode: BLE Frequency: Channel 39: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
12009.76	V	56.49	36.7	74	54	-17.51	-17.3
14897.55	V	56.75	36.2	74	54	-17.25	-17.8
18000.00	V	63.68	45.2	74	54	-10.32	-8.8
12041.04	H	55.65	35.4	74	54	-18.35	-18.6
14867.44	H	57.51	37.5	74	54	-16.49	-16.5
17867.82	H	63.94	45.3	74	54	-10.06	-8.7

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).

(2) Emission Level= Reading Level+Correct Factor.

(3) Correct Factor= Ant_F + Cab_L - Preamp

(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2388.588	H	49.47	74	38.3	54
2389.332	V	49.75	74	37.5	54

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2484.558	H	51.97	74	36.4	54
2484.707	V	52.22	74	43.4	54

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


All the modulation modes were tested, the data of the worst mode are described in the following table



Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz
Bluetooth DTS
Channel 39: 2480MHz


H



Test Model


Spurious Emission in Restricted Band 2483.5-2500MHz
Bluetooth DTS
Channel 39: 2480MHz

V




■ Spurious Emission below 1GHz (30MHz to 1GHz)


All modes have been tested, and the worst result recorded was report as below:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment				Height	Degree	Comment
			MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1	*	32.8925	46.81	-14.32	32.49	40.00	-7.51	QP			
2		50.4090	42.64	-11.96	30.68	40.00	-9.32	QP			
3		77.4230	38.32	-14.55	23.77	40.00	-16.23	QP			
4		131.4693	31.69	-14.23	17.46	43.50	-26.04	QP			
5		473.8347	29.19	-5.58	23.61	46.00	-22.39	QP			
6		833.3171	29.54	2.57	32.11	46.00	-13.89	QP			




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		33.9322	35.59	-14.15	21.44	40.00	-18.56	QP		
2		52.8294	29.36	-11.84	17.52	40.00	-22.48	QP		
3		76.8145	31.22	-14.46	16.76	40.00	-23.24	QP		
4		346.9612	27.84	-7.70	20.14	46.00	-25.86	QP		
5		604.5983	28.88	-2.78	26.10	46.00	-19.90	QP		
6	*	845.4583	30.06	2.89	32.95	46.00	-13.05	QP		






No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		30.1847	37.06	-14.57	22.49	40.00	-17.51	QP		
2		33.4302	36.24	-14.24	22.00	40.00	-18.00	QP		
3		38.9220	33.82	-13.12	20.70	40.00	-19.30	QP		
4		343.9330	27.43	-7.74	19.69	46.00	-26.31	QP		
5		620.4376	29.03	-2.49	26.54	46.00	-19.46	QP		
6	*	840.2860	29.21	2.86	32.07	46.00	-13.93	QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over Detector	Antenna Height cm	Table Degree degree	Comment
1		32.1231	43.80	-14.44	29.36	40.00	-10.64	QP		
2	*	50.3868	42.04	-11.96	30.08	40.00	-9.92	QP		
3		57.5687	38.19	-12.08	26.11	40.00	-13.89	QP		
4		77.4230	36.90	-14.55	22.35	40.00	-17.65	QP		
5		432.5457	29.20	-5.70	23.50	46.00	-22.50	QP		
6		810.6206	29.57	1.75	31.32	46.00	-14.68	QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	33.5624	36.72	-14.22	22.50	40.00	-17.50	QP			
2	52.8063	29.14	-11.84	17.30	40.00	-22.70	QP			
3	70.4600	29.59	-13.25	16.34	40.00	-23.66	QP			
4	293.7272	27.89	-9.37	18.52	46.00	-27.48	QP			
5	470.1110	29.15	-5.65	23.50	46.00	-22.50	QP			
6 *	848.0563	29.17	2.91	32.08	46.00	-13.92	QP			

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results

N/A.

The EUT is DC powered.

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

The EUT has 1 antenna: a Internal Antenna for BT with classic model, the gain is 3.23 dBi;

Note: Antennas use a permanently attached antenna which is not replaceable.
 Not using a standard antenna jack or electrical connector for antenna replacement
 The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

----- END OF REPORT -----