

FCC ID: 2AJFDSBT104

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] / [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:


Antenna Type :PCB Antenna

Antenna Gain: 1 dBi

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-4.227	0.378	-4±1	-3	0.501	<5	0.15535	3.00	YES
	2.441	-3.994	0.399	-4±1	-3	0.501	<5	0.15661	3.00	YES
	2.480	-4.375	0.365	-4±1	-3	0.501	<5	0.15785	3.00	YES
$\pi/4$ -DQPSK	2.402	-3.104	0.489	-3±1	-2	0.631	<5	0.19558	3.00	YES
	2.441	-2.825	0.522	-3±1	-2	0.631	<5	0.19716	3.00	YES
	2.480	-3.197	0.479	-3±1	-2	0.631	<5	0.19873	3.00	YES

Conclusion:

For the max result : $0.19873 \leq 3.0$ for 1-g SAR, No SAR is required.



Signature:

Date: 2017-10-16

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China