

A Test Lab Techno Corp.

Changan Lab: No. 140-1, Changan Street, Bade District, Taoyuan City 33465, Taiwan (R.O.C)

Tel: 886-3-271-0188 / Fax: 886-3-271-0190







Test Report No. : 1610FS13

Applicant : TBS Group Corporation

Product Type : Arofly ULTRA SMART BIKE METER SOLUTION (Bluetooth)

Trade Name : Arofly

Model Number : Arofly01

Date of Received : Aug. 04, 2016

Test Period : Oct. 13, 2016

Date of Issued : Oct. 26, 2016

Test Specification : ANSI / IEEE Std.C95.1-1992 / IEEE Std. 1528-2013

47 CFR § 2.1091

47 CFR § 1.1310

Location of Test Lab. : Chang-an Lab.

- 1. The test operations have to be performed with cautious behavior, the test results are as attached.
- The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
- 3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp.
- 4. This document may be altered or revised by A Test Lab Techno. Corp. personnel only, and shall be noted in the revision section of the document.

Approved By

Tested By

(Mark Duan)

Report Number: 1610FS13 Page 1 of 5



Contents

1.	Description of Equipment under Test (EUT)	. 3
2.	Human Exposure Assessment	. 4
3.	RF Output Power	. 5
4	Test Result	5



1. Description of Equipment under Test (EUT)

Applicant	TBS Group Corporation 7F3, No.79, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)				
Manufacturer	Auden Techno Corp. No.19 Lane 772 HoPing Rd., BaDe Dist. Taoyuan city Taiwan R.O.C.				
Product Type	Arofly ULTRA SMART BIKE METER SOLUTION (Bluetooth)				
Trade Name Arofly					
Model Number	Arofly01				
FCC ID 2AJGD-AROFLY01					
Frequency Range	Bluetooth LE: 2402 - 2480 MHz				
Antenna information	Model Number	Туре	Max. Gain (dBi)		
	C10754-30	PIFA Antenna	-1.07		
Temperature Range	-30 ~ +85°C				
RF Evaluation 0.000491 mW/cm ²					

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR \S 2.1091 / 47 CFR \S 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties

Report Number: 1610FS13 Page 3 of 5



2. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. " This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation

$$S = \frac{PG}{4\pi R^2}$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.



3. RF Output Power

The conducted power turn-up tolerance reference manufacturer specification.

Operate Band	Modulation Type	Data Rate (Mbps)	Frequency (MHz)	Average Power (dBm)
	GFSK		2402	4.45
Bluetooth LE		1	2440	4.16
			2480	3.82

4. Test Result

Band	Data Rate (Mbps)	Frequency (MHz)	Limit (mw)	Distance [R] (cm)	Max tune-up Power (upper limit) [P] (dBm)	ANT Gain (dBi)	Numeric Gain [G]	Duty Cycle	[P] x [G] with Duty cycle [TP] (mW)	Power Density [S] (mw/cm²)
	1	2402	1	20	5.00	-1.07	0.78	1	2.47	0.000491
Bluetooth LE		2440	1	20	5.00	-1.07	0.78	1	2.47	0.000491
		2480	1	20	5.00	-1.07	0.78	1	2.47	0.000491

Note: 1. The Numeric Gain calculated by 10^(ant. Gain(dBi) /10).

Report Number: 1610FS13 Page 5 of 5

^{2.} Each band max power which perform MPE of any configurations.