



FCC PART 15B

TEST REPORT

For

PO FUNG ELECTRONIC (HK) INTERNATIONAL GROUP COMPANY LIMITED

Room 1508, 15/F, Office Tower II, Grand Plaza, 625 Nathan Road, Kowloon, Hong Kong

FCC ID: 2AJGM-UV26

Report Type:	Product Name:
Original Report	Amateur Radio
Report Number:	2507R04211E-EM-01
Report Date:	2025-05-06
Reviewed By:	Ash Lin
Approved By:	Miles Chen
Prepared By:	Bay Area Compliance Laboratories Corp. (Xiamen) Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen Tel: +86-592-3200111 www.baclcorp.com.cn

TABLE OF CONTENTS

REPORT REVISION HISTORY3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST FACILITY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
TEST MODE AND VOLTAGE.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §15.107 - CONDUCTED EMISSION	11
APPLICABLE STANDARD	11
TEST SYSTEM SETUP.....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
RESULT & MARGIN CALCULATION.....	12
TEST DATA (WORST).....	13
FCC §15.109 - RADIATED EMISSION IN FREQUENCY	17
APPLICABLE STANDARD	17
TEST SYSTEM SETUP.....	17
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
RESULT & MARGIN CALCULATION.....	18
TEST DATA	19
FCC §15.121(B) – SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS.....	63
APPLICABLE STANDARD	63
TEST PROCEDURE	63
TEST DATA	64
EXHIBIT A - EUT PHOTOGRAPHS.....	65
EXHIBIT B – TEST SETUP PHOTOGRAPHS.....	66

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	2507R04211E-EM-01	R1V1	2025-05-06	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	PO FUNG ELECTRONIC (HK) INTERNATONAL GROUP COMPANY LIMITED			
Product Name:	Amateur Radio			
Tested Model:	UV26			
Series Model(s):	UV-26M, BF-26M, AT-26M, AT-26UV			
Trade Mark:	BAOFENG, pofung, ALERVITES			
Power Supply:	DC 7.4V from battery or DC 5V from adapter			
Adapter information	Model:	YZSJ-A207-05200-U		
	Input:	AC 100-240V, 50/60Hz, 0.35A		
	Output:	DC 5.0V, 2.0A		
★Highest Operating Frequency:	520 MHz			
EUT Receive Status:	Good			
<i>Note:</i>				
1. The highest operating frequency is provided by the applicant.				
2. The test model is identify with the series models except for the model name, please refer to declaration letter for more detail.				
3. All measurement and test data in this report was gathered from production sample serial number: 30F0-4 (Assigned by the BACL (Xiamen). The EUT was received on 2025-03-26).				

Objective

This report is prepared for *PO FUNG ELECTRONIC (HK) INTERNATONAL GROUP COMPANY LIMITED* in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commission's rules.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the product as specified in CISPR 16-4-2. This uncertainty represents expanded uncertainty expressed at 95% confidence level using a coverage factor of k=2.

$$u_c(y) = \sqrt{\sum_i c_i^2 u^2(x_i)}$$

Item	Frequency Range	$U_{lab} = 2 u_c(y)$ (Confidence of 95%)
Conducted Emission	150kHz-30MHz	2.45dB
Radiated Emission	30MHz~200MHz	3.47dB
	200MHz~1GHz	4.86dB
	1GHz~6GHz	4.88dB
Humidity		±5%
Temperature		±1°C

SYSTEM TEST CONFIGURATION

Test Mode and Voltage

The system was configured for testing in a typical mode (as normally used by a typical user).	
Test mode:	Test Mode 1: Charging & Scanning Test Mode 2: Charging & Receiving
Test voltage:	DC 5V from adapter (AC 120V/60Hz)
Remark:	During all emission tests, the EUT was configured to measure its highest possible emission level and the worst case's test data was presented in this test report.

Description of Test Configuration

Operation Modes	Operation Frequency Range (MHz)	Test Frequency (MHz)
Scanning	108-136	108-136
	136-174	136-174
	220-260	220-260
	350-390	350-390
	400-520	400-520
VHF Receiving	108-136	108.0125, 122, 135.9875
	136-174	136.0125, 155, 173.9875
	220-260	220.0125, 240, 259.9875
UHF Receiving	350-390	350.0125, 370, 389.9875
	400-520	400.0125, 460, 519.9875

EUT Exercise Software

No exercise software was used to test.

Special Accessories

No special accessory was used.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HP	RF Communications test set	8920A	3524A07202
Unknown	Antenna	Unknown	Unknown


External I/O Cable

Cable Description	Length (m)	From Port	To Port
Antenna Cable	3.0	8920A	Antenna
Power Cable	0.8	Adapter	EUT


Block Diagram of Test Setup

Conducted Emission:

Test Mode 1:




Test Mode 2:




Radiated Emission:

Test Mode 1:



Test Mode 2:



SUMMARY OF TEST RESULTS

Rule Part	Description of Test	Results
FCC§15.107	Conducted Emission	Compliant
FCC§15.109	Radiated Emission	Compliant
FCC §15.121(b)	Scanning receivers and frequency converters used with scanning receivers	Compliant

TEST EQUIPMENT LIST

Test Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission					
EMI Test Receiver	Rohde & Schwarz	ESR	103105	2025/02/20	2026/02/19
LISN	Rohde & Schwarz	ENV216	100129	2025/02/20	2026/02/19
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	0357.8810.54	2025/02/20	2026/02/19
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC001	2025/02/20	2026/02/19
Test Software	Audix	E3	18621a	N/A	N/A
Radiated Emission 30 MHz to 1 GHz					
EMI Test Receiver	Rohde & Schwarz	ESR	103103	2025/02/20	2026/02/19
Antenna	Sunol Sciences	JB6	A122022-5	2023/07/27	2026/07/26
Amplifier	Sonoma	310B	120903	2025/02/20	2026/02/19
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC002	2025/02/20	2026/02/19
Coaxial Cable	XINHANGWEIBO	XH460B-N-2M	CC006	2025/02/20	2026/02/19
Coaxial Cable	XINHANGWEIBO	XH460B-N-12M	CC007	2025/02/20	2026/02/19
Test Software	Audix	E3	18621a	N/A	N/A
Radiated Emission Above 1 GHz					
Spectrum Analyzer	Rohde & Schwarz	FSU	100405	2025/02/20	2026/02/19
Horn Antenna	EMCO	3115	9002-3355	2024/11/19	2027/11/18
Preamplifier	GLOBAL	1313-A100M18G	4121301	2025/01/16	2026/01/15
Coaxial Cable	XINHANGWEIBO	XH800A-N-6M	CC003	2025/02/20	2026/02/19
Coaxial Cable	XINHANGWEIBO	XH800A-N-1M	CC005	2025/02/20	2026/02/19
Test Software	Audix	E3	18621a	N/A	N/A
Scanning Receiver					
Coaxial Cable	WEIHE	WH316	RFCC002	Each time	Each time
RF Communications test set	HP	8920A	3524A07202	2024/04/26	2025/04/25
Power Splitter	narda	4426LB-2	1661	N/A	N/A
Microwave Analog Signal Generator	Agilent	N5183A	MY47420335	2025/02/20	2026/02/19
Attenuator	Electronic Corporation	30-WA-FFN-30	1172435	2025/02/20	2026/02/19

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Xiamen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.107 - CONDUCTED EMISSION

Applicable Standard


FCC §15.107

(a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

Test System Setup



The measurement procedure of test setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Result & Margin Calculation

The Result is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Result (dB μ V) = Reading (dB μ V) + Factor (dB)


The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V) –Result (dB μ V)

Test Data (Worst)

Project No.: 2507R04211E-EM
 Test Mode: Mode 1(400-520MHz)
 EUT Model: UV26

Temp/Humi/ATM: 23°C/54%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 5V from adapter
 (AC 120V/60Hz)




Trace: 1

Condition: QP/AV IF B/W:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	9.87	20.92	30.79	55.92	25.13	Line	Average
0.15	26.57	20.92	47.49	65.92	18.43	Line	QP
0.16	9.61	20.83	30.44	55.37	24.93	Line	Average
0.16	25.63	20.83	46.46	65.37	18.91	Line	QP
0.19	7.93	20.63	28.56	54.02	25.46	Line	Average
0.19	22.65	20.63	43.28	64.02	20.74	Line	QP
0.21	7.19	20.55	27.74	53.22	25.48	Line	Average
0.21	21.70	20.55	42.25	63.22	20.97	Line	QP
0.53	9.02	20.32	29.34	46.00	16.66	Line	Average
0.53	15.91	20.32	36.23	56.00	19.77	Line	QP
0.56	18.53	20.36	38.89	46.00	7.11	Line	Average
0.56	24.84	20.36	45.20	56.00	10.80	Line	QP

Project No.: 2507R04211E-EM
Test Mode: Mode 1(400-520MHz)
EUT Model: UV26


Temp/Humi/ATM: 23°C/54%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	9.23	20.73	29.96	55.93	25.97	Neutral	Average
0.15	26.47	20.73	47.20	65.93	18.73	Neutral	QP
0.16	9.05	20.71	29.76	55.36	25.60	Neutral	Average
0.16	25.60	20.71	46.31	65.36	19.05	Neutral	QP
0.20	7.52	20.67	28.19	53.52	25.33	Neutral	Average
0.20	22.81	20.67	43.48	63.52	20.04	Neutral	QP
0.46	8.68	20.42	29.10	46.71	17.61	Neutral	Average
0.46	17.04	20.42	37.46	56.71	19.25	Neutral	QP
0.54	14.35	20.37	34.72	46.00	11.28	Neutral	Average
0.54	19.24	20.37	39.61	56.00	16.39	Neutral	QP
0.56	20.61	20.35	40.96	46.00	5.04	Neutral	Average
0.56	27.70	20.35	48.05	56.00	7.95	Neutral	QP

Project No.: 2507R04211E-EM
Test Mode: Mode 2(460MHz)
EUT Model: UV26

Temp/Humi/ATM: 23°C/54%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Trace: 1

Condition: QP/AV IF B/W:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	8.92	20.93	29.85	55.99	26.14	Line	Average
0.15	25.91	20.93	46.84	65.99	19.15	Line	QP
0.16	9.07	20.83	29.90	55.36	25.46	Line	Average
0.16	25.40	20.83	46.23	65.36	19.13	Line	QP
0.18	7.47	20.70	28.17	54.42	26.25	Line	Average
0.18	22.46	20.70	43.16	64.42	21.26	Line	QP
0.52	10.89	20.32	31.21	46.00	14.79	Line	Average
0.52	18.04	20.32	38.36	56.00	17.64	Line	QP
0.55	17.49	20.34	37.83	46.00	8.17	Line	Average
0.55	20.05	20.34	40.39	56.00	15.61	Line	QP
0.57	20.96	20.37	41.33	46.00	4.67	Line	Average
0.57	25.01	20.37	45.38	56.00	10.62	Line	QP

Project No.: 2507R04211E-EM
Test Mode: Mode 2 (460MHz)
EUT Model: UV26

Temp/Humi/ATM: 23°C/54%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.15	8.66	20.73	29.39	55.97	26.58	Neutral	Average
0.15	26.20	20.73	46.93	65.97	19.04	Neutral	QP
0.17	7.62	20.70	28.32	55.11	26.79	Neutral	Average
0.17	24.47	20.70	45.17	65.11	19.94	Neutral	QP
0.20	7.43	20.67	28.10	53.52	25.42	Neutral	Average
0.20	22.85	20.67	43.52	63.52	20.00	Neutral	QP
0.46	8.79	20.42	29.21	46.70	17.49	Neutral	Average
0.46	17.40	20.42	37.82	56.70	18.88	Neutral	QP
0.55	13.41	20.36	33.77	46.00	12.23	Neutral	Average
0.55	21.41	20.36	41.77	56.00	14.23	Neutral	QP
0.57	19.60	20.35	39.95	46.00	6.05	Neutral	Average
0.57	28.14	20.35	48.49	56.00	7.51	Neutral	QP

FCC §15.109 - RADIATED EMISSION IN FREQUENCY

Applicable Standard


FCC§15.109

(a) Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:


Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

Test System Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW	Measurement	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	PK	PK
	120 kHz	/	QP	QP
Above 1 GHz	1 MHz	3 MHz	PK	PK
	1 MHz	10 Hz	AV	PK

Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Result & Margin Calculation

The Result is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor (dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

$$\text{Result (dB}\mu\text{V/m)} = \text{Reading (dB}\mu\text{V)} + \text{Factor (dB/m)}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Result (dB}\mu\text{V/m)}$$


Test Data

Please refer to below plots:

1) 30MHz-1GHz:


Project No.: 2507R04211E-EM
Test Mode: Mode 1(108-136MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)



Project No.: 2507R04211E-EM
Test Mode: Mode 1(108-136MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
37.50	35.17	-9.89	25.28	40.00	14.72	Vertical	QP
90.28	49.17	-17.00	32.17	43.50	11.33	Vertical	QP
153.77	43.64	-11.23	32.41	43.50	11.09	Vertical	Peak
187.14	45.53	-12.34	33.19	43.50	10.31	Vertical	QP
200.62	42.99	-11.76	31.23	43.50	12.27	Vertical	Peak
294.81	38.04	-9.31	28.73	46.00	17.27	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(136-174MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.16	27.84	-5.94	21.90	40.00	18.10	Horizontal	Peak
90.53	37.22	-17.02	20.20	43.50	23.30	Horizontal	Peak
176.96	37.41	-12.20	25.21	43.50	18.29	Horizontal	Peak
338.07	34.64	-8.37	26.27	46.00	19.73	Horizontal	Peak
946.65	26.21	3.13	29.34	46.00	16.66	Horizontal	Peak
991.17	26.22	3.92	30.14	54.00	23.86	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(136-174MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
37.37	37.84	-9.79	28.05	40.00	11.95	Vertical	Peak
90.43	49.40	-17.01	32.39	43.50	11.11	Vertical	QP
153.09	45.14	-11.31	33.83	43.50	9.67	Vertical	QP
187.53	46.34	-12.37	33.97	43.50	9.53	Vertical	QP
317.90	36.52	-8.82	27.70	46.00	18.30	Vertical	Peak
856.54	27.54	1.99	29.53	46.00	16.47	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(220-260MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.07	26.89	-5.89	21.00	40.00	19.00	Horizontal	Peak
168.52	36.36	-11.76	24.60	43.50	18.90	Horizontal	Peak
336.81	33.44	-8.38	25.06	46.00	20.94	Horizontal	Peak
805.81	27.84	1.29	29.13	46.00	16.87	Horizontal	Peak
882.92	27.20	2.37	29.57	46.00	16.43	Horizontal	Peak
994.47	26.12	4.00	30.12	54.00	23.88	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(220-260MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.89	37.37	-9.41	27.96	40.00	12.04	Vertical	Peak
90.14	49.04	-16.98	32.06	43.50	11.44	Vertical	QP
154.65	43.30	-11.34	31.96	43.50	11.54	Vertical	QP
187.24	43.97	-12.34	31.63	43.50	11.87	Vertical	QP
286.86	36.83	-9.26	27.57	46.00	18.43	Vertical	Peak
881.37	27.19	2.36	29.55	46.00	16.45	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(350-390MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.29	26.01	-5.68	20.33	40.00	19.67	Horizontal	Peak
91.01	39.27	-17.06	22.21	43.50	21.29	Horizontal	Peak
170.17	36.37	-11.87	24.50	43.50	19.00	Horizontal	Peak
344.18	34.80	-8.26	26.54	46.00	19.46	Horizontal	Peak
878.36	27.06	2.32	29.38	46.00	16.62	Horizontal	Peak
982.93	26.42	3.73	30.15	54.00	23.85	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(350-390MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
37.28	37.11	-9.72	27.39	40.00	12.61	Vertical	Peak
90.82	49.87	-17.04	32.83	43.50	10.67	Vertical	Peak
154.84	45.46	-11.38	34.08	43.50	9.42	Vertical	QP
186.56	45.18	-12.43	32.75	43.50	10.75	Vertical	QP
315.76	36.23	-8.87	27.36	46.00	18.64	Vertical	Peak
882.53	26.77	2.37	29.14	46.00	16.86	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(400-520MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.49	26.63	-5.73	20.90	40.00	19.10	Horizontal	Peak
132.92	30.56	-10.24	20.32	43.50	23.18	Horizontal	Peak
179.96	37.91	-12.36	25.55	43.50	17.95	Horizontal	Peak
342.24	32.87	-8.31	24.56	46.00	21.44	Horizontal	Peak
890.00	26.81	2.50	29.31	46.00	16.69	Horizontal	Peak
952.57	26.87	3.20	30.07	46.00	15.93	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(400-520MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.89	36.64	-9.41	27.23	40.00	12.77	Vertical	Peak
90.92	48.66	-17.05	31.61	43.50	11.89	Vertical	QP
154.55	44.36	-11.32	33.04	43.50	10.46	Vertical	QP
186.95	45.34	-12.34	33.00	43.50	10.50	Vertical	QP
317.31	36.78	-8.83	27.95	46.00	18.05	Vertical	Peak
945.29	26.28	3.12	29.40	46.00	16.60	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(108.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.94	26.70	-6.37	20.33	40.00	19.67	Horizontal	Peak
178.31	39.42	-12.21	27.21	43.50	16.29	Horizontal	Peak
333.61	34.48	-8.46	26.02	46.00	19.98	Horizontal	Peak
768.56	27.67	0.80	28.47	46.00	17.53	Horizontal	Peak
825.98	27.39	1.67	29.06	46.00	16.94	Horizontal	Peak
880.59	27.31	2.36	29.67	46.00	16.33	Horizontal	Peak


Project No.: 2507R04211E-EM
Test Mode: Mode 2(108.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)



Project No.: 2507R04211E-EM
Test Mode: Mode 2(122MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.07	27.20	-5.89	21.31	40.00	18.69	Horizontal	Peak
88.49	37.41	-17.19	20.22	43.50	23.28	Horizontal	Peak
183.36	39.19	-12.50	26.69	43.50	16.81	Horizontal	Peak
330.80	33.73	-8.58	25.15	46.00	20.85	Horizontal	Peak
894.46	26.67	2.43	29.10	46.00	16.90	Horizontal	Peak
930.26	27.63	2.87	30.50	46.00	15.50	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(122MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.89	40.44	-9.41	31.03	40.00	8.97	Vertical	QP
88.20	50.16	-17.19	32.97	43.50	10.53	Vertical	QP
154.45	44.19	-11.30	32.89	43.50	10.61	Vertical	Peak
189.66	44.92	-12.32	32.60	43.50	10.90	Vertical	Peak
200.53	43.95	-11.75	32.20	43.50	11.30	Vertical	Peak
852.95	28.20	1.95	30.15	46.00	15.85	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(135.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.29	26.96	-5.68	21.28	40.00	18.72	Horizontal	Peak
187.04	39.38	-12.33	27.05	43.50	16.45	Horizontal	Peak
328.47	33.63	-8.62	25.01	46.00	20.99	Horizontal	Peak
789.12	28.27	1.10	29.37	46.00	16.63	Horizontal	Peak
920.46	26.99	2.73	29.72	46.00	16.28	Horizontal	Peak
957.32	26.94	3.32	30.26	46.00	15.74	Horizontal	Peak


Project No.: 2507R04211E-EM
Test Mode: Mode 2(135.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)



Project No.: 2507R04211E-EM
Test Mode: Mode 2(136.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.46	26.14	-6.10	20.04	40.00	19.96	Horizontal	Peak
87.91	36.92	-17.20	19.72	40.00	20.28	Horizontal	Peak
179.67	39.63	-12.33	27.30	43.50	16.20	Horizontal	Peak
328.66	35.73	-8.62	27.11	46.00	18.89	Horizontal	Peak
832.38	27.33	1.78	29.11	46.00	16.89	Horizontal	Peak
869.44	27.44	2.13	29.57	46.00	16.43	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(136.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.11	38.18	-8.81	29.37	40.00	10.63	Vertical	QP
87.03	49.41	-17.30	32.11	40.00	7.89	Vertical	QP
155.32	43.41	-11.38	32.03	43.50	11.47	Vertical	Peak
187.24	45.19	-12.34	32.85	43.50	10.65	Vertical	Peak
199.75	44.69	-11.69	33.00	43.50	10.50	Vertical	Peak
928.71	27.09	2.85	29.94	46.00	16.06	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(155MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.39	26.58	-5.70	20.88	40.00	19.12	Horizontal	Peak
88.69	37.16	-17.18	19.98	43.50	23.52	Horizontal	Peak
189.95	39.85	-12.28	27.57	43.50	15.93	Horizontal	Peak
361.55	33.08	-7.68	25.40	46.00	20.60	Horizontal	Peak
803.87	27.80	1.26	29.06	46.00	16.94	Horizontal	Peak
854.99	28.03	1.96	29.99	46.00	16.01	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(155MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.01	39.31	-8.74	30.57	40.00	9.43	Vertical	QP
88.10	50.38	-17.19	33.19	43.50	10.31	Vertical	QP
154.16	44.35	-11.24	33.11	43.50	10.39	Vertical	Peak
188.30	44.25	-12.41	31.84	43.50	11.66	Vertical	QP
201.30	44.46	-11.80	32.66	43.50	10.84	Vertical	Peak
934.72	27.91	3.06	30.97	46.00	15.03	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(173.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
32.62	27.53	-6.73	20.80	40.00	19.20	Horizontal	Peak
152.51	33.91	-11.27	22.64	43.50	20.86	Horizontal	Peak
178.02	39.66	-12.18	27.48	43.50	16.02	Horizontal	Peak
314.50	34.80	-8.90	25.90	46.00	20.10	Horizontal	Peak
760.22	28.91	0.60	29.51	46.00	16.49	Horizontal	Peak
934.14	26.53	3.04	29.57	46.00	16.43	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(173.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.60	39.81	-9.19	30.62	40.00	9.38	Vertical	QP
87.91	50.71	-17.20	33.51	40.00	6.49	Vertical	QP
154.94	43.92	-11.40	32.52	43.50	10.98	Vertical	Peak
191.60	45.09	-12.17	32.92	43.50	10.58	Vertical	Peak
200.62	43.68	-11.76	31.92	43.50	11.58	Vertical	Peak
922.98	26.89	2.79	29.68	46.00	16.32	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(220.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.39	25.93	-5.70	20.23	40.00	19.77	Horizontal	Peak
115.26	31.76	-10.87	20.89	43.50	22.61	Horizontal	Peak
187.14	40.19	-12.34	27.85	43.50	15.65	Horizontal	Peak
330.80	33.29	-8.58	24.71	46.00	21.29	Horizontal	Peak
791.94	27.84	1.16	29.00	46.00	17.00	Horizontal	Peak
876.03	27.25	2.26	29.51	46.00	16.49	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(220.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.40	39.74	-9.04	30.70	40.00	9.30	Vertical	QP
89.36	51.20	-17.11	34.09	43.50	9.41	Vertical	QP
154.74	43.28	-11.36	31.92	43.50	11.58	Vertical	Peak
187.53	44.22	-12.37	31.85	43.50	11.65	Vertical	QP
199.94	45.12	-11.70	33.42	43.50	10.08	Vertical	Peak
841.99	27.61	1.81	29.42	46.00	16.58	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(240MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
32.04	26.78	-6.42	20.36	40.00	19.64	Horizontal	Peak
146.50	35.59	-11.06	24.53	43.50	18.97	Horizontal	Peak
188.11	39.95	-12.41	27.54	43.50	15.96	Horizontal	Peak
341.95	35.64	-8.31	27.33	46.00	18.67	Horizontal	Peak
851.98	27.32	1.95	29.27	46.00	16.73	Horizontal	Peak
909.60	26.91	2.66	29.57	46.00	16.43	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(240MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.44	39.79	-9.07	30.72	40.00	9.28	Vertical	QP
89.88	50.45	-16.99	33.46	43.50	10.04	Vertical	QP
145.72	42.39	-10.96	31.43	43.50	12.07	Vertical	Peak
189.66	46.44	-12.32	34.12	43.50	9.38	Vertical	QP
273.96	37.61	-9.67	27.94	46.00	18.06	Vertical	Peak
932.97	26.87	2.99	29.86	46.00	16.14	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(259.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.07	26.12	-5.89	20.23	40.00	19.77	Horizontal	Peak
89.66	37.18	-17.04	20.14	43.50	23.36	Horizontal	Peak
178.12	39.71	-12.19	27.52	43.50	15.98	Horizontal	Peak
342.24	33.65	-8.31	25.34	46.00	20.66	Horizontal	Peak
874.48	26.82	2.23	29.05	46.00	16.95	Horizontal	Peak
918.71	27.39	2.72	30.11	46.00	15.89	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(259.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.31	40.01	-8.96	31.05	40.00	8.95	Vertical	QP
89.85	50.58	-17.00	33.58	43.50	9.92	Vertical	QP
154.35	42.31	-11.28	31.03	43.50	12.47	Vertical	Peak
187.53	45.70	-12.37	33.33	43.50	10.17	Vertical	QP
827.15	27.81	1.70	29.51	46.00	16.49	Vertical	Peak
906.98	27.97	2.61	30.58	46.00	15.42	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(350.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.58	26.74	-5.74	21.00	40.00	19.00	Horizontal	Peak
189.47	40.99	-12.34	28.65	43.50	14.85	Horizontal	Peak
338.46	35.62	-8.37	27.25	46.00	18.75	Horizontal	Peak
795.72	27.40	1.24	28.64	46.00	17.36	Horizontal	Peak
849.46	27.44	1.93	29.37	46.00	16.63	Horizontal	Peak
889.52	27.77	2.49	30.26	46.00	15.74	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(350.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
35.72	39.56	-8.54	31.02	40.00	8.98	Vertical	QP
88.01	50.47	-17.19	33.28	43.50	10.22	Vertical	QP
156.49	44.49	-11.39	33.10	43.50	10.40	Vertical	Peak
187.92	46.51	-12.40	34.11	43.50	9.39	Vertical	QP
902.81	26.86	2.55	29.41	46.00	16.59	Vertical	Peak
980.21	26.25	3.66	29.91	54.00	24.09	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(370MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
32.04	26.66	-6.42	20.24	40.00	19.76	Horizontal	Peak
155.81	35.62	-11.32	24.30	43.50	19.20	Horizontal	Peak
177.15	39.37	-12.19	27.18	43.50	16.32	Horizontal	Peak
191.02	39.63	-12.18	27.45	43.50	16.05	Horizontal	Peak
333.90	34.82	-8.43	26.39	46.00	19.61	Horizontal	Peak
915.71	26.84	2.71	29.55	46.00	16.45	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(370MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.40	39.78	-9.04	30.74	40.00	9.26	Vertical	QP
87.81	51.71	-17.21	34.50	40.00	5.50	Vertical	QP
155.42	44.17	-11.36	32.81	43.50	10.69	Vertical	QP
184.91	45.69	-12.47	33.22	43.50	10.28	Vertical	Peak
836.56	27.58	1.79	29.37	46.00	16.63	Vertical	Peak
929.29	26.88	2.86	29.74	46.00	16.26	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(389.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.36	26.15	-6.04	20.11	40.00	19.89	Horizontal	Peak
176.86	38.22	-12.19	26.03	43.50	17.47	Horizontal	Peak
187.63	38.66	-12.38	26.28	43.50	17.22	Horizontal	Peak
337.10	34.33	-8.38	25.95	46.00	20.05	Horizontal	Peak
909.69	27.03	2.66	29.69	46.00	16.31	Horizontal	Peak
944.90	26.82	3.12	29.94	46.00	16.06	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(389.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.79	39.58	-9.34	30.24	40.00	9.76	Vertical	QP
88.01	50.32	-17.19	33.13	43.50	10.37	Vertical	QP
155.62	44.05	-11.34	32.71	43.50	10.79	Vertical	Peak
189.57	45.74	-12.33	33.41	43.50	10.09	Vertical	QP
831.80	28.16	1.77	29.93	46.00	16.07	Vertical	Peak
933.75	26.29	3.02	29.31	46.00	16.69	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.68	26.69	-5.77	20.92	40.00	19.08	Horizontal	Peak
189.95	40.11	-12.28	27.83	43.50	15.67	Horizontal	Peak
339.62	34.97	-8.36	26.61	46.00	19.39	Horizontal	Peak
820.16	27.08	1.62	28.70	46.00	17.30	Horizontal	Peak
851.59	27.65	1.95	29.60	46.00	16.40	Horizontal	Peak
918.71	26.48	2.72	29.20	46.00	16.80	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.68	38.87	-9.25	29.62	40.00	10.38	Vertical	QP
89.18	50.35	-17.14	33.21	43.50	10.29	Vertical	QP
156.39	43.58	-11.37	32.21	43.50	11.29	Vertical	Peak
188.69	45.10	-12.40	32.70	43.50	10.80	Vertical	QP
864.20	27.37	2.18	29.55	46.00	16.45	Vertical	Peak
945.49	26.45	3.12	29.57	46.00	16.43	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(460MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3 °C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.39	26.12	-5.70	20.42	40.00	19.58	Horizontal	Peak
146.40	34.97	-11.04	23.93	43.50	19.57	Horizontal	Peak
177.63	38.88	-12.19	26.69	43.50	16.81	Horizontal	Peak
324.88	35.24	-8.64	26.60	46.00	19.40	Horizontal	Peak
756.34	28.30	0.51	28.81	46.00	17.19	Horizontal	Peak
903.97	28.45	2.55	31.00	46.00	15.00	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(460MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.69	39.35	-9.26	30.09	40.00	9.91	Vertical	QP
87.91	50.74	-17.20	33.54	40.00	6.46	Vertical	QP
156.20	43.78	-11.34	32.44	43.50	11.06	Vertical	Peak
190.34	44.39	-12.25	32.14	43.50	11.36	Vertical	QP
819.68	27.57	1.61	29.18	46.00	16.82	Vertical	Peak
967.31	26.53	3.45	29.98	54.00	24.02	Vertical	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(519.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.46	26.57	-6.10	20.47	40.00	19.53	Horizontal	Peak
184.81	39.48	-12.48	27.00	43.50	16.50	Horizontal	Peak
318.96	34.19	-8.79	25.40	46.00	20.60	Horizontal	Peak
745.86	27.82	0.46	28.28	46.00	17.72	Horizontal	Peak
800.18	27.65	1.25	28.90	46.00	17.10	Horizontal	Peak
854.02	27.71	1.95	29.66	46.00	16.34	Horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 2(519.9875MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 22.3°C/59%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
36.48	38.24	-9.10	29.14	40.00	10.86	Vertical	QP
87.44	49.48	-17.26	32.22	40.00	7.78	Vertical	QP
155.62	44.09	-11.34	32.75	43.50	10.75	Vertical	Peak
189.99	45.27	-12.28	32.99	43.50	10.51	Vertical	QP
858.09	27.36	2.03	29.39	46.00	16.61	Vertical	Peak
941.99	26.43	3.05	29.48	46.00	16.52	Vertical	Peak

2) 1GHz ~ 5GHz (Worst)

Project No.: 2507R04211E-EM
 Test Mode: Mode 1(400-520MHz)
 EUT Model: UV26
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/57%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 5V from adapter
 (AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
3442.50	27.48	-7.77	19.71	54.00	34.29	horizontal	Average
3442.50	47.98	-7.77	40.21	74.00	33.79	horizontal	Peak
3970.50	27.94	-6.62	21.32	54.00	32.68	horizontal	Average
3970.50	47.59	-6.62	40.97	74.00	33.03	horizontal	Peak
4083.00	27.88	-6.22	21.66	54.00	32.34	horizontal	Average
4083.00	47.58	-6.22	41.36	74.00	32.64	horizontal	Peak
4439.00	27.93	-5.56	22.37	54.00	31.63	horizontal	Average
4439.00	47.73	-5.56	42.17	74.00	31.83	horizontal	Peak
4604.50	28.54	-5.26	23.28	54.00	30.72	horizontal	Average
4604.50	47.36	-5.26	42.10	74.00	31.90	horizontal	Peak
4990.50	29.00	-5.02	23.98	54.00	30.02	horizontal	Average
4990.50	48.06	-5.02	43.04	74.00	30.96	horizontal	Peak

Project No.: 2507R04211E-EM
Test Mode: Mode 1(400-520MHz)
EUT Model: UV26
Test distance: 3m

Temp/Humi/ATM: 23.8°C/57%/100.1kPa
Tested by: Apollo Luo
Power Source: DC 5V from adapter
(AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
3447.50	27.65	-7.75	19.90	54.00	34.10	vertical	Average
3447.50	47.98	-7.75	40.23	74.00	33.77	vertical	Peak
4027.00	28.33	-6.43	21.90	54.00	32.10	vertical	Average
4027.00	47.77	-6.43	41.34	74.00	32.66	vertical	Peak
4563.00	27.90	-5.30	22.60	54.00	31.40	vertical	Average
4563.00	47.12	-5.30	41.82	74.00	32.18	vertical	Peak
4695.50	27.86	-5.12	22.74	54.00	31.26	vertical	Average
4695.50	47.07	-5.12	41.95	74.00	32.05	vertical	Peak
4806.50	28.62	-5.24	23.38	54.00	30.62	vertical	Average
4806.50	47.42	-5.24	42.18	74.00	31.82	vertical	Peak
4939.00	28.72	-5.18	23.54	54.00	30.46	vertical	Average
4939.00	48.58	-5.18	43.40	74.00	30.60	vertical	Peak

Project No.: 2507R04211E-EM
 Test Mode: Mode 2(400.0125MHz)
 EUT Model: UV26
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/57%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 5V from adapter
 (AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
3604.00	27.73	-7.69	20.04	54.00	33.96	horizontal	Average
3604.00	48.33	-7.69	40.64	74.00	33.36	horizontal	Peak
4017.50	27.89	-6.45	21.44	54.00	32.56	horizontal	Average
4017.50	47.38	-6.45	40.93	74.00	33.07	horizontal	Peak
4196.00	27.36	-5.57	21.79	54.00	32.21	horizontal	Average
4196.00	46.68	-5.57	41.11	74.00	32.89	horizontal	Peak
4428.50	27.65	-5.59	22.06	54.00	31.94	horizontal	Average
4428.50	47.27	-5.59	41.68	74.00	32.32	horizontal	Peak
4585.00	28.92	-5.28	23.64	54.00	30.36	horizontal	Average
4585.00	48.71	-5.28	43.43	74.00	30.57	horizontal	Peak
4974.50	28.57	-5.07	23.50	54.00	30.50	horizontal	Average
4974.50	48.77	-5.07	43.70	74.00	30.30	horizontal	Peak

Project No.: 2507R04211E-EM
 Test Mode: Mode 2(400.0125MHz)
 EUT Model: UV26
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/57%/100.1kPa
 Tested by: Apollo Luo
 Power Source: DC 5V from adapter
 (AC 120V/60Hz)



Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4011.50	26.84	-6.47	20.37	54.00	33.63	vertical	Average
4011.50	47.18	-6.47	40.71	74.00	33.29	vertical	Peak
4066.00	27.41	-6.30	21.11	54.00	32.89	vertical	Average
4066.00	47.16	-6.30	40.86	74.00	33.14	vertical	Peak
4409.50	27.55	-5.64	21.91	54.00	32.09	vertical	Average
4409.50	47.25	-5.64	41.61	74.00	32.39	vertical	Peak
4566.00	27.90	-5.30	22.60	54.00	31.40	vertical	Average
4566.00	47.66	-5.30	42.36	74.00	31.64	vertical	Peak
4879.50	28.30	-5.30	23.00	54.00	31.00	vertical	Average
4879.50	48.03	-5.30	42.73	74.00	31.27	vertical	Peak
4988.50	28.74	-5.01	23.73	54.00	30.27	vertical	Average
4988.50	48.57	-5.01	43.56	74.00	30.44	vertical	Peak

FCC §15.121(b) – SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS


Applicable Standard

FCC §15.121(b).

(b) Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

Test Procedure

1. Connected the EUT as the below block diagram;



2. Apply a signal to the EUT antenna port at lowest, middle, highest channel frequencies of the operating band;
3. Adjust the audio output level of the EUT to it's rated value with the distortion less than 10%;
4. Adjust the 8920 output power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB; These output level of the 8920 at each channel frequency is the sensitivity of the EUT;
5. Select the lowest or worst case sensitivity level for all of the bands as the reference sensitivity;
6. Adjust the Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5 and its frequency to the frequency point in the Cellular Band;
7. Set the EUT squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level;
8. Set the EUT in a scanning mode and allow it to scan through it's complete receiving range;
9. If the EUT un-squelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38 dB;
10. Repeat above procedure at the frequencies 824, 836, 849 MHz for the mobile band, and 869, 881.5 and 894 MHz for the Cellular Base Band.

Test Data

Test Mode:	Scanning	Test Engineer:	Lucas Lin
Test Date:	2025-04-16	Test Result:	Pass

Environment Conditions:					
Temperature: (°C)	22.9	Relative Humidity: (%)	55	ATM Pressure: (kPa)	100.1

Scanning Frequency Range (MHz)	Test Frequency (MHz)	Measurement Result (Worst Case) (dB)	Limit (dB)
108-136		49	>38
136-174		46	>38
220-260	824, 836, 849, 869, 881.5, 894	45	>38
350-390		48	>38
400-520		48	>38

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2507R04211E-EM-EXP EUT EXTERNAL PHOTOGRAPHS and 2507R04211E-EM-INP EUT INTERNAL PHOTOGRAPHS

EXHIBIT B – TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2507R04211E-EM-TSP TEST SETUP PHOTOGRAPHS.

Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95 % confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

*******END OF REPORT*******