

# **Qingdao Richmat Intelligence Technology Inc**

## **FCC Class II Permissive Change Report**

**Report Type:**  
FCC Part 15.247 RF report

**MODEL:**  
HJ8258

**REPORT NUMBER:**  
2503B0475SHA-001

**ISSUE DATE:**  
April 7, 2025

**DOCUMENT CONTROL NUMBER:**  
TTRF15.247\_V1 © 2018 Intertek





Total Quality. Assured.

## TEST REPORT

Intertek Testing Services (Shanghai FTZ) Co., Ltd.  
Building No.86, 1198 Qinzhou Road (North)  
Caohejing Development Zone  
Shanghai 200233, China

Telephone: 86 21 6127 8200  
[www.intertek.com](http://www.intertek.com)

Report no.: 2503B0475SHA-001

**Applicant:** Qingdao Richmat Intelligence Technology Inc  
NO.78 Kongquehe 4th Road, Qingdao Clothing Industry park, Jimo,  
Qingdao, Shandong Province, China.

**Manufacturer:** Qingdao Richmat Intelligence Technology Inc  
NO.78 Kongquehe 4th Road, Qingdao Clothing Industry park, Jimo,  
Qingdao, Shandong Province, China.

**FCC ID:** 2AJJGHJ8258

### SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

**47CFR Part 15 (2023): Radio Frequency Devices (Subpart C)**

**ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices**

### PREPARED BY:

Project Engineer  
Scout Gong

### REVIEWED BY:

Reviewer  
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT****Content**

<b>REVISION HISTORY</b> .....	<b>4</b>
<b>MEASUREMENT RESULT SUMMARY</b> .....	<b>5</b>
<b>1 GENERAL INFORMATION</b> .....	<b>6</b>
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....	6
1.2 TECHNICAL SPECIFICATION.....	8
1.3 DESCRIPTION OF TEST FACILITY.....	9
<b>2 TEST SPECIFICATIONS</b> .....	<b>10</b>
2.1 STANDARDS OR SPECIFICATION .....	10
2.2 MODE OF OPERATION DURING THE TEST.....	10
2.3 TEST SOFTWARE LIST .....	11
2.4 TEST PERIPHERALS LIST.....	11
2.5 TEST ENVIRONMENT CONDITION:.....	11
2.6 INSTRUMENT LIST .....	12
2.7 MEASUREMENT UNCERTAINTY.....	13
<b>3 RADIATED EMISSION</b> .....	<b>14</b>
3.1 LIMIT .....	14
3.2 MEASUREMENT PROCEDURE .....	14
3.3 TEST CONFIGURATION .....	16
3.4 TEST RESULTS OF RADIATED EMISSIONS .....	18
<b>4 POWER LINE CONDUCTED EMISSION</b> .....	<b>23</b>
4.1 LIMIT .....	23
4.2 TEST CONFIGURATION .....	23
4.3 MEASUREMENT PROCEDURE .....	24
4.4 TEST RESULTS OF POWER LINE CONDUCTED EMISSION.....	25
<b>5 ASSIGNED BANDWIDTH (20DB BANDWIDTH)</b> .....	<b>29</b>
5.1 LIMIT .....	29
5.2 MEASUREMENT PROCEDURE .....	29
5.3 TEST CONFIGURATION .....	29
5.4 THE RESULTS.....	30
<b>6 ANTENNA REQUIREMENT</b> .....	<b>32</b>

**TEST REPORT****Revision History**

Report No.	Version	Description	Issued Date
2503B0475SHA-001	Rev. 01	Initial issue of report	April 7, 2025

**TEST REPORT****Measurement Result Summary**

TEST ITEM	FCC REFERENCE	RESULT
Radiated Emissions in restricted frequency bands	15.247(d), 15.205&15.209	Pass
Power line conducted emission	15.207(a)	Pass
Occupied bandwidth	-	Tested
Antenna requirement	15.203	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

## TEST REPORT

## 1 GENERAL INFORMATION

## 1.1 Description of Equipment Under Test (EUT)

Product name:	Module																																																								
Type/Model:	HJ8258																																																								
Description of EUT	The report is C2PC report, the following host model was added. Therefore, host model was tested.																																																								
Host models:	Control Box HJC9N-X-X-X-X-X-X-X-X, HJC18N-X-X-X-X-X-X ("X" represents the features supported by the product, and is represented by a number)  <table><thead><tr><th colspan="2">Model: HJC9N - X - X - X - X - X - X - X - X</th></tr></thead><tbody><tr><td><b>Number of drives</b></td><td></td></tr><tr><td>1 Drives</td><td>1</td></tr><tr><td>2 Drives</td><td>2</td></tr><tr><td>3 Drives</td><td>3</td></tr><tr><td>4 Drives</td><td>4</td></tr><tr><td><b>Hall control</b></td><td></td></tr><tr><td>Not supported</td><td>0</td></tr><tr><td>Supported</td><td>1</td></tr><tr><td><b>Peripheral - Vibratory massager</b></td><td></td></tr><tr><td>Not supported</td><td>0</td></tr><tr><td>1 Vibratory massager</td><td>1</td></tr><tr><td>2 Vibratory massagers</td><td>2</td></tr><tr><td><b>Peripherals - Light &amp; USB</b></td><td></td></tr><tr><td>Not supported</td><td>0</td></tr><tr><td>1*light &amp; 1*USB</td><td>1</td></tr><tr><td><b>MOS speed regulation</b></td><td></td></tr><tr><td>Not supported</td><td>0</td></tr><tr><td>Supported</td><td>1</td></tr><tr><td><b>Current sampling and overcurrent protection</b></td><td></td></tr><tr><td>Not supported</td><td>0</td></tr><tr><td>Supported</td><td>1</td></tr><tr><td><b>Device break detection</b></td><td></td></tr><tr><td>Not supported</td><td>0</td></tr><tr><td>Supported</td><td>1</td></tr><tr><td><b>Alarm clock function</b></td><td></td></tr><tr><td>Not supported</td><td>0</td></tr><tr><td>Supported</td><td>1</td></tr></tbody></table>	Model: HJC9N - X - X - X - X - X - X - X - X		<b>Number of drives</b>		1 Drives	1	2 Drives	2	3 Drives	3	4 Drives	4	<b>Hall control</b>		Not supported	0	Supported	1	<b>Peripheral - Vibratory massager</b>		Not supported	0	1 Vibratory massager	1	2 Vibratory massagers	2	<b>Peripherals - Light &amp; USB</b>		Not supported	0	1*light & 1*USB	1	<b>MOS speed regulation</b>		Not supported	0	Supported	1	<b>Current sampling and overcurrent protection</b>		Not supported	0	Supported	1	<b>Device break detection</b>		Not supported	0	Supported	1	<b>Alarm clock function</b>		Not supported	0	Supported	1
Model: HJC9N - X - X - X - X - X - X - X - X																																																									
<b>Number of drives</b>																																																									
1 Drives	1																																																								
2 Drives	2																																																								
3 Drives	3																																																								
4 Drives	4																																																								
<b>Hall control</b>																																																									
Not supported	0																																																								
Supported	1																																																								
<b>Peripheral - Vibratory massager</b>																																																									
Not supported	0																																																								
1 Vibratory massager	1																																																								
2 Vibratory massagers	2																																																								
<b>Peripherals - Light &amp; USB</b>																																																									
Not supported	0																																																								
1*light & 1*USB	1																																																								
<b>MOS speed regulation</b>																																																									
Not supported	0																																																								
Supported	1																																																								
<b>Current sampling and overcurrent protection</b>																																																									
Not supported	0																																																								
Supported	1																																																								
<b>Device break detection</b>																																																									
Not supported	0																																																								
Supported	1																																																								
<b>Alarm clock function</b>																																																									
Not supported	0																																																								
Supported	1																																																								

## TEST REPORT

	<b>Model:</b> HJC18N - X - X - X - X - X - X - X
	<b>Number of drives</b>
1 Drives	1
2 Drives	2
	<b>Hall control</b>
Not supported	0
Supported	1
	<b>Peripherals - Light /USB</b>
No light & No USB	0
1 light & 1 USB	1
	<b>Current sampling and overcurrent protection</b>
Not supported	0
Supported	1
	<b>Device break detection</b>
Not supported	0
Supported	1
	<b>Alarm clock function</b>
Not supported	0
Supported	1
<b>Rating:</b>	Module: DC 3.3V
<b>EUT type:</b>	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
<b>Software Version:</b>	/
<b>Hardware Version:</b>	/
<b>Sample No.:</b>	A250301-19-001, A250301-19-002
<b>Sample received date:</b>	March 1, 2025
<b>Date of test:</b>	March 1, 2025, to March 31, 2025

**TEST REPORT****1.2 Technical Specification**

Frequency Range:	2402-2480MHz
Support Standards:	Bluetooth LE
Type of Modulation:	GFSK
Channel Number:	40
Data Rate:	1Mbps
Channel Separation:	2MHz
Antenna Information:	3dBi, PCB antenna (declared by the manufacturer)

**TEST REPORT****1.3 Description of Test Facility**

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

**TEST REPORT**

## 2 TEST SPECIFICATIONS

### 2.1 Standards or specification

47CFR Part 15 (2023)

ANSI C63.10 (2020)

KDB 558074(v05)

### 2.2 Mode of operation during the test

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

Radiated test mode: EUT transmitted signal with BT antenna.

The lowest, middle and highest channel were tested as representatives.

Frequency Band (MHz)				2402 ~ 2480			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	<b>2402</b>	10	2422	<b>20</b>	<b>2442</b>	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	<b>39</b>	<b>2480</b>

#### Data rate VS Power:

The test setting software is offered by the manufactory.

Test software and Power Setting parameter			
Test Software		UartAssist.exe	
Working Mode		BLE	
Test Channel	2402MHz	2442MHz	2480MHz
Power Setting	default	default	default

**TEST REPORT****2.3 Test software list**

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

**2.4 Test peripherals list**

Item No.	Name	Band and Model	Description
1	Laptop computer	HP ProBook 6470b	100-240V AC, 50/60Hz
2	AC/DC Adapter	PS3-A29020-1	100-240V AC, 50/60Hz

**2.5 Test environment condition:**

Test items	Temperature	Humidity
Radiated emission	22°C	55% RH
Assigned bandwidth (20dB bandwidth)	22°C	55% RH
Power line conducted emission	/	/

**TEST REPORT**
**2.6 Instrument list**

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESR7	EC 6194	2026-02-17
<input checked="" type="checkbox"/>	Attenuator	Hua Xiang	Ts5-10db-6g	EC 6194-1	2025-12-06
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2025-07-23
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2026-01-09
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2025-08-18
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESR	EC 6501	2025-09-10
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2025-09-11
<input checked="" type="checkbox"/>	TRILOG broadband Antenna	Schwarzbeck	VULB9168	EC 6402	2026-03-18
<input checked="" type="checkbox"/>	Pre-amplifier	Tonscend	tap01018050	EC 6432-1	2025-12-03
<input checked="" type="checkbox"/>	Horn antenna	Tonscend	bha9120d	EC 6432-2	2026-03-19
<input checked="" type="checkbox"/>	Horn antenna	ETS	3116c	EC 5955	2025-08-14
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross	-	EC 3048	2026-07-11
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030B	EC 6078	2026-03-17
<input checked="" type="checkbox"/>	Coaxial cable	ETS	/	/	2026-03-04
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Therom-Hygrograph	Testo	175h1	EC 6640	2025-08-29
<input checked="" type="checkbox"/>	Therom-Hygrograph	Testo	175h1	EC 6641	2025-08-29

**TEST REPORT****2.7 Measurement uncertainty**

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	± 0.74dB
Radiated Emissions in restricted frequency bands below 1GHz	± 4.90dB
Radiated Emissions in restricted frequency bands above 1GHz	± 5.02dB
Emission outside the frequency band	± 2.89dB
Occupied Channel Bandwidth	± 0.88 %
Power line conducted emission	± 3.19dB

**TEST REPORT**

### 3 Radiated emission

Test result: Pass

#### 3.1 Limit

Fundamental Frequency (MHz)	Fundamental limit (dBuV/m)	Harmonic limit (dBuV/m)
<input type="checkbox"/> 902 - 928	94	54
<input checked="" type="checkbox"/> 2400 - 2483.5	94	54
<input type="checkbox"/> 5725 - 5875	94	54
<input type="checkbox"/> 24000 - 24250	108	68

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### 3.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters(0.1 meters for floor-standing device) above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, the lowest height of the magnetic antenna was 1 m above the ground.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**NOTE:**

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

**TEST REPORT****For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) or 0.1 meters (for floor-standing device) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or  $3 \times RBW$  (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported


**TEST REPORT****3.3 Test Configuration**

For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:



**TEST REPORT****For Radiated emission above 1GHz:**


**TEST REPORT****3.4 Test Results of Radiated Emissions**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


The worst waveform from 30MHz to 1000MHz is listed as below:

**Model: HJC9N**

Horizontal





Vertical



**TEST REPORT****Test data below 1GHz**

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	30.000	22.40	19.80	40.00	17.60	PK
H	185.511	26.30	10.80	43.50	17.20	PK
H	214.669	22.80	10.90	43.50	20.70	PK
H	646.212	27.20	21.60	46.00	18.80	PK
H	875.591	32.30	23.70	46.00	13.70	PK
H	980.561	32.10	24.90	54.00	21.90	PK
V	30.000	28.30	19.80	40.00	11.70	PK
V	43.607	26.50	12.50	40.00	13.50	PK
V	59.158	25.80	7.50	40.00	14.20	PK
V	78.597	30.10	8.20	40.00	9.90	PK
V	618.998	27.70	21.50	46.00	18.30	PK
V	877.535	31.60	23.70	46.00	14.40	PK

**TEST REPORT****Model: HJC18N****Horizontal****Vertical**

**TEST REPORT****Test data below 1GHz**

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	30.000	22.10	19.80	40.00	17.90	PK
H	197.174	27.30	10.80	43.50	16.20	PK
H	624.830	27.80	21.60	46.00	18.20	PK
H	757.014	33.20	22.40	46.00	12.80	PK
H	805.611	36.30	22.80	46.00	9.70	PK
H	955.291	32.60	24.70	46.00	13.40	PK
V	31.944	29.50	18.80	40.00	10.50	PK
V	55.271	23.80	8.30	40.00	16.20	PK
V	103.868	22.40	12.20	43.50	21.10	PK
V	160.241	22.70	11.40	43.50	20.80	PK
V	698.697	29.60	22.00	46.00	16.40	PK
V	832.826	34.20	23.30	46.00	11.80	PK

**TEST REPORT**
**Test result above 1GHz:**

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H/V	2402.00	86.20	32.60	114.00	27.80	PK
	H/V	2402.00	84.50	32.60	94.00	9.50	AV
	H/V	2390.00	42.20	32.60	74.00	31.80	PK
	H/V	2390.00	37.20	32.60	54.00	16.80	AV
	H/V	4804.00	58.90	-12.90	74.00	15.10	PK
	H/V	4804.00	43.30	-12.90	54.00	10.70	AV
M	H/V	2442.00	86.10	32.70	114.00	27.90	PK
	H/V	2442.00	82.50	32.70	94.00	11.50	AV
	H/V	4884.00	58.50	-12.40	74.00	15.50	PK
	H/V	4884.00	43.60	-12.40	54.00	10.40	AV
H	H/V	2480.00	86.30	32.90	114.00	27.70	PK
	H/V	2480.00	84.10	32.90	94.00	9.90	AV
	H/V	2483.50	43.70	32.90	74.00	30.30	PK
	H/V	2483.50	37.30	32.90	54.00	16.70	AV
	H/V	4960.00	54.70	-12.20	74.00	19.30	PK
	H/V	4960.00	42.20	-12.20	54.00	11.80	AV


Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.  
 2. Corrected Reading = Original Receiver Reading + Correct Factor  
 3. Margin = Limit - Corrected Reading  
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,  
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,  
 Limit = 40.00dBuV/m.  
 Then Correct Factor =  $30.20 + 2.00 - 32.00 = 0.20$ dB/m;  
 Corrected Reading =  $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$ ;  
 Margin =  $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$ .

**TEST REPORT****4 Power line conducted emission****Test result: Pass****4.1 Limit**

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

**4.2 Test Configuration**



## TEST REPORT

### 4.3 Measurement Procedure

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

**TEST REPORT****4.4 Test Results of Power line conducted emission****Model: HJC9N**

**TEST REPORT**
**Test Data:**



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1	159.000kHz	65.52	40.16	-25.36	33.96	6.20	QP	L1
2	208.500kHz	63.26	32.84	-30.42	26.64	6.20	QP	L1
3	244.500kHz	61.94	27.77	-34.17	21.57	6.20	QP	L1
4	294.000kHz	60.41	23.58	-36.83	17.38	6.20	QP	L1
5	339.000kHz	59.23	21.81	-37.42	15.61	6.20	QP	L1
6	442.500kHz	57.01	16.63	-40.38	10.43	6.20	QP	L1
7	154.500kHz	65.75	41.44	-24.31	35.24	6.20	QP	N
8	195.000kHz	63.82	34.42	-29.40	28.22	6.20	QP	N
9	235.500kHz	62.25	28.83	-33.42	22.63	6.20	QP	N
10	267.000kHz	61.21	24.05	-37.16	17.95	6.10	QP	N
11	433.500kHz	57.19	17.43	-39.76	11.23	6.20	QP	N
12	582.000kHz	56.00	20.31	-35.69	14.11	6.20	QP	N
13	163.500kHz	55.28	8.99	-46.29	2.79	6.20	CAV	L1
14	240.000kHz	52.10	7.20	-44.90	1.00	6.20	CAV	L1
15	343.500kHz	49.12	-1.11	-50.23	-7.31	6.20	CAV	L1
16	456.000kHz	46.77	-1.56	-48.33	-7.76	6.20	CAV	L1
17	595.500kHz	46.00	1.51	-44.49	-4.69	6.20	CAV	L1
18	3.233MHz	46.00	-2.15	-48.15	-8.45	6.30	CAV	L1
19	163.500kHz	55.28	8.60	-46.68	2.50	6.10	CAV	N
20	190.500kHz	54.01	4.34	-49.67	-1.76	6.10	CAV	N
21	492.000kHz	46.13	-0.89	-47.02	-7.09	6.20	CAV	N
22	591.000kHz	46.00	1.90	-44.10	-4.30	6.20	CAV	N
23	1.176MHz	46.00	-0.94	-46.94	-7.14	6.20	CAV	N
24	3.336MHz	46.00	-1.41	-47.41	-7.71	6.30	CAV	N

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Factor

3. Delta = Level- Limit

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

**TEST REPORT****Model: HJC18N**

**TEST REPORT**
**Test Data:**

No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1	181.500kHz	64.42	36.51	-27.91	30.31	6.20	QP	L1
2	231.000kHz	62.41	28.57	-33.84	22.37	6.20	QP	L1
3	253.500kHz	61.64	25.00	-36.64	18.80	6.20	QP	L1
4	298.500kHz	60.28	21.75	-38.53	15.55	6.20	QP	L1
5	366.000kHz	58.59	18.60	-39.99	12.40	6.20	QP	L1
6	27.596MHz	60.00	4.71	-55.29	-3.09	7.80	QP	L1
7	154.500kHz	65.75	40.31	-25.44	34.11	6.20	QP	N
8	181.500kHz	64.42	35.49	-28.93	29.39	6.10	QP	N
9	226.500kHz	62.58	29.85	-32.73	23.65	6.20	QP	N
10	267.000kHz	61.21	24.11	-37.10	18.01	6.10	QP	N
11	366.000kHz	58.59	18.54	-40.05	12.34	6.20	QP	N
12	406.500kHz	57.72	16.42	-41.30	10.22	6.20	QP	N
13	181.500kHz	54.42	5.66	-48.76	-0.54	6.20	CAV	L1
14	231.000kHz	52.41	-0.19	-52.60	-6.39	6.20	CAV	L1
15	573.000kHz	46.00	-0.01	-46.01	-6.21	6.20	CAV	L1
16	1.154MHz	46.00	6.32	-39.68	0.12	6.20	CAV	L1
17	1.266MHz	46.00	2.98	-43.02	-3.22	6.20	CAV	L1
18	2.324MHz	46.00	-1.97	-47.97	-8.17	6.20	CAV	L1
19	159.000kHz	55.52	7.69	-47.83	1.49	6.20	CAV	N
20	181.500kHz	54.42	6.80	-47.62	0.70	6.10	CAV	N
21	222.000kHz	52.74	5.05	-47.69	-1.15	6.20	CAV	N
22	577.500kHz	46.00	1.09	-44.91	-5.11	6.20	CAV	N
23	1.167MHz	46.00	7.13	-38.87	0.93	6.20	CAV	N
24	3.246MHz	46.00	-1.79	-47.79	-8.09	6.30	CAV	N

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Factor

3. Delta = Level- Limit

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

**TEST REPORT**

## 5 Assigned bandwidth (20dB bandwidth)

**Test result:** Pass

### 5.1 Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emission is contained within the allocated frequency band.

### 5.2 Measurement Procedure


The 20dB Bandwidth is measured using the Spectrum Analyzer.

Set Span = 2 to 3 times the 20 dB bandwidth, RBW = approximately 1% of the 20 dB bandwidth,

VBW>RBW, Sweep = auto, Detector = peak, Trace = max hold.

The test was performed at 2 channels (lowest and highest channel).


### 5.3 Test Configuration




## TEST REPORT

## 5.4 The results

Test Mode	Frequency (MHz)	20dB Bandwidth (MHz)	99% Bandwidth (MHz)	F <sub>L</sub> at 20dB BW (MHz)	F <sub>H</sub> at 20dB BW (MHz)
/	2402	1.0728	1.0273	>2400	/
	2480	1.1091	1.0469	/	<2483.5
Limit	N/A		N/A	F <sub>L</sub> >2400	F <sub>H</sub> <2483.5
<b>Result</b>	<b>Complied</b>				



## TEST REPORT



**TEST REPORT**

## 6 Antenna requirement

**Requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**Result:**

EUT uses PCB antenna to the intentional radiator, so it can comply with the provisions of this section.

\*\*\*\*\* END \*\*\*\*\*