

# 1 RF Exposure Report

## 1.1 RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS 102, Issue 5, Section 2.5.2 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached. Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

## 1.2 RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b) showed in Table 1. And as per the RSS 102, Issue 5, Section 2.5.2 the MPE limits mentioned in Table 2.

Table 1: Limits for Maximum Permissible Exposure (MPE) as per FCC

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 - 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 - 100000	--	--	1.0

F or  $f$  = Frequency in MHz

### 1.2.1 Friis Formula

Friis Transmission Formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$r$  = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

<b>RF Exposure</b>	<b>Reference Test Report No: ULR-TC568819300000030F 001</b>	<b>Seite 2 von 2</b> <i>Page 2 of 2</i>
--------------------	---	--

### 1.2.2 Test report reference

Maximum measured conducted output power readings are taken from module test report FR442807AD with FCC ID SQGBT900 for Bluetooth.

Refer SAR Test report with FCC ID 2AJKO198658 for RF exposure information for Wi-Fi 2.4 and Wi-Fi 5 GHz.

### 1.2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

Note:  $\pm 0.5$  dB tune up value is considered for MPE calculation.

Protocol: Bluetooth

## Test Results

Manufacturer has declared the tune-up value as  $\pm 0.5$  dBm is considered in MPE calculation.

**Antenna: Ceramic**

**Antenna gain (G) :** 0.5 dBi for BT 2.4 GHz

Protocol	Data Rate(Mbps)	Channel Frequency (MHz)	Maximum Pout(dBm)	Tune up value in (dB)	Output Power to Antenna (mW)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
BT	3	2480	8.26	0.5	7.51623	0.001677758	1