

Report Number: F690501/RF-RTL012909

Page:

8

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: 2AJKSKGC-108L

Equipment Under Test: WIRELESS CHARGER

Model Name : KGC-108L

Variant Model Name : KGC-108S

Applicant : Kum Oh Electronics Co., Ltd.

Manufacturer : Kum Oh Electronics Co., Ltd.

Date of Receipt : 2018.07.04

Date of Test(s) : 2018.07.07 ~ 2018.07.24

Date of Issue : 2018.07.25

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2018.07.25

Nancy Park

Technical Manager:

Date:

2018.07.25

Jungmin Yang



Report Number: F690501/RF-RTL012909 Page: 2 of 8

Table of contents

1. General information	3
2. Test Result	5



Report Number: F690501/RF-RTL012909 Page: of 8

1. General information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant Kum Oh Electronics Co., Ltd.

Address 35, Gilju-ro 444beon-gil, Bucheon-si, Gyeonggi-do, South Korea, 14556

Contact Person : Park, Chan-hong Phone No. : +82 32 712 0322

1.3. Details of Manufacturer

Company : Same as applicant Address : Same as applicant

1.4. Description of EUT

Kind of Product	WIRELESS CHARGER	
Model Name	KGC-108L	
Variant Model Name	KGC-108S	
Power Supply	DC 5.0 V	
Frequency Range	120 kHz ~ 190 kHz	
Antenna Type	Inductive loop coil antenna	



Report Number: F690501/RF-RTL012909 Page: of 8

1.5. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
E-Field Probe	D.A.R.E!! Instruments	RadiSense 4	13I00444SNO04	Jun. 21, 2018	Annual	Jun. 21, 2019
BroadBand Field Meter	NARDA	NBM-550	E-1196	Jun. 07, 2018	Annual	Jun. 07, 2019
H-Field Probe	NARDA	HF-3061	D-0336	Jun. 07, 2018	Annual	Jun. 07, 2019
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.	N/A	N.C.R.

▶ Support Equipment

Description Manufacturer		Model	FCC ID
Smart Wearable Device	Samsung Electronics Co., Ltd.	SM-R805U	A3LSMR805U

1.6. Test Report Revision

Revision	Report number Date of Issue		Description	
0	F690501/RF-RTL012909	2018.07.25	Initial	

1.7. Worst Case of Test Configurations

In order to check all kinds of possible configurations, EUT was evaluated with appropriate client and under each charging condition as below table.

EUT configuration Description 1 % of battery					
Charging Mode with client device (Model: SM-R805U, FCC ID: A3LSMR805U)	1 % of battery				
	50 % of battery				
	99 % of battery				

Note;

- EUT was investigated with client device under normal charging condition as above then worst value was only reported.

1.8. Information of Variant Model

Model Name	Description
KGC-108L	- Basic model.
KGC-108S	- Same as basic model, but the outside of plastic is different.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 http://www.sgsgroup.kr



Report Number: F690501/RF-RTL012909 Page: 5 of 8

2. Test Result

2.1. Test Setup



2.2. Measurement procedure

- a) The RF exposure test was performed in anechoic chamber.
- b) The measurement probe was placed at test distance (15 cm) which is between the edge of the charger and the geometric center of probe.
- c) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.
- d) The EUT was measured according to the dictates of KDB 680106 D01 v03.



Report Number: F690501/RF-RTL012909 Page: of 8

2.3. Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03.

- (1) Power transfer frequency is less that 1 Mz.
 - The device operates at a frequency 120 kHz to 190 kHz.
- (2) Output power from each primary coil is less than or equal to 15 watts.
 - Output power from primary coil: 5 watts.
- (3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
 - The transfer system including a charging system with one primary coils is to detect and allow only between individual pairs of coils.
- (4) Client device is placed directly in contact with the transmitter.
 - Client device is placed directly in contact with the transmitter.
- (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
 - Mobile exposure conditions only.
- (6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50 % of the MPE limit.
 - Refer to following test results.
 - The EUT H-Field Strength levels at 15 cm < 50 % of the MPE H-Field Strength limit 1.63 A/m
 - The H-Field Strength at 15 cm is not detected.



Report Number: F690501/RF-RTL012909 Page: 7 8

2.4. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

TABLE 1 - LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (쌘)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m) Power Density (\pi\text{\mathbb{M}}/c\pi')		Average Time (minutes)				
(A) Limits for Occupational /Control Exposures								
0.3-3.0	614	1.63	*(100)	6				
3.0-30	1842/f	4.89/f	*(900/f ²)	6				
30-300	61.4	0.163	1.0	6				
300-1 500			f/300	6				
1 500-100 000			5	6				
	(B) Limits for Ger	neral Population / Unc	ontrol Exposures					
<u>0.3-1.34</u>	<u>614</u>	<u>1.63</u>	*(100)	30				
1.34-30	824/f	2.19/f	*(180/f ²)	30				
30-300	27.5	0.073	0.2	30				
300-1 500			f/1 500	30				
1 500-100 000			1.0	30				

f = frequency in Mb

^{* =} Plane wave equivalent power density



Report Number: F690501/RF-RTL012909 Page: of 8

2.5. E and H field strength

Ambient temperature : (23 ± 1) °C Relative humidity : 47 % R.H.

2.5.1. E-Field Strength at from the edges surrounding the EUT

Test condition: Test condition: Charging mode (1 % battery status of client device)

Frequency (klb)	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Probe Position F (V/m)	Limits (V/m)
120 ~ 190	5.75	8.79	6.53	5.81	4.05	5.50	614

2.5.2. H-Field Strength at from the edges surrounding the EUT

Test condition: Test condition: Charging mode (1 % battery status of client device)

Frequency (klb)	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Probe Position F (A/m)	Limits (A/m)
120 ~ 190		Not detected					

Remark;

- H-field strength (A/m) = B-field (μ T) / 1.25
- Because of very low measurements, the H-field strength values were reported as "Not detected".

- End of the Test Report -