





MPE TEST REPORT

Applicant UAB TELTONIKA

FCC ID 2AJLOTM2500TLT

Product GSM/GPRS/GNSS/BLUETOOTH module

Model TM2500

Report No. RXA1606-0123MPE

Issue Date September 2, 2016

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Jiangpeng Lan

Jiang peng Lan

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Report No: RXA1606-0123MPE

Table of Contents

1	Test	t Laboratory	. 3
	1.1	Notes of the Test Report	. 3
	1.2	Test facility	. 3
	1.3	Testing Location	. 4
	1.4	Laboratory Environment	. 4
2	Des	cription of Equipment under Test	. 5
		kimum conducted output power (measured) and antenna Gain	



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology**

(shanghai) co., Ltd). The results documented in this report apply only to the tested sample, under the

conditions and modes of operation as described herein . Measurement Uncertainties were not taken

into account and are published for informational purposes only. This report is written to support

regulatory compliance of the applicable standards stated above. This report must not be used by the

client to claim product certification, approval, or endorsement by CNAS or any government agencies.

1.2 Test facility

CNAS (accreditation number:L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation

Service for Conformity Assessment (CNAS).

FCC (recognition number is 428261)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission

list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic

emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic

emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory

Accreditation to perform electromagnetic emission measurement.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Xu Kai

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: http://www.ta-shanghai.com

E-mail: xukai@ta-shanghai.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C		
Relative humidity	Min. = 30%, Max. = 70%		
Ground system resistance	< 0.5 Ω		

Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.



2 Description of Equipment under Test

Client Information

Applicant	UAB TELTONIKA	
Applicant address	Saltoniskiu st. 10c, Vilnius, Lithuania	
Manufacturer	UAB TELTONIKA	
Manufacturer address	Saltoniskiu st. 10c, Vilnius, Lithuania	

General Technologies

Model	TM2500
Product IMEI:	357454070000011
Hardware Version	TM2500_01
Software Version	TM25_D_00.00.01.00
Date of Testing:	July 28, 2016 ~ August 26, 2016



Report No: RXA1606-0123MPE

3 Maximum Radiated Output Power

Band	Radiated power (dBm)
GSM 850	33.49
GSM 1900	28.75
Bluetooth	-2.05



According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

TABLE 1 – LIMITS FOR MAXIMUN PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time		
(MHz)	Strength	Strength		934 195		
44.000	(V/m)	(A/m)	(mW/cm2)	(minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3-3.0	614	1.63	*(100)	6		
3-30	1842/f	4.89/f	*(900/f2)	6		
30-300	61.4	0.163	1.0	6		
300-1500			f/300	6		
1500-100,000			5	6		
(B)	Limits for General	Population/Uncont	rolled Exposure			
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	*(180/f2)	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/1500	30		
1500-100,000			1.0	30		

f = frequency in MHz

- Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.
- Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

^{* =} Plane-wave equivalent power density



The maximum permissible exposure for 1500~100,000MHz is 1.0.So

Band	The maximum permissible exposure		
GSM 850	0.56mW/cm ²		
GSM 1900	1.00mW/cm ²		
Bluetooth	1.00mW/cm ²		

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 865664 D01 is used in the calculation.

Equation from KDB 865664 D01, Edition 97-01 is:

S= PG /
$$4 \square R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

R = 20 cm

∏= 3.1416

Solving for S, the power density at 20 cm is

Band	PG (mW)	Test Result (mW/cm ²)	Limit Value (mW/cm²)	The MPE ratio
GSM 850	33.49	0.444	0.56	0.793
GSM 1900	28.75	0.149	1.0	0.149
Bluetooth	-2.05	0.000124	1.0	0.000124
Note: The MPE ratio = Mac Test Result÷Limit Value				

So the simultaneous transmitting antenna pairs as below:

∑of MPE ratios= GSM + Bluetooth =0.793+0.000124=0.793124 <1

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.