

# Single Modular approval Declaration letter

We , EULUM DESIGN, LLC apply Single modular approval for  
FCC ID: 2AJML- EUCSBM

According to 996369 D01 Module Equip Auth Guide v01r04 and 15.212 requirement:

- 1) The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly;

*Answer : YES, both side shielded*

- 2) The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;

*Answer : Yes ; All inputs to the modules are buffered through logic or microprocessor inputs.*

- 3) The modular transmitter must have its own power supply regulation.

*Answer : Yes ; A low drop out regulator is used for modular power supply regulation.*

- 4) The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);

*Answer : Yes ; Device is equipped with Chip Antenna. The EUT meets the FCC antenna requirements; unique antenna connector and photo of antenna are shown in the test report.*

- (5) The module must demonstrate compliance in a stand-alone configuration;

*Answer : Yes , distance between modular and all AEs are bigger than 10cm , refer to setup photo.*

- (6) The module must be labelled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labelling requirements);

*Answer : Yes ; The modular has a permanent fixed label, and below statement was listed in the Users Manual; The host device must be labelled to display the FCC ID of the module Contains FCC ID: 2AJML- EUCSBM*

- (7) The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee;

*Answer : Yes ; The module comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee, Refer to test report and user manual .*

- (8) The module must comply with RF exposure requirements

*Answer : Yes , Transmitter meets MPE calculation of 47 CFR 1.1307 . Refer to MPE Reports and Refer to modular installation manual*



(signature)

(printed name) Marcus Worthington