



# FCC RF Test Report

**APPLICANT** : LC Future Center Limited Taiwan Branch  
**EQUIPMENT** : Notebook  
**BRAND NAME** : Lenovo  
**MODEL NAME** : TP00086A  
**FCC ID** : 2AJN7-TP00086AUC  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

Equipment: AirPrime EM7455 and Intel 8260NGW tested inside of Lenovo Notebook.

This is a partial report which is included the conducted emission and radiated emission test items. The product was received on Nov. 18, 2016 and testing was completed on Dec. 19, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



***SPORTON INTERNATIONAL INC.***  
No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY</b> .....	<b>3</b>
<b>SUMMARY OF TEST RESULT</b> .....	<b>4</b>
<b>1 GENERAL DESCRIPTION</b> .....	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT .....	6
1.6 Testing Location .....	6
1.7 Applicable Standards.....	6
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST</b> .....	<b>7</b>
2.1 Descriptions of Test Mode .....	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System .....	8
2.4 Support Unit used in test configuration and system .....	9
2.5 EUT Operation Test Setup .....	9
<b>3 TEST RESULT</b> .....	<b>10</b>
3.1 Radiated Band Edges and Spurious Emission Measurement .....	10
3.2 AC Conducted Emission Measurement.....	14
<b>4 LIST OF MEASURING EQUIPMENT</b> .....	<b>18</b>
<b>5 UNCERTAINTY OF EVALUATION</b> .....	<b>19</b>

**APPENDIX A. RADIATED SPURIOUS EMISSION****APPENDIX B. RADIATED SPURIOUS EMISSION PLOTS****APPENDIX C. DUTY CYCLE PLOTS****APPENDIX D. SETUP PHOTOGRAPHS****APPENDIX E. ANTENNA INFORMATION**



# REVISION HISTORY



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.91 dB at 2489.520 MHz
3.2	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.80 dB at 0.478 MHz



## 1 General Description

### 1.1 Applicant

**LC Future Center Limited Taiwan Branch**

7F., No.780, Bei'an Rd., Zhongshan Dist., Taipei City 104, Taiwan (R.O.C.)

### 1.2 Manufacturer

**LC Future Center Limited Taiwan Branch**

7F., No.780, Bei'an Rd., Zhongshan Dist., Taipei City 104, Taiwan (R.O.C.)

### 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Notebook
<b>Brand Name</b>	Lenovo
<b>Model Name</b>	TP00086A
<b>FCC ID</b>	2AJN7-TP00086AUC
<b>Sample 1</b>	EUT with Antenna 1
<b>Sample 2</b>	EUT with Antenna 2
<b>Integrated WWAN Module</b>	Manufacturer: Sierra Wireless Brand Name: AirPrime Model Name: EM7455
<b>Integrated WLAN Module</b>	Brand Name: Intel Model Name: 8260NGW
<b>EUT supports Radios application</b>	WCDMA/HSPA/LTE WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
<b>EUT Stage</b>	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Number of Channels</b>	40
<b>Carrier Frequency of Each Channel</b>	40 Channel(37 hopping + 3 advertising channel)
<b>Type of Modulation</b>	Bluetooth LE : GFSK

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	CO05-HY	03CH07-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ANSI C63.10-2013

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).
- b. AC power line Conducted Emission was tested under maximum output power.


### 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: Bluetooth Link + TF + TC Mode 2: WLAN (2.4GHz) Link + TF + TC
<b>Remark:</b>	
<ol style="list-style-type: none"><li>1. The worst case of conducted emission is mode 2; only the test data of it was reported.</li><li>2. All the test cases were performed with sample 2.</li><li>3. TF stands for Test Function, and consists of MPEG4 and Camera.</li><li>4. TC stands for Test Configuration, and consists of Earphone, USB HD, iPod, Adapter, SD Card, and HDMI.</li></ol>	

## 2.3 Connection Diagram of Test System

<Bluetooth – LE Tx Mode>



<AC Conducted Emission Mode>





## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LCD Monitor	DELL	U2410	FCC DoC	Shielded, 1.6 m	Unshielded, 1.8 m
2.	iPod	Apple	A1285	DoC	Shielded, 1.0m	N/A
3.	Earphone	lenovo	TS300-01MS21-8S	FCC DoC	Unshielded,1.2m	N/A
4.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
5.	HD USB	lenovo	F310S	FCC DoC	Shielded, 0.5m	N/A
6.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, “Tx Tool” installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.



### 3 Test Result

#### 3.1 Radiated Band Edges and Spurious Emission Measurement

##### 3.1.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

##### 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.



### 3.1.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.

For average measurement:


- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.1.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.1.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.1.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A and B.

### 3.1.7 Duty Cycle

Please refer to Appendix C.

### 3.1.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A and B.



## 3.2 AC Conducted Emission Measurement

### 3.2.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.


### 3.2.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.2.4 Test Setup



### 3.2.5 Test Result of AC Conducted Emission







## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 19, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Dec. 19, 2016	Aug. 29, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	Dec. 19, 2016	Nov. 28, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 06, 2016	Dec. 19, 2016	Dec. 05, 2017	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Jan. 13, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Jan. 12, 2017	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Aug. 18, 2017	Radiation (03CH07-HY)
EMI Test Receiver	Keysight	N9038A(MXE )	MY541300 85	20Hz ~ 8.4GHz	Oct. 26, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Oct. 25, 2017	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Dec. 14, 2016 ~ Dec. 16, 2016	Sep. 01, 2017	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz ~ 18GHz	Apr. 15, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Apr. 14, 2017	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 18, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Mar. 17, 2017	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A023 62	1GHz~ 26.5GHz	Oct. 12, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Oct. 11, 2017	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Feb. 27, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Feb. 26, 2017	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Dec. 14, 2016 ~ Dec. 16, 2016	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Dec. 14, 2016 ~ Dec. 16, 2016	N/A	Radiation (03CH07-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Jun. 13, 2017	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	584	18GHz- 40GHz	Nov. 08, 2016	Dec. 14, 2016 ~ Dec. 16, 2016	Nov. 07, 2017	Radiation (03CH07-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.70
--	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.70
--	------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.50
--	------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.20
--	------



## Appendix A. Radiated Spurious Emission

Test Engineer :	Jesse Wang, James Chiu, and Daniel Lee	Temperature :		21~23°C	
		Relative Humidity :		47~51%	

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	(P/A)	(H/V)
BLE CH 00 2402MHz		2321.445	54.4	-19.6	74	50.2	31.98	7.18	34.96	364	233	P	H
		2331.84	45.42	-8.58	54	41.22	31.98	7.18	34.96	364	233	A	H
	*	2402	96.31	-	-	91.79	32.19	7.31	34.98	364	233	P	H
	*	2402	95.76	-	-	91.24	32.19	7.31	34.98	364	233	A	H
													H
													H
		2384.76	55.7	-18.3	74	51.22	32.14	7.31	34.97	278	168	P	V
		2325.33	46.71	-7.29	54	42.51	31.98	7.18	34.96	278	168	A	V
	*	2402	101.25	-	-	96.73	32.19	7.31	34.98	278	168	P	V
	*	2402	100.77	-	-	96.25	32.19	7.31	34.98	278	168	A	V
BLE CH 19 2440MHz													V
		2356.48	55.2	-18.8	74	50.84	32.09	7.24	34.97	343	107	P	H
		2365.86	45.54	-8.46	54	41.18	32.09	7.24	34.97	343	107	A	H
	*	2440	94.6	-	-	89.89	32.34	7.36	34.99	343	107	P	H
	*	2440	94.11	-	-	89.4	32.34	7.36	34.99	343	107	A	H
		2492.72	54.65	-19.35	74	49.76	32.5	7.4	35.01	343	107	P	H
		2488.17	46.08	-7.92	54	41.18	32.5	7.4	35	343	107	A	H
		2312.24	55.15	-18.85	74	50.99	31.93	7.18	34.95	270	174	P	V
		2363.2	47.83	-6.17	54	43.47	32.09	7.24	34.97	270	174	A	V
	*	2440	101.57	-	-	96.86	32.34	7.36	34.99	270	174	P	V
	*	2440	101.09	-	-	96.38	32.34	7.36	34.99	270	174	A	V
		2489.22	55.66	-18.34	74	50.76	32.5	7.4	35	270	174	P	V
		2490.13	45.96	-8.04	54	41.06	32.5	7.4	35	270	174	A	V



<b>BLE CH 39 2480MHz</b>	*	2480	96.26	-	-	91.41	32.45	7.4	35	380	135	P	H
	*	2480	95.81	-	-	90.96	32.45	7.4	35	380	135	A	H
		2489.28	56.49	-17.51	74	51.59	32.5	7.4	35	380	135	P	H
		2489.48	48.46	-5.54	54	43.56	32.5	7.4	35	380	135	A	H
													H
													H
	*	2480	101.61	-	-	96.76	32.45	7.4	35	297	166	P	V
	*	2480	101.17	-	-	96.32	32.45	7.4	35	297	166	A	V
		2489.6	61.1	-12.9	74	56.2	32.5	7.4	35	297	166	P	V
		2489.52	53.09	-0.91	54	48.19	32.5	7.4	35	297	166	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## BLE (Harmonic @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4806	40.24	-33.76	74	53.81	33.68	11.83	59.08	100	0	P	H
													H
													H
													H
		4806	41.63	-32.37	74	55.2	33.68	11.83	59.08	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4878	37.74	-36.26	74	51.61	33.54	11.53	58.94	100	0	P	H
		7320	38.89	-35.11	74	48.39	34.65	13.81	57.96	100	0	P	H
													H
													H
		4878	40.03	-33.97	74	53.9	33.54	11.53	58.94	100	0	P	V
		7320	39.56	-34.44	74	49.06	34.65	13.81	57.96	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4962	38.63	-35.37	74	52.81	33.37	11.22	58.77	100	0	P	H
		7440	38.58	-35.42	74	48.33	34.33	14.05	58.13	100	0	P	H
													H
													H
		4962	39.19	-34.81	74	53.37	33.37	11.22	58.77	100	0	P	V
		7440	38.75	-35.25	74	48.5	34.33	14.05	58.13	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## Emission below 1GHz

## 2.4GHz BLE (LF)



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak or Average</b>
H/V	<b>Horizontal or Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dB $\mu$ V/m )	( dB )	( dB $\mu$ V/m )	( dB $\mu$ V )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dB $\mu$ V/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

#### For Peak Limit @ 2390MHz:

1. Level(dB $\mu$ V/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB $\mu$ V) – 35.86 (dB)

= 55.45 (dB $\mu$ V/m)

2. Over Limit(dB)

= Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

= 55.45(dB $\mu$ V/m) – 74(dB $\mu$ V/m)

= -18.55(dB)

#### For Average Limit @ 2390MHz:

1. Level(dB $\mu$ V/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dB $\mu$ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dB $\mu$ V) – 35.86 (dB)

= 43.54 (dB $\mu$ V/m)

2. Over Limit(dB)

= Level(dB $\mu$ V/m) – Limit Line(dB $\mu$ V/m)

= 43.54(dB $\mu$ V/m) – 54(dB $\mu$ V/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



## Appendix B. Radiated Spurious Emission

<b>Test Engineer :</b>	Jesse Wang, James Chiu, and Daniel Lee	<b>Temperature :</b>	21~23°C
		<b>Relative Humidity :</b>	47~51%





### Note symbol


-L	Low channel location
-R	High channel location




## 2.4GHz 2400~2483.5MHz



## BLE (Band Edge @ 3m)


BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
2	Horizontal	Fundamental
Peak	 <p>Site : 03CH074HY Condition : PEAK_BE_74 3m HF-ANT_130822 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Detector : Peak Project : 6N0822-08 Mode : 4</p>	 <p>Site : 03CH074HY Condition : PEAK_74 3m HF-ANT_130822 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWF:Auto Detector : Peak Project : 6N0822-08 Mode : 4</p>
Avg.	 <p>Site : 03CH074HY Condition : AVG_BE_54 3m HF-ANT_130822 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWF:Auto Detector : Peak Project : 6N0822-08 Mode : 4</p>	 <p>Site : 03CH074HY Condition : AVG_54 3m HF-ANT_130822 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWF:Auto Detector : Peak Project : 6N0822-08 Mode : 4</p>











BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
2	Horizontal	Fundamental
Peak	 <p>Level (dBuV/m)</p> <p>Date: 2016-12-14</p> <p>PEAK_BE_74</p> <p>Site: 03CH07-HY Condition: PEAK_BE_74 3m HF-ANT_130829 HORIZONTAL Detector: RBW-1000.000KHz VBW-3000.000KHz SWT-Auto Project: 6N0822-08 Mode: 5</p>	Left blank
Avg.	 <p>Level (dBuV/m)</p> <p>Date: 2016-12-14</p> <p>AVG_BE_54</p> <p>Site: 03CH07-HY Condition: AVG_BE_54 3m HF-ANT_130829 HORIZONTAL Detector: RBW-1000.000KHz VBW-3.000KHz SWT-Auto Project: 6N0822-08 Mode: 5</p>	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
2	Vertical	Fundamental
Peak	 <p>Site: 03CH07-HY Condition: PEAK_BE_74 3m HF-ANT_130829 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector: Peak Project: 6N0822-08 Mode: 5</p>	Left blank
Avg.	 <p>Site: 03CH07-HY Condition: AVG_BE_54 3m HF-ANT_130829 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector: Peak Project: 6N0822-08 Mode: 5</p>	Left blank











2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
2	Horizontal	Vertical
Peak	 <p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 6N0822-08 Mode : 4</p>	 <p>Site : 03CH07-HY Condition : PEAK_74 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 6N0822-08 Mode : 4</p>
Avg.		








## Emission below 1GHz


## 2.4GHz BLE (LF)



## Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth – LE	62.99	388	2.58	3kHz

## Bluetooth – LE



Date: 6.DEC.2016 21:13:45



## Appendix E. Antenna Information

Antenna Information			
Antenna 1	Manufacturer	Amphenol	
	Antenna Type	Main:PIFA Antenna	Aux:PIFA Antenna
	Part number	LX7847-16-000-C	LX7848-16-000-C
	Peak gain	Main Antenna : WLAN(2.4GHz):-6.76 WLAN(5GHz):-1.84	Aux Antenna : WLAN(2.4GHz):-6.52 Bluetooth :-6.52 WLAN(5GHz):0.14
Antenna 2	Manufacturer	Speedwire	
	Antenna Type	Main:PIFA Antenna	Aux:PIFA Antenna
	Part number	F.0G.ZV-0006-003-00	F.0G.ZV-0006-004-00
	Peak gain	Main Antenna : WLAN(2.4GHz):1.5 WLAN(5GHz):-1.97	Aux Antenna : WLAN(2.4GHz):1.68 Bluetooth :1.68 WLAN(5GHz):-0.3