

Maximum Permissive Exposure

FCC ID: 2AJNIWB060

Product Name: The Multi-Angle Digital Wireless Parking Camera

Model No: WB060

- According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (Minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits For Occupational / Control Exposures (f = frequency) | | | | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | ... | ... | f/300 | 6 |
| 1500-100,000 | ... | ... | 5.0 | 6 |
| (B) Limits For General Population / Uncontrolled Exposure (f = frequency) | | | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | ... | ... | f/1500 | 30 |
| 1500-100,000 | ... | ... | 1.0 | 30 |

2. MPE Calculation

Fortress Auto Int'l Ltd declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

Based on safety distance (r) **20cm**, the antenna gain (G) is **2.377Numerical**, and the highest power output (P) is **152.405mW**, the power density (S) is **0.072071mW/cm²**.

RF Exposure Calculations:

$$S = (P * G) / (4 * \pi * r^2) \text{ or } r = \sqrt{(P * G) / (4 * \pi * S)}$$

Where :

| | |
|---|---|
| Based on safety distance (r)= | 20 cm |
| Highest Power Output (P)= | 21.83 dBm = 152.405 mW |
| Antenna Gain (G)= | 3.76 dBi = 2.377 Numerical |
| MPE (S) = (P*G) / (4*π*r ²) = | = (0.405*1.000)/(4*π*20 ²)= 0.072071 mW/cm ² |

Sincerely Yours,



Mr. Ben Cheng
Manager
AUDIX Technology Corporation