



TEST REPORT

Applicant	AOK Electronic Limited
Address	Tianxin Industrial District, Dahou Village, Xiegang Town, Dongguan City, Guangdong Province, China

Manufacturer or Supplier	AOK Electronic Limited
Address	Tianxin Industrial District, Dahou Village, Xiegang Town, Dongguan City, Guangdong Province, China
Product	Weather Station
Brand Name	N/A
Model	AOK-2022C
Additional Model & Model Difference	N/A
Date of tests	March 16~April 01, 2019

the tests have been carried out according to the requirements of the following standards:

◯ FCC Part 15, Subpart C, Section 15.231e (2015-10)

CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

Tested by Aaron Liang Project Engineer / EMC Department	Approved by David Huang Manager / EMC Department
Aaron Liang	David Huang
	Date: April 01, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



TABLE OF CONTENTS

R	ELEA	ASE C	CONTROL RECORD	
1	S	UMM	ARY OF TEST RESULTS	5
2	M	IEASU	UREMENT UNCERTAINTY	5
3	G	ENEF	RAL INFORMATION	(
	3.1	GEN	IERAL DESCRIPTION OF EUT	6
	3.2	DES	CRIPTION OF TEST MODES	7
	3.3	TES	T MODE APPLICABILITY AND TESTED CHANNEL DETAIL	7
	3.4	GEN	IERAL DESCRIPTION OF APPLIED STANDARDS	9
	3.5	DES	CRIPTION OF SUPPORT UNITS	9
4.	Т	EST 1	TYPES AND RESULTS	10
	4.1	RAD	DIATED EMISSION MEASUREMENT	10
	4.	.1.1	LIMITS OF RADIATED EMISSION MEASUREMENT	10
	4.	.1.2	TEST INSTRUMENTS	11
	4.	.1.3	TEST PROCEDURES	
	4.	.1.4	TEST SETUP	13
	4.	.1.5	EUT OPERATING CONDITIONS	
	4.	.1.6	TEST RESULTS	15
	4.2	20DI	B BANDWIDTH MEASUREMENT	19
	4.	.2.1	LIMITS OF 20DB BANDWIDTH MEASUREMENT	
	4.	.2.2	TEST INSTRUMENTS	19
	4.	.2.3	TEST PROCEDURE	20
	4.	.2.4	DEVIATION FROM TEST STANDARD	
	4.	.2.5	TEST SETUP	
	4.	.2.6	EUT OPERATING CONDITIONS	
	-	.2.7	TEST RESULTS	
	4.3	DEA	CTIVATION TIME MEASUREMENT	
	4.	.3.1	LIMITS OF DEACTIVATION TIME MEASUREMENT	
	4.	.3.2	TEST INSTRUMENTS	
		.3.3	TEST PROCEDURE	
		.3.4	DEVIATION FROM TEST STANDARD	
		.3.5	TEST SETUP	
	4.	.3.6	EUT OPERATING CONDITIONS	23



	4.3.7	TEST RESULTS	24
5	PHOT	OGRAPHS OF THE TEST CONFIGURATION	25
6	APPE	NDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EU	Т
BY.	THE LA	В	26

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>

Page 3 of 26



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF190425N028	Original release	April 01, 2019

Fax: +86 769 8593 1080 Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8998 2098

, China Email: <u>customerservice.dg@cn.bureauveritas.c</u>



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.231)				
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK	
§15.203	Antenna Requirement	PASS	Compliant	
§15.207 (a)	AC Power Conducted Emission	N/A	EUT is powered by battery	
§15.209 §15.231(e)	Radiated Emission	PASS	Compliant	
§15.231 (e)	Deactivation Testing	PASS	Compliant	
§15.231(c)	20dB Bandwidth Test	PASS	Compliant	

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	3.11dB
	9KHz ~ 30MHz	3.11dB
Radiated emissions	30MHz ~ 1GHz	5.12dB
Nadiated emissions	1GHz ~ 18GHz	5.34dB
	18GHz ~ 40GHz	5.20dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Fax: +86 769 8593 1080

Tel: +86 769 8998 2098



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Weather Station
MODEL NO.	AOK-2022C
FCC ID	2AJOATX2022C
NOMINAL VOLTAGE	DC 3V (1.5V*AA*2) from Battery
MODULATION TYPE	ASK
OPERATING FREQUENCY	433.92MHz
NUMBER OF CHANNEL	1
ANTENNA TYPE	Wire Antenna with 0dBi
I/O PORTS	Refer to the user's manual

NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- 3. Please refer to the EUT photo document (Reference No.:190425N028) for detailed product photo.

Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8998 2098



3.2 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y plane for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

FREQUENCY	TEST MODES
433.92MHz	Transmitting

3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE			APPLICAI	DESCRIPTION			
MODE	RE≥1G	RE < 1G	PLC	EB	DT	DC	Described in the interest of t
-	\checkmark	\checkmark	-	$\sqrt{}$	\checkmark	\checkmark	DC 3V from New Battery

Where RE≥1G: Radiated Emission above 1GHz PLC: Power Line Conducted Emission

EB: 20dB Bandwidth measurement

RE < 1G: Radiated Emission below 1GHz

DT: Deactivation Time measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

POWER LINE CONDUCTED EMISSION TEST:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations
between available modulations, data rates and antenna ports (if EUT with antenna diversity
architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1	1	ASK

RADIATED EMISSION TEST:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations.

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	
1	1	ASK	

Guangdong 523942, China

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



EMISSION BANDWIDTH MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1	1	ASK

DEACTIVATION TIME MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1	1	ASK

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE≥1G	24deg. C, 54%RH	DC 3V from New Battery	Evans He
RE<1G	24deg. C, 54%RH	DC 3V from New Battery	Evans He
EB	25deg. C, 59%RH	DC 3V from New Battery	Aaron Liang
DT	25deg. C, 59%RH	DC 3V from New Battery	Aaron Liang

Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8998 2098

Fax: +86 769 8593 1080

Page 8 of 26



3.4 GENERAL DESCRITION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C Section 15.231e (2015-10) ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	N/A	N/A	N/A	N/A	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

Fax: +86 769 8593 1080

Tel: +86 769 8998 2098

Email: customerservice.dg@cn.bureauveritas.com

Page 9 of 26 Report Version 1



4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.231(e), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency (MHz) Field strength of fundamental (microvolts/meter)		Field strength of spurious emission (microvolts/meter)
40.66–40.70	1,000	100
70–130	500	50
130–174	500 to 1,500 ¹	50 to 150 ¹
174–260	1,500	150
260–470	1,500 to 5,000 ¹	150 to 500 ¹
Above 470	5,000	500

NOTE:

- 1. ¹ Linear interpolations.
- 2. The lower limit shall apply at the transition frequencies.
- 3. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 4. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

Equipment	Model No.	Serial No.	Last Cal.	Next Cal.
EMI test receiver	ESL6	1300.5001K06 -100262-eQ	01/04/2019	01/03/2020
Active Antenna	AL-130	121031	02/08/2019	02/07/2020
3m Semi-anechoic Chamber	9m*6m*6m	N/A	10/18/2019	10/17/2019
Signal Amplifier	8447E	443008	01/25/2019	01/24/2020
MXA signal analyzer	N9020A	MY49100060	01/04/2019	01/03/2020
Horn Antenna	HAH-118	71259	01/26/2019	01/25/2020
Horn Antenna	HAH-118	71283	02/02/2019	02/01/2020
AMPLIFIER	EM01G26G	60613	01/25/2019	01/24/2020
AMPLIFIER	Emc012645	980077	01/04/2019	01/03/2020
Bilog Antenna (30MHz~6GHz)	JB6	A110712	02/08/2019	02/07/2020

NOTE:

- 1. The test was performed in 966 Chamber.
- 2. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.
- 4. The FCC Site Registration No. is 749762.

Fax: +86 769 8593 1080

Tel: +86 769 8998 2098

Email: customerservice.dg@cn.bureauveritas.com

Report Version 1

Page 11 of 26



4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters (below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position Y, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level.
- h. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. Fundamental AV value =PK Emission +20*log(duty cycle)
- 4. All modes of operation were investigated and the worst-case emissions are reported.


Fax: +86 769 8593 1080

Tel: +86 769 8998 2098




4.1.4 TEST SETUP

Below 30MHz



Below 1GHz test setup




Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.5 EUT OPERATING CONDITIONS

- a. Turned on the power of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



4.1.6 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M							
No.	Freq. (MHz)	Average Factor (dB)	Field Strength(PK) (dBuV/m)	Field Strength(AV) (dBuV/m)	Limit(PK) (dBuV/m)	Limit(AV) (dBuV/m)	Margin(PK) (dB)	Margin(AV) (dB)
1	*433.92	-35.34	64	28.66	92.87	72.87	-28.87	-44.21
2	#867.84	-35.34	41.57	6.23	72.87	52.87	-31.3	-46.64
		ANTENNA	A POLARITY	& TEST DIST	ANCE: VI	ERTICAL	AT 3M	
No. Freq. (MHz) Average Field Strength(PK) Strength(AV) (dBuV/m) Factor (dB) (dBuV/m) (dBuV/m) Field Strength(AV) (dBuV/m) (dBuV/m) (dBuV/m) (dBuV/m)						Margin(AV) (dB)		
1	*433.92	-35.34	74.46	39.12	92.87	72.87	-18.41	-33.75
2	#867.84	-35.34	44.57	9.23	72.87	52.87	-28.3	-43.64

NOTE:

- 1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) at frequency below 1GHz.
- 2. Margin value = Field Strength Limit value.
- 3. " * ": Fundamental frequency.
- 4. " # ": Harmonic frequency
- 5. Fundamental AV value =PK Emission + $20*log(duty\ cycle)$ Where the duty factor is calculated from following formula:20 log (Duty cycle) = 20 log (1.71%) = -35.34dB, Please see page 16~17 for plotted duty.
- 6. The emission levels of other frequencies were less than 20dB margin against the limit.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



ABOVE 1GHz WORST-CASE DATA:

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M								
No.	Freq. (MHz)	Average Factor (dB)	Field Strength(PK) (dBuV/m)	Field Strength(AV) (dBuV/m)	Limit(PK) (dBuV/m)	Limit(AV) (dBuV/m)	• , ,	Margin(AV) (dB)	
1	1301.76	-35.34	41.21	5.87	74	54	-32.79	-48.13	
2	1735.68	-35.34	43.25	7.91	74	54	-30.75	-46.09	
3	2169.6	-35.34	45.21	9.87	74	54	-28.79	-44.13	
4	2603.52	-35.34	46.57	11.23	74	54	-27.43	-42.77	
		ANTENNA	A POLARI	TY & TEST D	STANCE: V	ERTICAL	AT 3M		
No. Freq. Average (MHz) Factor (dB) Field Strength(PK) (dBuV/m) Factor (dB) (dBuV/m) Field Strength(AV) (dBuV/m) (dBuV/m) Field Strength(AV) (dBuV/m) (dBuV/m) (dBuV/m)						U ,	Margin(AV) (dB)		
1	1301.76	-35.34	43.57	8.23	74	54	-30.43	-45.77	
2	1735.68	-35.34	44.24	8.9	74	54	-29.76	-45.1	
3	2169.6	-35.34	45.24	9.9	74	54	-28.76	-44.1	
4	2603.52	-35.34	44.25	8.91	74	54	-29.75	-45.09	

NOTE:

- 1 The resolution bandwidth of test receiver/spectrum analyzer is 1MHz for Peak detection (PK) at frequency above 1GHz.
- 2 Margin value = Field Strength Limit value.
- 3 " # ": Harmonic frequency
- 4 Fundamental AV value =PK Emission +20*log(duty cycle)Where the duty factor is calculated from following formula: 20 log (Duty cycle) = 20 log (1.71%) = -35.34dB, Please see page 16~17 for plotted duty.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



Duty Cycle:


Tp = 57ms

Ton= Ton 1+Ton 2+Ton 3 = 0.404 + 0.41 + 0.162 = 0.976 ms

Duty Cycle = Ton / Tp * 100% = 0.976 / 57 * 100% = 1.71%

Factor = 20Log(Duty Cycle) = 20 log (1.71%) = -35.34dB

Тр




Fax: +86 769 8593 1080

Tel: +86 769 8998 2098



Ton= Ton 1+Ton 2+Ton 3 = 0.404 + 0.41 + 0.162 = 0.976 ms



Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



4.2 20dB BANDWIDTH MEASUREMENT

4.2.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

According to FCC 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Limit=Fundamental Frequency×0.25%=433.92MHz×0.25%=1084.8 kHz

4.2.2 TEST INSTRUMENTS

Equipment	Model No.	Serial No.	Last Cal.	Next Cal.
DC Power Supply	E3640A	MY40004013	01/04/2019	01/03/2020
MXA Signal Analyzer	N9020A	MY49100060	01/04/2019	01/03/2020
MXG Vector Signal Generator	N5182A	MY50140530	01/04/2019	01/03/2020
Series Signal Generator	E4421B	US40051152	05/12/2019	05/11/2020
RF control unit	JS0806-0806-2	188060112	04/25/2018	04/24/2019
Wireless Connectivity Tester	CMW270	1201.0002K75- 101601-PE	04/25/2018	04/24/2019
Weinschel	1580-1	TL177	01/04/2019	01/03/2020
Universal Radio Communica	CMU200	121393	02/11/2018	02/10/2019

NOTE: 1. The test was performed in RF Oven room.

Fax: +86 769 8593 1080 Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8998 2098

Page 19 of 26

^{2.} The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.




4.2.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set the frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



4.2.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. Enable EUT under transmission condition continuously at specific channel frequency.

Fax: +86 769 8593 1080


Tel: +86 769 8998 2098



4.2.7 TEST RESULTS

FREQUENCY (MHz)	20dB BANDWIDTH (kHz)	MAXIMUM LIMIT (kHz)	PASS/FAIL	
433.92	152.6	1084.8	PASS	

Test Data:



Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



4.3 DEACTIVATION TIME MEASUREMENT

4.3.1 LIMITS OF DEACTIVATION TIME MEASUREMENT

According to FCC 15.231(e), In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

4.3.2 TEST INSTRUMENTS

Equipment	Model No.	Serial No.	Last Cal.	Next Cal.
DC Power Supply	E3640A	MY40004013	01/04/2019	01/03/2020
MXA Signal Analyzer	N9020A	MY49100060	01/04/2019	01/03/2020
MXG Vector Signal Generator	N5182A	MY50140530	01/04/2019	01/03/2020
Series Signal Generator	E4421B	US40051152	05/12/2019	05/11/2020
RF control unit	JS0806-0806-2	188060112	04/25/2018	04/24/2019
Wireless Connectivity Tester	CMW270	1201.0002K75- 101601-PE	04/25/2018	04/24/2019
Weinschel	1580-1	TL177	01/04/2019	01/03/2020
Universal Radio Communica	CMU200	121393	02/11/2018	02/10/2019

NOTE: 1. The test was performed in RF Oven room.

4.3.3 TEST PROCEDURE

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency, than set the spectrum analyzer to Zero Span for the release time reading. During the testing, the transmission duration was measured and recorded.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080


^{2.} The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. With the EUT's antenna attached, which was connected to the spectrum analyzer set to the EUT's operation frequencies.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080




4.3.7 TEST RESULTS

Test Data: Duration=162.0ms<1 second



10s<57s>918.5ms*30



Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

Fax: +86 769 8593 1080 Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8998 2098

Page 25 of 26



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---

Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8998 2098

Page 26 of 26