

Report No.: EED32J00120204 Page 1 of 8

# **RF Exposure Evaluation Report**

**Product** : ECH relay

Trade mark : ECH

Model/Type reference : Refer to chapter 4.3

Serial Number : N/A

Report Number : EED32J00120204 FCC ID : 2AJOC-ECHC1

**Date of Issue** : Oct. 20, 2017

47 CFR Part 1.1307

Test Standards : 47 CFR Part 1.1310

KDB447498D01v06

Test result : PASS

#### Prepared for:

ECH (Changzhou) Medical Instrument Co., Itd. No. 65, West Huiling Rd., Zouqu County Zhonglou District, Changzhou, Jiangsu

#### Prepared by:

Centre Testing International Group Co., Ltd. Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China

TEL: +86-755-3368 3668 FAX: +86-755-3368 3385

Tested By:

10M-chen

Compiled by:

Approved by

Report Seal

Reviewed by:

Date:

kein lang

Tom chen (Test Project)

Kevin yang (Reviewer)

Oct. 20, 2017

Kevin lan (Project Engineer)

Sheek Luo (Lab supervisor)

Check No.: :2827502834









Page 2 of 8

Report No.: EED32J00120204

2 Version

Version No.	Date	19	Description	on	
00	Oct. 20, 2017				
7		130			
	(5)	(0,)		0.	

















































































Page 3 of 8

Report No.: EED32J00120204

3 Contents

	Page
1 COVER PAGE	 1
2 VERSION	 2
3 CONTENTS	 3
4 GENERAL INFORMATION	 2
4.1 CLIENT INFORMATION	2
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD4.4 TEST LOCATION	
4.4 TEST LOCATION	
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	
5 RF EXPOSURE EVALUATION	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
5.1.1 Limits	
5.1.2 Test Procedure	 7
5.1.3 EUT RF Exposure Evaluation	
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	8

















































Report No. : EED32J00120204 Page 4 of 8

## 4 General Information

#### 4.1 Client Information

Applicant:	ECH (Changzhou) Medical Instrument Co., ltd.		
Address of Applicant:	No. 65, West Huiling Rd., Zouqu County Zhonglou District, Changzhou, Jiangsu		
Manufacturer:	ECH (Changzhou) Medical Instrument Co., ltd.		
Address of Manufacturer: No. 65, West Huiling Rd., Zouqu County Zhonglou District, Jiangsu			
Factory:	Shanghai Chenguo Electronic Technology Co., Ltd.		
Address of Factory:	Shanghai Fengxian Fengpu Industrial Zone, 518 Far East Road		

#### 4.2 General Description of EUT

Product Name:	ECH relay
Model No.(EUT):	Refer to chapter 4.3
Test Mode No.:	ECH-c1-WLSD-C, ECH-c1-LSD-C
Trade Mark:	ECH
EUT Supports Radios application:	BT: 4.0 BT Signal mode, 2402-2480MHz Wi-Fi: 802.11 b/g/n(20M), 2412MHz-2462MHz

4.3 Product Specification subjective to this standard

Frequency Range:	BT: 4.0 BT Signal mode, 2402-2480MHz Wi-Fi: 802.11 b/g/n(20M), 2412MHz-2462MHz			
Modulation Type:	BT: GFSK Wi-Fi: DSSS, OFDM			
Test Power Grade:	N/A			
Test Software of EUT:	N/A			
Antenna Type:	PCB antenna			
Antenna Gain:	3dBi			
Power Supply:	DC 5V by USB port			
75	22.00dBm			
Conduct Peak Power:	The Maximum Conduct Peak Power data refer to the maximum tolerances declared by the manufacturer.			
USB Micro-B Plug cable:	137.5cm(Unshielded)			
Sample Received Date:	Jun. 16, 2017			
Sample tested Date:	Jun. 16, 2017 to Sep. 13, 2017			

The tested sample(s) and the sample information are provided by the client.

According to whether there are Ethernet, they can be divided into two categories. There are the Ethernet for one kind, the other kind without Ethernet. The models without the Ethernet, there will be the Bluetooth and WLAN. The models with the Ethernet also have Bluetooth and WLAN. but if the Ethernet is connected to the router, the WLAN will can't transfer data by firmware. Except the color and the appearance are different, all of them are the same.

The Model No. Below with the Ethernet, only the model ECH-c1-WLSD-C was tested, since except the color of appearance are different, all the others are the same.

Model No.:ECH-c1-WLSD-C,ECH-c1-WLSD-B, ECH-c1-WL-C, ECH-c1-WL-B, ECH-c1-WLD-B, ECH-c1-WLD-C, ECH-c1-WSD-B, ECH-c1-WSD-C, ECH-c1-W-B, ECH-c1-W-C, ECH-c1-WD-C, ECH-c1-WD-B.









Report No.: EED32J00120204

Page 5 of 8

The Model No. Below without the Ethernet, only the model ECH-c1-LSD-C was tested, except the color of appearance are different, all the others are the same.

Model No.:ECH-c1-LSD-C, ECH-c1-LSD-B, ECH-c1-L-C, ECH-c1-L-B, ECH-c1-LD-C, ECH-c1-LD-B.

The model ECH-c1-WLSD-C were fully tested, the model ECH-c1-LSD-C was only tested the Output Power and the Radiated Spurious Emissions other tests data please refer to the model ECH-c1-WLSD-C.

#### 4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax:+86 (0) 755 3368 3385

No tests were sub-contracted.

FCC Designation No.: CN1164 FCC-Registration No.: 886427

Centre Testing International Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 886427.

#### 4.5 Deviation from Standards

None.

#### 4.6 Abnormalities from Standard Conditions

None.

# 4.7 Other Information Requested by the Customer

None.

























































Report No.: EED32J00120204 Page 6 of 8

# 5 RF Exposure Evaluation

# 5.1 RF Exposure Compliance Requirement

#### **5.1.1 Limits**

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1-LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
(A) Lim	its for Occupational	/Controlled Exposure	es	
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6
(B) Limits	for General Populati	on/Uncontrolled Exp	osure	
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P\*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.



























Report No.: EED32J00120204 Page 7 of 8

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

### 5.1.3 EUT RF Exposure Evaluation

Antenna Gain: 3dBi


Output Power Into Antenna & RF Exposure Evaluation Distance:

Max Conducted Peak	Gain	EIRP*	EIRP	R	S	Limit	Result	
Output Power(dBm)	(dBi)	(dBm)	(mW)	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )		
22.00	3	25.00	316.23	20	0.063	1.0	Pass	

**Note:** The Maximum Conduct Peak Power data refer to the maximum tolerances declared by the manufacturer.









Report No.: EED32J00120204 Page 8 of 8

## **PHOTOGRAPHS OF EUT Constructional Details**

Refer to Report No. EED32J00120202 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.











