FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Report No.: RSHA181207002-00B

Limits for General Population/Uncontrolled Exposure								
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)				
0.3-1.34	614	1.63	*(100)	30				
1.34-30	824/f	2.19/f	*(180/f²)	30				
30-300	27.5	0.073	0.2	30				
300-1500	/		f/1500	30				
1500-100,000	/		1.0	30				

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4 \pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

Calculated Data:

For LTE mode:

Mode	Frequency Range	Max Antenna Gain		Target Output Power		Evaluation Distance	Power Density	MPE Limit
1/1040	(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
Band 5	824-849	2.70	1.86	22	158.49	20	0.0587	0.55
Band 41	2516-2670	3.70	2.34	23	199.53	20	0.0930	1.00

Report No.: RSHA181207002-00B

For Wi-Fi mode:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance	Power Density	MPE Limit (mW/cm²)
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm ²)	(// /
802.11b	2412-2462	2.20	1.66	17.00	50.12	20	0.0165	1.00
802.11g		2.20	1.66	16.00	39.81	20	0.0131	1.00
802.11n-HT20		2.20	1.66	15.00	31.62	20	0.0104	1.00
802.11n-HT40	2422-2452	2.20	1.66	15.00	31.62	20	0.0104	1.00

Mode	Frequency (MHz)	Antenna Gain		Conducted output power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
802.11a	5150-5250	2.20	1.66	14.00	25.12	20	0.0083	1.00
802.11n-HT20		2.20	1.66	15.00	31.62	20	0.0104	1.00
802.11n-HT40		2.20	1.66	15.00	31.62	20	0.0104	1.00
802.11a	5725-5850	2.20	1.66	14.00	25.12	20	0.0083	1.00
802.11n-HT20		2.20	1.66	15.00	31.62	20	0.0104	1.00
802.11n-HT40		2.20	1.66	16.00	39.81	20	0.0131	1.00

Note:

 The target output power was declared by the Manufacturer.
2.4GWi-Fi and 5GWi-Fi cannot transmit simultaneously.
Wi-Fi and LTE can transmit simultaneously, The worst condition is 802.11b of 2.4G Wi-Fi and LTE Band 5, as below:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} = 0.0165/1.00 + 0.0587/0.55 = 0.0165 + 0.1067 = 0.1232 < 1.0$$

Result: The device meet FCC MPE at 20 cm distance.