



FCC PART 90 TEST REPORT

For

Guangdong Shangrila Networking Technology Co., Ltd

4F, Building 13, Xinzhu Court, No.4 Xinzhu Road, Songshan Lake, Dongguan, China 523808

FCC ID: 2AJOPFM416416S

Report Type: Original Report		Product Type		
Report Number:	RSZ160829801-0	0		
Report Date:	2016-09-30			
Reviewed By:	Dean Liu RF Engineer		Dean	L. Lau
	Jerry Zhang EMC Manager		Jerry	Zhang
Test Laboratory:	Bay Area Compli No.69 Pulongcun			ongguan)
	Tangxia, Donggu Tel: +86-769-868 Fax: +86-769-868 www.baclcorp.co	an, Guangdong, C 58888 358891		

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.(Dongguan). This report may contain data or test methods that are not covered by the NVLAP accreditation scope and shall be marked with an asterisk "*" and noted.


TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	4
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	
SUPPORT EQUIPMENT LIST AND DETAILS	
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC §1.1310 & §2.1093 - RF EXPOSURE	7
APPLICABLE STANDARD	7
TEST RESULT	7
FCC §2.1046 & §90.205- RF OUTPUT POWER	8
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST FROEEDORE TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC	10
APPLICABLE STANDARD	10
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	10
FCC §2.1049 &§90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK	15
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS.	
Test Procedure	
TEST DATA	17
FCC §2.1051& §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	20
APPLICABLE STANDARD	20
TEST EQUIPMENT LIST AND DETAILS.	
TEST PROCEDURE	
TEST DATA	
FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS.	
TEST PROCEDURE	
TEST DATA	
FCC §2.1055 & §90.213- FREQUENCY STABILITY	
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS.	
TEST PROCEDURE	
Test Data	26

Report No.: RSZ160829801-00

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR	28
APPLICABLE STANDARD	28
TEST EQUIPMENT LIST AND DETAILS.	28
TEST PROCEDURE	
Test Data	20

Report No.: RSZ160829801-00



GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Guangdong Shangrila Networking Technology Co., Ltd's product, model number: FM-416S (FCC ID: 2AJOPFM416416S) or the "EUT" in this report was a dPMR Two-way Radio, which was measured approximately: 116 mm (L) x54 mm (W) x 30 mm (H), rated with input voltage: DC 3.7V rechargeable battery.

Report No.: RSZ160829801-00

Note: For the product, series model FM-416S and FM-416 are identical schematics, the differences between them is just the model number due to marketing purpose and different shell (front appearance). FM-416S was selected for fully testing, which was explained in the attached product similarity declaration letter.

* All measurement and test data in this report was gathered from production sample serial number: 160829801 (Assigned by BACL, Dongguan). The EUT supplied by the applicant was received on 2016-08-29.

Objective

This test report is prepared on behalf of *Guangdong Shangrila Networking Technology Co.*, *Ltd* in accordance with Part 2, Part 90 of the Federal Communications Commission rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 90 – PRIVATE LAND MOBILE RADIO SERVICES

Applicable Standards: TIA-603-D.

All emissions measurement was performed and Bay Area Compliant Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliant Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliant Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in Compliant with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 90 Page 4 of 30

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode.

EUT Specification:


Operating Frequency Band	400-470 MHz
Modulation Mode	FM & 4FSK
Channel Spacing	6.25 kHz,12.5 kHz
Rated Output Power	2 W

Report No.: RSZ160829801-00

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Weinschel Corp	Terminal Load(100W)	1440-3	MD447

Block Diagram of Test Setup



FCC Part 90 Page 5 of 30

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
FCC§1.1310 & §2.1093	RF exposure	Compliant
§2.1046;§90.205	RF Output Power	Compliant
§2.1047;§90.207	Modulation Characteristic	Compliant
\$2.1049;\$90.209; \$90.210	Occupied Bandwidth & Emission Mask	Compliant
§2.1051;§90.210	Spurious Emission at Antenna Terminal	Compliant
§2.1053;§90.210	Spurious Radiated Emissions	Compliant
§2.1055; §90.213	Frequency Stability	Compliant
§90.214	Transient Frequency Behavior	Compliant

Report No.: RSZ160829801-00

Test Time: $2016-09-20 \sim 2016-09-30$.

FCC Part 90 Page 6 of 30

FCC §1.1310 & §2.1093 - RF EXPOSURE

Report No.: RSZ160829801-00

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RSZ160829802-20.

FCC Part 90 Page 7 of 30

FCC §2.1046 & §90.205- RF OUTPUT POWER

Applicable Standard

FCC §2.1046 and §90.205.

Test Procedure

Conducted RF Output Power:

TIA-603-D section 2.2.1

Spectrum Analyzer Setting:

 $\begin{array}{cc} \underline{R\ B/W} & Video\ B/W \\ \hline 100\ kHz & 300\ kHz \end{array}$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2016-05-09	2017-05-09
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
Giga	Signal Generator	1026	320408	2016-05-09	2017-05-09
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A

Report No.: RSZ160829801-00

FCC Part 90 Page 8 of 30

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	55 %
ATM Pressure:	98.9 kPa

The testing was performed by Gavin Xu on 2016-09-22.

Test Result: Compliant. Please refer to following tables

Conducted Power:

Modulation	Channel	\mathbf{f}_{c}	Conduted Output	Conduted Output	Note	
Mode	Spacing	MHz	Power (dBm)	Power (W)	Note	
		400.0125	33.02	2.004	Not for FCC Review	
Analog	12.5 kHz	425.0125	33.08	2.032	/	
		450.0125	33.09	2.037		
			33.06	2.023	/	
		400.0125	33.10	2.042	Not for FCC Review	
Digital	6.25 kHz	425.0125	33.22	2.099	/	
		450.0125	33.15	2.065		
		469.9875	33.07	2.028	/	

Report No.: RSZ160829801-00

Note: the rated output power is 2 W.

FCC Part 90 Page 9 of 30

FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC

Applicable Standard

FCC§2.1047 & §90.207:

(a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.

Report No.: RSZ160829801-00

(b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

Test Procedure

Test Method: TIA/EIA-603D 2.2.3

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
НР	RF Communications Test Set	8920A	00 235	2016-05-09	2017-05-09
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	98.9 kPa

The testing was performed by Gavin Xu on 2016-09-29.

Test Result: Compliant. Please refer to following table and plots.

FCC Part 90 Page 10 of 30


MODULATION LIMITING

Report No.: RSZ160829801-00

Carrier Frequency: 450.0125 MHz, Channel Spacing = 12.5 kHz

	Instant	aneous	Steady	y-state	
Audio Frequency (Hz)	Deviation (@+20dB) [KHz]	Deviation (@-20dB) [KHz]	Deviation (@+20dB) [KHz]	Deviation (@-20dB) [KHz]	Limit [KHz]
300	1.576	0.111	1.465	0.124	2.5
400	1.867	0.125	1.562	0.125	2.5
500	2.235	0.132	2.125	0.132	2.5
600	2.248	0.142	2.158	0.144	2.5
700	2.224	0.152	2.215	0.154	2.5
800	2.268	0.168	2.222	0.177	2.5
900	2.248	0.195	2.165	0.196	2.5
1000	2.315	0.201	2.187	0.235	2.5
1200	2.358	0.201	2.354	0.215	2.5
1400	2.345	0.231	2.364	0.241	2.5
1600	2.365	0.268	2.332	0.275	2.5
1800	2.37	0.275	2.325	0.285	2.5
2000	2.354	0.265	2.315	0.265	2.5
2200	2.268	0.286	2.246	0.325	2.5
2400	2.254	0.301	2.216	0.331	2.5
2600	2.254	0.302	2.245	0.316	2.5
2800	2.223	0.321	2.254	0.315	2.5
3000	1.628	0.318	1.586	0.302	2.5

FCC Part 90 Page 11 of 30



Report No.: RSZ160829801-00


FCC Part 90 Page 12 of 30

Audio Frequency Response

Report No.: RSZ160829801-00

Carrier Frequency: 450.0125 MHz, Channel Spacing = 12.5 kHz

Audio	Response
Frequency	Attenuation
Hz	dB
300	-10.40
400	-7.96
500	-5.45
600	-4.15
700	-3.35
800	-1.68
900	-0.88
1000	0.00
1200	1.29
1400	1.47
1600	3.76
1800	4.64
2000	5.53
2200	6.11
2400	6.31
2600	6.66
2800	6.95
3000	7.28




FCC Part 90 Page 13 of 30

Audio Frequency Low Pass Filter Response

Report No.: RSZ160829801-00

Carrier Frequency: 450.0125 MHz, Channel Spacing = 12.5 kHz

Audio Frequency	Response Attenuation	Limit
kHz	dB	dB
3.0	-10.6	0.0
3.5	-18.2	-6.7
4.0	-30.4	-12.5
5.0	-40.6	-22.2
7.0	-49.0	-36.8
10.0	-56.4	-52.3
15.0	-72.3	-69.9
20.0	-85.7	-82.5
30.0	-87.9	-82.5
50.0	-90.1	-82.5
70.0	-93.5	-82.5



FCC Part 90 Page 14 of 30

FCC §2.1049 &§90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK

Applicable Standard

FCC §2.1049,§90.209 and §90.210

Applicable Emission Masks

Report No.: RSZ160829801-00

Frequency band (MHz)	Mask for equipment with audio low pass filter	Mask for equipment without audio low pass filter
Below 25	A or B	A or C
25-50	В	С
72-76	В	С
150-174	B, D, or E	C, D or E
150 paging only	В	С
220-222	F	F
421-512	B, D, or E	C, D, or E
450 paging only	В	G
806-809/851-854	В	Н
809-824/854-869	В	G
896-901/935-940	I	J
902-928	K	K
929-930	В	G
4940-4990 MHz	L or M	L or M
5850-5925		
All other bands	В	С

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f0 to 5.625 kHz removed from f0: Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least 7.27(fd-2.88 kHz) dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 12.5 kHz: At least 50 + 10 log (P) dB or 70 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

FCC Part 90 Page 15 of 30

Emission Mask E—6.25 kHz or less channel bandwidth equipment. For transmitters designed to operate with a 6.25 kHz or less bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

Report No.: RSZ160829801-00

- (1) On any frequency from the center of the authorized bandwidth f0 to 3.0 kHz removed from f0: Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least 30 + 16.67(fd-3 kHz) or 55 + 10 log (P) or 65 dB, whichever is the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6 kHz: At least 55 + 10 log (P) or 65 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2016-05-09	2017-05-09
HP	RF Communications Test Set	8920A	00 235	2016-05-09	2017-05-09
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

FCC Part 90 Page 16 of 30

Test Data

Environmental Conditions

Temperature:	24~25 ℃
Relative Humidity:	53~56 %
ATM Pressure:	99.9~100.0 kPa

The testing was performed by Gavin Xu from 2016-09-27 to 20116-09-30.


Test Result: Compliant. Please refer to the following tables and plots.

Modulation Channel Mode Spacing		\mathbf{f}_{c}	99% Occupied Bandwidth	26 dB Bandwidth
Mode	Spacing	MHz	kHz	kHz
Analog	12.5 kHz	450.0125	10.22	9.72
Analog	12.3 KHZ	453.7125	10.22	5.31
Digital	6.25 kHz	450.0125	4.81	3.81

Report No.: RSZ160829801-00

Analog Modulation


99% Occupied Bandwidth & 26 dB Emissions Bandwidth 12.5 kHz, 450.0125 MHz




FCC Part 90 Page 17 of 30

Emission Mask D with 12.5 kHz, 450.0125 MHz

Report No.: RSZ160829801-00



99% Occupied Bandwidth & 26 dB Emissions Bandwidth 12.5 kHz, 453.7125 MHz




FCC Part 90 Page 18 of 30


Digital Modulation:

99% Occupied Bandwidth & 26 dB Emissions Bandwidth 6.25 kHz, 450.0125 MHz

Report No.: RSZ160829801-00



Emission Mask E with 6.25 kHz, 450.0125 MHz



FCC Part 90 Page 19 of 30

FCC §2.1051& §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Applicable Standard

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

Report No.: RSZ160829801-00

- (1) On any frequency from the center of the authorized bandwidth f0 to 5.625 kHz removed from f0: Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least 7.27(fd-2.88 kHz) dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 12.5 kHz: At least 50 + 10 log (P) dB or 70 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

Emission Mask E—6.25 kHz or less channel bandwidth equipment. For transmitters designed to operate with a 6.25 kHz or less bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f0 to 3.0 kHz removed from f0: Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least 30 + 16.67(fd-3 kHz) or 55 + 10 log (P) or 65 dB, whichever is the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6 kHz: At least 55 + 10 log (P) or 65 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

FCC Part 90 Page 20 of 30

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	831259/019	2016-05-09	2017-05-09
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-08	2017-05-08
Chengdu E- Microwave Inc	Band-stop Filters	OBSF-400- 512-S	OE01601514	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

Report No.: RSZ160829801-00

Test Procedure

Adjust the spectrum analyzer for the following settings:

- 1) Resolution Bandwidth = 100 kHz for spurious emissions below 1 GHz, and 1 MHz for spurious emissions above 1 GHz.
- 2) Video Bandwidth ≥ 3 times the resolution bandwidth.
- 3) Sweep Speed ≤2000 Hz per second.
- 4) Detector Mode = mean or average power.

Test Data

Environmental Conditions

Temperature:	24~26 ℃
Relative Humidity:	53~57 %
ATM Pressure:	98.9~99.8 kPa

The testing was performed by Gavin Xu o from 2016-09-20 to 2016-09-27.

Note: For conducted spurious emissions were tested at high rated power, which was the worst case.


FCC Part 90 Page 21 of 30

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).


Analog Modulation:

30 MHz - 1 GHz, Spacing Channel 12.5 kHz, 450.0125MHz

Report No.: RSZ160829801-00



1 GHz - 5GHz, Spacing Channel 12.5 kHz, 450.0125 MHz




FCC Part 90 Page 22 of 30


Digital Modulation:

30 MHz - 1 GHz, Spacing Channel 6.25 kHz, 450.0125 MHz

Report No.: RSZ160829801-00



1 GHz - 5GHz, Spacing Channel 6.25 kHz, 450.0125 MHz



FCC Part 90 Page 23 of 30

FCC §2.1053 & §90.210 - RADIATED SPURIOUS EMISSIONS

Report No.: RSZ160829801-00

Applicable Standard

FCC §2.1053 and §22.359 and §90.210

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Signal Generator	1026	320408	2015-11-23	2016-11-22
R&S	EMI Test Receiver	ESCI	100224	2016-08-03	2017-08-02
Sunol Sciences	Antenna	ЈВ3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2016-09-01	2017-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
Ducommun Technolagies	Horn Antenna	ARH-4223- 02	1007726-01 1304	2014-06-16	2017-06-15
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06
Mini-Circuits	HIGH PASS FILTER	BHP-550+	YZU15801121	2016-05-06	2017-05-06
Weinschel Corp	Terminal Load(100W)	1440-3	MD447	/	/

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

For part 90:

Spurious emissions in dB = $10 \log_{10}$ (TXpwr in Watts/0.001)-the absolute level

FCC Part 90 Page 24 of 30

Spurious attenuation limit in dB =50+10 Log₁₀ (power out in Watts) for EUT with a 12.5 kHz channel bandwidth.

Report No.: RSZ160829801-00

Spurious attenuation limit in dB =55+10 Log₁₀ (power out in Watts) for EUT with a 6.25 kHz channel bandwidth.

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	53 %
ATM Pressure:	99.7 kPa

The testing was performed by Gavin Xu on 2016-09-27.

Test Mode: Transmitting

			Si	ubstituted Me	ethod			
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	S.G. Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
		Analog Mod	lulation 450.	0125MHz, Ch	annel Spacing 1	2.5kHz		
900.03	Н	48.00	-44.9	0.0	1.0	-45.9	-20.0	25.9
900.03	V	40.96	-54.0	0.0	1.0	-55.0	-20.0	35.0
1350.04	Н	46.21	-53.5	8.6	1.1	-46.0	-20.0	26.0
1350.04	V	39.16	-60.2	8.6	1.1	-52.7	-20.0	32.7
1800.05	Н	59.63	-39.5	11.1	1.2	-29.6	-20.0	9.6
1800.05	V	65.29	-33.5	11.1	1.2	-23.6	-20.0	3.6
2250.06	Н	45.66	-50.0	11.0	1.5	-40.5	-20.0	20.5
2250.06	V	42.51	-52.8	11.0	1.5	-43.3	-20.0	23.3
		Digital M	odulation 45	0.0125MHz, 0	Channel Spacing	6.25kHz		
900.03	Н	40.46	-52.5	0.0	1.0	-53.5	-25.0	28.5
900.03	V	47.89	-47.1	0.0	1.0	-48.1	-25.0	23.1
1350.04	Н	45.65	-54.0	8.6	1.1	-46.5	-25.0	21.5
1350.04	V	41.17	-58.2	8.6	1.1	-50.7	-25.0	25.7
1800.05	Н	59.25	-39.8	11.1	1.2	-29.9	-25.0	4.9
1800.05	V	62.89	-35.9	11.1	1.2	-26.0	-25.0	1.0
2250.06	Н	44.27	-51.4	11.0	1.5	-41.9	-25.0	16.9
2250.06	V	41.42	-53.9	11.0	1.5	-44.4	-25.0	19.4

Note1: For radiated spurious emissions were tested at high rated power, which was the worst case. Note2: The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi

for frequency above 1GHz. Note3: Absolute Level = SG Level - Cable loss + Antenna Gain Margin = Limit-Absolute Level

FCC Part 90 Page 25 of 30

FCC §2.1055 & §90.213- FREQUENCY STABILITY

Applicable Standard

FCC §2.1055, §90.213

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-4	2015-11-01	2016-10-31
UNI-T	Multimeter	UT39A	M130199938	2016-04-10	2017-04-10
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06

Report No.: RSZ160829801-00

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The power leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	54 %
ATM Pressure:	98.9 kPa

The testing was performed by Gavin Xu on 2016-09-28.

Test Mode: Transmitting

FCC Part 90 Page 26 of 30

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

For Analog Modulation

Reference Frequency: 450.0125MHz, 12.5 kHz, Limit: 2.5 ppm			
Temerature	Voltage	Reading Frequency Err	
℃	V_{DC}	MHz	ppm
50		450.01268	0.42
40		450.01270	0.47
30		450.01273	0.54
20		450.01281	0.73
10	3.7	450.01269	0.45
0	=	450.01285	0.82
-10	=	450.01263	0.31
-20		450.01262	0.28
-30		450.01264	0.33
20	3.2	450.01263	0.31

Report No.: RSZ160829801-00

For Digital Modulation

Reference Frequency: 460.0125MHz, 6.25 kHz, Limit: 1.0ppm			
Temerature	Voltage	Reading Frequency Err	
°C	V_{DC}	MHz	ppm
50		450.01259	0.20
40		450.01275	0.56
30		450.01276	0.58
20		450.01281	0.69
10	3.7	450.01288	0.84
0		450.01270	0.44
-10		450.01274	0.53
-20		450.01276	0.58
-30		450.01279	0.64
20	3.2	450.01272	0.49

Note: The extreme voltage is declared by the manufacturer.

FCC Part 90 Page 27 of 30

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR

Applicable Standard

Regulations: FCC §90.214

Test method: ANSI/TIA-603-D 2010, section 2.2.19.3

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2016-05-09	2017-05-09
HP	Signal Generator	E4422B	MY41000355	2015-11-23	2016-11-22
Cheng Du Ou Li Tong	Two way power splitter	EMPD-T- 2-10-1000	OE01201041	2016-05-06	2017-05-06
Weinschel Corp	Attenuator(10dB)	53-20-34	LN749	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06

Report No.: RSZ160829801-00

Test Procedure


- a) Connect the EUT and test equipment as shown on the following block diagram.
- b) Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- c) Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at ± 12.5 kHz deviation and set its output level to -100dBm.
- d) Turn on the transmitter.
- e) Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as P₀.
- f) Turn off the transmitter.
- g) Adjust the RF level of the signal generator to provide RF power equal to P₀. This signal generator RF level shall be maintained throughout the rest of the measurement.
- h) Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- i) Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at ±4 divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to "Video", and tune the "trigger level" on suitable level. Then set the "tiger offset" to -10ms for turn on and -15ms for turn off.
- j) Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be t_{on}. The trace should be maintained within the allowed divisions during the period t₁ and t₂.

FCC Part 90 Page 28 of 30

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

k) Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period t₃.

Report No.: RSZ160829801-00



Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	53 %
ATM Pressure:	98.9 kPa

The testing was performed by Gavin Xu on 2016-09-27...


Channel Spacing (kHz)	Transient Period (ms)	Maximum frequency difference	Result
12.5	$<10(t_1)$	±12.5 kHz	
	$<25(t_2)$	±6.25 kHz	Pass
	<10(t ₃)	±12.5 kHz	

Please refer to the following plots.


FCC Part 90 Page 29 of 30

Turn on

Report No.: RSZ160829801-00



Turn off



***** END OF REPORT *****

FCC Part 90 Page 30 of 30