

## **FCC Test Report**

Report No.: RF171110W004-1

FCC ID: 2AJOTTA-1016

Test Model: TA-1016

Received Date: Nov. 13, 2017

**Test Date:** Nov. 14, 2017 ~ Dec. 26, 2017

**Issued Date:** Jan. 02, 2018

Applicant: HMD Global Oy

Address: Karaportti 2, 02610 Espoo, Finland

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan

Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City,

Taiwan (R.O.C)

Test Location (1): NO. B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North

Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong

518057, China

Test Location (2): No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)

FCC Registration /

788550 / TW0003

**Designation Number:** 





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report No.: RF171110W004-1 Page No. 1 / 62 Report Format Version: 6.1.1



# **TABLE OF CONTENTS**

RELEASI	CONTROL RECORD	5
1 CER	TIFICATION	6
2 SUN	IMARY OF TEST RESULTS	7
2.1 M	EASUREMENT UNCERTAINTY	7
3 GEN	IERAL INFORMATION	8
3.1 G	ENERAL DESCRIPTION OF EUT	8
	ESCRIPTION OF TEST MODES	
3.2.	CONFIGURATION OF SYSTEM UNDER TEST	10
3.2.2	2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	10
	ENERAL DESCRIPTION OF APPLIED STANDARDS	
3.4 D	ESCRIPTION OF SUPPORT UNITS	12
4 TES	T TYPES AND RESULTS	13
4.1 C	ONDUCTED EMISSION MEASUREMENT	13
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	13
4.1.2	2 TEST INSTRUMENTS	13
4.1.3	3 TEST PROCEDURES	14
4.1.4	DEVIATION FROM TEST STANDARD	14
4.1.5	5 TEST SETUP	15
4.1.6	EUT OPERATING CONDITIONS	15
4.1.7		
4.2 R	ADIATED EMISSION AND BANDEDGE MEASUREMENT	18
4.2.		
4.2.2	2 TEST INSTRUMENTS	19
4.2.3		
4.2.4	DEVIATION FROM TEST STANDARD	20
4.2.5	5 TEST SETUP	21
4.2.6	EUT OPERATING CONDITIONS	22
4.2.7	7 TEST RESULTS	23
4.3 N	UMBER OF HOPPING FREQUENCY USED	31
4.3.	LIMIT OF HOPPING FREQUENCY USED	31
4.3.2	2 TEST SETUP	31
4.3.3	3 TEST INSTRUMENTS	31
4.3.4	TEST PROCEDURES	32
4.3.5	DEVIATION FROM TEST STANDARD	32
4.3.6		
4.4 D	WELL TIME ON EACH CHANNEL	35
4.4.	LIMIT OF DWELL TIME USED	35



	4.4.2	TEST SETUP	35
	4.4.3	TEST INSTRUMENTS	35
	4.4.4	TEST PROCEDURES	35
	4.4.5	DEVIATION FROM TEST STANDARD	36
	4.4.6	TEST RESULTS	36
4.	5 CHA	NNEL BANDWIDTH	. 40
	4.5.1	LIMITS OF CHANNEL BANDWIDTH	40
	4.5.2	TEST SETUP	40
	4.5.3	TEST INSTRUMENTS	40
	4.5.4	TEST PROCEDURE	40
	4.5.5	DEVIATION FROM TEST STANDARD	40
	4.5.6	EUT OPERATING CONDITION	40
	4.5.7	TEST RESULTS	41
4.	6 HOP	PING CHANNEL SEPARATION	. 47
	4.6.1	LIMIT OF HOPPING CHANNEL SEPARATION	47
	4.6.2	TEST SETUP	47
	4.6.3	TEST INSTRUMENTS	47
	4.6.4	TEST PROCEDURES	47
	4.6.5	DEVIATION FROM TEST STANDARD	47
	4.6.6	TEST RESULTS	48
4.	7 MAX	IMUM OUTPUT POWER	. 52
	4.7.1	LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT	52
	4.7.2	TEST SETUP	52
	4.7.3	TEST INSTRUMENTS	52
	4.7.4	TEST PROCEDURES	53
	4.7.5	DEVIATION FROM TEST STANDARD	53
	4.7.6	EUT OPERATING CONDITION	53
	4.7.7	TEST RESULTS	54
	4.7.7.1	MAXIMUM PEAK OUTPUT POWER	54
	4.7.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE)	55
4.	8 OUT	OF BAND MEASUREMENT	. 56
	4.8.1	LIMITS OF OUT OF BAND MEASUREMENT	56
	4.8.2	TEST INSTRUMENTS	56
	4.8.3	TEST PROCEDURE	56
	4.8.4	DEVIATION FROM TEST STANDARD	56
	4.8.5	EUT OPERATING CONDITION	56
	4.8.6	TEST RESULTS	56
5	DHO	TOGRAPHS OF THE TEST CONFIGURATION	61



6	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO TH	Е
FUT	RY THE LAR	6:

Report No.: RF171110W004-1 Page No. 4 / 62 Report Format Version: 6.1.1



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF171110W004-1	Original release	Jan. 02, 2018

Report No.: RF171110W004-1 Page No. 5 / 62 Report Format Version: 6.1.1



# 1 CERTIFICATION

**Product:** Smart Phone

Brand: Nokia

Test Model: TA-1016

Sample Status: Identical Prototype

Applicant: HMD Global Oy

Test Date: Nov. 14, 2017 ~ Dec. 26, 2017

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Yuqiang Yin / Engineer

Approved by: Date: Jan. 02. 2018

Dylan Chiou / Project Engineer



## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C								
STANDARD SECTION	REMARK							
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.63dB at 10.504000MHz.					
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.					
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.					
15.247(a)(1)	Hopping Channel Separation     Spectrum Bandwidth of a     Frequency Hopping Sequence     Spread Spectrum System	PASS	Meet the requirement of limit.					
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.					
15.247(d)& 15.209	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -9.17dB at 2483.5MHz.					
15.247(d)	Out of band Measurement	PASS	Meet the requirement of limit.					
15.203	Antenna Requirement	PASS	No antenna connector is used.					

**NOTE:** If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

## 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
	9KHz ~ 30MHz	2.68dB
Radiated emissions	30MHz ~ 1GMHz	3.26dB
Nadiated emissions	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



# **3 GENERAL INFORMATION**

## 3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Smart Phone
MODEL NAME	TA-1016
POWER SUPPLY	5/9Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, π/4 DQPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	9.462mW (Max. Measured)
ANTENNA TYPE	PIFA Antenna with -1.7dBi gain
HW VERSION	5
SW VERSION	00WW_1_300
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable: non-shielded, detachable, 1.0meter Earphone cable: non-shielded, detachable, 1.4meter

#### NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

#### **List of Accessories:**

ACCESSORIES	BRAND	MODEL	MANUFACTURER	SPECIFICATION
Adapter 1	Nokia	FC0302	Salcomp	I/P: 100-240Vac, 0.5A O/P: 5Vdc, 2.5A/ 9Vdc, 2.0A / 12Vdc, 1.5A
Adapter 2	Nokia	AD-18WU	DVE	I/P: 100-240Vac, 0.5A O/P: 5Vdc, 2.5A/ 9Vdc, 2.0A / 12Vdc, 1.5A
Adapter 3	Nokia	AD-18WU	Salcomp	I/P: 100-240Vac, 0.5A O/P: 5Vdc, 3.0A/ 9Vdc, 2.0A / 12Vdc, 1.5A
Battery	SCUD	HE345	SCUD	Rating: 3.85Vdc, 3000mAh
Earphone 1	Foxconn	WH-108	Foxconn	1.4m non-shielded cable w/o core
Earphone 2	Foxconn	WH-108	OBO PRO.2 INC.	1.4m non-shielded cable w/o core
USB Cable 1	FIT	CUDU01B-FA203-DH	Foxconn	1.0m non-shielded cable w/o core
USB Cable 2	Shenglan	JCT024-F001	Shenglan	1.0m non-shielded cable w/o core
USB Cable 3	Yinrun	YR680004-A	Yinrun	1.0m non-shielded cable w/o core

Report No.: RF171110W004-1 Page No. 8 / 62 Report Format Version: 6.1.1



# 3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



#### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

#### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE		APPLICA	ABLE TO		DESCRIPTION
MODE	RE<1G	RE≥1G	PLC	APCM	DESCRIPTION
-	<b>√</b>	<b>√</b>	$\sqrt{}$	<b>√</b>	-

Where

**RE<1G:** Radiated Emission below 1GHz **PLC:** Power Line Conducted Emission

**RE≥1G:** Radiated Emission above 1GHz

**APCM:** Antenna Port Conducted Measurement

#### **RADIATED EMISSION TEST (BELOW 1 GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE	AVAILABLE	TESTED	MODULATION	MODULATION	PACKET
MODE	CHANNEL	CHANNEL	TECHNOLOGY	TYPE	TYPE
-	0 to 78	78	FHSS	GFSK	DH5

#### **RADIATED EMISSION TEST (ABOVE 1 GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	DH5

Report No.: RF171110W004-1 Page No. 10 / 62 Report Format Version: 6.1.1



#### **POWER LINE CONDUCTED EMISSION TEST:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE	AVAILABLE	TESTED	MODULATION	MODULATION	PACKET
MODE	CHANNEL	CHANNEL	TECHNOLOGY	TYPE	TYPE
-	0 to 78	78	FHSS	GFSK	DH5

#### **ANTENNA PORT CONDUCTED MEASUREMENT:**

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

Following channel(s) was (were) selected for the final test as listed below.

	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
	0 to 78	0, 39, 78	FHSS	GFSK	DH5
I	0 to 78	0, 39, 78	FHSS	π/4 DQPSK	DH5
	0 to 78	0, 39, 78	FHSS	8DPSK	DH5

## **TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	22deg. C, 54%RH	DC 5/9V from adaptor	Alex Chen
RE≥1G	22deg. C, 54%RH	DC 5/9V from adaptor	Alex Chen
PLC	24deg. C, 55%RH	DC 5/9V from adaptor	Felix Chen
APCM	25deg. C, 60%RH	DC 3.85V from battery	Wenliang Wu

Report No.: RF171110W004-1 Page No. 11 / 62 Report Format Version: 6.1.1



#### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247 ANSI C63.10-2013

#### FCC Public Notice DA 00-705

**NOTE:** 1. All test items have been performed and recorded as per the above standards.

 The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

#### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m

Report No.: RF171110W004-1 Page No. 12 / 62 Report Format Version: 6.1.1



## 4 TEST TYPES AND RESULTS

#### 4.1 CONDUCTED EMISSION MEASUREMENT

## 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)		
	Quasi-peak	Average	
0.15 ~ 0.5	66 to 56	56 to 46	
0.5 ~ 5	56	46	
5 ~ 30	60	50	

**NOTE**: 1.The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
- All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

## 4.1.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCS 30	100288	Aug. 17, 2017	Aug. 16, 2018
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond2-01	Sep. 08, 2017	Sep. 07, 2018
LISN/AMN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Jan. 17, 2017	Jan. 16, 2018
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 2.
- 3. The VCCI Site Registration No. is C-2047.



#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.


#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

Report No.: RF171110W004-1 Page No. 14 / 62 Report Format Version: 6.1.1



#### 4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



## 4.1.7 TEST RESULTS


#### **CONDUCTED WORST-CASE DATA:**

Frequency Range	1150KH7 ~ 30MH7		Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	1120\/ac 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Felix Chen	TEST DATE	2017/11/14

Frequency (MHz)	QuasiPeak (dB¦ÌV)	CAverage (dB¦ÌV)	Limit (dB¦ÌV)	Margin (dB)	Line	Filter	Corr. (dB)
0.166000		23.60	55.16	-31.56	L	ON	9.7
0.166000	41.13		65.16	-24.03	L	ON	9.7
0.236000		21.18	52.24	-31.06	L	ON	9.7
0.236000	37.71		62.24	-24.53	L	ON	9.7
0.604000		17.29	46.00	-28.71	L	ON	9.7
0.604000	33.95		56.00	-22.05	L	ON	9.7
0.820000		6.67	46.00	-39.33	L	ON	9.7
0.820000	19.76		56.00	-36.24	L	ON	9.7
10.432000		34.54	50.00	-15.46	L	ON	9.9
10.432000	44.29		60.00	-15.71	L	ON	9.9
10.536000		32.91	50.00	-17.09	L	ON	9.9
10.536000	42.30		60.00	-17.70	L	ON	9.9

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.



Report No.: RF171110W004-1 Page No. 16 / 62 Report Format Version: 6.1.1




Frequency Range	1150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	1120\/ac 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Felix Chen	TEST DATE	2017/11/14

Frequency (MHz)	QuasiPeak (dB¦ÌV)	CAverage (dB¦ÌV)	Limit (dB¦ÌV)	Margin (dB)	Line	Filter	Corr. (dB)
0.204000		36.10	53.45	-17.35	N	ON	9.9
0.204000	48.36		63.45	-15.09	N	ON	9.9
0.212000		30.41	53.13	-22.72	N	ON	9.9
0.212000	45.82		63.13	-17.31	N	ON	9.9
0.604000		31.45	46.00	-14.55	N	ON	10.1
0.604000	41.88		56.00	-14.12	N	ON	10.1
0.684000		25.49	46.00	-20.51	N	ON	10.0
0.684000	34.92		56.00	-21.08	N	ON	10.0
10.248000		36.81	50.00	-13.19	N	ON	9.9
10.248000	44.39		60.00	-15.61	N	ON	9.9
10.504000		37.37	50.00	-12.63	N	ON	9.9
10.504000	45.36		60.00	-14.64	N	ON	9.9

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.



Note: Conducted Emission was performed by **Bureau Veritas Consumer Products Services (H.K.)**Ltd., Taoyuan Branch.

Report No.: RF171110W004-1 Page No. 17 / 62 Report Format Version: 6.1.1



#### 4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Report No.: RF171110W004-1 Page No. 18 / 62 Report Format Version: 6.1.1



## 4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn- CT0001143-1216	May 06,17	May 05,18
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
Loop antenna	Daze	ZN30900A	0708	Nov. 20,17	Nov. 19,18
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-4 0-K-SG/QMS- 00361	15433	Dec. 16,16	Dec. 15,18
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SM A	1505	Jul. 24,17	Jul. 23,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 10,17	Mar. 09,18
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 24,17	Jul. 23,18

**NOTE:** 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

- 2. The test was performed in 3m Chamber.
- 3. The FCC Site Registration No. is 525120.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) /
  1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test.
  The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### NOTE:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
- 4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit.
- 5. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD


No deviation.

Report No.: RF171110W004-1 Page No. 20 / 62 Report Format Version: 6.1.1




# 4.2.5 TEST SETUP

# < Frequency Range below 30MHz >




# < Frequency Range 30MHz~1GHz >





## <Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



## 4.2.7 TEST RESULTS

#### **BELOW 1GHz WORST-CASE DATA:**

**9 KHz – 30 KHz data:** the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

#### 30 MHz - 1GHz data:


#### **GFSK DH5**

CHANNEL	Channel 78	DETECTOR FUNCTION	Ouesi Beek (OD)
FREQUENCY RANGE		DETECTOR FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
96.93	22.49	50.32	43.5	-21.01	7.66	1.52	37.01	100	152	QP
142.52	27.42	54.11	43.5	-16.08	8.3	1.84	36.83	100	221	QP
167.74	30.99	55.65	43.5	-12.51	10.08	1.98	36.72	100	274	QP
192.96	27.02	51.45	43.5	-16.48	10.03	2.13	36.59	100	302	QP
232.73	18.96	41.53	46	-27.04	11.61	2.35	36.53	100	87	QP
422.85	20.91	36.99	46	-25.09	17.47	3.22	36.77	100	55	QP

#### **REMARKS:**

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



Report No.: RF171110W004-1 Page No. 23 / 62 Report Format Version: 6.1.1




CHANNEL	Channel 78	DETECTOR FUNCTION	Ouggi Book (OD)
FREQUENCY RANGE		DETECTOR FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
42.61	29.55	56.8	40	-10.45	9.23	0.98	37.46	100	123	QP
91.11	26.72	55.26	43.5	-16.78	7.02	1.47	37.03	100	57	QP
142.52	26.1	52.79	43.5	-17.4	8.3	1.84	36.83	100	326	QP
192.96	25.62	50.05	43.5	-17.88	10.03	2.13	36.59	100	215	QP
315.18	12.8	32.9	46	-33.2	13.64	2.79	36.53	100	72	QP
449.04	17.01	32.76	46	-28.99	17.79	3.3	36.84	100	18	QP

#### **REMARKS:**

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



Report No.: RF171110W004-1 Page No. 24 / 62 Report Format Version: 6.1.1



## **ABOVE 1GHz WORST-CASE DATA:**

**Note:** For higher frequency, the emission is too low to be detected.

## **GFSK DH5**

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE		DETECTOR FUNCTION	Average (AV)

	Δ	NTENN	A POLAF	RITY & TE	ST DISTA	NCE: H	ORIZONT	AL AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.97	49.45	54	-10.03	32.29	8.15	45.92	100	225	Average
2390	54.82	60.3	74	-19.18	32.29	8.15	45.92	100	225	Peak
2402	91.98	97.43			32.3	8.17	45.92	100	225	Average
2402	96.32	101.77			32.3	8.17	45.92	100	225	Peak
2483.5	44.26	49.45	54	-9.74	32.38	8.32	45.89	100	225	Average
2483.5	54.92	60.11	74	-19.08	32.38	8.32	45.89	100	225	Peak
		ANTEN	NA POLA	ARITY & 1	EST DIST	ANCE: \	VERTICA	L AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.11	49.59	54	-9.89	32.29	8.15	45.92	100	278	Average
2390	54.26	59.74	74	-19.74	32.29	8.15	45.92	100	278	Peak
2402	94.61	100.06			32.3	8.17	45.92	100	278	Average
2402	100.92	106.37			32.3	8.17	45.92	100	278	Peak
2483.5	44.38	49.57	54	-9.62	32.38	8.32	45.89	100	278	Average
2483.5	55.32	60.51	74	-18.68	32.38	8.32	45.89	100	278	Peak

#### **REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level – Limit value.
- 2. 2402MHz: Fundamental frequency.

Report No.: RF171110W004-1 Page No. 25 / 62 Report Format Version: 6.1.1



CHANNEL	TX Channel 39	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	Δ	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.04	49.52	54	-9.96	32.29	8.15	45.92	100	228	Average
2390	54.64	60.12	74	-19.36	32.29	8.15	45.92	100	228	Peak
2441	90.7	96.03			32.34	8.24	45.91	100	228	Average
2441	98.52	103.85			32.34	8.24	45.91	100	228	Peak
2483.5	44.39	49.58	54	-9.61	32.38	8.32	45.89	100	228	Average
2483.5	45.17	50.36	74	-28.83	32.38	8.32	45.89	100	228	Peak
		ANTEN	NA POLA	ARITY & 1	EST DIST	ANCE: \	VERTICA	L AT 3 M	<del>-</del>	<u>-</u>
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.23	49.71	54	-9.77	32.29	8.15	45.92	100	280	Average
2390	54.43	59.91	74	-19.57	32.29	8.15	45.92	100	280	Peak
2441	95.23	100.56			32.34	8.24	45.91	100	280	Average
2441	101.71	107.04			32.34	8.24	45.91	100	280	Peak
2483.5	44.5	49.69	54	-9.5	32.38	8.32	45.89	100	280	Average
2483.5	55.09	60.28	74	-18.91	32.38	8.32	45.89	100	280	Peak

## **REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level – Limit value.
- 2. 2441MHz: Fundamental frequency.

Report No.: RF171110W004-1 Page No. 26 / 62 Report Format Version: 6.1.1



CHANNEL	TX Channel 78	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	Δ	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.33	49.81	54	-9.67	32.29	8.15	45.92	105	230	Average
2390	54.73	60.21	74	-19.27	32.29	8.15	45.92	105	230	Peak
2480	87.69	92.9			32.38	8.31	45.9	105	230	Average
2480	96.16	101.37			32.38	8.31	45.9	105	230	Peak
2483.5	44.83	50.02	54	-9.17	32.38	8.32	45.89	105	230	Average
2483.5	55.64	60.83	74	-18.36	32.38	8.32	45.89	105	230	Peak
		ANTEN	INA POLA	ARITY & 1	EST DIST	ANCE: \	VERTICA	L AT 3 M	-	
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	43.94	49.42	54	-10.06	32.29	8.15	45.92	105	275	Average
2390	54.54	60.02	74	-19.46	32.29	8.15	45.92	105	275	Peak
2480	93.01	98.22			32.38	8.31	45.9	105	275	Average
2480	99.52	104.73			32.38	8.31	45.9	105	275	Peak
2483.5	44.26	49.45	54	-9.74	32.38	8.32	45.89	105	275	Average
2483.5	54.4	59.59	74	-19.6	32.38	8.32	45.89	105	275	Peak

## **REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level – Limit value.
- 2. 2480MHz: Fundamental frequency.

Report No.: RF171110W004-1 Page No. 27 / 62 Report Format Version: 6.1.1



## BT\_8DPSK

CHANNEL	TX Channel 0	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.06	49.54	54	-9.94	32.29	8.15	45.92	100	228	Average
2390	54.81	60.29	74	-19.19	32.29	8.15	45.92	100	228	Peak
2402	87.94	93.39			32.3	8.17	45.92	100	228	Average
2402	96.21	101.66			32.3	8.17	45.92	100	228	Peak
2483.5	44.27	49.46	54	-9.73	32.38	8.32	45.89	100	228	Average
2483.5	55.52	60.71	74	-18.48	32.38	8.32	45.89	100	228	Peak
		ANTEN	NA POLA	ARITY & 1	EST DIST	ANCE: \	VERTICA	L AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.33	49.81	54	-9.67	32.29	8.15	45.92	108	274	Average
2390	55.05	60.53	74	-18.95	32.29	8.15	45.92	108	274	Peak
2402	90.71	96.16			32.3	8.17	45.92	108	274	Average
2402	98.43	103.88			32.3	8.17	45.92	108	274	Peak
2483.5	44.38	49.57	54	-9.62	32.38	8.32	45.89	108	274	Average
2483.5	55.53	60.72	74	-18.47	32.38	8.32	45.89	108	274	Peak

## **REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level – Limit value.
- 2. 2402MHz: Fundamental frequency.

Report No.: RF171110W004-1 Page No. 28 / 62 Report Format Version: 6.1.1



CHANNEL	TX Channel 39	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK	
2390	44.09	49.57	54	-9.91	32.29	8.15	45.92	100	220	Average	
2390	55.06	60.54	74	-18.94	32.29	8.15	45.92	100	220	Peak	
2441	86.19	91.52			32.34	8.24	45.91	100	220	Average	
2441	96.33	101.66			32.34	8.24	45.91	100	220	Peak	
2483.5	44.34	49.53	54	-9.66	32.38	8.32	45.89	100	220	Average	
2483.5	55.22	60.41	74	-18.78	32.38	8.32	45.89	100	220	Peak	
	-	ANTEN	INA POLA	ARITY & 1	EST DIST	ANCE: \	VERTICA	L AT 3 M	<del>-</del>	<u>-</u>	
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK	
2390	44.16	49.64	54	-9.84	32.29	8.15	45.92	100	278	Average	
2390	54.68	60.16	74	-19.32	32.29	8.15	45.92	100	278	Peak	
2441	90.51	95.84			32.34	8.24	45.91	100	278	Average	
2441	99.6	104.93			32.34	8.24	45.91	100	278	Peak	
2483.5	44.38	49.57	54	-9.62	32.38	8.32	45.89	100	278	Average	

## **REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level – Limit value.
- 2. 2441MHz: Fundamental frequency.

Report No.: RF171110W004-1 Page No. 29 / 62 Report Format Version: 6.1.1



CHANNEL	TX Channel 78	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK	
2390	43.91	49.39	54	-10.09	32.29	8.15	45.92	108	225	Average	
2390	55.03	60.51	74	-18.97	32.29	8.15	45.92	108	225	Peak	
2480	83.16	88.37			32.38	8.31	45.9	108	225	Average	
2480	96.03	101.24			32.38	8.31	45.9	108	225	Peak	
2483.5	44.2	49.39	54	-9.8	32.38	8.32	45.89	108	225	Average	
2483.5	54.95	60.14	74	-19.05	32.38	8.32	45.89	108	225	Peak	
		ANTEN	INA POLA	ARITY & 1	EST DIST	ANCE: \	VERTICA	L AT 3 M			
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK	
2390	44.08	49.56	54	-9.92	32.29	8.15	45.92	108	276	Average	
2390	54.66	60.14	74	-19.34	32.29	8.15	45.92	108	276	Peak	
2480	88.65	93.86			32.38	8.31	45.9	108	276	Average	
2480	98.65	103.86			32.38	8.31	45.9	108	276	Peak	
2483.5	44.52	49.71	54	-9.48	32.38	8.32	45.89	108	276	Average	
2483.5	55.14	60.33	74	-18.86	32.38	8.32	45.89	108	276	Peak	

## **REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level – Limit value.
- 2. 2480MHz: Fundamental frequency.

Note: The test, calibration and test results are compliance with the A2LA (Certificate # 3939.01).

Report No.: RF171110W004-1 Page No. 30 / 62 Report Format Version: 6.1.1




## 4.3 NUMBER OF HOPPING FREQUENCY USED

## 4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

## 4.3.2 TEST SETUP



## 4.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Mar. 01,17	Feb. 28,18
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510523	Mar. 01,17	Feb. 28,18
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510332	Mar. 01,17	Feb. 28,18
Power Sensor		MA2411B	1339352	Mar. 01,17	Feb. 28,18
CBT32 BLUETOOTH TESTER 4HU	Rohde&Schwarz	CBT32	101176	Jun. 26,17	Jun. 25,18

#### NOTE:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 2. The test was performed in RF Oven room.

Report No.: RF171110W004-1 Page No. 31 / 62 Report Format Version: 6.1.1



#### 4.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.


#### 4.3.6 TEST RESULTS


There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

Report No.: RF171110W004-1 Page No. 32 / 62 Report Format Version: 6.1.1




## **GFSK**








## 8DPSK





Note: The test, calibration and test results are compliance with the A2LA (Certificate # 3939.01).




#### 4.4 DWELL TIME ON EACH CHANNEL

#### 4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 4.4.2 TEST SETUP



#### 4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

#### 4.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

Report No.: RF171110W004-1 Page No. 35 / 62 Report Format Version: 6.1.1



# 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

## 4.4.6 TEST RESULTS

## **GFSK**


	Number of	period(chamiler number 6.4 666)				Length of	Result	Limit	PASS/
Mode	Hopping Channel	period (sec)	sweep time (sec)	times in a sweep	times in a period	transmission time (msec)	(msec)	(msec)	FAIL
DH1	79	31.6	5	50	316	0.42	132.72	400	PASS
DH3	79	31.6	5	26	164.32	1.685	276.88	400	PASS
DH5	79	31.6	5	17	107.44	2.95	316.95	400	PASS

**NOTE:** Test plots of the transmitting time slot are shown on next page.

Report No.: RF171110W004-1 Page No. 36 / 62 Report Format Version: 6.1.1



## **GFSK**






	Number of	Number of transmission in a period(channel number*0.4 sec)			Length of Result		Limit	PASS /	
Mode	Hopping Channel	period (sec)	sweep time (sec)	times in a sweep	times in a period	transmission time (msec)	(msec)	(msec)	FAIL
DH1	79	31.6	5	49	309.68	0.426	131.92	400	PASS
DH3	79	31.6	5	27	170.64	1.68	286.68	400	PASS
DH5	79	31.6	5	18	113.76	2.945	335.02	400	PASS

**NOTE:** Test plots of the transmitting time slot are shown on next page.

Report No.: RF171110W004-1 Page No. 38 / 62 Report Format Version: 6.1.1





Note: The test, calibration and test results are compliance with the A2LA (Certificate # 3939.01).




#### 4.5 CHANNEL BANDWIDTH

#### 4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

#### 4.5.2 TEST SETUP



#### 4.5.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

#### 4.5.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

#### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


Report No.: RF171110W004-1 Page No. 40 / 62 Report Format Version: 6.1.1




## 4.5.7 TEST RESULTS


## **GFSK**

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.95
39	2441	0.95
78	2480	0.96














## π/4 DQPSK

CHANNEL FREQUENCY (MHz)		20dB BANDWIDTH (MHz)
0	2402	1.31
39	2441	1.28
78	2480	1.30














CHANNEL CHANNEL FREQUENCY (MHz)		20dB BANDWIDTH (MHz)
0	2402	1.30
39	2441	1.30
78	2480	1.30







### **CH 78**



Note: The test, calibration and test results are compliance with the A2LA (Certificate # 3939.01).




#### 4.6 HOPPING CHANNEL SEPARATION

#### 4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

## 4.6.2 TEST SETUP



#### 4.6.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

#### 4.6.4 TEST PROCEDURES

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- 3. By using the MaxHold function record the separation of two adjacent channels.
- 4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- 5. Repeat above procedures until all frequencies measured were complete.

#### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

 Report No.: RF171110W004-1
 Page No. 47 / 62
 Report Format Version: 6.1.1




## 4.6.6 TEST RESULTS


## **GFSK**


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	0.95	0.63	PASS
39	2441	1.00	0.95	0.63	PASS
78	2480	1.00	0.96	0.64	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.













CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.30	0.87	PASS
39	2441	1.00	1.30	0.87	PASS
78	2480	1.00	1.30	0.87	PASS


NOTE: The minimum limit is two-third 20dB bandwidth.











Note: The test, calibration and test results are compliance with the A2LA (Certificate # 3939.01).




## 4.7 MAXIMUM OUTPUT POWER

## 4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

## 4.7.2 TEST SETUP



#### 4.7.3 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Spectrum Analyzer Agilent	N9010A	MY52220314	No. 24, 2017	Nov. 23, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	100115	Nov. 23, 2017	Nov. 22, 2018
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(RFC- SMS-100-SMS-120+ RFC-SMS-100-SMS- 400)	Jun. 23, 2017	Jun. 22, 2018
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 24, 2017	Oct. 23, 2018
Bluetooth Tester	CBT	100946	Jul. 29, 2016	Jul. 28, 2018
Power Meter Anritsu	ML2495A	1012010	Aug. 15, 2017	Aug. 14, 2018
Power Sensor Anritsu	MA2411B	1315050	Aug. 15, 2017	Aug. 14, 2018
RF Coaxial Cable HUBER+SUHNNER	EMC104-SM-SM-8000 &3000	140811+170717	Oct. 20, 2017	Oct. 19, 2018
RF Coaxial Cable HUBER+SUHNNER	SUCOFLEX 104	EMC104-SM-SM-100 0(140807)	Oct. 20, 2017	Oct. 19, 2018
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Oct. 20, 2017	Oct. 19, 2018

NOTE:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

Report No.: RF171110W004-1 Page No. 52 / 62 Report Format Version: 6.1.1



## 4.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

## 4.7.5 DEVIATION FROM TEST STANDARD No deviation.

## 4.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF171110W004-1 Page No. 53 / 62 Report Format Version: 6.1.1



## 4.7.7 TEST RESULTS

## 4.7.7.1 MAXIMUM PEAK OUTPUT POWER

## **GFSK**

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	9.76	9.462	125	PASS
39	2441	9.14	8.204	125	PASS
78	2480	9.30	8.511	125	PASS

## $\pi$ /4 DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	8.70	7.413	125	PASS
39	2441	7.88	6.138	125	PASS
78	2480	8.26	6.699	125	PASS

## 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	POWER OUTPUT (dBm)	POWER OUTPUT (mW)	POWER LIMIT (mW)	PASS/FAIL
0	2402	8.91	7.780	125	PASS
39	2441	8.17	6.561	125	PASS
78	2480	8.47	7.031	125	PASS

Report No.: RF171110W004-1 Page No. 54 / 62 Report Format Version: 6.1.1



## 4.7.7.2 Average Output Power (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

#### **GFSK**

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	9.29	N/A
39	2441	8.69	N/A
78	2480	8.67	N/A

#### π/4 DQPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL
0	2402	6.75	N/A
39	2441	5.52	N/A
78	2480	6.14	N/A

#### 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL		
0	2402	6.70	N/A		
39	2441	5.44	N/A		
78	2480	6.10	N/A		

Note: Conducted power performed by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**.

Report No.: RF171110W004-1 Page No. 55 / 62 Report Format Version: 6.1.1



#### 4.8 OUT OF BAND MEASUREMENT

#### 4.8.1 LIMITS OF OUT OF BAND MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

#### 4.8.2 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

#### 4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

#### 4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


## 4.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.


Report No.: RF171110W004-1 Page No. 56 / 62 Report Format Version: 6.1.1




#### **GFSK**
















Note: The test, calibration and test results are compliance with the A2LA (Certificate # 3939.01).



## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

Report No.: RF171110W004-1 Page No. 61 / 62 Report Format Version: 6.1.1



# 6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

	No	any	/ modifications	are made	to the	e EUT b	y the	lab c	during	the	tes
--	----	-----	-----------------	----------	--------	---------	-------	-------	--------	-----	-----

---END---

Report No.: RF171110W004-1 Page No. 62 / 62 Report Format Version: 6.1.1