



BUREAU  
VERITAS

Test Report No.: FV180604W006-1



## VARIANT EMC TEST REPORT

Applicant:	FIH International Co., Ltd.
Address:	No.18, Tongji zhonglu, Beijing Economic & Technological Development Area

Manufacturer or Supplier	HMD Global Oy
Address	Karaportti 2 02610 Espoo FINLAND
Product	GSM/WCDMA/LTE Mobile Phone
Brand Name	Nokia
Model Name	TA-1049
FCC ID	2AJOTTA-1049
Date of tests	Jun. 05, 2018 ~ Jun. 25, 2018

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

FCC Part 15, Subpart B, Class B  
 ANSI C63.4:2014

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Alex Chen Engineer / Mobile Department	Approved by Sam Tung Manager / Mobile Department

Date: Jul. 02, 2018      Date: Jul. 02, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>3</b>
<b>1 GENERAL INFORMATION .....</b>	<b>4</b>
1.1 GENERAL DESCRIPTION OF EUT.....	4
1.2 SUMMARY OF TEST RESULTS.....	6
1.3 MEASUREMENT UNCERTAINTY .....	6
1.4 DESCRIPTION OF TEST MODES.....	7
1.5 DESCRIPTION OF SUPPORT UNITS.....	8
1.6 CONFIGURATION OF SYSTEM UNDER TEST .....	9
<b>2 EMISSION TEST .....</b>	<b>11</b>
2.1 CONDUCTED EMISSION MEASUREMENT .....	11
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	11
2.1.2 TEST INSTRUMENTS.....	11
2.1.3 TEST PROCEDURES .....	12
2.1.4 DEVIATION FROM TEST STANDARD .....	12
2.1.5 TEST SETUP .....	13
2.1.6 EUT OPERATING CONDITIONS .....	13
2.1.7 TEST RESULTS .....	14
2.2 RADIATED EMISSION MEASUREMENT.....	16
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	16
2.2.2 TEST INSTRUMENTS.....	17
2.2.3 TEST PROCEDURE.....	18
2.2.4 DEVIATION FROM TEST STANDARD .....	19
2.2.5 TEST SETUP .....	20
2.2.6 EUT OPERATING CONDITIONS .....	20
2.2.7 TEST RESULTS .....	21
<b>3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....</b>	<b>23</b>



BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FV180604W006-1	Original release	Jul. 02, 2018



BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## 1 GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	GSM/WCDMA/LTE Mobile Phone	
BRAND NAME	Nokia	
MODEL NAME	TA-1049	
NOMINAL VOLTAGE	5.0Vdc (adapter or host equipment) 3.9Vdc (Li-ion, ion battery )	
BATTERY	Brand Name: SCUD Model Name: HE336 Power Rating: DC 3.85V, 2900mAh, Li-ion	
MODULATION TYPE	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
	BT_LE	DTS
	Bluetooth	GFSK, π/4-DQPSK, 8DPSK
	GPS/ GLONASS	C/A code
	FM	FSK
	GSM/EDGE	GMSK, 8PSK
	WCDMA	BPSK/QPSK
OPERATING FREQUENCY	LTE	QPSK/16QAM
	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20) 5150 ~ 5250MHz, 5250 ~ 5350MHz, 5470 ~ 5725MHz, 5725 ~ 5825MHz for 11a/n(HT20)/n(HT40)
	Bluetooth/BT_LE	2402MHz ~ 2480MHz
	GPS	1575.42MHz
	GLONASS	1602MHz
	FM	98MHz
	GSM/EDGE	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR GSM 1900)
WCDMA	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA Band 2) 1712.4MHz ~ 1752.6MHz (FOR WCDMA Band 4) 826.4MHz ~ 846.6MHz (FOR WCDMA Band 5)
	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 2502.5 ~ 2567.5 MHz (FOR LTE Band7)



BUREAU  
VERITAS

Test Report No.: FV180604W006-1

		699.7MHz ~ 715.3MHz (FOR LTE Band12) 706.5MHz ~ 713.5MHz (FOR LTE Band17) 2572.5MHz ~ 2617.5MHz (FOR LTE Band38)
HW VERSION	HW0309	
SW VERSION	000C_0_34A	
I/O PORTS	Refer to user's manual	
CABLE	USB cable: non-shielded, detachable, 1.0m Earphone cable: non-shielded, detachable, 1.5m	
ACCESSORY DEVICES	Refer to note as below	

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. This report is issued as a supplementary report to the original report FV180131W003-1. The differences compared with original report are updated HW and adding 2<sup>nd</sup> Manufacturer of components and antenna.

**List of Accessories:**

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Adapter 1	Salcomp	Salcomp (Shenzhen) Co., Ltd.	FC0202	I/P: 100-240Vac, 150mA O/P: 5Vdc, 1000mA
Adapter 2	Aohai	DONGGUAN AOHAI TECHNOLOGY CO., LTD.	AD-5WU	I/P: 100-240Vac, 150mA O/P: 5Vdc, 1000mA
Battery	SCUD	SCUD (Fujian) Electronics CO., Ltd.	HE336	Rating: 3.85Vdc, 2900mAh
Earphone 1	Nokia	FIT	WH-108	1.5m non-shielded cable w/o core
Earphone 2	Nokia	OBO	WH-108	1.5m non-shielded cable w/o core
USB Cable	Nokia	FIH	CA-190CD	1.0m non-shielded cable w/o core



BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## 1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Remark
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	PASS	Meets limits minimum passing margin is -9.59dB at 0.516000MHz.
	Radiated Emission Test (30MHz ~ 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -12.38dB at 373.38MHz
	Radiated Emission Test (Above 1GHz)	N/A	N/A

## 1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	+/-2.66dB
Radiated emissions	30MHz ~ 1GHz	+/-3.26dB
	1GHz ~ 18GHz	+/-4.48dB



BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## 1.4 DESCRIPTION OF TEST MODES

For Conducted Emission evaluation, 240Vac/60Hz & 120/60Hz had been covered during the pre-test. The worst data was found at **120Vac/60Hz** and recorded in the applied test report.

Test Mode	Test Condition
<b>Radiated emission test</b>	
1	GSM850 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx + Back camera on
2	GSM1900 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx+ Front camera on
3	WCDMA B2 Idle + Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
4	WCDMA B4 Idle + Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
5	WCDMA B5 Idle + Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
6	LTE B2 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx + FM RX
7	LTE B4 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
8	LTE B5 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
9	LTE B7 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ MPEG4
10	LTE B12 Idle+ Adapter 2 + Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
11	LTE B17 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
12	LTE B38 Idle+ USB Link+ Earphone 2 + BT Idle+ WIFI Idle(5G)+ Glonass Rx
<b>Conducted emission test</b>	
1	GSM850 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx + Back camera on
2	GSM1900 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx+ Front camera on
3	WCDMA B2 Idle + Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
4	WCDMA B4 Idle + Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
5	WCDMA B5 Idle + Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
6	LTE B2 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx + FM RX
7	LTE B4 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
8	LTE B5 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
9	LTE B7 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ MPEG4
10	LTE B12 Idle+ Adapter 2 + Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx
11	LTE B17 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx
12	LTE B38 Idle+ USB Link+ Earphone 2 + BT Idle+ WIFI Idle(5G)+ Glonass Rx

### NOTE:

1. For conducted emission test, test mode 1 was the worst case and only this mode was presented in



**BUREAU  
VERITAS**

**Test Report No.: FV180604W006-1**

this report.

2. For radiated emission test, test mode 12 was the worst case and only this mode was presented in this report

## 1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

### FOR EMISSION TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Wireless AP	ABOCOM	WR224GR	060500749P	N/A
2	Notebook	DELL	E6420	9H12FS1	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	DC Line: Unshielded, Undetachable, 2.0m




BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## 1.6 CONFIGURATION OF SYSTEM UNDER TEST

### Test configuration 1







BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## Test configuration 2





BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## 2 EMISSION TEST

### 2.1 CONDUCTED EMISSION MEASUREMENT

#### 2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:** 1. The lower limit shall apply at the transition frequencies.  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.  
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Mar. 15,18	Mar. 14,19
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 18,17	Sep. 17,18

**NOTE:** 1. The test was performed in CE shielded room.  
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



**BUREAU  
VERITAS**

Test Report No.: FV180604W006-1

### 2.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 2.1.4 DEVIATION FROM TEST STANDARD

No deviation.



## 2.1.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 2.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.



BUREAU  
VERITAS

Test Report No.: FV180604W006-1


## 2.1.7 TEST RESULTS

TEST VOLTAGE	DC 5.0V From Adapter Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	23deg. C, 52RH	TESTED BY	John

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.516000	---	36.41	46.00	-9.59	L	ON	9.7
0.516000	44.29	---	56.00	-11.71	L	ON	9.7
1.192000	---	26.11	46.00	-19.89	L	ON	9.7
1.192000	36.96	---	56.00	-19.04	L	ON	9.7
1.992000	---	27.50	46.00	-18.50	L	ON	9.7
1.992000	38.11	---	56.00	-17.89	L	ON	9.7
2.672000	---	28.27	46.00	-17.73	L	ON	9.7
2.672000	38.95	---	56.00	-17.05	L	ON	9.7
5.072000	---	33.02	50.00	-16.98	L	ON	9.7
5.072000	43.16	---	60.00	-16.84	L	ON	9.7
6.196000	---	30.32	50.00	-19.68	L	ON	9.8
6.196000	39.69	---	60.00	-20.31	L	ON	9.8

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



BUREAU  
VERITAS


Test Report No.: FV180604W006-1

TEST VOLTAGE	DC 5.0V From Adapter Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	23deg. C, 52RH	TESTED BY	John

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.432000	---	34.11	47.21	-13.10	N	ON	10.1
0.432000	43.70	---	57.21	-13.51	N	ON	10.1
0.520000	---	33.81	46.00	-12.19	N	ON	10.1
0.520000	42.83	---	56.00	-13.17	N	ON	10.1
0.792000	---	31.40	46.00	-14.60	N	ON	10.0
0.792000	42.94	---	56.00	-13.06	N	ON	10.0
1.734000	---	30.90	46.00	-15.10	N	ON	9.8
1.734000	41.74	---	56.00	-14.26	N	ON	9.8
3.064000	---	34.69	46.00	-11.31	N	ON	9.8
3.064000	43.60	---	56.00	-12.40	N	ON	9.8
16.432000	---	37.40	50.00	-12.60	N	ON	10.0
16.432000	45.84	---	60.00	-14.16	N	ON	10.0

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## 2.2 RADIATED EMISSION MEASUREMENT

### 2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

#### TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dB $\mu$ V/m)				
Frequencies (MHz)	FCC 15B/ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5		
88-216	43.5	33.1	40	30
216-230				
230-960	46.4	35.6		
960-1000	49.5	43.5	47	37
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined
3000+	Peak: 69.5	Peak: 63.5	Not defined	Not defined

Radiated Emissions Limits at 3 meters (dB $\mu$ V/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40		
88-216	54	43.5	50.5	40.5
216-230				
230-960	56.9	46		
960-1000	60	54	57.5	47.5
1000-3000			Avg: 56 Peak: 76	Avg: 50 Peak: 70
3000+	Avg: 60 Peak: 80	Avg: 54 Peak: 74	Avg: 60 Peak: 80	Avg: 54 Peak: 74

BUREAU  
VERITAS

Test Report No.: FV180604W006-1

**Frequency Range (For unintentional radiators)**

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40GHz, whichever is lower

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>u</sub>V/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. QP detector shall be applied if not specified.

**2.2.2 TEST INSTRUMENTS****Frequency range below 1GHz**

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Apr. 21,18	Apr. 20,19
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 16,18	Mar. 15,19
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18

**Frequency range above 1GHz**

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Apr. 21,18	Apr. 20,19
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 16,18	Mar. 15,19
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18

**NOTE:**

1. The test was performed in 3m chamber.
2. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRRG/CHINA and NIM/CHINA.
3. The FCC Site Registration No. is 525120.



BUREAU  
VERITAS

Test Report No.: FV180604W006-1

## 2.2.3 TEST PROCEDURE

### <Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

#### NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Emission level – Limit value.



BUREAU  
VERITAS

Test Report No.: FV180604W006-1

### <Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

#### NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 10Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
5. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
6. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier)
7. Margin value = Emission level – Limit value.


### 2.2.4 DEVIATION FROM TEST STANDARD

No deviation.




## 2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



\* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

## 2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.

BUREAU  
VERITAS

Test Report No.: FV180604W006-1


## 2.2.7 TEST RESULTS

TEST VOLTAGE	DC 5.0V From Adapter Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Star Le		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
31.94	27.27	48.22	40	-12.73	15.91	0.8	37.66	100	120	QP
71.71	15.41	43.87	40	-24.59	7.67	1.2	37.33	100	260	QP
199.75	24.49	48.66	43.5	-19.01	10.59	1.79	36.55	100	20	QP
254.07	25.43	47.25	46	-20.57	12.79	2.05	36.66	100	180	QP
328.76	33.09	52.78	46	-12.91	14.75	2.33	36.77	100	100	QP
373.38	33.62	51.7	46	-12.38	16.22	2.51	36.81	100	170	QP

**REMARKS:**

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above equipment noise floor are reported.



BUREAU  
VERITAS


Test Report No.: FV180604W006-1

TEST VOLTAGE	DC 5.0V From Adapter Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Star Le		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
37.76	16.08	40.25	40	-23.92	12.49	0.89	37.55	100	20	QP
73.65	18.48	46.86	40	-21.52	7.75	1.2	37.33	100	30	QP
200.72	24.55	48.68	43.5	-18.95	10.63	1.79	36.55	100	190	QP
369.5	32.69	50.92	46	-13.31	16.09	2.49	36.81	100	100	QP
427.7	31.54	48.35	46	-14.46	17.35	2.72	36.88	100	160	QP
596.48	31.72	46	46	-14.28	19.93	3.15	37.36	100	50	QP

**REMARKS:**

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above equipment noise floor are reported.





**BUREAU  
VERITAS**

Test Report No.: FV180604W006-1

### **3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications were made to the EUT by the lab during the test.

**---END---**