



BUREAU  
VERITAS

Test Report No.: RF180411W007-12



# FCC TEST REPORT

## (PART 24)

Applicant:	FIH International Co., Ltd.
Address:	No.18, Tongji zhonglu, Beijing Economic & Technological Development Area

Manufacturer or Supplier:	HMD Global Oy
Address:	Karaportti 2 02610 Espoo FINLAND
Product:	GSM/WCDMA/LTE Mobile Phone
Brand Name:	Nokia
Model Name:	TA-1057
FCC ID:	2AJOTTA-1057
Date of tests:	Mar. 23, 2018 ~ Apr. 28, 2018

The tests have been carried out according to the requirements of the following standard:

FCC PART 24, Subpart E    ANSI C63.26-2015  
 ANSI/TIA/EIA-603-D    ANSI/TIA/EIA-603-E

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Yuqiang Yin Engineer / Mobile Department	Approved by Sam Tung Manager / Mobile Department

Date: May 02, 2018      Date: May 02, 2018

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	4
1 SUMMARY OF TEST RESULTS .....	5
1.1 MEASUREMENT UNCERTAINTY .....	5
1.2 TEST SITE AND INSTRUMENTS .....	6
2 GENERAL INFORMATION.....	7
2.1 GENERAL DESCRIPTION OF EUT .....	7
2.2 CONFIGURATION OF SYSTEM UNDER TEST .....	8
2.3 DESCRIPTION OF SUPPORT UNITS.....	9
2.4 TEST ITEM AND TEST CONFIGURATION.....	10
2.5 EUT OPERATING CONDITIONS.....	11
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	11
3 TEST TYPES AND RESULTS .....	12
3.1 OUTPUT POWER MEASUREMENT .....	12
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT.....	12
3.1.2 TEST PROCEDURES .....	12
3.1.3 TEST SETUP .....	13
3.1.4 TEST RESULTS .....	14
3.2 FREQUENCY STABILITY MEASUREMENT .....	16
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT.....	16
3.2.2 TEST PROCEDURE .....	16
3.2.3 TEST SETUP .....	16
3.2.4 TEST RESULTS .....	17
3.3 OCCUPIED BANDWIDTH MEASUREMENT .....	19
3.3.1 TEST PROCEDURES .....	19
3.3.2 TEST SETUP .....	19
3.3.3 TEST RESULTS .....	20
3.4 BAND EDGE MEASUREMENT .....	22
3.4.1 LIMITS OF BAND EDGE MEASUREMENT .....	22
3.4.2 TEST SETUP .....	22
3.4.3 TEST PROCEDURES .....	22
3.4.4 TEST RESULTS .....	23
3.5 CONDUCTED SPURIOUS EMISSIONS .....	24
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT .....	24
3.5.2 TEST PROCEDURE .....	24
3.5.3 TEST SETUP .....	24
3.5.4 TEST RESULTS .....	25
3.6 RADIATED EMISSION MEASUREMENT .....	27
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	27
3.6.2 TEST PROCEDURES .....	27
3.6.3 DEVIATION FROM TEST STANDARD .....	27
3.6.4 TEST SETUP .....	28
3.6.5 TEST RESULTS .....	30
3.7 PEAK TO AVERAGE RATIO .....	44
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT .....	44
3.7.2 TEST SETUP .....	44
3.7.3 TEST PROCEDURES .....	44
3.7.4 TEST RESULTS .....	45



**Test Report No.: RF180411W007-12**

**4 INFORMATION ON THE TESTING LABORATORIES ..... 51**

**5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE  
EUT BY THE LAB ..... 52**



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF180411W007-5	Original release	May 02, 2018
RF180411W007-12	Based on the original report RF180411W007-5 changing model name & FCC ID and disable one SIM card.	May 02, 2018



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 24.232	Equivalent Isotropic Radiated Power	PASS	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	PASS	Meet the requirement of limit.
24.232(d)	Peak to average ratio	PASS	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -18.21dB at 46.490MHz.

### 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.68dB
	30MHz ~ 1GHz	3.26dB
	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## 1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 16,18	Mar. 15,19
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510332	Jun. 28,17	Jun. 27,18
Bilog Antenna 1	ETS-LINDGREN	3143B	00161964	Nov. 26,16	Nov. 25,18
Bilog Antenna 2	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
Horn Antenna 1	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
Horn Antenna 2	ETS-LINDGREN	3117	00168692	Nov. 26,16	Nov. 25,18
Loop antenna	Daze	ZN30900A	0708	Nov. 20,17	Nov. 19,18
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40 -K-SG/QMS-00 361	15433	Dec. 16,16	Dec. 15,18
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Mar. 02,18	Mar. 01,19
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 24,17	Jul. 23,18
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May 06,17	May 05,18
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SM A	1505	Jul. 24,17	Jul. 23,18
Power Meter	Anritsu	ML2495A	1506002	Mar. 02,18	Mar. 01,19
Power Sensor	Anritsu	MA2411B	1339352	Mar. 16,18	Mar. 15,19
Humid & Temp Programmable Tester	Juyi	ITH-120-45-CP -AR	IAA1504-001	Jul. 18,17	Jul. 17,18
MXG Analog Microwave Signal Generator	KEYSIGHT	N5183A	MY50143024	Mar. 13,18	Mar. 12,19

**NOTE:**

1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRRG/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 525120.



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	GSM/WCDMA/LTE Mobile Phone	
BRAND NAME	Nokia	
MODEL NAME	TA-1057	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.9Vdc (Li-ion, battery)	
MODULATION TYPE	<b>GSM, GPRS:</b> GMSK <b>EDGE:</b> GMSK, 8PSK	
FREQUENCY RANGE	GSM, GPRS, EDGE	1850.2MHz ~ 1909.8MHz
MAX. EIRP POWER	GSM	1239mW
	EDGE	519mW
EMISSION DESIGNATOR	GSM	247KGXW
	EDGE	247KG7W
ANTENNA TYPE	Fixed Internal Antenna with 3.17dBi gain	
HW VERSION	HW 0341	
SW VERSION	000C_0_34A	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable: non-shielded, detachable, 1.0m Earphone cable: non-shielded, detachable, 1.5m	

#### NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

#### List of Accessories:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Adapter 1	Salcomp	Salcomp (Shenzhen) Co., Ltd.	FC0202	I/P: 100-240Vac, 150mA O/P: 5Vdc, 1000mA
Adapter 2	Aohai	DONGGUAN AOHAI TECHNOLOGY CO., LTD.	AD-5WU	I/P: 100-240Vac, 150mA O/P: 5Vdc, 1000mA
Battery	SCUD	SCUD (Fujian) Electronics CO., Ltd.	HE336	Rating: 3.85Vdc, 2900mAh
Earphone 1	Nokia	FIT	WH-108	1.5m non-shielded cable w/o core
Earphone 2	Nokia	OBO	WH-108	1.5m non-shielded cable w/o core
USB Cable	Nokia	FIH	CA-190CD	1.0m non-shielded cable w/o core




BUREAU  
VERITAS


Test Report No.: RF180411W007-12

## 2.2 CONFIGURATION OF SYSTEM UNDER TEST

### FOR RADIATION EMISSION TEST



### FOR CONDUCTED & E.I.R.P. TEST





BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## 2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

**NOTE:**

1. All power cords of the above support units are non shielded (1.8m).



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## 2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter + USB Cable + Earphone with GSM link
B	EUT + Battery with GSM link

### GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	EIRP	512 to 810	512, 661, 810	GSM, EDGE
B	FREQUENCY STABILITY	512 to 810	512, 810	GSM, EDGE
B	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM, EDGE
B	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM, EDGE
B	BAND EDGE	512 to 810	512, 810	GSM, EDGE
B	CONDUCED EMISSION	512 to 810	512, 661, 810	GSM, EDGE
A	RADIATED EMISSION	512 to 810	512, 661, 810	GSM, EDGE

### TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	25deg. C, 57%RH	3.9Vdc from Battery	Star Le
FREQUENCY STABILITY	23deg. C, 61%RH	DC 3.7V/3.9V/4.0V	Wenliang Wu
OCCUPIED BANDWIDTH	23deg. C, 61%RH	3.9Vdc from Battery	Wenliang Wu
PEAK TO AVERAGE RATIO	23deg. C, 61%RH	3.9Vdc from Battery	Wenliang Wu
BAND EDGE	23deg. C, 61%RH	3.9Vdc from Battery	Wenliang Wu
CONDUCED EMISSION	23deg. C, 61%RH	3.9Vdc from Battery	Wenliang Wu
RADIATED EMISSION	23deg. C, 70%RH	5Vdc from adapter	Star Le



**BUREAU  
VERITAS**

Test Report No.: RF180411W007-12

## 2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

## 2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 24**

**KDB 971168 D01 Power Meas License Digital Systems v03**

**ANSI/TIA/EIA-603-D**

**ANSI/TIA/EIA-603-E**

**ANSI C63.26-2015**

**NOTE:** All test items have been performed and recorded as per the above standards.



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3 TEST TYPES AND RESULTS

#### 3.1 OUTPUT POWER MEASUREMENT

##### 3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

##### 3.1.2 TEST PROCEDURES

###### EIRP MEASUREMENT:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM & GPRS.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
- d. 
$$\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$$

###### CONDUCTED POWER MEASUREMENT:


The EUT was set up for the maximum power with GSM, GPRS & EDGE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.




### 3.1.3 TEST SETUP

#### EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>




<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### CONDUCTED POWER MEASUREMENT:





BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3.1.4 TEST RESULTS

#### CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900		
Channel	512	661	810
<b>Frequency (MHz)</b>	<b>1850.2</b>	<b>1880.0</b>	<b>1909.8</b>
<b>GSM</b>	<b>29.69</b>	29.59	29.41
<b>GPRS 8</b>	29.68	29.58	29.40
<b>GPRS 10</b>	27.69	27.59	27.41
<b>GPRS 11</b>	24.75	24.65	24.47
<b>GPRS 12</b>	23.20	23.10	22.92
<b>EDGE 8 (MCS9)</b>	24.91	24.81	24.63
<b>EDGE 10 (MCS9)</b>	21.98	21.88	21.70
<b>EDGE 11 (MCS9)</b>	20.30	20.20	20.02
<b>EDGE 12 (MCS9)</b>	18.71	18.61	18.43



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

**EIRP POWER (dBm)**  
**GSM**

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
512	1850.2	-13.55	43.83	30.28	1066.60	H
661	1880.0	-12.83	43.57	30.74	1185.77	H
810	1909.8	-13.64	44.57	30.93	<b>1238.80</b>	H
512	1850.2	-26.88	46.39	19.51	89.33	V
661	1880.0	-26.82	47.10	20.28	106.61	V
810	1909.8	-25.45	45.98	20.53	112.88	V

**REMARKS:** 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).  
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

**EDGE**

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
512	1850.2	-16.74	43.83	27.09	511.68	H
661	1880.0	-16.55	43.57	27.02	503.50	H
810	1909.8	-17.42	44.57	27.15	<b>518.80</b>	H
512	1850.2	-28.45	46.39	17.94	62.20	V
661	1880.0	-27.93	47.10	19.17	82.53	V
810	1909.8	-27.65	45.98	18.32	67.97	V

**REMARKS:** 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).  
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss



### 3.2 FREQUENCY STABILITY MEASUREMENT

#### 3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

#### 3.2.2 TEST PROCEDURE

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

#### 3.2.3 TEST SETUP





BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3.2.4 TEST RESULTS

**GSM1900**

#### FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
3.9	0.0008	0.0010	2.5
3.7	-0.0008	-0.0010	2.5
4.0	0.0007	0.0009	2.5

**NOTE:** The applicant defined the normal working voltage of the battery is from 3.7Vdc to 4.0Vdc.

#### FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0057	-0.0055	2.5
-20	-0.0052	-0.0050	2.5
-10	-0.0048	-0.0046	2.5
0	-0.0042	-0.0040	2.5
10	-0.0035	-0.0033	2.5
20	-0.0034	-0.0032	2.5
30	-0.0026	-0.0024	2.5
40	-0.0022	-0.0020	2.5
50	-0.0004	-0.0002	2.5
60	-0.0003	-0.0002	2.5



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

EDGE 1900

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
3.9	0.0009	0.0009	2.5
3.7	-0.0008	-0.0010	2.5
4.0	0.0008	0.0009	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.7Vdc to 4.0Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0051	-0.0047	2.5
-20	-0.0050	-0.0047	2.5
-10	-0.0049	-0.0046	2.5
0	-0.0044	-0.0041	2.5
10	-0.0040	-0.0037	2.5
20	-0.0030	-0.0028	2.5
30	-0.0025	-0.0023	2.5
40	-0.0015	-0.0014	2.5
50	0.0004	0.0004	2.5
60	0.0007	0.0007	2.5




### 3.3 OCCUPIED BANDWIDTH MEASUREMENT

#### 3.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

#### 3.3.2 TEST SETUP






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3.3.3 TEST RESULTS

Channel	Frequency (MHz)	99% Occupied bandwidth (kHz)	Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)
		GSM			EDGE
512	1850.2	247.00	512	1850.2	242.00
661	1880.0	244.00	661	1880.0	244.00
810	1909.8	245.00	810	1909.8	247.00






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

Channel	Frequency (MHz)	26dB bandwidth (kHz)	CHANNEL	FREQUENCY (MHz)	26dB bandwidth (MHz)
		GSM			EDGE
512	1850.2	320.61	512	1850.2	318.62
661	1880.0	321.75	661	1880.0	317.58
810	1909.8	321.01	810	1909.8	316.52






### 3.4 BAND EDGE MEASUREMENT

#### 3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

#### 3.4.2 TEST SETUP



#### 3.4.3 TEST PROCEDURES


- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1.5 MHz. RBW of the spectrum is 10kHz and VBW of the spectrum is 30kHz (GSM/GPRS/ EDGE).
- c. Record the max trace plot into the test report.



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3.4.4 TEST RESULTS





### 3.5 CONDUCTED SPURIOUS EMISSIONS


#### 3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to  $-13\text{dBm}$ .

#### 3.5.2 3.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 9 kHz to 19.1GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

#### 3.5.3 TEST SETUP






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3.5.4 TEST RESULTS






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## EDGE


### CHANNEL 512

FREQUENCY RANGE : 30MHz~19.1GHz




### CHANNEL 661

FREQUENCY RANGE : 30MHz~19.1GHz



### CHANNEL 810

FREQUENCY RANGE : 30MHz~19.1GHz





BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3.6 RADIATED EMISSION MEASUREMENT

#### 3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to  $-13\text{dBm}$ .

#### 3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c.  $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$


**NOTE:** The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

#### 3.6.3 DEVIATION FROM TEST STANDARD


No deviation

## 3.6.4 TEST SETUP

&lt;Below 30MHz&gt;




&lt; Frequency Range 30MHz~1GHz &gt;





< Frequency Range above 1GHz >



For the actual test configuration, please refer to the attached file (Test Setup Photo).



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3.6.5 TEST RESULTS


#### BELOW 1GHz WORST-CASE DATA

**9 KHz – 30 MHz data:** the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

#### 30 MHz – 1GHz data:

##### PCS 1900:

MODE	TX channel 661	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			




Freq	Level	Read	Limit	Over	Factor	Remark	Pol/Phase
		MHz	dBm	Line			
1 PP	30.000	-33.33	-52.67	-13.00	-20.33	19.34 Peak	Horizontal
2	46.490	-40.27	-46.61	-13.00	-27.27	6.34 Peak	Horizontal
3	100.810	-46.57	-35.25	-13.00	-33.57	-11.32 Peak	Horizontal
4	165.800	-60.15	-41.89	-13.00	-47.15	-18.26 Peak	Horizontal
5	186.170	-51.90	-34.30	-13.00	-38.90	-17.60 Peak	Horizontal
6	285.110	-61.11	-46.57	-13.00	-48.11	-14.54 Peak	Horizontal



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

MODE	TX channel 661	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



Freq	Level	Read	Limit	Over	Factor	Remark	Pol/Phase
		Level	Line	Limit			
MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	46.490	-31.21	-27.57	-13.00	-18.21	-3.64 Peak	Vertical
2	97.900	-43.89	-33.25	-13.00	-30.89	-10.64 Peak	Vertical
3	137.670	-54.77	-39.95	-13.00	-41.77	-14.82 Peak	Vertical
4	164.830	-50.77	-36.01	-13.00	-37.77	-14.76 Peak	Vertical
5	186.170	-47.57	-35.18	-13.00	-34.57	-12.39 Peak	Vertical
6	261.830	-58.56	-47.09	-13.00	-45.56	-11.47 Peak	Vertical



BUREAU  
VERITAS

Test Report No.: RF180411W007-12


### ABOVE 1GHz DATA

**Note:** For higher frequency, the emission is too low to be detected.

**PCS 1900:**

**CH 512**

<b>MODE</b>	TX channel 512	<b>FREQUENCY RANGE</b>	Above 1000MHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH	<b>INPUT POWER</b>	DC 5V from adapter
<b>TESTED BY</b>	Star Le		
<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>			




	Freq	Read Level	Limit Level	Over Line	Over Limit	Over Factor	Over Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-42.50	-45.61	-13.00	-29.50	3.11	Peak	Horizontal
2 PP	5558.000	-42.23	-51.26	-13.00	-29.23	9.03	Peak	Horizontal



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



Freq	Level	Read	Limit	Over	Remark	Pol/Phase
		Line	Limit Factor	Factor		
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 PP 3698.000	-41.21	-44.78	-13.00	-28.21	3.57 Peak	Vertical
2 5558.000	-42.16	-50.25	-13.00	-29.16	8.09 Peak	Vertical




BUREAU  
VERITAS

Test Report No.: RF180411W007-12

CH 661

MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			




Freq	Level	Read	Limit	Over	Remark	Pol/Phase
		Level	Line	Limit Factor		
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	3755.000	-49.20	-52.59	-13.00	-36.20	3.39 Peak
2	PP 5640.000	-44.72	-53.84	-13.00	-31.72	9.12 Peak



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



Freq	Level	Read	Limit	Over	Remark	Pol/Phase
		Level	Line	Limit Factor		
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	3755.000	-50.76	-54.15	-13.00	-37.76	3.39 Peak
2	PP 5640.000	-44.77	-53.89	-13.00	-31.77	9.12 Peak




BUREAU  
VERITAS

Test Report No.: RF180411W007-12

CH 810

MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			




	Freq	Read Level	Limit Level	Over Line	Over Limit	Over Factor	Over Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-45.04	-48.15	-13.00	-32.04	3.11	Peak	Horizontal
2	PP 5558.000	-42.13	-51.16	-13.00	-29.13	9.03	Peak	Horizontal



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	Freq	Read Level	Limit Level	Over Line	Limit Factor	Over Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-43.66	-47.23	-13.00	-30.66	3.57	Peak	Vertical
2	PP 5558.000	-42.52	-50.61	-13.00	-29.52	8.09	Peak	Vertical




BUREAU  
VERITAS

Test Report No.: RF180411W007-12

EDGE 1900:

CH 512

MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			




	Freq	Read Level	Limit Level	Over Line	Limit Factor	Over Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-55.34	-58.45	-13.00	-42.34	3.11	Peak	Horizontal
2	PP 5558.000	-48.59	-57.62	-13.00	-35.59	9.03	Peak	Horizontal



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	Freq	Read Level	Limit Level	Over Line	Over Limit	Over Factor	Over Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-54.56	-58.13	-13.00	-41.56	3.57	Peak	Vertical
2	PP 5558.000	-47.72	-55.81	-13.00	-34.72	8.09	Peak	Vertical




BUREAU  
VERITAS

Test Report No.: RF180411W007-12

CH 661

MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			




Freq	Level	Read	Limit	Over	Remark	Pol/Phase
		Level	Line	Limit Factor		
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	3755.000	-52.39	-55.78	-13.00	-39.39	3.39 Peak
2	PP 5640.000	-47.47	-56.59	-13.00	-34.47	9.12 Peak



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



Freq	Level	Read	Limit	Over	Factor	Remark	Pol/Phase
		Level	Line	Limit			
MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-49.76	-53.15	-13.00	-36.76	3.39 Peak	Vertical
2	PP 5640.000	-43.77	-52.89	-13.00	-30.77	9.12 Peak	Vertical




BUREAU  
VERITAS

Test Report No.: RF180411W007-12

CH 810

MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			




Freq	Level	Read	Limit	Over	Factor	Remark	Pol/Phase
		Level	Line	Limit			
MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3812.000	-53.00	-56.66	-13.00	-40.00	3.66 Peak	Horizontal
2	PP 5721.000	-49.14	-58.35	-13.00	-36.14	9.21 Peak	Horizontal



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



Freq	Level	Read	Limit	Over	Remark	Pol/Phase
		Level	Line	Limit Factor		
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	3812.000	-53.42	-57.56	-13.00	-40.42	4.14 Peak
2	PP 5721.000	-50.36	-58.78	-13.00	-37.36	8.42 Peak




### 3.7 PEAK TO AVERAGE RATIO

#### 3.7.1 LIMITS OF peak to average ratio MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

#### 3.7.2 TEST SETUP



#### 3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.




BUREAU  
VERITAS

Test Report No.: RF180411W007-12

### 3.7.4 TEST RESULTS

#### GSM

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
512	1850.2	2.67






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
661	1880	2.68






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
810	1909.8	2.66






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## EDGE

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
512	1850.2	5.58






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
661	1880	5.60






BUREAU  
VERITAS

Test Report No.: RF180411W007-12

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
810	1909.8	5.56





BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## 4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Shenzhen EMC/RF Lab:**

Tel: +86-755-88696566

Fax: +86-755-88696577

**Email:** [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



BUREAU  
VERITAS

Test Report No.: RF180411W007-12

## 5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---