



## **VARIANT EMC TEST REPORT**

Applicant:	FIH International Co., Ltd.
Address:	No.18, Tongji zhonglu, Beijing Economic & Technological Development Area

Manufacturer or Supplier	HMD Global Oy
Address	Karaportti 2 02610 Espoo FINLAND
Product	GSM/WCDMA/LTE Mobile Phone
Brand Name	Nokia
Model Name	TA-1074
FCC ID	2AJOTTA-1074
Date of tests	May 23, 2018 ~ Jun. 22, 2018

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

**ANSI C63.4:2014** 

## CONCLUSION: The submitted sample was found to $\underline{\text{COMPLY}}$ with the test requirement

Prepared by Alex Chen Engineer / Mobile Department	Approved by Sam Tung Manager / Mobile Department	
Roger	rwb	
Date: Jul. 10, 2018	Date: Jul. 10, 2018	

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Tel: +86 755 8869 6566 Fax: +86 755 8869 6577

Email: customerservice.sz@cn.bureauveritas.com



# **TABLE OF CONTENTS**

RELEASE	CONTROL RECORD	3
1 GENE	RAL INFORMATION	4
1.1 G	ENERAL DESCRIPTION OF EUT	4
	UMMARY OF TEST RESULTS	
1.3 M	EASUREMENT UNCERTAINTY	6
	ESCRIPTION OF TEST MODES	
	ESCRIPTION OF SUPPORT UNITS	
1.6 C	ONFIGURATION OF SYSTEM UNDER TEST	9
2 EMISS	SION TEST	11
2.1 CO	NDUCTED EMISSION MEASUREMENT	11
2.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	11
2.1.2	TEST INSTRUMENTS	
2.1.3	TEST PROCEDURES	12
2.1.4	DEVIATION FROM TEST STANDARD	
2.1.5	TEST SETUP	13
2.1.6	EUT OPERATING CONDITIONS	13
2.1.7	TEST RESULTS	
2.2 R	ADIATED EMISSION MEASUREMENT	
2.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	16
2.2.2	TEST INSTRUMENTS	17
2.2.3	TEST PROCEDURE	
2.2.4	DEVIATION FROM TEST STANDARD	
2.2.5	TEST SETUP	
2.2.6	EUT OPERATING CONDITIONS	
2.2.7	TEST RESULTS	20
3 APPE	NDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO	THE EUT

Email: <u>customerservice.sz@cn.bureauveritas.com</u>



## **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FV180522W002-1	Original release	Jul. 10, 2018

Tel: +86 755 8869 6566 Fax: +86 755 8869 6577

Email: <u>customerservice.sz@cn.bureauveritas.com</u>



## 1 GENERAL INFORMATION

## 1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	GSM/WCDMA/LTE Mobile Phone		
BRAND NAME	Nokia		
MODEL NAME	TA-1074		
NOMINAL VOLTAGE	5.0Vdc (adapter or 3.9Vdc (Li-ion, ion I		
BATTERY	Brand Name: SCUD Model Name: HE336 Power Rating: DC 3.85V, 2900mAh, Li-ion		
	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM	
	BT_LE	DTS	
	Bluetooth	GFSK, π/4-DQPSK, 8DPSK	
MODULATION TYPE	GPS/ GLONASS	C/A code	
MODOLATION TITLE	FM	FSK	
	GSM/EDGE	GMSK, 8PSK	
	WCDMA	BPSK/QPSK	
	LTE	QPSK/16QAM	
	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20) 5150 ~ 5250MHz, 5250 ~ 5350MHz, 5470 ~ 5725MHz, 5725 ~ 5825MHz for 11a/n(HT20)/n(HT40)	
	Bluetooth/BT_LE	2402MHz ~ 2480MHz	
	GPS	1575.42MHz	
	GLONASS	1602MHz	
OPERATING	FM	98MHz	
FREQUENCY	GSM/EDGE	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR GSM 1900)	
	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA Band 2) 1712.4MHz ~ 1752.6MHz (FOR WCDMA Band 4) 826.4MHz ~ 846.6MHz (FOR WCDMA Band 5)	
	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 2502.5 ~ 2567.5 MHz (FOR LTE Band7)	

BV 7Layers Communications Technology (Shenzhen) Co. Ltd No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen51800, China Tel: +86 755 8869 6566 Fax: +86 755 8869 6577

Email: <a href="mailto:customerservice.sz@cn.bureauveritas.com">customerservice.sz@cn.bureauveritas.com</a>



	699.7MHz ~ 715.3MHz (FOR LTE Band12) 706.5MHz ~ 713.5MHz (FOR LTE Band17) 2572.5MHz ~ 2617.5MHz (FOR LTE Band38)			
HW VERSION	HW 0345			
SW VERSION	000C_0_34A			
I/O PORTS	Refer to user's manual			
CABLE	USB cable: non-shielded, detachable, 1.0m Earphone cable: non-shielded, detachable, 1.5m			
ACCESSORY DEVICES	Refer to note as below			

#### NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. The test data include in this report is copied from the original report FV180522W002. The differences compared with original report changing model name & FCC ID and disable one SIM card.

#### **List of Accessories:**

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Adapter 1	Salcomp	Salcomp (Shenzhen) Co., Ltd.	omp (Shenzhen) Co., Ltd. FC0202	
Adapter 2	Aohai	DONGGUAN AOHAI TECHNOLOGY CO., LTD.	AD-5WU	I/P: 100-240Vac, 150mA O/P: 5Vdc, 1000mA
Battery	SCUD (Fujian) Electronics CO., Ltd. HE336		Rating: 3.85Vdc, 2900mAh	
Earphone 1	Nokia	FIT	WH-108	1.5m non-shielded cable w/o core
Earphone 2	Nokia	ОВО	WH-108	1.5m non-shielded cable w/o core
USB Cable	Nokia	FIH	CA-190CD	1.0m non-shielded cable w/o core



#### 1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B					
Standard Section Test Item		Result	Remark		
500 D	Conducted Test	PASS	Meets limits minimum passing margin is -10.09dB at 17.928000MHz.		
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Radiated Emission Test (30MHz ~ 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -10.20dB at 390.84MHz		
	Radiated Emission Test (Above 1GHz)	N/A	N/A		

### 1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY	
Conducted emissions	150kHz ~ 30MHz	+/-2.66dB	
Dedicted emissions	30MHz ~ 1GHz	+/-3.26dB	
Radiated emissions	1GHz ~ 18GHz	+/-4.48dB	



### 1.4 DESCRIPTION OF TEST MODES

For Conducted Emission evaluation, 240Vac/60Hz & 120/60Hz had been covered during the pre-test. The worst data was found at **120Vac/60Hz** and recorded in the applied test report.

Test Mode	Test Condition				
	Radiated emission test				
1	GSM850 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx + Back camera on				
2	GSM1900 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx+ Front camera on				
3	WCDMA B2 Idle + Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx				
4	WCDMA B4 Idle + Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx				
5	WCDMA B5 Idle + Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx				
6	LTE B2 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx + FM RX				
7	LTE B4 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx				
8	LTE B5 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx				
9	LTE B7 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ MPEG4				
10	LTE B12 Idle+ Adapter 2 + Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx				
11	LTE B17 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx				
12	LTE B38 Idle+ USB Link+ Earphone 2 + BT Idle+ WIFI Idle(5G)+ Glonass Rx				
	Conducted emission test				
1	GSM850 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx + Back camera on				
2	GSM1900 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx+ Front camera on				
3	WCDMA B2 Idle + Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx				
4	WCDMA B4 Idle + Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx				
5	WCDMA B5 Idle + Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx				
6	LTE B2 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx + FM RX				
7	LTE B4 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx				
8	LTE B5 Idle+ Adapter 2+ Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx				
9	LTE B7 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx+ MPEG4				
10	LTE B12 Idle+ Adapter 2 + Earphone 2+ USB cable+ BT Idle+ WIFI Idle(5G)+ Glonass Rx				
11	LTE B17 Idle+ Adapter 1+ Earphone 1+ USB cable+ BT Idle+ WIFI Idle(2.4G)+ GPS Rx				
12	LTE B38 Idle+ USB Link+ Earphone 2 + BT Idle+ WIFI Idle(5G)+ Glonass Rx				

#### NOTE:

1. For conducted emission test, test mode 1 was the worst case and only this mode was presented in



this report.

2. For radiated emission test, test mode 12 was the worst case and only this mode was presented in this report

### 1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

#### **FOR EMISSION TESTS**

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Wireless AP	ABOCOM	WR224GR	060500749P	N/A
2	Notebook	DELL	E6420	9H12FS1	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	DC Line: Unshielded, Undetachable, 2.0m

Tel: +86 755 8869 6566 Fax: +86 755 8869 6577


Report Version 1


n51800, China Email: customerservice.sz@cn.bureauveritas.com



## 1.6 CONFIGURATION OF SYSTEM UNDER TEST


## **Test configuration 1**








## **Test configuration 2**





Tel: +86 755 8869 6566 Fax: +86 755 8869 6577

Email: <a href="mailto:customerservice.sz@cn.bureauveritas.com">customerservice.sz@cn.bureauveritas.com</a>



### **EMISSION TEST**

### **CONDUCTED EMISSION MEASUREMENT**

#### 2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)		
	Quasi-peak	Average	
0.15 ~ 0.5	66 to 56	56 to 46	
0.5 ~ 5	56	46	
5 ~ 30	60	50	

**NOTE**: 1.The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
- 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### **TEST INSTRUMENTS** 2.1.2

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Mar. 15,18	Mar. 14,19
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 18,17	Sep. 17,18

**NOTE:** 1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



## 2.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

#### 2.1.4 DEVIATION FROM TEST STANDARD


No deviation.

Tel: +86 755 8869 6566 Fax: +86 755 8869 6577

Email: customerservice.sz@cn.bureauveritas.com



## 2.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 2.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.

Report Version 1




#### 2.1.7 TEST RESULTS

TEST VOLTAGE	DC 5.0V From Adapter Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	23deg. C, 52RH	TESTED BY	John

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156000		28.54	55.67	-27.13	L	ON	9.6
0.156000	41.31		65.67	-24.36	L	ON	9.6
0.392000		17.92	48.02	-30.10	L	ON	9.7
0.392000	32.42		58.02	-25.60	L	ON	9.7
0.484000		22.68	46.27	-23.59	L	ON	9.7
0.484000	33.40		56.27	-22.87	L	ON	9.7
0.800000		16.68	46.00	-29.32	L	ON	9.7
0.800000	28.82		56.00	-27.18	L	ON	9.7
17.556000		34.23	50.00	-15.77	L	ON	9.9
17.556000	42.85		60.00	-17.15	L	ON	9.9
17.896000		33.56	50.00	-16.44	L	ON	9.9
17.896000	42.52		60.00	-17.48	L	ON	9.9

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.



Email: <u>customerservice.sz@cn.bureauveritas.com</u>




TEST VOLTAGE		Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	23deg. C, 52RH	TESTED BY	John

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154000		29.63	55.78	-26.15	N	ON	9.9
0.154000	43.41		65.78	-22.37	N	ON	9.9
0.208000		17.20	53.28	-36.08	N	ON	9.9
0.208000	30.35		63.28	-32.93	N	ON	9.9
0.404000		23.91	47.77	-23.86	N	ON	10.1
0.404000	36.68		57.77	-21.09	N	ON	10.1
4.280000		22.32	46.00	-23.68	N	ON	9.8
4.280000	30.67		56.00	-25.33	N	ON	9.8
17.516000		33.60	50.00	-16.40	N	ON	10.0
17.516000	41.53		60.00	-18.47	N	ON	10.0
17.928000		39.91	50.00	-10.09	N	ON	10.0
17.928000	47.61		60.00	-12.39	N	ON	10.0

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.



Tel: +86 755 8869 6566 Fax: +86 755 8869 6577

 $\textbf{Email:}\ \underline{\text{customerservice.sz@cn.bureauveritas.com}}$ 

#### 2.2 RADIATED EMISSION MEASUREMENT

#### 2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBµV/m)						
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B		
30-88	39	29.5				
88-216	43.5	33.1	40	30		
216-230	46.4	25.6				
230-960	40.4	35.6	47	27		
960-1000	49.5	43.5	47	37		
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined		
3000+	Peak: 69.5	Peak: 63.5	Not defined	Not defined		

Radiated Emissions Limits at 3 meters (dBμV/m)						
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B		
30-88	49.5	40				
88-216	54	43.5	50.5	40.5		
216-230	56.9	46				
230-960	50.9	40	57.5	47 E		
960-1000	60	54	57.5	47.5		
1000-3000			Avg: 56	Avg: 50		
	Avg: 60	Avg: 54	Peak: 76	Peak: 70		
3000+	Peak: 80	Peak: 74	Avg: 60	Avg: 54		
			Peak: 80	Peak: 74		

Email: customerservice.sz@cn.bureauveritas.com

**BV 7Layers Communications** 

Technology (Shenzhen) Co. Ltd



Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40GHz, whichever is lower

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- 4. QP detector shall be applied if not specified.

#### 2.2.2 TEST INSTRUMENTS

Frequency range below1GHz

respectively sample motion some						
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.	
3m Semi-anechoic	ETS-LINDGREN	0~*6~*6~	Euroshieldpn-	Apr 21 10	Apr. 20.10	
Chamber	E I S-LINDGREN	9111 6111 6111	CT0001143-1216	Apr. 21,18	Apr. 20,19	
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18	
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 16,18	Mar. 15,19	
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18	

**NOTE:** 1. The test was performed in 3m chamber.

- 2. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 3. The FCC Site Registration No. is 525120.

Page 17 of 22



#### **TEST PROCEDURE** 2.2.3

#### <Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

#### NOTE:

- 1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
- 4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) Amplifier Gain(dB) (if the raw value contains the amplifier).
- 5. Margin value = Emission level Limit value.

#### 2.2.4 DEVIATION FROM TEST STANDARD


No deviation.

**BV 7Layers Communications** 

Technology (Shenzhen) Co. Ltd



### 2.2.5 TEST SETUP



\*: depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

### 2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.




#### 2.2.7 **TEST RESULTS**

TEST VOLTAGE	DC 5.0V From Adapter Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Vicent Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
76.56	17.53	45.81	40	-22.47	7.86	1.2	37.34	100	360	QP
173.56	25.88	50.6	43.5	-17.62	10.26	1.69	36.67	100	360	QP
199.75	25.75	49.92	43.5	-17.75	10.59	1.79	36.55	100	360	QP
258.92	26.75	48.45	46	-19.25	12.9	2.07	36.67	100	360	QP
303.54	32.42	53.03	46	-13.58	13.92	2.22	36.75	100	360	QP
391.81	28.65	46.05	46	-17.35	16.83	2.59	36.82	100	360	QP

- **REMARKS:** 1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
  - 2. Negative sign (-) in the margin column signify levels below the limit.
  - 3. Frequency range scanned: 30MHz to 1000MHz.
  - 4. Only emissions significantly above equipment noise floor are reported.



Tel: +86 755 8869 6566 Fax: +86 755 8869 6577


Email: customerservice.sz@cn.bureauveritas.com



TEST VOLTAGE	DC 5.0V From Adapter Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz		
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz		
TESTED BY	Vicent Chen				

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
40.67	21.16	47.31	40	-18.84	10.42	0.93	37.5	100	35	QP
76.56	19.87	48.15	40	-20.13	7.86	1.2	37.34	100	187	QP
99.84	18.88	45.54	43.5	-24.62	9.19	1.31	37.16	100	206	QP
199.75	25.16	49.33	43.5	-18.34	10.59	1.79	36.55	100	98	QP
306.45	30.97	51.48	46	-15.03	14.01	2.24	36.76	100	302	QP
390.84	35.8	53.24	46	-10.20	16.8	2.58	36.82	100	75	QP

- REMARKS: 1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
  - 2. Negative sign (-) in the margin column signify levels below the limit.
  - 3. Frequency range scanned: 30MHz to 1000MHz.
  - 4. Only emissions significantly above equipment noise floor are reported.



Tel: +86 755 8869 6566 Fax: +86 755 8869 6577

Email: customerservice.sz@cn.bureauveritas.com



# APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING **CHANGES TO THE EUT BY THE LAB**

No any modifications were made to the EUT by the lab during the test.

---END---

Tel: +86 755 8869 6566 Fax: +86 755 8869 6577 Email: customerservice.sz@cn.bureauveritas.com

Technology (Shenzhen) Co. Ltd