

FCC Test Report

Report No.: RF180523C10-5 R1

FCC ID: 2AJOTTA-1082

Test Model: TA-1082

Received Date: May 23, 2018

Test Date: Jun. 29, 2018

Issued Date: Oct. 24, 2018

Applicant: HMD Global Oy

Address: Bertel Jungin aukio 9, 02600 Espoo, Finland

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C)

Test Location (1): No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,

R.O.C

FCC Registration /

427177 / TW0011

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: RF180523C10-5 R1 Page No. 1 / 22 Report Format Version: 6.1.1

Cancels and replaces the report no.: RF180523C10-5 dated on Jul. 05, 2018



Table of Contents

R	Release Control Record	3
1	Certificate of Conformity	4
2	2 Summary of Test Results	5
	Measurement Uncertainty Modification Record	
3	General Information	6
	3.1 General Description of EUT	7 8 10 10
4	1 Test Types and Results	
4		111112131314
	4.1 Radiated Emission and Bandedge Measurement 4.1.1 Limits of Radiated Emission and Bandedge Measurement 4.1.2 Test Instruments 4.1.3 Test Procedures 4.1.4 Deviation from Test Standard 4.1.5 Test Set Up 4.1.6 EUT Operating Conditions	11111213131415
5	4.1 Radiated Emission and Bandedge Measurement 4.1.1 Limits of Radiated Emission and Bandedge Measurement 4.1.2 Test Instruments 4.1.3 Test Procedures 4.1.4 Deviation from Test Standard 4.1.5 Test Set Up 4.1.6 EUT Operating Conditions 4.1.7 Test Results	1111121313141516



Release Control Record

Issue No.	Description	Date Issued
RF180523C10-5	Original Release	Jul. 05, 2018
RF180523C10-5 R1	Revise applicant's address	Oct. 24, 2018

Report No.: RF180523C10-5 R1 Page No. 3 / 22 Cancels and replaces the report no.: RF180523C10-5 dated on Jul. 05, 2018



1 Certificate of Conformity

Product: Smart Phone

Brand: NOKIA

Test Model: TA-1082

Sample Status: Production Unit

Applicant: HMD Global Oy

Test Date: Jun. 29, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

This report is issued as a supplementary report to BV CPS report no.: RF180523C09-5. This report shall be used by combining with its original report.

Ivonne Wu / Supervisor

Approved by : , Date: Oct. 24, 2018

Dylan Chiou / Project Engineer



2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)							
FCC Clause	Test Item	Result	Remarks				
15.207	AC Power Conducted Emission	N/A	Refer to Note				
15.205 & 209 Radiated Emissions		Pass	Meet the requirement of limit. Minimum passing margin is -12.45 dB at 2487.22 MHz.				
15.247(d) Band Edge Measurement		N/A	Refer to Note				
15.247(d) Antenna Port Emission		N/A	Refer to Note				
15.247(a)(2) 6 dB Bandwidth		N/A	Refer to Note				
Occupied Bandwidth Measurement		N/A	Refer to Note				
15.247(b) Conducted Power		N/A	Refer to Note				
15.247(e)	15.247(e) Power Spectral Density		Refer to Note				
15.203	Antenna Requirement	Pass	No antenna connector is used.				

Note: Only radiated emissions test had been performed for the addendum. Refer to original report for other test data.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
Radiated Emissions up to 1 GHZ	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
Radiated Effissions above 1 GHz	18 GHz ~ 40 GHz	1.1508 dB

2.2 Modification Record

There were no modifications required for compliance.



3 General Information

3.1 General Description of EUT

Product	Smart Phone			
Brand	NOKIA			
Test Model	TA-1082			
Status of EUT	Production Unit			
	5.0 Vdc or 9 Vdc or 12 Vdc (adapter)			
Power Supply Rating	5.0 Vdc (host equipment)			
	3.85 Vdc (Li-ion battery)			
Modulation Type	GFSK			
Transfer Rate	LE 4.0: 1 Mbps			
Transfer Rate	LE 5.0: 2 Mbps			
Operating Frequency	2402 ~ 2480 MHz			
Number of Channel	40			
Antenna Type	PIFA antenna with -1.5 dBi gain			
Antenna Connector	N/A			
Accessory Device	Refer to Note as below			
Data Cable Supplied	Refer to Note as below			

Note:

1. This report is issued as a supplementary report to BV CPS report no.: RF180523C09-5. The difference is listed as below. Only radiated emission test was verified in this report.

Report No.	FCC ID	Model	Difference
RF180523C09-5	2AJOTTA-1087	TA-1087	Dual SIM
RF180523C10-5	2AJOTTA-1082	TA-1082	Single SIM
* The models have	the same layout, circu	uit, and components,	but different SIM tray.

- 2. The EUT's accessories list refers to Ext. Pho.
- 3. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or User's Manual.



3.2 Description of Test Modes

40 channels are provided to this EUT:

Channel	Freq. (MHz)						
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



3.2.1 Test Mode Applicability and Tested Channel Detail

<LE 4.0>

EUT Configure	Applic	able To	Description
Mode	RE≥1G	RE<1G	Description
-	V	√	-

Where

RE≥1G: Radiated Emission above 1 GHz

RE<1G: Radiated Emission below 1 GHz

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Note: "-"means no effect.

Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	1

Radiated Emission Test (Below 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode Available Channel		Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	1

Report No.: RF180523C10-5 R1 Page No. 8 / 22 Report Format Version: 6.1.1

Cancels and replaces the report no.: RF180523C10-5 dated on Jul. 05, 2018



<LE 5.0>

EUT Configure		Applic	able To		Description
Mode	RE≥1G	RE<1G	PLC	APCM	Description
-	V	V	V	V	-

Where RE≥1G: Radiated Emission above 1 GHz RE<1G: Radiated Emission below 1 GHz

PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Note: "-"means no effect.

Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode Available Channel		Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	2

Radiated Emission Test (Below 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	2

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode Available Channel		Tested Channel	Modulation Type	Data Rate (Mbps)
-	- 0 to 39		GFSK	2

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao

Report No.: RF180523C10-5 R1 Page No. 9 / 22 Report Format Version: 6.1.1


Cancels and replaces the report no.: RF180523C10-5 dated on Jul. 05, 2018



3.3 **Description of Support Units**

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 Configuration of System under Test



General Description of Applied Standards 3.4

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247) KDB 558074 D01 DTS Meas Guidance v04

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Report No.: RF180523C10-5 R1 Page No. 10 / 22 Report Format Version: 6.1.1



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Report No.: RF180523C10-5 R1 Page No. 11 / 22 Report Format Version: 6.1.1



4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Jul. 05, 2017	Jul. 04, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
Double Ridge Guide Horn Antenna EMCO	3115	5619	Nov. 30, 2017	Nov. 29, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 06, 2017	Dec. 05, 2018
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 07, 2017	Jul. 06, 2018
Loop Antenna	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
Preamplifier Agilent	8447D	2944A10628	Oct. 13, 2018	Oct. 12, 2019
Preamplifier Agilent	8449B	3008A01962	Oct. 13, 2018	Oct. 12, 2019
RF signal cable ETS-LINDGREN	5D-FB	Cable-RF1-01(RF C-SMS-100-SMS -120+MY13379/4	Jun. 20, 2018	Jun. 19, 2019
RF signal cable ETS-LINDGREN	8D-FB	Cable-RF1-02(RF C-SMS-100-NMS -120+8120_5140 _2911)	Jun. 20, 2018	Jun. 19, 2019
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HsinTien Chamber 1.
- 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The IC Site Registration No. is IC7450I-1.



4.1.3 Test Procedures

For Radiated Emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

For Radiated Emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz. (RBW = 1 MHz, VBW = 10 kHz)
- 4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.


Report No.: RF180523C10-5 R1 Page No. 13 / 22 Report Format Version: 6.1.1

Cancels and replaces the report no.: RF180523C10-5 dated on Jul. 05, 2018




4.1.5 Test Set Up

<Radiated Emission below 30 MHz>




<Radiated Emission 30 MHz to 1 GHz>





<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.



4.1.7 Test Results

Above 1 GHz Data:

<LE 4.0>

EUT Test Condition		Measurement Detail		
Channel	Channel 39	Frequency Range	1 GHz ~ 25 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao	

	Antennal Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	93.25	91.29			31.88	5.5	35.42	160	300	Average
2480	94.11	92.15			31.88	5.5	35.42	160	300	Peak
2486.48	41.33	39.34	54	-12.67	31.88	5.53	35.42	160	300	Average
2486.48	51.99	50	74	-22.01	31.88	5.53	35.42	160	300	Peak
4960	40	31.73	54	-14	33.99	8.29	34.01	145	240	Average
4960	47.25	38.98	74	-26.75	33.99	8.29	34.01	145	240	Peak
		А	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	84.19	82.23			31.88	5.5	35.42	102	321	Average
2480	85.22	83.26			31.88	5.5	35.42	102	321	Peak
2490	41.44	39.43	54	-12.56	31.9	5.53	35.42	102	321	Average
2490	52.2	50.19	74	-21.8	31.9	5.53	35.42	102	321	Peak
4960	39.95	31.68	54	-14.05	33.99	8.29	34.01	111	247	Average
4960	47.2	38.93	74	-26.8	33.99	8.29	34.01	111	247	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2480 MHz: Fundamental frequency.



Report Format Version: 6.1.1

<LE 5.0>

EUT Test Condition		Measurement Detail		
Channel	Channel 39	Frequency Range	1 GHz ~ 25 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao	

Automort Bolovito O Toot Biotomore Heritagnital et O										
Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	91	89.04			31.88	5.5	35.42	110	260	Average
2480	93.03	91.07			31.88	5.5	35.42	110	260	Peak
2488	41.44	39.43	54	-12.56	31.9	5.53	35.42	110	260	Average
2488	49.66	47.65	74	-24.34	31.9	5.53	35.42	110	260	Peak
4960	39.8	31.53	54	-14.2	33.99	8.29	34.01	102	14	Average
4960	47	38.73	74	-27	33.99	8.29	34.01	102	14	Peak
		А	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	82.77	80.81			31.88	5.5	35.42	102	321	Average
2480	84	82.04			31.88	5.5	35.42	102	321	Peak
2487.22	41.55	39.56	54	-12.45	31.88	5.53	35.42	102	321	Average
2487.22	49.95	47.96	74	-24.05	31.88	5.53	35.42	102	321	Peak
4960	39.62	31.35	54	-14.38	33.99	8.29	34.01	132	333	Average
4960	47.1	38.83	74	-26.9	33.99	8.29	34.01	132	333	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2480 MHz: Fundamental frequency.



9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz Worst-Case Data:

<LE 4.0>

EUT Test Condition		Measurement Detail		
Channel	Channel 39	Frequency Range	30 MHz ~ 1 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao	

	Antennal Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
91.02	14.64	34.61	43.5	-28.86	10.69	1.11	31.77	106	111	Peak
162.3	19.86	41.78	43.5	-23.64	8.82	1.52	32.26	195	7	Peak
273.81	17.12	34.62	46	-28.88	12.67	1.94	32.11	199	177	Peak
388.2	20.95	36.05	46	-25.05	14.75	2.34	32.19	147	187	Peak
668.2	19.6	29.94	46	-26.4	18.74	3.05	32.13	195	336	Peak
825.7	23.02	30.85	46	-22.98	20.71	3.38	31.92	134	230	Peak
		А	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
47.82	18.82	35.63	40	-21.18	14.51	0.9	32.22	105	125	Peak
157.98	14.12	36.2	43.5	-29.38	8.67	1.52	32.27	177	141	Peak
260.85	12.13	29.79	46	-33.87	12.5	1.94	32.1	195	260	Peak
460.3	13.66	27.5	46	-32.34	15.73	2.56	32.13	199	165	Peak
642.3	17.35	28.2	46	-28.65	18.32	2.99	32.16	127	13	Peak
806.1	20.4	28.69	46	-25.6	20.42	3.32	32.03	124	204	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin value = Emission level - Limit value



Report Format Version: 6.1.1

<LE 5.0>

EUT Test Condition		Measurement Detail		
Channel	Channel 39	Frequency Range	30 MHz ~ 1 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao	

	Antennal Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
90.48	15.18	35.32	43.5	-28.32	10.46	1.11	31.71	190	99	Peak
153.66	18.08	40.33	43.5	-25.42	8.5	1.52	32.27	185	5	Peak
269.49	15.88	33.42	46	-30.12	12.63	1.94	32.11	158	164	Peak
393.1	16.46	31.47	46	-29.54	14.85	2.34	32.2	128	298	Peak
729.1	25.81	35.16	46	-20.19	19.61	3.16	32.12	196	158	Peak
802.6	21.18	29.55	46	-24.82	20.36	3.32	32.05	117	276	Peak
		А	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
47.01	16.97	33.78	40	-23.03	14.51	0.9	32.22	169	9	Peak
159.33	14.69	36.73	43.5	-28.81	8.71	1.52	32.27	112	300	Peak
266.79	11.8	29.38	46	-34.2	12.59	1.94	32.11	127	9	Peak
475.7	14.92	28.5	46	-31.08	15.98	2.56	32.12	159	256	Peak
638.1	17.93	28.89	46	-28.07	18.27	2.93	32.16	105	247	Peak
857.2	23.2	30.39	46	-22.8	21.12	3.44	31.75	127	111	Peak

Remarks:

 Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin value = Emission level – Limit value



5 Pictures of T	est Arrangements						
Please refer to the attached file (Test Setup Photo).							

Report No.: RF180523C10-5 R1 Page No. 20 / 22 Cancels and replaces the report no.: RF180523C10-5 dated on Jul. 05, 2018



Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---

Cancels and replaces the report no.: RF180523C10-5 dated on Jul. 05, 2018



Annex A – Test Report for TA-1087 (Dual SIM)							

Report No.: RF180523C10-5 R1 Page No. 22 / 22 Cancels and replaces the report no.: RF180523C10-5 dated on Jul. 05, 2018



FCC Test Report

Report No.: RF180523C09-5 R1

FCC ID: 2AJOTTA-1087

Test Model: TA-1087

Received Date: May 23, 2018

Test Date: Jun. 05, 2018 ~ Jun. 14, 2018

Issued Date: Oct. 24, 2018

Applicant: HMD Global Oy

Address: Bertel Jungin aukio 9, 02600 Espoo, Finland

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C)

Test Location (1): No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,

R.O.C

FCC Registration /

427177 / TW0011

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: RF180523C09-5 R1 Page No. 1 / 49 Report Format Version: 6.1.1 Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



Table of Contents

Re	Release Control Record4					
1	Cert	tificate of Conformity	5			
2	Sun	nmary of Test Results	6			
	2.1	Measurement Uncertainty	6			
	2.2	Modification Record	6			
3	Gen	neral Information	7			
	3.1	General Description of EUT	. 7			
		Description of Test Modes	8			
		3.2.1 Test Mode Applicability and Tested Channel Detail	9			
		Duty Cycle of Test Signal				
	3.4	Description of Support Units				
	2.5	3.4.1 Configuration of System under Test				
		·				
4		t Types and Results				
	4.1	Radiated Emission and Bandedge Measurement				
		4.1.1 Limits of Radiated Emission and Bandedge Measurement				
		4.1.2 Test Instruments				
		4.1.3 Test Procedures				
		4.1.5 Test Set Up				
		4.1.6 EUT Operating Conditions				
		4.1.7 Test Results				
	4.2	Conducted Emission Measurement				
		4.2.1 Limits of Conducted Emission Measurement				
		4.2.2 Test Instruments				
		4.2.3 Test Procedures				
		4.2.4 Deviation from Test Standard				
		4.2.6 EUT Operating Conditions				
		4.2.7 Test Results				
	4.3	6 dB Bandwidth Measurement				
		4.3.1 Limits of 6 dB Bandwidth Measurement				
		4.3.2 Test Setup				
			32			
		4.3.4 Test Procedure				
		4.3.6 EUT Operating Conditions				
		4.3.7 Test Results				
	4.4	Occupied Bandwidth Measurement				
		4.4.1 Test Setup				
		4.4.2 Test Instruments	35			
		4.4.3 Test Procedure				
		4.4.4 Deviation from Test Standard				
		4.4.5 EUT Operating Conditions				
	15	4.4.6 Test Results Conducted Output Power Measurement				
	4.5	4.5.1 Limits of Conducted Output Power Measurement				
		4.5.2 Test Setup				
		4.5.3 Test Instruments				
		4.5.4 Test Procedures				
		4.5.5 Deviation from Test Standard				
		4.5.6 EUT Operating Conditions				
		4.5.7 Test Results	39			



4.6	Power Spectral Density Measurement	40
	4.6.1 Limits of Power Spectral Density Measurement	
	4.6.2 Test Setup	
	4.6.3 Test Instruments	40
	4.6.4 Test Procedure	40
	4.6.5 Deviation from Test Standard	40
	4.6.6 EUT Operating Condition	40
	4.6.7 Test Results	41
4.7	Conducted Out of Band Emission Measurement	43
	4.7.1 Limits of Conducted Out of Band Emission Measurement	
	4.7.2 Test Setup	43
	4.7.3 Test Instruments	
	4.7.4 Test Procedure	43
	4.7.5 Deviation from Test Standard	43
	4.7.6 EUT Operating Condition	43
	4.7.7 Test Results	
5 Pic	tures of Test Arrangements	48
Appei	ndix – Information on the Testing Laboratories	49



Release Control Record

Issue No.	Description	Date Issued
RF180523C09-5	Original Release	Jun. 28, 2018
RF180523C09-5 R1	Revise applicant's address	Oct. 24, 2018

Report No.: RF180523C09-5 R1 Page No. 4 / 49 Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



1 Certificate of Conformity

Product: Smart Phone

Brand: NOKIA

Test Model: TA-1087

Sample Status: Production Unit

Applicant: HMD Global Oy

Test Date: Jun. 05, 2018 ~ Jun. 14, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Ivonne Wu / Supervisor

Approved by : , Date: Oct. 24, 2018

Dylan Chiou / Project Engineer



2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)								
FCC Clause	Test Item	Result	Remarks					
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -12.25 dB at 0.15782 MHz.					
15.205 & 209 Radiated Emissions		Pass	Meet the requirement of limit. Minimum passing margin is -12.14 dB at 2495.08 MHz.					
15.247(d)	Band Edge Measurement	Pass	Meet the requirement of limit.					
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.					
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.					
	Occupied Bandwidth Measurement	Pass	Reference only					
15.247(b)	247(b) Conducted Power		Meet the requirement of limit.					
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.					
15.203	Antenna Requirement	Pass	No antenna connector is used.					

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
Radiated Emissions up to 1 GHZ	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
Radiated Emissions above 1 GHZ	18 GHz ~ 40 GHz	1.1508 dB

2.2 Modification Record

There were no modifications required for compliance.



3 General Information

3.1 General Description of EUT

Product	Smart Phone				
Brand	NOKIA				
Test Model	TA-1087				
Status of EUT	Production Unit				
	5.0 Vdc or 9 Vdc or 12 Vdc (adapter)				
Power Supply Rating	5.0 Vdc (host equipment)				
	3.85 Vdc (Li-ion battery)				
Modulation Type	GFSK				
Transfer Data	LE 4.0: 1 Mbps				
Transfer Rate	LE 5.0: 2 Mbps				
Operating Frequency	2402 ~ 2480 MHz				
Number of Channel	40				
Output Dawer	LE 4.0: 2.57 mW				
Output Power	LE 5.0: 2.877 mW				
Antenna Type	PIFA antenna with -1.5 dBi gain				
Antenna Connector	N/A				
Accessory Device	Refer to Note as below				
Data Cable Supplied	Refer to Note as below				

Note:

- 1. The EUT's accessories list refers to Ext. Pho.
- 2. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or User's Manual.



3.2 Description of Test Modes

40 channels are provided to this EUT:

Channel	Freq. (MHz)						
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



3.2.1 Test Mode Applicability and Tested Channel Detail

<LE 4.0>

EUT Configure		Applica	able To		Description	
Mode	RE≥1G	RE<1G	PLC	APCM	Description	
-	V	V	V	V	-	

Where

RE≥1G: Radiated Emission above 1 GHz

RE<1G: Radiated Emission below 1 GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Note: "-"means no effect.

Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)	
-	0 to 39	0, 19, 39	GFSK	1	

Radiated Emission Test (Below 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	1

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
 Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	1

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	1

Report No.: RF180523C09-5 R1 Page No. 9 / 49 Report Format Version: 6.1.1

Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



<LE 5.0>

EUT Configure		Applic	able To	Dogginston	
Mode	RE≥1G	RE<1G	PLC	APCM	Description
-	V	V	√	√	-

Where **RE≥1G:** Radiated Emission above 1 GHz

RE<1G: Radiated Emission below 1 GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Note: "-"means no effect.

Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	2

Radiated Emission Test (Below 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	2

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	2

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	2

Report No.: RF180523C09-5 R1 Page No. 10 / 49 Report Format Version: 6.1.1

Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



Test Condition:


Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Jisyong Wang
APCM	25 deg. C, 65 % RH	3.85 Vdc	Carlos Chen

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %, duty factor shall be considered.

<LE 4.0>

Duty cycle = 382/626 = 0.610, Duty factor = 10 * log(1/0.610) = 2.15



<LE 5.0>

Duty cycle = 200/631 = 0.317, Duty factor = $10 * \log(1/0.317) = 4.99$






3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247) KDB 558074 D01 DTS Meas Guidance v04

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Report No.: RF180523C09-5 R1 Page No. 12 / 49 Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Report No.: RF180523C09-5 R1 Page No. 13 / 49 Report Format Version: 6.1.1

Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Jul. 05, 2017	Jul. 04, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
Double Ridge Guide Horn Antenna EMCO	3115	5619	Nov. 30, 2017	Nov. 29, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 06, 2017	Dec. 05, 2018
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 07, 2017	Jul. 06, 2018
Bluetooth Tester	CBT	100980	Jun. 28, 2017	Jun. 27, 2019
Loop Antenna	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
Preamplifier Agilent	310N	187226	Jun. 23, 2017	Jun. 22, 2018
Preamplifier Agilent	83017A	MY39501357	Jun. 23, 2017	Jun. 22, 2018
Power Meter Anritsu	ML2495A	1012010	Aug. 15, 2017	Aug. 14, 2018
Power Sensor Anritsu	MA2411B	1315050	Aug. 15, 2017	Aug. 14, 2018
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 26, 2017	Jun. 25, 2018
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 26, 2017	Jun. 25, 2018
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HsinTien Chamber 1.
- 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The IC Site Registration No. is IC7450I-1.



4.1.3 **Test Procedures**

For Radiated Emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

For Radiated Emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz. (RBW = 1 MHz, VBW = 10 kHz)
- 4. All modes of operation were investigated and the worst-case emissions are reported.

Deviation from Test Standard 4.1.4


No deviation.

Report No.: RF180523C09-5 R1 Page No. 15 / 49 Report Format Version: 6.1.1




4.1.5 Test Set Up

<Radiated Emission below 30 MHz>




<Radiated Emission 30 MHz to 1 GHz>





<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.

Report No.: RF180523C09-5 R1 Page No. 17 / 49 Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



4.1.7 Test Results

Above 1 GHz Data:

<LE 4.0>

EUT Test Condition		Measurement Detail				
Channel	Channel 0	Frequency Range	1 GHz ~ 25 GHz			
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)			
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao			

		An	tennal Po	larity & T	est Dista	nce: Horiz	ontal at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2335.65	41.46	39.91	54	-12.54	31.74	5.33	35.52	161	300	Average
2335.65	51.64	50.09	74	-22.36	31.74	5.33	35.52	161	300	Peak
2402	93.35	91.62			31.8	5.4	35.47	161	300	Average
2402	94.1	92.37			31.8	5.4	35.47	161	300	Peak
4804	40.28	32.19	54	-13.72	33.96	8.25	34.12	187	9	Average
4804	47.88	39.79	74	-26.12	33.96	8.25	34.12	187	9	Peak
		А	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2376.42	41.33	39.67	54	-12.67	31.78	5.37	35.49	100	330	Average
2376.42	51.66	50	74	-22.34	31.78	5.37	35.49	100	330	Peak
2402	84.49	82.76			31.8	5.4	35.47	100	330	Average
2402	85.47	83.74			31.8	5.4	35.47	100	330	Peak
4804	40.25	32.16	54	-13.75	33.96	8.25	34.12	107	7	Average
4804	47.04	38.95	74	-26.96	33.96	8.25	34.12	107	7	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2402 MHz: Fundamental frequency.

Report No.: RF180523C09-5 R1 Page No. 18 / 49 Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



EUT Test Condition		Measurement Detail				
Channel	Channel 19	Frequency Range	1 GHz ~ 25 GHz			
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)			
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao			

		An	tennal Po	larity & T	est Distar	nce: Horiz	ontal at 3	<u> m</u>		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2374.62	41.07	39.41	54	-12.93	31.78	5.37	35.49	161	300	Average
2374.62	52.27	50.61	74	-21.73	31.78	5.37	35.49	161	300	Peak
2440	93.47	91.62			31.85	5.46	35.46	161	300	Average
2440	94.9	93.05			31.85	5.46	35.46	161	300	Peak
2491.36	41.67	39.66	54	-12.33	31.9	5.53	35.42	161	300	Average
2491.36	51.95	49.94	74	-22.05	31.9	5.53	35.42	161	300	Peak
4880	40.09	31.9	54	-13.91	33.98	8.27	34.06	134	55	Average
4880	48.64	40.45	74	-25.36	33.98	8.27	34.06	134	55	Peak
		Α	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2378.4	41.18	39.52	54	-12.82	31.78	5.37	35.49	100	330	Average
2378.4	51.28	49.62	74	-22.72	31.78	5.37	35.49	100	330	Peak
2440	84.49	82.64			31.85	5.46	35.46	100	330	Average
2440	85.6	83.75			31.85	5.46	35.46	100	330	Peak
2484.6	41.61	39.62	54	-12.39	31.88	5.53	35.42	100	330	Average
2484.6	51.75	49.76	74	-22.25	31.88	5.53	35.42	100	330	Peak
4880	39.97	31.78	54	-14.03	33.98	8.27	34.06	194	6	Average
4880	48.15	39.96	74	-25.85	33.98	8.27	34.06	194	6	Peak

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2440 MHz: Fundamental frequency.



EUT Test Condition		Measurement Detail				
Channel	Channel 39	Frequency Range	1 GHz ~ 25 GHz			
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)			
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao			

		Δn	tennal Po	larity & T	est Dista	nce: Horiz	ontal at 3	ł m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	93.47	91.51			31.88	5.5	35.42	161	300	Average
2480	94.43	92.47			31.88	5.5	35.42	161	300	Peak
2495.08	41.86	39.84	54	-12.14	31.9	5.53	35.41	161	300	Average
2495.08	52.08	50.06	74	-21.92	31.9	5.53	35.41	161	300	Peak
4960	40.02	31.75	54	-13.98	33.99	8.29	34.01	187	249	Average
4960	47.43	39.16	74	-26.57	33.99	8.29	34.01	187	249	Peak
		Α	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	84.47	82.51			31.88	5.5	35.42	100	330	Average
2480	85.45	83.49			31.88	5.5	35.42	100	330	Peak
2498.84	41.73	39.71	54	-12.27	31.9	5.53	35.41	100	330	Average
2498.84	52.29	50.27	74	-21.71	31.9	5.53	35.41	100	330	Peak
4960	40.04	31.77	54	-13.96	33.99	8.29	34.01	124	326	Average

33.99

34.01

8.29

124

326

Peak

4960 Remarks:

 Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin value = Emission level – Limit value

74

-26.48

2. 2480 MHz: Fundamental frequency.

39.25

47.52



<LE 5.0>

EUT Test Condition		Measurement Detail					
Channel	Channel 0	Frequency Range	1 GHz ~ 25 GHz				
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)				
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao				

	Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark	
2379.39	41.29	39.63	54	-12.71	31.78	5.37	35.49	102	247	Average	
2379.39	52.22	50.56	74	-21.78	31.78	5.37	35.49	102	247	Peak	
2402	91.1	89.37			31.8	5.4	35.47	102	247	Average	
2402	93.82	92.09			31.8	5.4	35.47	102	247	Peak	
4804	40.17	32.08	54	-13.83	33.96	8.25	34.12	146	326	Average	
4804	47.48	39.39	74	-26.52	33.96	8.25	34.12	145	326	Peak	
		Α	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m			
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark	
2377.23	41.13	39.47	54	-12.87	31.78	5.37	35.49	100	330	Average	
2377.23	51.4	49.74	74	-22.6	31.78	5.37	35.49	100	330	Peak	
2402	83.49	81.76			31.8	5.4	35.47	100	330	Average	
2402	85.47	83.74			31.8	5.4	35.47	100	330	Peak	
4804	40	31.91	54	-14	33.96	8.25	34.12	155	258	Average	
4804	47.26	39.17	74	-26.74	33.96	8.25	34.12	155	258	Peak	

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2402 MHz: Fundamental frequency.



EUT Test Condition		Measurement Detail				
Channel	Channel 19	Frequency Range	1 GHz ~ 25 GHz			
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)			
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao			

		An	tennal Po	larity & T	est Dista	nce: Horiz	ontal at 3	3 m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2372.01	40.81	39.15	54	-13.19	31.78	5.37	35.49	102	247	Average
2372.01	49.58	47.92	74	-24.42	31.78	5.37	35.49	102	247	Peak
2440	91.41	89.56			31.85	5.46	35.46	102	247	Average
2440	93.51	91.66			31.85	5.46	35.46	102	247	Peak
2487.56	40.97	38.96	54	-13.03	31.9	5.53	35.42	102	247	Average
2487.56	49.72	47.71	74	-24.28	31.9	5.53	35.42	102	247	Peak
4880	40	31.81	54	-14	33.98	8.27	34.06	154	79	Average
4880	48.55	40.36	74	-25.45	33.98	8.27	34.06	154	79	Peak
		А	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2373.09	40.99	39.33	54	-13.01	31.78	5.37	35.49	100	330	Average
2373.09	49.54	47.88	74	-24.46	31.78	5.37	35.49	100	330	Peak
2440	82.19	80.34			31.85	5.46	35.46	100	330	Average
2440	84.33	82.48			31.85	5.46	35.46	100	330	Peak
2487	41.38	39.39	54	-12.62	31.88	5.53	35.42	100	330	Average
2487	50.05	48.06	74	-23.95	31.88	5.53	35.42	100	330	Peak
4880	39.54	31.35	54	-14.46	33.98	8.27	34.06	200	196	Average
4880	47.58	39.39	74	-26.42	33.98	8.27	34.06	200	196	Peak

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2440 MHz: Fundamental frequency.



EUT Test Condition		Measurement Detail				
Channel	Channel 39	Frequency Range	1 GHz ~ 25 GHz			
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)			
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao			

		An	tennal Po	larity & T	est Dista	nce: Horiz	ontal at 3	3 m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	91.05	89.09			31.88	5.5	35.42	102	247	Average
2480	93.28	91.32			31.88	5.5	35.42	102	247	Peak
2486	41.53	39.54	54	-12.47	31.88	5.53	35.42	102	247	Average
2486	49.91	47.92	74	-24.09	31.88	5.53	35.42	102	247	Peak
4960	39.86	31.59	54	-14.14	33.99	8.29	34.01	154	155	Average
4960	47.19	38.92	74	-26.81	33.99	8.29	34.01	154	155	Peak
		Α	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	82.88	80.92			31.88	5.5	35.42	100	330	Average
2480	84.17	82.21			31.88	5.5	35.42	100	330	Peak
2490.12	41.61	39.6	54	-12.39	31.9	5.53	35.42	100	330	Average
2490.12	50.04	48.03	74	-23.96	31.9	5.53	35.42	100	330	Peak
4960	39.77	31.5	54	-14.23	33.99	8.29	34.01	134	159	Average

33.99

34.01

134

159

Peak

8.29

4960 Remarks:

 Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin value = Emission level – Limit value

74

-26.64

2. 2480 MHz: Fundamental frequency.

39.09

47.36



9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz Worst-Case Data:

<LE 4.0>

EUT Test Condition		Measurement Detail			
Channel	Channel 39	Frequency Range	30 MHz ~ 1 GHz		
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao		

		Antennal Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark	
88.59	17.8	38.55	43.5	-25.7	9.95	1.11	31.81	122	165	Peak	
157.71	20.68	42.76	43.5	-22.82	8.67	1.52	32.27	196	137	Peak	
276.24	20.31	37.79	46	-25.69	12.7	1.94	32.12	153	224	Peak	
374.2	21.63	36.99	46	-24.37	14.52	2.26	32.14	151	146	Peak	
599.6	19.33	30.73	46	-26.67	17.92	2.87	32.19	133	253	Peak	
938.4	28.27	34.19	46	-17.73	21.66	3.62	31.2	168	199	Peak	
		А	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m			
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark	
49.17	19.23	36	40	-20.77	14.55	0.9	32.22	134	206	Peak	
87.78	15.35	36.1	40	-24.65	9.95	1.11	31.81	192	317	Peak	
155.55	16.31	38.5	43.5	-27.19	8.56	1.52	32.27	143	253	Peak	
381.9	18.2	33.4	46	-27.8	14.63	2.34	32.17	163	82	Peak	
427.4	19.18	33.65	46	-26.82	15.3	2.41	32.18	163	346	Peak	
937.7	29.68	35.6	46	-16.32	21.66	3.62	31.2	178	24	Peak	

Remarks:

 Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin value = Emission level – Limit value



<LE 5.0>

EUT Test Condition		Measurement Detail			
Channel	Channel 39	Frequency Range	30 MHz ~ 1 GHz		
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao		

	Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark	
89.13	17.13	37.57	43.5	-26.37	10.21	1.11	31.76	132	160	Peak	
163.11	20.21	42.1	43.5	-23.29	8.85	1.52	32.26	145	122	Peak	
276.78	18.82	36.21	46	-27.18	12.7	2.03	32.12	178	2	Peak	
376.3	21.37	36.72	46	-24.63	14.54	2.26	32.15	125	167	Peak	
577.2	19.06	30.85	46	-26.94	17.59	2.82	32.2	143	120	Peak	
937.7	27.58	33.5	46	-18.42	21.66	3.62	31.2	165	111	Peak	
		А	ntennal P	olarity &	Test Dist	ance: Ver	tical at 3	m			
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark	
49.98	18.54	35.32	40	-21.46	14.54	0.9	32.22	128	247	Peak	
87.24	15.35	36.4	40	-24.65	9.7	1.11	31.86	196	312	Peak	
156.36	15.66	37.81	43.5	-27.84	8.6	1.52	32.27	200	55	Peak	
374.9	18.14	33.5	46	-27.86	14.53	2.26	32.15	120	156	Peak	
600.3	20.13	31.52	46	-25.87	17.93	2.87	32.19	187	124	Peak	
937	29.66	35.6	46	-16.34	21.65	3.62	31.21	133	269	Peak	

Remarks:

 Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin value = Emission level – Limit value



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Fraguency (MUz)	Conducted Limit (dBuV)					
Frequency (MHz)	Quasi-Peak	Average				
0.15 - 0.5	66 - 56	56 - 46				
0.50 - 5.0	56	46				
5.0 - 30.0	60	50				

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 23, 2017	Nov. 22, 2018
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Sep. 05, 2017	Sep. 04, 2018
LISN/AMN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 06, 2018	Mar. 05, 2019
LISN/AMN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 15, 2017	Aug. 14, 2018
Software ADT	BV ADT_Cond_ V7.3.7.4	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz - 30 MHz.


Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.2.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.



4.2.7 Test Results


CONDUCTED WORST-CASE DATA

<LE4.0>

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Jisyong Wang	Test Date	2018/6/14

	Phase Of Power : Line (L)										
	Frequency	Correction	Readin	g Value	Emissio	n Level	Lir	nit	Margin		
No		Factor	(dB	uV)	(dB	(dBuV)		(dBuV)		(dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.15782	10.10	43.23	27.15	53.33	37.25	65.58	55.58	-12.25	-18.33	
2	0.18557	10.10	40.96	25.25	51.06	35.35	64.23	54.23	-13.17	-18.88	
3	0.21282	10.10	38.49	23.46	48.59	33.56	63.09	53.09	-14.50	-19.53	
4	0.24025	10.11	35.43	21.60	45.54	31.71	62.09	52.09	-16.55	-20.38	
5	0.55241	10.12	29.18	17.54	39.30	27.66	56.00	46.00	-16.70	-18.34	
6	12.46650	10.77	26.22	10.82	36.99	21.59	60.00	50.00	-23.01	-28.41	

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Jisyong Wang	Test Date	2018/6/14

	Phase Of Power : Neutral (N)										
	Frequency	Correction	Readin	Reading Value		n Level		nit	Margin		
No		Factor	(dB	uV)	(dB	(dBuV)		(dBuV)		(dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.17737	10.10	37.01	20.05	47.11	30.15	64.61	54.61	-17.50	-24.46	
2	0.20458	10.10	35.37	21.22	45.47	31.32	63.42	53.42	-17.95	-22.10	
3	0.24775	10.11	33.26	19.53	43.37	29.64	61.83	51.83	-18.46	-22.19	
4	0.54089	10.12	24.94	12.26	35.06	22.38	56.00	46.00	-20.94	-23.62	
5	0.96328	10.13	19.42	4.05	29.55	14.18	56.00	46.00	-26.45	-31.82	
6	6.52721	10.37	19.61	6.37	29.98	16.74	60.00	50.00	-30.02	-33.26	

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






<LE5.0>

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Jisyong Wang	Test Date	2018/6/14

	Phase Of Power : Line (L)									
No	Frequency	Correction	Reading Value		Emission Level		Limit (dBuV)		Margin (dB)	
No	(MHz)	Factor (dB)	Q.P.	uV) AV.	Q.P.	uV) AV.	Q.P.	AV.	Q.P.	AV.
1	0.18128	10.10	40.38	24.85	50.48	34.95	64.43	54.43	-13.95	-19.48
2	0.20893	10.10	36.47	21.25	46.57	31.35	63.25	53.25	-16.68	-21.90
3	0.25192	10.11	33.84	19.25	43.95	29.36	61.69	51.69	-17.74	-22.33
4	0.27918	10.11	31.63	16.89	41.74	27.00	60.84	50.84	-19.10	-23.84
5	2.82444	10.23	21.40	5.30	31.63	15.53	56.00	46.00	-24.37	-30.47
6	7.01987	10.45	23.73	6.23	34.18	16.68	60.00	50.00	-25.82	-33.32

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Jisyong Wang	Test Date	2018/6/14

	Phase Of Power : Neutral (N)										
	Frequency	Correction	Readin	Reading Value		Emission Level		Limit		Margin	
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.16955	10.10	34.49	17.49	44.59	27.59	64.98	54.98	-20.39	-27.39	
2	0.20083	10.10	33.42	16.82	43.52	26.92	63.58	53.58	-20.06	-26.66	
3	0.29858	10.11	29.74	13.54	39.85	23.65	60.28	50.28	-20.43	-26.63	
4	0.56055	10.12	24.09	10.48	34.21	20.60	56.00	46.00	-21.79	-25.40	
5	2.13628	10.18	15.51	2.57	25.69	12.75	56.00	46.00	-30.31	-33.25	
6	12.62290	10.63	15.28	1.45	25.91	12.08	60.00	50.00	-34.09	-37.92	

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






4.3 6 dB Bandwidth Measurement

4.3.1 Limits of 6 dB Bandwidth Measurement

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100 kHz
- b. Set the video bandwidth (VBW) \geq 3 x RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 **Deviation from Test Standard**

No deviation.

4.3.6 **EUT Operating Conditions**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF180523C09-5 R1 Page No. 32 / 49 Report Format Version: 6.1.1


Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



4.3.7 Test Results

<LE 4.0>


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.67	0.5	Pass
19	2440	0.68	0.5	Pass
39	2480	0.68	0.5	Pass





<LE 5.0>


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	1.16	0.5	Pass
19	2440	1.17	0.5	Pass
39	2480	1.17	0.5	Pass





4.4 **Occupied Bandwidth Measurement**

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1 % to 5 % of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.4.4 **Deviation from Test Standard**

No deviation.

4.4.5 **EUT Operating Conditions**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF180523C09-5 R1 Page No. 35 / 49


Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



4.4.6 Test Results

<LE 4.0>


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
0	2402	1.04	Pass
19	2440	1.02	Pass
39	2480	1.02	Pass





<LE 5.0>

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
0	2402	2.05	Pass
19	2440	2.05	Pass
39	2480	2.05	Pass






4.5 **Conducted Output Power Measurement**

4.5.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt (30 dBm)

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 **Test Procedures**

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Deviation from Test Standard 4.5.5

No deviation.

4.5.6 **EUT Operating Conditions**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF180523C09-5 R1 Page No. 38 / 49 Report Format Version: 6.1.1

Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



4.5.7 Test Results

<LE 4.0>

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
0	2402	2.36	3.73	30	Pass
19	2440	1.754	2.44	30	Pass
39	2480	2.57	4.10	30	Pass

<LE 5.0>

1000	all olds							
Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail			
0	2402	2.618	4.18	30	Pass			
19	2440	1.963	2.93	30	Pass			
39	2480	2.877	4.59	30	Pass			




4.6 **Power Spectral Density Measurement**

4.6.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm.

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

Test Procedure 4.6.4

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d. Set the VBW \geq 3 × RBW.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

4.6.5 **Deviation from Test Standard**

No deviation.

4.6.6 **EUT Operating Condition**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


Report No.: RF180523C09-5 R1 Page No. 40 / 49 Report Format Version: 6.1.1



4.6.7 Test Results

<LE 4.0>


Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	2402	-11.27	8	Pass
19	2440	-12.53	8	Pass
39	2480	-11.33	8	Pass





<LE 5.0>

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	2402	-13.36	8	Pass
19	2440	-14.74	8	Pass
39	2480	-12.89	8	Pass






4.7 Conducted Out of Band Emission Measurement

4.7.1 Limits of Conducted Out of Band Emission Measurement

Below -20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

MEASUREMENT PROCEDURE REF

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep = auto couple.
- 5. Trace Mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum amplitude level.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


Report No.: RF180523C09-5 R1 Page No. 43 / 49 Report Format Version: 6.1.1

Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018




4.7.7 Test Results


<LE 4.0>


















5 Pictures of Test Arrangements	
Please refer to the attached file (Test Setup Photo).	

Report No.: RF180523C09-5 R1 Page No. 48 / 49 Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018



Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---

Cancels and replaces the report no.: RF180523C09-5 dated on Jun. 28, 2018