

FCC Test Report

(PART 27)

Report No.: RF180626C02-2

FCC ID: 2AJOTTA-1096

Test Model: TA-1096

Received Date: Jun. 26, 2018

Test Date: Jul. 20, 2018

Issued Date: Jul. 31, 2018

Applicant: HMD Global Oy

Address: Karaportti 2, 02610 Espoo, Finland

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City 33383, Taiwan (R.O.C)

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan, R.O.C

FCC Registration /
Designation Number: 427177 / TW0011



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	8
2.2 Test Site and Instruments	9
3 General Information	10
3.1 General Description of EUT	10
3.2 Configuration of System under Test.....	12
3.2.1 Description of Support Units.....	12
3.3 Test Mode Applicability and Tested Channel Detail	13
3.4 EUT Operating Conditions	14
3.5 General Description of Applied Standards.....	14
4 Test Types and Results	15
4.1 Output Power Measurement.....	15
4.1.1 Limits of Output Power Measurement.....	15
4.1.2 Test Procedures.....	15
4.1.3 Test Setup.....	16
4.1.4 Test Results	17
4.2 Radiated Emission Measurement.....	19
4.2.1 Limits of Radiated Emission Measurement.....	19
4.2.2 Test Procedure	19
4.2.3 Deviation from Test Standard	19
4.2.4 Test Setup.....	20
4.2.5 Test Results	21
5 Pictures of Test Arrangements.....	35
Appendix – Information on the Testing Laboratories	36
Annex A – Test Report for TA-1085 (Dual SIM)	37

Release Control Record

Issue No.	Description	Date Issued
RF180626C02-2	Original Release	Jul. 31, 2018

1 Certificate of Conformity

Product: Smart Phone

Brand: NOKIA

Test Model: TA-1096

Sample Status: Engineering Sample

Applicant: HMD Global Oy

Test Date: Jul. 20, 2018

Standards: FCC Part 27, Subpart C, H, F, L

This report is issued as a supplementary report to BV CPS report no.: RF180626C09-2. This report shall be used by combining with its original report.

Prepared by : 
Ivonne Wu / Supervisor

Approved by : 
Dylan Chiou / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2 (WCDMA)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Equivalent Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	N/A	Refer to Note
2.1049 27.53(h)	Occupied Bandwidth	N/A	Refer to Note
27.50(d)(5)	Peak to Average Ratio	N/A	Refer to Note
27.53(h)	Band Edge Measurements	N/A	Refer to Note
2.1051 27.53(h)	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 27.53(h)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -37.60 dB at 3465.20 MHz.

Note: Only EIRP and radiated spurious emissions tests had been performed for the addendum. Refer to original report for other test data.

Applied Standard: FCC Part 27 & Part 2 (LTE 4)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	N/A	Refer to Note
2.1049 27.53(h)	Occupied Bandwidth	N/A	Refer to Note
27.50(d)(5)	Peak to Average Ratio	N/A	Refer to Note
27.53(h)	Band Edge Measurements	N/A	Refer to Note
2.1051 27.53(h)	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 27.53(h)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -27.14 dB at 5196.00 MHz.

Note: Only EIRP and radiated spurious emissions tests had been performed for the addendum. Refer to original report for other test data.

Applied Standard: FCC Part 27 & Part 2 (LTE 12)

FCC Clause	Test Item	Result	Remarks
2.1046 27.50(c)(10)	Maximum Peak Output Power	N/A	Refer to Note
2.1047	Modulation Characteristics	N/A	Refer to Note
2.1055 27.54	Frequency Stability	N/A	Refer to Note
2.1049 27.53(g)	Occupied Bandwidth	N/A	Refer to Note
27.50(d)(5)	Peak to Average Ratio	N/A	Refer to Note
27.53(g)	Band Edge Measurements	N/A	Refer to Note
2.1051 27.53(g)	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 27.53(g)	Radiated Spurious Emissions	N/A	Refer to Note

Note: Refer to original report for other test data.

Applied Standard: FCC Part 27 & Part 2 (LTE 13)

FCC Clause	Test Item	Result	Remarks
2.1046 27.50(b)(10)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	N/A	Refer to Note
2.1055 27.54	Frequency Stability	N/A	Refer to Note
2.1049 27.53(g)	Occupied Bandwidth	N/A	Refer to Note
27.50(d)(5)	Peak to Average Ratio	N/A	Refer to Note
27.53(g)	Band Edge Measurements	N/A	Refer to Note
2.1051 27.53(g)	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 27.53(g)(f)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -12.36 dB at 1564.00 MHz.

Note: Only ERP and radiated spurious emissions tests had been performed for the addendum. Refer to original report for other test data.

Applied Standard: FCC Part 27 & Part 2 (LTE 17)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(c)(10)	Maximum Peak Output Power	N/A	Refer to Note
2.1047	Modulation Characteristics	N/A	Refer to Note
2.1055 27.54	Frequency Stability	N/A	Refer to Note
2.1049 27.53(g)	Occupied Bandwidth	N/A	Refer to Note
27.50(d)(5)	Peak to Average Ratio	N/A	Refer to Note
27.53(g)	Band Edge Measurements	N/A	Refer to Note
2.1051 27.53(g)	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 27.53(g)	Radiated Spurious Emissions	N/A	Refer to Note

Note: Refer to original report for other test data.

Applied Standard: FCC Part 27 & Part 2 (LTE 66)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Maximum Peak Output Power	N/A	Refer to Note
2.1047	Modulation Characteristics	N/A	Refer to Note
2.1055 27.54	Frequency Stability	N/A	Refer to Note
2.1049 27.53(h)	Occupied Bandwidth	N/A	Refer to Note
27.50(d)(5)	Peak to Average Ratio	N/A	Refer to Note
27.53(h)	Band Edge Measurements	N/A	Refer to Note
2.1051 27.53(h)	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 27.53(h)	Radiated Spurious Emissions	N/A	Refer to Note

Note: Refer to original report for other test data.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9010A	MY52220314	Nov. 24, 2017	Nov. 23, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
Double Ridge Guide Horn Antenna EMCO	3115	5619	Nov. 30, 2017	Nov. 29, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 06, 2017	Dec. 05, 2018
HORN Antenna Schwarzbeck	BBHA 9120D	9120D-969	Dec. 12, 2017	Dec. 11, 2018
Fixed Attenuator Woken	00801A1GGAM02Y	NA	May 17, 2018	May 16, 2019
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 24, 2017	Oct. 23, 2018
Preamplifier Agilent	310N	187226	Jun. 19, 2018	Jun. 18, 2019
Preamplifier Agilent	83017A	MY39501357	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(RF C-SMS-100-SMS-120+RFC-SMS-100-SMS-400)	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(RF C-SMS-100-SMS-24)	Jun. 19, 2018	Jun. 18, 2019
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Radio Communication Analyzer Anritsu	MT8820C	6201010284	Dec. 28, 2017	Dec. 27, 2018
Temperature & Humidity Chamber	GTH-120-40-CP-AR	MAA1306-019	Sep. 08, 2017	Sep. 07, 2018
DC Power Supply Topward	33010D	807748	Oct. 25, 2016	Oct. 24, 2018
Digital Multimeter Fluke	87-III	70360742	Jun. 29, 2018	Jun. 28, 2019

Note:

1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	Smart Phone	
Brand	NOKIA	
Test Model	TA-1096	
Status of EUT	Engineering Sample	
Power Supply Rating	5.0 Vdc or 9 Vdc or 12 Vdc (adapter) 5.0 Vdc (host equipment) 3.85 Vdc (Li-ion battery)	
Modulation Type	WCDMA	QPSK
	LTE	QPSK, 16QAM
Frequency Range	WCDMA	1712.4 ~ 1752.6 MHz
	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	1710.7 ~ 1754.3 MHz
	LTE Band 4 (Channel Bandwidth: 3 MHz)	1711.5 ~ 1753.5 MHz
	LTE Band 4 (Channel Bandwidth: 5 MHz)	1712.5 ~ 1752.5 MHz
	LTE Band 4 (Channel Bandwidth: 10 MHz)	1715.0 ~ 1750.0 MHz
	LTE Band 4 (Channel Bandwidth: 15 MHz)	1717.5 ~ 1747.5 MHz
	LTE Band 4 (Channel Bandwidth: 20 MHz)	1720.0 ~ 1745.0 MHz
	LTE Band 12 (Channel Bandwidth: 1.4 MHz)	699.7 ~ 715.3 MHz
	LTE Band 12 (Channel Bandwidth: 3 MHz)	700.5 ~ 714.5 MHz
	LTE Band 12 (Channel Bandwidth: 5 MHz)	701.5 ~ 713.5 MHz
	LTE Band 12 (Channel Bandwidth: 10 MHz)	704.0 ~ 711.0 MHz
	LTE Band 13 (Channel Bandwidth: 5 MHz)	779.5 ~ 784.5 MHz
	LTE Band 13 (Channel Bandwidth: 10 MHz)	782.0 MHz
	LTE Band 17 (Channel Bandwidth: 5 MHz)	706.5 ~ 713.5 MHz
	LTE Band 17 (Channel Bandwidth: 10 MHz)	709.0 ~ 711.0 MHz
	LTE Band 66 (Channel Bandwidth: 1.4 MHz)	1710.7 ~ 1779.3 MHz
	LTE Band 66 (Channel Bandwidth: 3 MHz)	1711.5 ~ 1778.5 MHz
	LTE Band 66 (Channel Bandwidth: 5 MHz)	1712.5 ~ 1777.5 MHz
	LTE Band 66 (Channel Bandwidth: 10 MHz)	1715.0 ~ 1775.0 MHz
	LTE Band 66 (Channel Bandwidth: 15 MHz)	1717.5 ~ 1772.5 MHz
	LTE Band 66 (Channel Bandwidth: 20 MHz)	1720.0 ~ 1770.0 MHz
Max. ERP Power	LTE Band 13 (Channel Bandwidth: 10 MHz)	36.62 mW
Max. EIRP Power	WCDMA	211.59 mW
	LTE Band 4 (Channel Bandwidth: 20 MHz)	223.10 mW
Antenna Type	PIFA Antenna	

Antenna Gain	WCDMA	0.72 dBi
	LTE Band 4	0.72 dBi
	LTE Band 12	-3.14 dBi
	LTE Band 13	-3.91 dBi
	LTE Band 17	-3.14 dBi
	LTE Band 66	0.72 dBi
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:

1. This report is issued as a supplementary report to BV CPS report no.: RF180626C09. The difference is listed as below. Only ERP/EIRP and radiated spurious emissions tests were verified in this report.

Report No.	FCC ID	Model	Difference
RF180626C09-2	2AJOTTA-1085	TA-1085	Dual SIM
RF180626C02-2	2AJOTTA-1096	TA-1096	Single SIM

* The models have the same layout, circuit, and components, but different SIM tray.

2. There're 2 configurations for the EUT listed as below.

Main Sample: EUT + Battery 1

2nd Sample: EUT + Battery 2


❖ Only the worst test data of main sample was presented in the report.

3. The EUT's accessories list refers to Ext. Pho.


4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.R.P. / E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

EUT Configure Mode	Description
A	Main Sample
B	2 nd Sample

SIM	Band	ERP / EIRP	Radiated Emission
1	WCDMA	Z-plane	Y-axis
	LTE Band 4	X-plane	X-axis
	LTE Band 13	Z-plane	X-axis

WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
A	EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
A	Radiated Emission	1312 to 1513	1312, 1413, 1513	WCDMA

LTE Band 4

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
A	EIRP	20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
A	Radiated Emission	20050 to 20300	20050, 20175, 20300	20 MHz	QPSK	1 RB / 0 RB Offset

LTE Band 13

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
A	ERP	23230	23230	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
A	Radiated Emission	23230	23230	10 MHz	QPSK	1 RB / 0 RB Offset

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP / EIRP	25 deg. C, 65 % RH	3.85 Vdc	Charles Hsiao
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao / Karl Lee

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

Note: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 776-787 MHz band are limited to 3 watts ERP

4.1.2 Test Procedures


EIRP / ERP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5 MHz for WCDMA and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15 dB.


4.1.3 Test Setup

EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

ERP Power (dBm)

Mode A

LTE Band 13							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Z	23230	782.0	-14.95	32.737	15.64	36.62	H
	23230	782.0	-17.75	32.52	12.62	18.28	V
Channel Bandwidth: 10 MHz / 16QAM							
Z	23230	782.0	-15.99	32.737	14.60	28.82	H
	23230	782.0	-18.87	32.52	11.50	14.13	V

Note: ERP (dBm) = Reading (dBm) + Correction Factor (dB) – 2.15

EIRP Power (dBm)

Mode A

WCDMA							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	1312	1712.4	-19.23	42.49	23.26	211.59	H
	1413	1732.6	-19.25	42.33	23.08	203.10	
	1513	1752.6	-18.88	42.10	23.22	209.89	
	1312	1712.4	-24.25	42.99	18.74	74.82	V
	1413	1732.6	-24.51	42.74	18.23	66.53	
	1513	1752.6	-24.02	42.21	18.19	65.92	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 4							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20050	1720.0	-19.00	42.49	23.49	223.10	H
	20175	1732.5	-18.88	42.33	23.45	221.16	
	20300	1745.0	-18.62	42.10	23.48	222.84	
	20050	1720.0	-24.23	42.99	18.76	75.16	V
	20175	1732.5	-24.51	42.74	18.23	66.53	
	20300	1745.0	-24.20	42.21	18.01	63.24	
Channel Bandwidth: 20 MHz / 16QAM							
X	20050	1720.0	-19.88	42.49	22.61	182.18	H
	20175	1732.5	-19.75	42.33	22.58	181.01	
	20300	1745.0	-19.74	42.10	22.36	172.19	
	20050	1720.0	-25.23	42.99	17.76	59.70	V
	20175	1732.5	-25.62	42.74	17.12	51.52	
	20300	1745.0	-25.01	42.21	17.20	52.48	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

4.2 Radiated Emission Measurement

4.2.1 Limits of Radiated Emission Measurement

- a. The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. The limit of emission is equal to -13 dBm.
- b. For operations in the 775-788 MHz, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz. The limit of emissions is equal to -40 dBm.

4.2.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15 dB.


Note: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.2.3 Deviation from Test Standard


No deviation.

4.2.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.5 Test Results

Mode A

WCDMA:


Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : Band IV_Link_CH1312

Tested by: Charles Hsiao


Freq	Level	Read	Limit	Over	Remark
		MHz	dBm	dBm	
1 pp	3424.80	-52.55	-66.92	-13.00	-39.55 14.37 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1
Condition: PART 27(B4/B17) Vertical
Remark : Band IV_Link_CH1312
Tested by: Charles Hsiao

Freq	Read		Limit		Over	Factor	Remark
	Level	Level	Line	Limit			
MHz	dBm	dBm	dBm	dB	dB		
1 pp	3424.80	-51.89	-66.26	-13.00	-38.89	14.37	Peak


Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1

Condition: PART 27(B4/B17) Horizontal

Remark : Band IV_Link_CH1413

Tested by: Charles Hsiao


	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	
	MHz	dBm	dBm	dBm	dB	
1	118.29	-81.92	-73.54	-13.00	-68.92	-8.38 Peak
2	183.90	-70.95	-65.31	-13.00	-57.95	-5.64 Peak
3	274.08	-73.13	-67.40	-13.00	-60.13	-5.73 Peak
4	379.80	-72.16	-68.39	-13.00	-59.16	-3.77 Peak
5	562.50	-71.43	-70.29	-13.00	-58.43	-1.14 Peak
6	885.90	-65.69	-68.16	-13.00	-52.69	2.47 Peak
7 pp	3465.20	-50.60	-64.94	-13.00	-37.60	14.34 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14



Site : 966 chamber 1

Condition: PART 27(B4/B17) Vertical

Remark : Band IV_Link_CH1413

Tested by: Charles Hsiao

Freq	Read		Limit	Over	Remark	
	Level	Level	Line	Limit Factor		
	MHz	dBm	dBm	dB	dB	
1	114.78	-78.40	-69.77	-13.00	-65.40	-8.63 Peak
2	225.21	-66.90	-61.05	-13.00	-53.90	-5.85 Peak
3	275.43	-76.13	-70.39	-13.00	-63.13	-5.74 Peak
4	431.60	-72.19	-68.75	-13.00	-59.19	-3.44 Peak
5	738.90	-70.29	-69.18	-13.00	-57.29	-1.11 Peak
6	848.10	-66.87	-68.34	-13.00	-53.87	1.47 Peak
7 pp	3465.20	-51.89	-66.23	-13.00	-38.89	14.34 Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1

Condition: PART 27(B4/B17) Horizontal

Remark : Band IV_Link_CH1513

Tested by: Charles Hsiao


Freq	Read	Limit	Over	Factor	Remark	
	Level	Level	Line			
MHz	dBm	dBm	dBm	dB	dB	
1 pp	3505.20	-51.99	-66.27	-13.00	-38.99	14.28 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1

Condition: PART 27(B4/B17) Vertical

Remark : Band IV_Link_CH1513

Tested by: Charles Hsiao


Freq	Read		Limit		Over	Factor	Remark
	Level	Level	Line	Limit			
MHz	dBm	dBm	dBm	dB	dB		
1 pp	3505.20	-52.00	-66.28	-13.00	-39.00	14.28	Peak

LTE Band 4
Channel Bandwidth: 20 MHz / QPSK
Low Channel


Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1

Condition: PART 27(B4/B17) Horizontal

Remark : LTE_Band 4_Link_CH20050

Tested by: Karl Lee


Freq	Level	Read	Limit	Over	Factor	Remark	
		MHz	dBm	dBm	Line	Limit	
1 pp	3440.00	-52.23	-66.58	-13.00	-39.23	14.35	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1
Condition: PART 27(B4/B17) Vertical
Remark : LTE_Band 4_Link_CH20050
Tested by: Karl Lee

Freq	Read		Limit	Over	Remark	
	Level	Level	Line	Limit Factor		
MHz	dBm	dBm	dBm	dB	dB	
1 pp	3440.00	-51.98	-66.33	-13.00	-38.98	14.35 Peak


Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1

Condition: PART 27(B4/B17) Horizontal

Remark : LTE_Band 4_Link_CH20175

Tested by: Karl Lee


	Freq	Read Level	Limit Level	Over Line	Over Limit	Over Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	99.12	-80.27	-70.09	-13.00	-67.27	-10.18	Peak
2	202.80	-63.83	-57.69	-13.00	-50.83	-6.14	Peak
3	257.88	-75.68	-70.10	-13.00	-62.68	-5.58	Peak
4	428.80	-73.75	-70.37	-13.00	-60.75	-3.38	Peak
5	624.80	-70.10	-70.25	-13.00	-57.10	0.15	Peak
6	791.40	-68.40	-69.84	-13.00	-55.40	1.44	Peak
7	3465.00	-50.87	-65.21	-13.00	-37.87	14.34	Peak
8 pp	5196.00	-40.14	-60.26	-13.00	-27.14	20.12	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14



Site : 966 chamber 1

Condition: PART 27(B4/B17) Vertical

Remark : LTE_Band 4_Link_CH20175

Tested by: Karl Lee

Freq	Level	Read	Limit	Over	Remark	
		MHz	dBm	dBm		
1	88.05	-78.36	-67.47	-13.00	-65.36	-10.89 Peak
2	168.78	-72.89	-66.09	-13.00	-59.89	-6.80 Peak
3	203.34	-69.41	-63.28	-13.00	-56.41	-6.13 Peak
4	493.20	-75.94	-70.85	-13.00	-62.94	-5.09 Peak
5	785.10	-69.03	-70.02	-13.00	-56.03	0.99 Peak
6	958.70	-64.61	-69.74	-13.00	-51.61	5.13 Peak
7	3465.00	-52.43	-66.77	-13.00	-39.43	14.34 Peak
8 pp	5197.50	-42.19	-62.31	-13.00	-29.19	20.12 Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1

Condition: PART 27(B4/B17) Horizontal

Remark : LTE_Band 4_Link_CH20300

Tested by: Karl Lee


	Freq	Read Level	Limit Level	Over Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3490.00	-51.65	-65.96	-13.00	-38.65	14.31	Peak
2 pp	5235.00	-44.15	-64.31	-13.00	-31.15	20.16	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1
Condition: PART 27(B4/B17) Vertical
Remark : LTE_Band 4_Link_CH20300
Tested by: Karl Lee


Freq	Level	Read	Limit	Over	Remark	
		MHz	dBm	dBm		
1	3490.00	-52.85	-67.16	-13.00	-39.85	14.31 Peak
2 pp	5235.00	-43.25	-63.41	-13.00	-30.25	20.16 Peak

LTE Band 13
Channel Bandwidth: 10 MHz / QPSK
Middle Channel


Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1

Condition: PART 27(B13) Horizontal

Remark : LTE_Band 13_Link_CH23230

Tested by: Karl Lee


Freq	Level	Read	Limit	Over	Factor	Remark
		MHz	dBm	dBm		
1	93.45	-78.77	-68.26	-13.00	-65.77	-10.51 Peak
2	153.93	-65.25	-57.41	-13.00	-52.25	-7.84 Peak
3	277.05	-72.39	-66.63	-13.00	-59.39	-5.76 Peak
4	387.50	-72.80	-69.44	-13.00	-59.80	-3.36 Peak
5	554.10	-71.85	-70.35	-13.00	-58.85	-1.50 Peak
6	927.20	-65.94	-70.05	-13.00	-52.94	4.11 Peak
7 pp	1564.00	-52.36	-59.22	-40.00	-12.36	6.86 Peak
8	2346.00	-40.78	-51.72	-13.00	-27.78	10.94 Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1

Condition: PART 27(B13) Vertical

Remark : LTE_Band 13_Link_CH23230

Tested by: Karl Lee

Freq	Level	Read	Limit	Over	Remark	
		MHz	dBm	dBm		
1	39.72	-79.94	-70.73	-13.00	-66.94	-9.21 Peak
2	124.77	-80.79	-72.84	-13.00	-67.79	-7.95 Peak
3	248.70	-76.55	-71.02	-13.00	-63.55	-5.53 Peak
4	386.80	-73.73	-70.32	-13.00	-60.73	-3.41 Peak
5	811.70	-66.65	-68.53	-13.00	-53.65	1.88 Peak
6	953.80	-65.89	-71.01	-13.00	-52.89	5.12 Peak
7 pp	1564.00	-58.16	-65.02	-40.00	-18.16	6.86 Peak
8	2346.00	-41.13	-52.07	-13.00	-28.13	10.94 Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---