FCC RF Test Report

APPLICANT : HMD global Oy EQUIPMENT : Mobile Phone

BRAND NAME : Nokia MODEL NAME : TA-1179

FCC ID : 2AJOTTA-1179

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION : (DTS) Digital Transmission System

The product was completed on Mar. 30, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Journes Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 1 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

TABLE OF CONTENTS

RE۱	/ISIO	N HISTORY	3
SUI	MMAR	Y OF TEST RESULT	4
1	GENE	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Product Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	6
	1.5	Modification of EUT	6
	1.6	Testing Location	6
	1.7	Applicable Standards	6
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Carrier Frequency Channel	8
	2.2	Test Mode	9
	2.3	Connection Diagram of Test System	10
	2.4	Support Unit used in test configuration and system	10
	2.5	EUT Operation Test Setup	11
	2.6	Measurement Results Explanation Example	11
3	TEST	RESULT	12
	3.1	6dB and 99% Bandwidth Measurement	12
	3.2	Output Power Measurement	17
	3.3	Power Spectral Density Measurement	18
	3.4	Conducted Band Edges and Spurious Emission Measurement	23
	3.5	Radiated Band Edges and Spurious Emission Measurement	28
	3.6	AC Conducted Emission Measurement	32
	3.7	Antenna Requirements	34
4	LIST	OF MEASURING EQUIPMENT	35
5	UNCE	ERTAINTY OF EVALUATION	36
API	PENDI	IX A. CONDUCTED TEST RESULTS	
API	PENDI	IX B. AC CONDUCTED EMISSION TEST RESULT	
API	PENDI	IX C. RADIATED SPURIOUS EMISSION	
API	PENDI	IX D. DUTY CYCLE PLOTS	
API	PENDI	IX E. SETUP PHOTOGRAPHS	

Report No. : FR930509-04B

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR930509-04B	Rev. 01	Initial issue of report	Apr. 30, 2019

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 3 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No. : FR930509-04B

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 15.45 dB at 2483.500 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 4.52 dB at 0.747 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 4 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No. : FR930509-04B

1 General Description

1.1 Applicant

HMD global Oy

Bertel Jungin aukio 9, 02600 Espoo, Finland

1.2 Manufacturer

HMD global Oy

Bertel Jungin aukio 9, 02600 Espoo, Finland

1.3 Product Feature of Equipment Under Test

Product Feature				
Equipment	Mobile Phone			
Brand Name	Nokia			
Model Name	TA-1179			
FCC ID	2AJOTTA-1179			
	GSM/GPRS/EGPRS/WCDMA/HSPA/			
FLIT cumparts Padios application	DC-HSDPA/HSPA+/LTE/FM Receiver/GNSS			
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20			
	Bluetooth BR/EDR/LE			
	Conducted: N/A			
IMEI Code	Conduction: 352916100002667/352916100002675			
	Radiation: 352916100002923/31			
HW Version	DVT_0.2			
SW Version	00WW_0_095			
EUT Stage	Identical Prototype			

Remark:

- 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. This project is FCC change ID application (original report FCC ID: 2AJOTTA-1184) and changed dual SIM card slot to single SIM card slots, changed Model Name. Since the test result is not affected by the changes, so all the test results release from original report which can be referred to Sporton report number FR930509-01B, FCC ID: 2AJOTTA-1184.
- 3. There are two types of EUT. According to the difference, choose sample 1 to perform full test.

Object	Sample 1 with D	ual SIMs(TA-1184)	Sample 2 with Dual SIMs(TA-1184)		
Object	Specifications	Supplier	Specifications	Supplier	
Memory	3+32G	Kingston	3+32G	Foresee	
TP+LCD	HQ23201454000	K&D	HQ23201454000	Holitech	
Battery Cover	HQ20704757000	Goodmark-new	HQ20746201000	Zhiyin	
Front Camera	HQ20207233000	Jinkang	HQ20207233000	Tianshi	
Rear Camera	HQ20207234000	Tianshi	HQ20207234000	Guangzhen	

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 5 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

Speaker	HQ20312058000	Xichun	HQ20312058000	Xinrongda
Receiver	HQ20321087000	Dongsheng	HQ20321087000	Xinrongda
MIC	HQ12030105000	Knowles	HQ12030105000	Minxinwei
Motor	HQ20400123000	Kunwang	HQ20400123000	Jinlangda

Report No.: FR930509-04B

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification				
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz			
Number of Channels	40			
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)			
Maximum Output Power to Antenna	-2.15 dBm (0.00061 W)			
99% Occupied Bandwidth	0.927MHz			
Antenna Type / Gain	IFA Antenna type with gain -0.18 dBi			
Type of Modulation	Bluetooth LE : GFSK			

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.				
	No. 1098, Pengxi North Road, Kunshan Economic Development Zone,				
Test Site Location	Jiangsu Province 215335, China				
lest Site Location	TEL: 86-512-57900158				
	FAX: 86-512-57900958				
	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.		
Test Site No.	TH01-KS				
Test Site NO.	CO01-KS	CN5013	630927		
	03CH06-KS				

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

 Sporton International (Kunshan) Inc.
 Page Number
 : 6 of 36

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 30, 2019

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

FCC ID: 2AJOTTA-1179 Report Template No.: BU5-FR15CBT4.0 Version 2.0



- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r01
- ANSI C63.10-2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 7 of 36

Report Issued Date : Apr. 30, 2019

Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 2.0

Report No.: FR930509-04B

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
2400-2483.5 MHz	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 8 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases					
Test Item	Data Rate / Modulation					
rest item	Bluetooth – LE / GFSK					
Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps					
TCs	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps					
105	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps					
Radiated	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps					
TCs	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps					
108	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps					
AC	Mode 1: GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable(Charging					
Conducted	, , ,					
Emission	from Adapter) + Earphone + Battery1					

Remark:


 For Radiated Test Cases, The tests were performance with Adapter, Battery 1, Earphone, USB Cable.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 9 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
3.	Notebook	Lenovo	G480	PRC4	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	Router	D-link	DIR-855	KA2DIR855A2		Unshielded,1.8m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 10 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.10 dB.

 $Offset(dB) = RF \ cable \ loss(dB).$ = 5.10 (dB) Report No.: FR930509-04B

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 11.8
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- 5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
- 6. Measure and record the results in the test report.

3.1.4 Test Setup



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 12 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

6 dB Bandwidth Plot on Channel 00



Date: 16.MAR.2019 23:17:24

6 dB Bandwidth Plot on Channel 19



Date: 16.MAR.2019 23:22:26

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 13 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

6 dB Bandwidth Plot on Channel 39



Date: 16.MAR.2019 23:24:56


TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 14 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.1.6 Test Result of 99% Occupied Bandwidth


Please refer to Appendix A.

99% Bandwidth Plot on Channel 00



Date: 16.MAR.2019 23:18:51

99% Occupied Bandwidth Plot on Channel 19




Date: 16.MAR.2019 23:23:06

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 15 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

99% Occupied Bandwidth Plot on Channel 39



Date: 16.MAR.2019 23:25:45

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 16 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

- The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1
 Peak power meter method.
- 2. The RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Olny)

Please refer to Appendix A.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 17 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

- The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.


Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 18 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B


3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00



Date: 16.MAR.2019 23:18:26

PSD 100kHz Plot on Channel 19




Date: 16.MAR.2019 23:22:58

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 19 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

PSD 100kHz Plot on Channel 39




Date: 16.MAR.2019 23:25:25

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 20 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B


3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 16.MAR.2019 23:17:53

PSD 3kHz Plot on Channel 19




Date: 16.MAR.2019 23:22:39

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 21 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

PSD 3kHz Plot on Channel 39



Date: 16.MAR.2019 23:25:13

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 22 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

- 1. The testing follows ANSI C63.10-2013 clause 11.13
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup




Sporton International (Kunshan) Inc. TEL: +86-512-57900158

FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 23 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B


3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 16.MAR.2019 23:18:44

High Band Edge Plot on Channel 39



Date: 16.MAR.2019 23:25:35


Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 24 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B


3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 16.MAR.2019 23:19:04

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 16.MAR.2019 23:19:22

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 25 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01


Report No.: FR930509-04B

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 16.MAR.2019 23:23:16

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 16.MAR.2019 23:23:36

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 26 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01


Report No.: FR930509-04B

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 16.MAR.2019 23:25:54

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 16.MAR.2019 23:26:09

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 27 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 28 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.5.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
- The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Sporton International (Kunshan) Inc.
TEL: +86-512-57900158

FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 29 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01


Report No.: FR930509-04B

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 30 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 31 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR930509-04B

Eroquency of emission (MUz)	Conducted	limit (dΒμV)
Frequency of emission (MHz)	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

^{*}Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


 Sporton International (Kunshan) Inc.
 Page Number
 : 32 of 36

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 30, 2019

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

FCC ID: 2AJOTTA-1179 Report Template No.: BU5-FR15CBT4.0 Version 2.0

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 33 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 34 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 2.0

Report No.: FR930509-04B

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	Mar. 16, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GH z	Jan. 14, 2019	Mar. 16, 2019	Jan. 13, 2020	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 14, 2019	Mar. 16, 2019	Jan. 13, 2020	Conducted (TH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Mar. 30, 2019	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Mar. 30, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary	MessTec	AN3016	060105	9kHz~30MHz	Nov. 17, 2018	Mar. 30, 2019	Nov. 16, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Mar. 30, 2019	Oct. 11, 2019	Conduction (CO01-KS)
EMI Test Receiver	Keysight	N9038A	MY564000 23	3Hz~8.5GHz;M ax 30dBm	Oct. 12, 2018	Mar. 24, 2019	Oct. 11, 2019	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY574710 84	10Hz-44GHz	Jun. 25, 2018	Mar. 24, 2019	Jun. 24, 2019	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Mar. 24, 2019	Oct. 18, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 28, 2018	Mar. 24, 2019	Dec. 27, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 20, 2018	Mar. 24, 2019	Oct. 19, 2019	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Mar. 24, 2019	Jan. 04, 2020	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2018	Mar. 24, 2019	Aug. 05, 2019	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35- HG	2014749	18~40GHz	Jan. 14, 2019	Mar. 24, 2019	Jan. 13, 2020	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Apr. 17, 2018	Mar. 24, 2019	Apr. 16, 2019	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY532702 03	500MHz~26.5G Hz	Apr. 18, 2018	Mar. 24, 2019	Apr. 17, 2019	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Mar. 24, 2019	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 24, 2019	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Mar. 24, 2019	NCR	Radiation (03CH06-KS)

NCR: No Calibration Required

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 35 of 36
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No. : FR930509-04B

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

<u>Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)</u>

Measuring Uncertainty for a Level of Confidence	3 0 AB
of 95% (U = 2Uc(y))	2.9 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

1		
	Measuring Uncertainty for a Level of Confidence	5 0 ID
		5.0 dB
	of 95% (U = 2Uc(y))	

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

1		
	Measuring Uncertainty for a Level of Confidence	E 0 4D
	of 95% (U = 2Uc(y))	5.0 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : 36 of 36

Report Issued Date : Apr. 30, 2019

Report Version : Rev. 01

Report No.: FR930509-04B

Appendix A. Conducted Test Results

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : A1 of A1
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 2.0

Report No. : FR930509-04B

Report Number : FR930509-04B

Bluetooth Low Energy

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2019.03.16	Relative Humidity:	51~54	%

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	0.93	0.65	0.50	Pass
BLE	1Mbps	1	19	2440	0.93	0.65	0.50	Pass
BLE	1Mbps	1	39	2480	0.93	0.65	0.50	Pass

TEST RESULTS DATA

Peak Power Table

Mod.	Data Rate	N TX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	-3.14	30.00	-0.18	-3.32	36.00	Pass
BLE	1Mbps	1	19	2440	-2.15	30.00	-0.18	-2.33	36.00	Pass
BLE	1Mbps	1	39	2480	-3.51	30.00	-0.18	-3.69	36.00	Pass

TEST RESULTS DATA Average Power Table

(Reporting Only)

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.17	-3.86
BLE	1Mbps	1	19	2440	2.17	-2.95
BLE	1Mbps	1	39	2480	2.17	-4.24


TEST RESULTS DATA

Peak Power Density

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-4.14	-20.16	-0.18	8.00	Pass
BLE	1Mbps	1	19	2440	-3.18	-19.23	-0.18	8.00	Pass
BLE	1Mbps	1	39	2480	-4.68	-20.87	-0.18	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Appendix B. AC Conducted Emission Test Results



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : B1 of B2
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B



Temperature : 23.3~24.2°C Test Engineer : Amos Zhang Relative Humidity: 28~30% Test Voltage: Phase: 120Vac / 60Hz Neutral Remark: All emissions not reported here are more than 10 dB below the prescribed limit. 80 Level (dBuV) 70.0 FCC PART 15C 60.0 FCC PART 15C(AVG) 50.0 40.0 30.0 20.0 10.0 0.15 .2

Frequency (MHz)

: CO01-KS

Condition : FCC PART 15C LISN-N-181119-060105 NEUTRAL

Project : (FR) 930509-01

			0ver	Limit	Read	LISN	Cable	
	Freq	Level	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.150	57.96	-8.04	66.00	47.30	0.18	10.48	QP
2	0.150	44.26	-11.74	56.00	33.60	0.18	10.48	Average
3	0.598	43.98	-12.02	56.00	33.60	0.14	10.24	QP
4	0.598	41.28	-4.72	46.00	30.90	0.14	10.24	Average
5	0.747	45.48	-10.52	56.00	35.10	0.14	10.24	QP
6 *	0.747	41.48	-4.52	46.00	31.10	0.14	10.24	Average
7	0.974	45.27	-10.73	56.00	34.91	0.13	10.23	QP
8	0.974	40.77	-5.23	46.00	30.41	0.13	10.23	Average
9	2.099	42.98	-13.02	56.00	32.60	0.15	10.23	QP
10	2.099	36.98	-9.02	46.00	26.60	0.15	10.23	Average
11	2.946	41.00	-15.00	56.00	30.60	0.16	10.24	QP
12	2.946	27.00	-19.00	46.00	16.60	0.16	10.24	Average
								_

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179

Page Number : B2 of B2 Report Issued Date: Apr. 30, 2019 Report Version : Rev. 01

Report No.: FR930509-04B

20

30

Appendix C. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2364.21	46.4	-27.6	74	48.29	-1.89	32.97	5.59	100	76	Р	Η
		2388.91	36.05	-17.95	54	37.82	-1.77	33	5.63	100	76	Α	Η
D. E		2402	84.21		_	86.01	-1.8	33.03	5.63	100	76	Р	Н
BLE CH 00		2402	83.44			85.24	-1.8	33.03	5.63	100	76	Α	Н
2402MHz		2376.69	46.38	-27.62	74	48.22	-1.84	33	5.61	400	105	Р	V
2402191112		2356.8	36.03	-17.97	54	37.92	-1.89	32.97	5.59	400	105	Α	V
		2402	84.3			86.1	-1.8	33.03	5.63	400	105	Р	V
		2402	83.48		_	85.28	-1.8	33.03	5.63	400	105	Α	V
		2490.58	48.1	-25.9	74	48.14	-0.04	32.49	5.74	378	115	Р	Н
		2483.5	38.5	-15.5	54	38.74	-0.24	32.49	5.72	378	115	Α	Н
DI E		2480	90.09	_	_	90.33	-0.24	32.49	5.72	378	115	Р	Н
BLE CH 39		2480	89.44	_	_	89.68	-0.24	32.49	5.72	378	115	Α	Н
2480MHz		2491.54	48.02	-25.98	74	48.06	-0.04	32.49	5.74	368	75	Р	V
240011112		2483.5	38.55	-15.45	54	38.79	-0.24	32.49	5.72	368	75	Α	V
		2480	90.83	_	_	91.07	-0.24	32.49	5.72	368	75	Р	V
		2480	90.24	_	_	90.48	-0.24	32.49	5.72	368	75	Α	V
Remark	 No other spurious found. All results are PASS against Peak and Average limit line. 												

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : C1 of C5
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

15C 2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE		4806	35.32	-38.68	74	59.77	-24.45	63.76	8.43	150	360	Р	Н
CH 00 2402MHz		4806	34.87	-39.13	74	59.32	-24.45	63.76	8.43	150	360	Р	V
		4878	35.01	-38.99	74	59.26	-24.25	63.73	8.43	150	360	Р	Н
BLE CH 40		7320	39.19	-34.81	74	57.92	-18.73	64.37	10.08	150	360	Р	Н
CH 19 2440MHz		4878	35.62	-38.38	74	59.87	-24.25	63.73	8.43	150	360	Р	V
2440111112		7320	40.15	-33.85	74	58.88	-18.73	64.37	10.08	150	360	Р	V
		4962	36.24	-37.76	74	60.22	-23.98	63.69	8.44	150	360	Р	Н
BLE		7440	39.82	-34.18	74	58.22	-18.4	64.38	10.18	150	360	Р	Н
CH 39 2480MHz		4960	36.23	-37.77	74	60.21	-23.98	63.69	8.44	150	360	Р	V
240UNITZ		7440	40.93	-33.07	74	59.33	-18.4	64.38	10.18	150	360	Р	V

emark

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : C2 of C5
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

15C Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
		30.97	17.12	-22.88	40	25.98	-8.86	32.97	0.47		—	Р	Н	
		419.94	19.63	-26.37	46	28.67	-9.04	33.16	2.16	_		Р	Н	
		555.74	21.96	-24.04	46	28.72	-6.76	33.31	2.49			Р	Н	
		751.68	23.55	-22.45	46	28.13	-4.58	33.11	3.01			Р	Н	
0.4011		909.79	24.06	-21.94	46	26.3	-2.24	32.2	3.37	100	0	Р	Н	
2.4GHz		976.72	24.39	-29.61	54	25.17	-0.78	31.47	3.5			Р	Н	
BLE LF		30	16.41	-23.59	40	24.73	-8.32	32.98	0.46			Р	V	
		104.69	12.92	-30.58	43.5	27.84	-14.92	32.92	1.01			Р	V	
		547.98	21.35	-24.65	46	28.22	-6.87	33.31	2.47			Р	V	
		780.78	22.73	-23.27	46	26.81	-4.08	33.04	3.09	_	_	Р	V	
		872.93	24.25	-21.75	46	27.02	-2.77	32.47	3.31	_	_	Р	V	
		929.19	24.36	-21.64	46	26.15	-1.79	31.96	3.41	100	0	Р	V	
Remark		No other spurious found.												
	2. Al	I results are F	ASS agains	ot IIIIIII II	ie.									

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : C3 of C5
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No. : FR930509-04B

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions						
	shall not exceed the level of the fundamental frequency per 15.209(c).						
!	Test result is over limit line.						
P/A	Peak or Average						
H/V	Horizontal or Vertical						

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : C4 of C5
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B

A calculation example for radiated spurious emission is shown as below:

Report No.: FR930509-04B

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01 2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

1. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

 Sporton International (Kunshan) Inc.
 Page Number
 : C5 of C5

 TEL: +86-512-57900158
 Report Issued Date
 : Apr. 30, 2019


 FAX: +86-512-57900958
 Report Version
 : Rev. 01

 FCC ID: 2AJOTTA-1179
 Report Template No.: BU5-FR15CBT4.2/5.0 Version 2.0

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE v4.0	60.65	0.380	2.6336	2.7KHz

Bluetooth LE v4.0



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AJOTTA-1179 Page Number : D1 of D1
Report Issued Date : Apr. 30, 2019
Report Version : Rev. 01

Report No.: FR930509-04B