

TEST REPORT



Applicant:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland

Manufacturer or Supplier:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland
Product:	Tablet PC
Brand Name:	NOKIA
Model Name:	TA-1505
FCC ID:	2AJOTTA-1505
Date of tests:	Aug. 03, 2022 ~ Sep. 20, 2022

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- ☒ FCC Part 15, Subpart C, Section 15.247 ☒ ANSI C63.10-2013
☒ FCC Part 15, Subpart E, Section 15.407
☒ FCC Part 27 ☒ ANSI/TIA/EIA-603-D
☒ FCC Part 2 ☒ ANSI/TIA/EIA-603-E ☒ ANSI C63.26-2015

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Sep. 20, 2022	Date: Sep. 20, 2022

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION.....	4
1.1 GENERAL DESCRIPTION OF EUT.....	4
2 SUMMARY OF TEST RESULTS	6
2.1 TEST RESULTS	6
2.2 MEASUREMENT UNCERTAINTY	6
2.3 TEST INSTRUMENTS.....	7
2.4 REFERENCED STANDARDS.....	8
2.5 TEST CONFIGURATIONS	9
2.6 TEST DATA.....	10
2.6.1 EUT OPERATING CONDITIONS.....	11
2.6.2 TEST RESULTS	12

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P22070038RF09	Original release	Sep. 20, 2022

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Tablet PC	
BRAND NAME	NOKIA	
MODEL NAME	TA-1505	
NOMINAL VOLTAGE	5.0Vdc(adapter or host equipment) 3.85Vdc (Li-ion, battery)	
MODULATION TYPE	BT_LE	GFSK
	Bluetooth	GFSK, $\pi/4$ -DQPSK, 8DPSK
	FM	FM
	WLAN	DSSS, OFDM
	GPS/GALILEO/GLO NASS	BPSK
	GSM/GPRS/EDGE	GMSK, 8PSK
	WCDMA	QPSK
	LTE	QPSK/16QAM/64QAM
OPERATING FREQUENCY OPERATING FREQUENCY	Bluetooth/BT_LE	2402MHz ~ 2480MHz
	FM	87.5MHz ~ 108MHz
	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20/40) 5180 ~ 5240MHz, 5260 ~ 5320 MHz, 5500 ~ 5720MHz, 5745 ~ 5825 MHz for 11a/ n(HT20)/ n(HT40) / ac(VHT20)/ ac(VHT40) / ac(VHT80)
	GPS/GALILEO/GLO NASS	1559MHz ~ 1610MHz
	GSM	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR GSM 1900)
	WCDMA	1852.4MHz ~ 1907.6MHz(FOR WCDMA Band 2) 1712.4MHz ~ 1752.6MHz(FOR WCDMA Band 4) 826.4MHz ~ 846.6MHz (FOR WCDMA Band 5)
	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 2502.5MHz ~ 2567.5MHz (FOR LTE Band7) 2505.5MHz ~ 2564.7Hz (FOR LTE Band7C) 699.7MHz ~ 715.3MHz (FOR LTE Band12)

		779.5MHz ~ 784.5MHz (FOR LTE Band13) 706.5MHz ~ 713.5MHz (FOR LTE Band17) 2572.5MHz ~ 2617.5MHz (FOR LTE Band38) 2498.5MHz ~ 2687.5MHz (FOR LTE Band41) 1710.7MHz ~ 1779.3MHz (FOR LTE Band66)
HW VERSION	EM_U1630_V1.2 L20	
SW VERSION	V0.492_B01	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable: non-shielded cable, with w/o ferrite core, 1 meter Earphone: non-shielded cable, with w/o ferrite core, 1.5 meter	
ACCESSORY DEVICES	Refer to note as below	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Battery	NOKIA	Guangdong Fenghua New Energy Co., Ltd.	WTT80	Capacity: 3.8 Vdc, 8000mAh
AC Adapter	NOKIA	Shenzhen Baijunda Electronic Co., Ltd	AD-010U	I/P: 100-240Vac, 0.35A, O/P: 5.0Vdc, 2.0A
Earphone	NOKIA	JUWEI ELECTRONICS CO., LTD	JWEP1242-W09H	Signal Line, 1.5meter
USB Cable	NOKIA	Saibao (Jiangxi) Industrial Co., Ltd	AC-2A	Signal Line, 1.0meter

2 SUMMARY OF TEST RESULTS

2.1 TEST RESULTS

TEST TYPE	Result
Radiated Emissions	Pass

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Radiated emissions & Radiated Power (30MHz~1GMHz)	±4.98dB
Radiated emissions & Radiated Power (1GMHz ~6GMHz)	±4.70dB
Radiated emissions (6GMHz ~18GMHz)	±4.60dB
Radiated emissions (18GMHz ~40GMHz)	±4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Mar. 06,22	Mar. 05,23
Horn Antenna	ETS-LINDGREN	3117	00168692	Mar. 06,22	Mar. 05,23
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Aug. 28, 21	Aug. 27, 22
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Aug. 27, 22	Aug. 26, 23
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 02,22	Jun. 01,23
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 21,22	Feb. 20,23
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May.12,22	May.11,23
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.12,22	May.11,23
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 21,22	Feb.20,23
DC Source	Kikusui/JP	PMX18-5A	0000001	Aug. 25,21	Aug. 24,22
DC Source	Kikusui/JP	PMX18-5A	0000001	Aug. 24,22	Aug. 23,23
Power Meter	Anritsu	ML2495A	1506002	Feb. 22,22	Feb. 21,23
Power Sensor	Anritsu	MA2411B	1339352	May. 14,22	May. 13,23
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.05,21	Sep. 04,22
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep. 04,22	Sep. 03,23
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.15,22	May.14,23
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 15,22	Feb. 14,23
Test Software	E3	V 9.160323	N/A	N/A	N/A
Temperature Chamber	ESPEC	SH-242	93000855	May. 12,22	May. 11,23
MXG Analog Microwave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 18,22	Feb. 17,23
Base station R&S CMW500	Rohde&Schwarz	CMW500	153085	May.12,22	May.11,23

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
 4. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2.4 Referenced Standards

The following referenced standards are necessary for the report. For undated references in this report, the cited version applies.

No.	Identify	Note
1	FCC Part 15, Subpart C, Section 15.247	For BT/BLE/2.4G WIFI
2	FCC Part 15, Subpart E, Section 15.407	For 5G WIFI
3	FCC PART 22, Subpart H	For WWAN
4	FCC PART 24, Subpart E	For WWAN
5	FCC Part 27	For WWAN

Note: More informations and test procedures pls refer to 15.247/15.407/Part22/Part24/ Part27 reports.


2.5 Test Configurations

Test Configurations	Description
Worst case test Mode	
1	2.4G WIFI(N40-CH 9)+LTE B13(5M CH 23230)
2	5G WIFI(AC80-CH 42)+LTE B13(5M CH 23230)


- Note:**
1. Test equipment and site refer to Referenced Standards report
 2. For higher frequency, the emission is 20dB below the limit was not record

2.6 Test Data


<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.6.1 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

2.6.2 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

2.4G WIFI(N40-CH9)+LTE B13(5M CH 23230):

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:

2.4G WIFI(N40-CH9)


802.11n(40MHz)

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
40.553	28.79	52.82	40	-11.21	12.81	0.37	37.21	126	120	QP
77.824	20.89	49.68	40	-19.11	7.7	0.49	36.98	115	330	QP
185.334	26.26	50.55	43.5	-17.24	11.37	0.71	36.37	100	77	QP
201.87	20.66	44.83	43.5	-22.84	11.38	0.74	36.29	200	39	QP
254.833	23.32	45.2	46	-22.68	13.55	0.84	36.27	182	311	QP
380.548	23.01	42.59	46	-22.99	15.77	1.04	36.39	102	234	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.




CHANNEL	TX Channel 9	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
36.574	29.34	50.27	40	-10.66	16.04	0.34	37.31	112	105	QP
54.52	31.26	58.61	40	-8.74	9.2	0.42	36.97	101	245	QP
140.821	26.75	53.69	43.5	-16.75	9.03	0.64	36.61	167	252	QP
185.318	18.19	42.57	43.5	-25.31	11.28	0.71	36.37	142	296	QP
273.27	21.7	43.85	46	-24.3	13.25	0.87	36.27	200	269	QP
432.8	24	42.64	46	-22	16.73	1.12	36.49	147	221	QP

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.



ABOVE 1GHz WORST-CASE DATA:

Note: 1. For radiated emissions testing, the full testing range of different modes have been scanned, only the worst case harmonic data is reported in the sheet.

2. All other emissions that more than 20dB below the limit were not recorded

802.11n40:

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.5	59.54	74	-22.5	31.75	6.18	45.97	100	145	Peak
2390	43.6	51.64	54	-10.4	31.75	6.18	45.97	100	145	Average
2452	98.51	106.25	/	/	31.95	6.26	45.95	100	145	Peak
2452	90.47	98.21	/	/	31.95	6.26	45.95	100	145	Average
2483.5	58.51	66.08	74	-15.49	32.05	6.31	45.93	100	145	Peak
2483.5	50.58	58.15	54	-3.42	32.05	6.31	45.93	100	145	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	51.27	58.92	74	-22.73	32.14	6.18	45.97	100	245	Peak
2390	42.89	50.54	54	-11.11	32.14	6.18	45.97	100	245	Average
2452	94.53	101.94	/	/	32.28	6.26	45.95	100	245	Peak
2452	85.84	93.25	/	/	32.28	6.26	45.95	100	245	Average
2483.5	56.28	63.54	74	-17.72	32.36	6.31	45.93	100	245	Peak
2483.5	48.95	56.21	54	-5.05	32.36	6.31	45.93	100	245	Average

REMARKS:


- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 2452MHz: Fundamental frequency.

LTE B13

CHANNEL BANDWIDTH: 5MHz / QPSK


MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1572.000	-55.10	-55.26	-40.00	-15.10	0.16	Peak	Horizontal
2		2346.000	-52.77	-57.65	-13.00	-39.77	4.88	Peak	Horizontal



MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1564.000	-56.50	-56.93	-40.00	-16.50	0.43	Peak	Vertical
2	2352.000	-54.11	-58.65	-13.00	-41.11	4.54	Peak	Vertical



NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

5G WIFI(AC80-CH42)+LTE B13(5M CH 23230):

BELOW 1GHz WORST-CASE DATA:

30MHz – 1GHz data:

5G WIFI(AC80-CH42)

Band1


802.11ac (80MHz)

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
38.928	33.62	56.23	40	-6.38	14.28	0.36	37.25	198	298	QP
78.318	21.49	50.28	40	-18.51	7.7	0.49	36.98	190	145	QP
185.348	25.02	49.31	43.5	-18.48	11.37	0.71	36.37	177	76	QP
310.58	21.56	42.68	46	-24.44	14.23	0.93	36.28	145	51	QP
438.28	26.66	45.1	46	-19.34	16.93	1.13	36.5	159	206	QP
538.928	20.6	37.31	46	-25.4	18.72	1.28	36.71	150	218	QP

REMARKS:

1. Emission level (dBuV/m) = Read level (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.




CHANNEL	TX Channel 42	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
43.288	26.24	51.28	40	-13.76	11.74	0.37	37.15	177	338	QP
90.318	27.82	55.61	43.5	-15.68	8.62	0.51	36.92	179	223	QP
173.618	19	43.63	43.5	-24.5	11.1	0.7	36.43	173	46	QP
360.34	22.59	42.55	46	-23.41	15.39	1.01	36.36	149	227	QP
431.928	24.03	42.67	46	-21.97	16.72	1.12	36.48	163	143	QP
490.555	22.37	40.28	46	-23.63	17.48	1.21	36.6	181	274	QP

REMARKS:

1. Emission level (dBuV/m) = Read level (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

802.11ac (80MHz)

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	58.27	59.34	74	-15.73	34.52	9.92	45.51	100	180	Peak
5150	50.75	51.82	54	-3.25	34.52	9.92	45.51	100	180	Average
5210	92.01	93.05	/	/	34.57	9.9	45.51	100	180	Peak
5210	84.89	85.93	/	/	34.57	9.9	45.51	100	180	Average
5350	55.34	56.32	74	-18.66	34.68	9.85	45.51	100	180	Peak
5350	47.69	48.67	54	-6.31	34.68	9.85	45.51	100	180	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	54.94	55.93	74	-19.06	34.6	9.92	45.51	100	295	Peak
5150	50.07	51.06	54	-3.93	34.6	9.92	45.51	100	295	Average
5210	85.34	86.35	/	/	34.6	9.9	45.51	100	295	Peak
5210	79.26	80.27	/	/	34.6	9.9	45.51	100	295	Average
5350	54.29	55.35	74	-19.71	34.6	9.85	45.51	100	295	Peak
5350	48.1	49.16	54	-5.9	34.6	9.85	45.51	100	295	Average

REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 5210MHz: Fundamental frequency.

LTE B13

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1572.000	-53.15	-53.31	-40.00	-13.15	0.16	Peak	Horizontal
2	2346.000	-53.73	-58.61	-13.00	-40.73	4.88	Peak	Horizontal



MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1564.000	-54.97	-55.40	-40.00	-14.97	0.43	Peak	Vertical
2		2352.000	-53.38	-57.92	-13.00	-40.38	4.54	Peak	Vertical

