

FCC TEST REPORT

(PART 22)

Applicant:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland

Manufacturer or Supplier:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland
Product:	Mobile phone
Brand Name:	HMD
Model Name:	H1715V
FCC ID	2AJOTTA-1715
Date of tests	Jan. 13, 2025 ~ Mar. 20, 2025

The tests have been carried out according to the requirements of the following standard:

☒ **FCC PART 22, Subpart H**
☒ **ANSI/TIA/EIA-603-D**
☒ **ANSI/TIA/EIA-603-E**

☒ **FCC Part 2**
☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
	
Date: Mar. 20, 2025	Date: Mar. 20, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
1.1 MEASUREMENT UNCERTAINTY	6
1.2 TEST SITE AND INSTRUMENTS	7
2 GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 CONFIGURATION OF SYSTEM UNDER TEST	11
2.3 DESCRIPTION OF SUPPORT UNITS	12
2.4 TEST ITEM AND TEST CONFIGURATION.....	13
2.5 EUT OPERATING CONDITIONS	15
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
3 TEST TYPES AND RESULTS.....	16
3.1 OUTPUT POWER MEASUREMENT.....	16
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	16
3.1.2 TEST PROCEDURES	16
3.1.3 TEST SETUP.....	17
3.1.4 TEST RESULTS	17
CA_5B(ANT2)	18
3.2 FREQUENCY STABILITY MEASUREMENT.....	22
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	22
3.2.2 TEST PROCEDURE.....	22
3.2.3 TEST SETUP	22
3.2.4 TEST RESULTS	22
3.3 OCCUPIED BANDWIDTH MEASUREMENT	23
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT	23
3.3.2 TEST SETUP.....	23
3.3.3 TEST PROCEDURES	23
3.3.4 TEST RESULTS	23
3.4 BAND EDGE MEASUREMENT.....	24
3.4.1 LIMITS OF BAND EDGE MEASUREMENT	24
3.4.2 TEST SETUP	24
3.4.3 TEST PROCEDURES	25
3.4.4 TEST RESULTS	25
3.5 CONDUCTED SPURIOUS EMISSIONS	26
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	26
3.5.2 TEST PROCEDURE.....	26
3.5.3 TEST SETUP.....	26
3.5.4 TEST RESULTS	26
3.6 RADIATED EMISSION MEASUREMENT	27
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	27
3.6.2 TEST PROCEDURES	27
3.6.3 DEVIATION FROM TEST STANDARD	27
3.6.4 TEST SETUP	28
3.6.5 TEST RESULTS	30
3.7 PEAK TO AVERAGE RATIO	56
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	56
3.7.2 TEST SETUP	56
3.7.3 TEST PROCEDURES	56
3.7.4 TEST RESULTS	57
4 PHOTOGRAPHS OF THE TEST CONFIGURATION	58
5 INFORMATION ON THE TESTING LABORATORIES	59
6 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	60
7 APPENDIX:.....	61
CA_5B.....	61
26DB BANDWIDTH AND OCCUPIED BANDWIDTH.....	61
TEST RESULT	61
TEST GRAPHS	62
BAND EDGE.....	70



Test Report No.: PSU-NQN2412090210RF06

TEST RESULT	70
TEST GRAPHS	70
CONDUCTED SPURIOUS EMISSION	73
TEST RESULT	73
TEST GRAPHS	73



Test Report No.: PSU-NQN2412090210RF06

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-NQN2412090210RF06	Original release	Mar. 20, 2025



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	Test lab*
§2.1046	Conducted Output Power	Compliance	A
§22.913 (a)(5)	Equivalent Isotropic Radiated Power	Compliance	A
§2.1055 §22.355	Frequency Stability	Compliance	A
§2.1049	Occupied Bandwidth	Compliance	A
§22.913 (d)	Peak to average ratio*	Compliance	A
§2.1051 §22.917(a)	Band Edge Measurements	Compliance	A
§2.1051 §22.917(a)	Conducted Spurious Emissions	Compliance	A
§2.1053 §22.917(a)	Radiated Spurious Emissions	Compliance	A

* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

*Test Lab Information Reference

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Maximum Peak Output Power	$\pm 2.06\text{dB}$
Frequency Stability	$\pm 76.97\text{Hz}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Band Edge Measurements	$\pm 4.70\text{dB}$
Peak to average ratio	$\pm 0.76\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,24	Aug.28,26
Pre-Amplifier	R&S	SCU08F1	101028	Sep.15,24	Sep.14,26
Vector Signal Generator	R&S	SMBV100B	102176	Feb.15,24	Feb.14,26
Signal Generator	R&S	SMB100A	182185	Feb.15,24	Feb.14,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESR26	101734	Feb.24,24	Feb.23,26
EMI TEST Receiver	R&S	ESW44	101973	Feb.24,24	Feb.23,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.27,24	Feb.26,26
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.21,24	Aug.20,26
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Feb.22,24	Feb.21,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.21,24	Aug.20,26
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,24	Feb.21,26
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.26,24	Jun.25,26
Test Software	EMC32	EMC32	N/A	N/A	N/A
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	Sep.30,24	Sep.39,26
DC Source	HYELEC	HY3010B	551016	Aug.30,24	Aug.29,26
Hygrothermograph	DELI	20210528	SZ014	Sep.05,24	Sep.04,26
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.26,24	Oct.25,25
CABLE	R&S	W12.14	N/A	Apr.26,24	Oct.25,25
CABLE	R&S	J12J103539-00-1	SEP-03-20-069	Apr.26,24	Oct.25,25
CABLE	R&S	J12J103539-00-1	SEP-03-20-070	Apr.26,24	Oct.25,25
Temperature Chamber	votsch	VT4002	58566078100050	May.30,24	May.29,26

NOTE:

1. The calibration interval of the above test instruments is 6 months or 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	Mobile phone	
BRAND NAME*	HMD	
MODEL NAME*	H1715V	
NOMINAL VOLTAGE*	3.87Vdc(Battery) 5.0Vdc(Adapter)	
MODULATION TYPE	LTE	QPSK, 16QAM, 64QAM, 256QAM
FREQUENCY RANGE	LTE Band CA_5B (Channel Bandwidth: 10MHz-10MHz)	829MHz ~ 844MHz
	LTE Band CA_5B (Channel Bandwidth: 10MHz-5MHz)	829MHz ~ 846.2MHz
	LTE Band CA_5B (Channel Bandwidth: 3MHz-5MHz)	825.6MHz ~ 846.5MHz
	LTE Band CA_5B (Channel Bandwidth: 5MHz-10MHz)	826.8MHz ~ 844MHz
	LTE Band CA_5B (Channel Bandwidth: 5MHz-3MHz)	826.5MHz ~ 847.4MHz
	CA	CA_2A-5A CA_4A-5A
MAX. ERP POWER	LTE Band CA_5B (Channel Bandwidth: 10MHz-10MHz)	69.34mW
	LTE Band CA_5B (Channel Bandwidth: 10MHz-5MHz)	66.53mW
	LTE Band CA_5B (Channel Bandwidth: 3MHz-5MHz)	63.39mW
	LTE Band CA_5B (Channel Bandwidth: 5MHz-10MHz)	66.07mW
	LTE Band CA_5B (Channel Bandwidth: 5MHz-3MHz)	65.01mW
EMISSION DESIGNATORGOGN	LTE Band CA_5B (Channel Bandwidth: 10MHz-10MHz)	QPSK: 19M0G7D
		16QAM: 19M0W7D
	LTE Band CA_5B (Channel Bandwidth: 10MHz-5MHz)	QPSK: 14M2G7D
		16QAM: 14M2W7D



	LTE Band CA_5B (Channel Bandwidth: 3MHz-5MHz)	QPSK: 7M57G7D
		16QAM: 7M56W7D
	LTE Band CA_5B (Channel Bandwidth: 5MHz-10MHz)	QPSK: 14M2G7D
		16QAM: 14M2W7D
	LTE Band CA_5B (Channel Bandwidth: 5MHz-3MHz)	QPSK: 7M58G7D
		16QAM: 7M55W7D
ANTENNA GAIN*	LTE CA_5B	-4.2dBi
ANTENNA TYPE*	PIFA	
HW VERSION*	V1.0	
SW VERSION*	000T_0_310	
I/O PORTS*	Refer to user's manual	
CABLE SUPPLIED*	N/A	
EXTREME TEMPERATURE*	-10°C-55°C	
EXTREME VOLTAGE*	3.6V-4.45V	

NOTE:

1. *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receivers.

MODULATION MODE	TX FUNCTION
LTE	1TX/1RX

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in the test report.
5. The power of single LTE band is larger than that in CA mode, so single LTE band can cover the RSE risk of CA part.
6. The differences between the sample 1 and sample 2 as Listings below, others are the same. And only the worst case was shown in the test report.

Object	Sample 1 1 st source		Sample 2 2 nd source	
	Specifications	Supplier	Specifications	Supplier
Display	JL-P067P003-05	Jinglong	Y92321	Digital



Memory (RAM) Memory (ROM)	FLXC2004G-N1	Longsys	BWCGBX32N2A-32G	Biwin
	MEMDNN064G-M1D03	Longsys	BWCTAMV11X64G	Biwin
Motor	C0830H-C138ZN-021	KunWang	CY0830-05-FPC-182	Chaoying
FPS Side fingerprint	SA-FC15X00-1470-B0	Shenao	HT.ZN-2832B	Huate
Mic	SM2718B381YR2-01	Rayking	S150B381-155	Goertek
GPS LNA	AW5005EDNR	AWINIC	WS7916DE	WILL



List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Battery	HMD	HUNAN GAOYUAN BATTERY CO.,LTD	CH426385	Capacity: 3.87Vdc, 4000mAh
USB Cable	Saibao	Saibao (Jiangxi) Industry Co.,Ltd.	SZN-A046A	Signal Line,1.0meter
USB Cable	Juwei	Huizhou Juwei Electronics Co.,Ltd	JWUB1913-ZN01H	Signal Line,1.0meter
Adapter	HMD	Shenzhen Baijunda Electronic Co., Ltd.	HAD-010U	I/P: 100- 240 Vac, 50/60Hz, 0.35 A, O/P: 5.0 Vdc, 2.0A 10.0W



2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION





2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	ThinkPad E14	HRSW00024	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in ERP and radiated emission was found when positioned on X-plane for GSM /EDGE /WCDMA /LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter with GSM or WCDMA or LTE link
B	EUT + DC Supply with GSM or WCDMA or LTE link

CA_5B MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE PCC CHANNEL	AVAILABLE SCC CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE(PCC)	MODE(SCC)
A	ERP	20450 to 21501	20549 to 20600	Low, Middle, High	10MHz+10MHz	QPSK, 16QAM, 64QAM, 256QAM	1RB/ 49RB Offset	1RB/ 0RB Offset
		20450 to 20550	20522 to 20622	Low, Middle, High	10MHz+5MHz	QPSK, 16QAM, 64QAM, 256QAM	1RB/ 49RB Offset	1RB/ 0RB Offset
		20428 to 20528	20500 to 20600	Low, Middle, High	5MHz+10MHz	QPSK, 16QAM, 64QAM, 256QAM	1RB/ 24RB Offset	1RB/ 0RB Offset
		20425 to 20595	20464 to 20634	Low, Middle, High	5MHz+3MHz	QPSK, 16QAM, 64QAM, 256QAM	1RB/ 24RB Offset	1RB/ 0RB Offset
		20416 to 20586	20455 to 20625	Low, Middle, High	3MHz+5MHz	QPSK, 16QAM, 64QAM, 256QAM	1RB/ 14RB Offset	1RB/ 0RB Offset
A	OCCUPIED BANDWIDTH	20450 to 21501	20549 to 20600	Low, Middle, High	10MHz+10MHz	QPSK, 16QAM	50RB/ 0RB Offset	50RB/ 0RB Offset
		20450 to 20550	20522 to 20622	Low, Middle, High	10MHz+5MHz	QPSK, 16QAM	25RB/ 0RB Offset	25RB/ 0RB Offset
		20428 to 20528	20500 to 20600	Low, Middle, High	5MHz+10MHz	QPSK, 16QAM	25RB/ 0RB Offset	50RB/ 0RB Offset
		20425 to 20595	20464 to 20634	Low, Middle, High	5MHz+3MHz	QPSK, 16QAM	25RB/ 0RB Offset	15RB/ 0RB Offset
		20416 to 20586	20455 to 20625	Low, Middle, High	3MHz+5MHz	QPSK, 16QAM	15RB/ 0RB Offset	25RB/ 0RB Offset
A	BAND EDGE	20450 to 21501	20549 to 20600	Low	10MHz+10MHz	QPSK, 16QAM	1RB/ 0RB Offset	1RB/ 50RB Offset
							1RB/ 49RB Offset	50RB/ 0RB Offset
							50RB/ 0RB Offset	50RB/ 0RB Offset
				High	10MHz+10MHz	QPSK, 16QAM	1RB/ 0RB Offset	1RB/ 50RB Offset
							1RB/ 49RB Offset	50RB/ 0RB Offset
							50RB/ 0RB Offset	50RB/ 0RB Offset
A	CONDUCTED EMISSION	20850 to 21152	21048 to 21350	Low, Middle, High	10MHz+10MHz	QPSK, 16QAM	1RB/ 49RB Offset	1RB/ 0RB Offset
A	RADIATED EMISSION	20428 to 20528	20500 to 20600	Middle	5MHz+10MHz	QPSK	1RB/ 99RB Offset	1RB/ 0RB Offset
		20416 to 20586	20455 to 20625	Middle	3MHz+5MHz	QPSK	1RB/ 99RB Offset	1RB/ 0RB Offset



		20450 to 20550	20522 to 20622	Middle	10MHz+5MHz	QPSK	1RB/ 99RB Offset	1RB/ 0RB Offset
		20850 to 21152	21048 to 21350	Low, Middle, High	10MHz+10MHz	QPSK	1RB/ 99RB Offset	1RB/ 0RB Offset

Note: 1.This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION			
TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	23deg. C, 70%RH	DC 3.87V By Battery	Hanwen Xu
FREQUENCY STABILITY	23deg. C, 70%RH	DC 3.87V By Battery	Hanwen Xu
OCCUPIED BANDWIDTH	23deg. C, 70%RH	DC 3.87V By Battery	Hanwen Xu
BAND EDGE	23deg. C, 70%RH	DC 3.87V By Battery	Hanwen Xu
CONDCUDED EMISSION	23deg. C, 70%RH	DC 3.87V By Battery	Hanwen Xu
RADIATED EMISSION	23deg. C, 70%RH	AC 120V/60Hz	Hanwen Xu
PEAK TO AVERAGE RATIO	23deg. C, 70%RH	DC 3.87V By Battery	Hanwen Xu

2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

3.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

CONDUCTED POWER MEASUREMENT:


The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.



3.1.3 TEST SETUP

EIRP / ERP Measurement:

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm):



CA_5B(Ant2)

CA_5B (Ant2)										
Combination 10MHz+10MHz (50RB+50RB)										
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Total RB Size	Measured Power (dBm)
					RB Size	RB offset	RB Size	RB offset		
20450	829	20549	838.9	QPSK	1	49	1	0	1	24.76
				16QAM	1	49	1	0	1	23.92
				64QAM	1	49	1	0	1	22.61
				256QAM	1	49	1	0	1	19.73
20476	831.6	20575	841.5	QPSK	1	49	1	0	1	24.73
				16QAM	1	49	1	0	1	23.93
				64QAM	1	49	1	0	1	22.44
				256QAM	1	49	1	0	1	19.82
20501	834.1	20600	844	QPSK	1	49	1	0	1	24.62
				16QAM	1	49	1	0	1	23.91
				64QAM	1	49	1	0	1	22.25
				256QAM	1	49	1	0	1	19.78
Combination 10MHz+5MHz (50RB+25RB)										
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Total RB Size	Measured Power (dBm)
					RB Size	RB offset	RB Size	RB offset		
20450	829	20522	836.2	QPSK	1	49	1	0	1	24.58
				16QAM	1	49	1	0	1	23.81
				64QAM	1	49	1	0	1	22.48
				256QAM	1	49	1	0	1	19.49
20500	834	20572	841.2	QPSK	1	49	1	0	1	24.53
				16QAM	1	49	1	0	1	23.83
				64QAM	1	49	1	0	1	22.37
				256QAM	1	49	1	0	1	19.63
20550	839	20622	846.2	QPSK	1	49	1	0	1	24.46
				16QAM	1	49	1	0	1	23.70
				64QAM	1	49	1	0	1	22.13
				256QAM	1	49	1	0	1	19.54
Combination 5MHz+10MHz (25RB+50RB)										
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Total RB Size	Measured Power (dBm)
					RB Size	RB offset	RB Size	RB offset		
20428	826.8	20500	834	QPSK	1	24	1	0	1	24.54
				16QAM	1	24	1	0	1	23.82
				64QAM	1	24	1	0	1	22.55
				256QAM	1	24	1	0	1	19.50
20478	831.8	20550	839	QPSK	1	24	1	0	1	24.55
				16QAM	1	24	1	0	1	23.76
				64QAM	1	24	1	0	1	22.36
				256QAM	1	24	1	0	1	19.61
20528	836.8	20600	844	QPSK	1	24	1	0	1	24.49
				16QAM	1	24	1	0	1	23.70
				64QAM	1	24	1	0	1	22.10
				256QAM	1	24	1	0	1	19.53



Combination 5MHz+3MHz (25RB+15RB)										
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Total RB Size	Measured Power (dBm)
					RB Size	RB offset	RB Size	RB offset		
20425	826.5	20464	830.4	QPSK	1	24	1	0	1	24.48
				16QAM	1	24	1	0	1	23.57
				64QAM	1	24	1	0	1	22.52
				256QAM	1	24	1	0	1	19.42
20510	835	20549	838.9	QPSK	1	24	1	0	1	24.41
				16QAM	1	24	1	0	1	23.78
				64QAM	1	24	1	0	1	22.25
				256QAM	1	24	1	0	1	19.65
20595	843.5	20634	847.4	QPSK	1	24	1	0	1	24.33
				16QAM	1	24	1	0	1	23.76
				64QAM	1	24	1	0	1	22.04
				256QAM	1	24	1	0	1	19.46
Combination 3MHz+5MHz (15RB+25RB)										
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Total RB Size	Measured Power (dBm)
					RB Size	RB offset	RB Size	RB offset		
20416	825.6	20455	829.5	QPSK	1	14	1	0	1	24.37
				16QAM	1	14	1	0	1	23.57
				64QAM	1	14	1	0	1	22.54
				256QAM	1	14	1	0	1	19.45
20501	834.1	20540	838	QPSK	1	14	1	0	1	24.35
				16QAM	1	14	1	0	1	23.65
				64QAM	1	14	1	0	1	22.28
				256QAM	1	14	1	0	1	19.57
20586	842.6	20625	846.5	QPSK	1	14	1	0	1	24.28
				16QAM	1	14	1	0	1	23.66
				64QAM	1	14	1	0	1	22.10
				256QAM	1	14	1	0	1	19.46



ERP POWER (dBm)

CA_5B_Ant2													
Combination 10MHz+10MHz (50RB+50RB)													
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Measured Power (dBm)	Gain (dBi)	ERP (dBm)	ERP (mW)	FCC Limit (W)
					RB Size	RB offset	RB Size	RB offset					
20450	829	20549	838.9	QPSK	1	49	1	0	24.76	-4.20	18.41	69.34	7
				16QAM	1	49	1	0	23.92	-4.20	17.57	57.15	7
				64QAM	1	49	1	0	22.61	-4.20	16.26	42.27	7
				256QAM	1	49	1	0	19.73	-4.20	13.38	21.78	7
20476	831.6	20575	841.5	QPSK	1	49	1	0	24.73	-4.20	18.38	68.87	7
				16QAM	1	49	1	0	23.93	-4.20	17.58	57.28	7
				64QAM	1	49	1	0	22.44	-4.20	16.09	40.64	7
				256QAM	1	49	1	0	19.82	-4.20	13.47	22.23	7
20501	834.1	20600	844	QPSK	1	49	1	0	24.62	-4.20	18.27	67.14	7
				16QAM	1	49	1	0	23.91	-4.20	17.56	57.02	7
				64QAM	1	49	1	0	22.25	-4.20	15.90	38.90	7
				256QAM	1	49	1	0	19.78	-4.20	13.43	22.03	7
Combination 10MHz+5MHz (50RB+25RB)													
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Measured Power (dBm)	Gain (dBi)	ERP (dBm)	ERP (mW)	FCC Limit (W)
					RB Size	RB offset	RB Size	RB offset					
20450	829	20522	836.2	QPSK	1	49	1	0	24.58	-4.20	18.23	66.53	7
				16QAM	1	49	1	0	23.81	-4.20	17.46	55.72	7
				64QAM	1	49	1	0	22.48	-4.20	16.13	41.02	7
				256QAM	1	49	1	0	19.49	-4.20	13.14	20.61	7
20500	834	20572	841.2	QPSK	1	49	1	0	24.53	-4.20	18.18	65.77	7
				16QAM	1	49	1	0	23.83	-4.20	17.48	55.98	7
				64QAM	1	49	1	0	22.37	-4.20	16.02	39.99	7
				256QAM	1	49	1	0	19.63	-4.20	13.28	21.28	7
20550	839	20622	846.2	QPSK	1	49	1	0	24.46	-4.20	18.11	64.71	7
				16QAM	1	49	1	0	23.70	-4.20	17.35	54.33	7
				64QAM	1	49	1	0	22.13	-4.20	15.78	37.84	7
				256QAM	1	49	1	0	19.54	-4.20	13.19	20.84	7
Combination 3MHz+5MHz (15RB+25RB)													
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Measured Power (dBm)	Gain (dBi)	ERP (dBm)	ERP (mW)	FCC Limit (W)
					RB Size	RB offset	RB Size	RB offset					
20416	825.6	20455	829.5	QPSK	1	14	1	0	24.37	-4.20	18.02	63.39	7
				16QAM	1	14	1	0	23.57	-4.20	17.22	52.72	7
				64QAM	1	14	1	0	22.54	-4.20	16.19	41.59	7
				256QAM	1	14	1	0	19.45	-4.20	13.10	20.42	7
20501	834.1	20540	838	QPSK	1	14	1	0	24.35	-4.20	18.00	63.10	7
				16QAM	1	14	1	0	23.65	-4.20	17.30	53.70	7
				64QAM	1	14	1	0	22.28	-4.20	15.93	39.17	7
				256QAM	1	14	1	0	19.57	-4.20	13.22	20.99	7
20586	842.6	20625	846.5	QPSK	1	14	1	0	24.28	-4.20	17.93	62.09	7
				16QAM	1	14	1	0	23.66	-4.20	17.31	53.83	7
				64QAM	1	14	1	0	22.10	-4.20	15.75	37.58	7
				256QAM	1	14	1	0	19.46	-4.20	13.11	20.46	7



Combination 5MHz+10MHz (25RB+50RB)													
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Measured Power (dBm)	Gain (dBi)	ERP (dBm)	ERP (mW)	FCC Limit (W)
					RB Size	RB offset	RB Size	RB offset					
20428	826.8	20500	834	QPSK	1	24	1	0	24.54	-4.20	18.19	65.92	7
				16QAM	1	24	1	0	23.82	-4.20	17.47	55.85	7
				64QAM	1	24	1	0	22.55	-4.20	16.20	41.69	7
				256QAM	1	24	1	0	19.50	-4.20	13.15	20.65	7
20478	831.8	20550	839	QPSK	1	24	1	0	24.55	-4.20	18.20	66.07	7
				16QAM	1	24	1	0	23.76	-4.20	17.41	55.08	7
				64QAM	1	24	1	0	22.36	-4.20	16.01	39.90	7
				256QAM	1	24	1	0	19.61	-4.20	13.26	21.18	7
20528	836.8	20600	844	QPSK	1	24	1	0	24.49	-4.20	18.14	65.16	7
				16QAM	1	24	1	0	23.70	-4.20	17.35	54.33	7
				64QAM	1	24	1	0	22.10	-4.20	15.75	37.58	7
				256QAM	1	24	1	0	19.53	-4.20	13.18	20.80	7
Combination 5MHz+3MHz (25RB+15RB)													
PCC Channel	PCC Frequency (MHz)	SCC Channel	SCC Frequency (MHz)	Modulation	PCC		SCC		Measured Power (dBm)	Gain (dBi)	ERP (dBm)	ERP (mW)	FCC Limit (W)
					RB Size	RB offset	RB Size	RB offset					
20425	826.5	20464	830.4	QPSK	1	24	1	0	24.48	-4.20	18.13	65.01	7
				16QAM	1	24	1	0	23.57	-4.20	17.22	52.72	7
				64QAM	1	24	1	0	22.52	-4.20	16.17	41.40	7
				256QAM	1	24	1	0	19.42	-4.20	13.07	20.28	7
20510	835	20549	838.9	QPSK	1	24	1	0	24.41	-4.20	18.06	63.97	7
				16QAM	1	24	1	0	23.78	-4.20	17.43	55.34	7
				64QAM	1	24	1	0	22.25	-4.20	15.90	38.90	7
				256QAM	1	24	1	0	19.65	-4.20	13.30	21.38	7
20595	843.5	20634	847.4	QPSK	1	24	1	0	24.33	-4.20	17.98	62.81	7
				16QAM	1	24	1	0	23.76	-4.20	17.41	55.08	7
				64QAM	1	24	1	0	22.04	-4.20	15.69	37.07	7
				256QAM	1	24	1	0	19.46	-4.20	13.11	20.46	7

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP



3.2.4 TEST RESULTS

Please Refer to Appendix of this test report.




3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.4 TEST RESULTS

Please Refer to Appendix of this test report.




3.4 BAND EDGE MEASUREMENT

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.4.2 TEST SETUP





3.4.3 TEST PROCEDURES

- a) All measurements were done at low and high operational frequency range
- b) Connect the transmitter to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.
- c) Tune the analyzer to the nominal center frequency of the emission bandwidth

(EBW)
- d) .Set the resolution bandwidth (RBW) $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
- e) Beyond the 1MHz band from the band edge, RBW=1MHz was used.
- f) Set the video bandwidth (VBW) to $\geq 3 \times$ RBW.
- g) Select the average power (RMS) display detector.
- h) Set the number of measurement points to ≥ 1001 .
- i) Use auto-coupled sweep time.
- j) Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.
- k) The RF fundamental frequency should be excluded against the limit line in the operating frequency band and use RBW is 10KHz or 100KHz.
- l) Record the max trace plot into the test report.

3.4.4 TEST RESULTS

Please Refer to Appendix of this test report.



3.5 CONDUCTED SPURIOUS EMISSIONS


3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.5.2 TEST PROCEDURE

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9kHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP



3.5.4 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

Please Refer to Appendix of this test report.



3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,
 $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}.$

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


3.6.3 DEVIATION FROM TEST STANDARD

No deviation





3.6.4 TEST SETUP

< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >





Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



3.6.5 TEST RESULTS


NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA

LTE CA_5B			
MODE	TX channel PCC 20450	FREQUENCY RANGE	Below 1000MHz
	TX channel SCC 20549		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	37.600	-69.15	-13.00	56.15	0.16	H	1	1.00
1	65.050	-76.43	-13.00	63.43	-6.30	H	355.7	2.00
1	120.100	-81.04	-13.00	68.04	-12.51	H	218	1.00
1	194.750	-74.45	-13.00	61.45	-4.99	H	49.9	2.00
1	232.450	-74.93	-13.00	61.93	1.56	H	49.9	2.00
1	281.600	-72.75	-13.00	59.75	-1.54	H	218	1.00






MODE	TX channel PCC 20450	FREQUENCY RANGE	Below 1000MHz
	TX channel SCC 20549		
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	32.800	-70.51	-13.00	57.51	-6.90	V	1	2.00
1	58.500	-74.90	-13.00	61.90	-3.60	V	355.7	2.00
1	99.150	-64.13	-13.00	51.13	5.03	V	247.9	1.00
1	195.100	-79.60	-13.00	66.60	-6.74	V	45	2.00
1	285.900	-76.22	-13.00	63.22	-1.11	V	138.3	2.00
1	433.350	-76.10	-13.00	63.10	1.32	V	338.4	1.00





**ABOVE 1GHz DATA****Note:** For higher frequency, the emission is too low to be detected.**LTE Band CA_2A-5A**

CHANNEL BANDWIDTH	(20+10) MHz / QPSK	MODE	TX channel 20525
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,649.000	-45.30	-13.00	32.30	24.43	H	212.9	1.00
3	2,473.500	-49.77	-13.00	36.77	20.30	H	130.8	2.00
4	3,702.000	-50.85	-13.00	37.85	21.12	H	250.3	2.00
4	5,553.000	-45.93	-13.00	32.93	24.26	H	1	1.00







**LTE Band CA_2A-5A**


CHANNEL BANDWIDTH	(20+10) MHz / QPSK	MODE	TX channel 20525
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,664.000	-44.88	-13.00	31.88	24.99	H	322.6	2.00
3	2,496.000	-49.52	-13.00	36.52	20.76	H	56.6	2.00
4	3,742.000	-49.02	-13.00	36.02	21.35	H	48	2.00
4	5,613.000	-50.35	-13.00	37.35	24.60	H	130.8	2.00













LTE Band CA_4A-5A

CHANNEL BANDWIDTH	(20+10) MHz / QPSK	MODE	TX channel 20525
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,649.000	-44.53	-13.00	31.53	24.43	H	36.7	1.00
3	2,473.500	-49.58	-13.00	36.58	20.30	H	1	2.00
4	3,422.000	-52.47	-13.00	39.47	20.52	H	359	2.00
4	5,133.000	-50.22	-13.00	37.22	23.57	H	358.5	1.00









LTE Band CA_4A-5A


CHANNEL BANDWIDTH	(20+10) MHz / QPSK	MODE	TX channel 20525
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,664.000	-44.58	-13.00	31.58	24.99	H	316.9	2.00
3	2,496.000	-49.20	-13.00	36.20	20.76	H	73.4	1.00
4	3,447.000	-50.30	-13.00	37.30	20.34	H	1	1.00
4	5,170.500	-48.40	-13.00	35.40	23.73	H	331	1.00













LTE Band CA_5B

CHANNEL BANDWIDTH	(3+5) MHz / QPSK	MODE	TX channel PCC 20501
			TX channel SCC 20540
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,665.500	-51.88	-13.00	38.88	19.58	H	72.4	1.00
2	1,671.500	-50.30	-13.00	37.30	19.83	H	288.8	2.00
3	2,498.250	-46.61	-13.00	33.61	23.86	H	0.9	2.00
3	2,507.250	-48.48	-13.00	35.48	23.82	H	359.1	1.00









LTE Band CA_5B

CHANNEL BANDWIDTH	(5+10) MHz / QPSK	MODE	TX channel PCC 20478
			TX channel SCC 20550
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,659.100	-52.42	-13.00	39.42	19.29	H	283.9	2.00
2	1,669.000	-50.67	-13.00	37.67	19.73	H	359	1.00
3	2,488.650	-48.10	-13.00	35.10	23.94	H	209.8	2.00
3	2,503.500	-47.57	-13.00	34.57	23.84	H	1	2.00









LTE Band CA_5B

CHANNEL BANDWIDTH	(10+5) MHz / QPSK	MODE	TX channel PCC 20500
			TX channel SCC 20572
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,659.000	-51.46	-13.00	38.46	19.29	H	288.8	2.00
2	1,677.900	-51.57	-13.00	38.57	20.12	H	359	2.00
3	2,488.500	-47.97	-13.00	34.97	23.94	H	0.9	2.00
3	2,516.850	-47.75	-13.00	34.75	24.36	H	1	1.00









LTE Band CA_5B

CHANNEL BANDWIDTH	(10+10) MHz / QPSK	MODE	TX channel PCC 20450
			TX channel SCC 20549
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,649.000	-52.28	-13.00	39.28	18.65	H	359	2.00
2	1,668.800	-51.68	-13.00	38.68	19.73	H	359	2.00
3	2,473.500	-47.08	-13.00	34.08	24.39	H	359	2.00
3	2,503.200	-47.86	-13.00	34.86	23.84	H	359	1.00









LTE Band CA_5B

CHANNEL BANDWIDTH	(10+10) MHz / QPSK	MODE	TX channel PCC 20476
			TX channel SCC 20575
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,645.200	-52.08	-13.00	39.08	18.07	H	1	2.00
2	1,674.000	-51.47	-13.00	38.47	19.77	H	1	2.00
3	2,481.300	-46.24	-13.00	33.24	23.95	H	359	2.00
3	2,511.000	-47.71	-13.00	34.71	23.55	H	1	1.00









LTE Band CA_5B

CHANNEL BANDWIDTH	(10+10) MHz / QPSK	MODE	TX channel PCC 20501
			TX channel SCC 20600
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	AC 120V/60Hz	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	1,659.200	-52.34	-13.00	39.34	19.29	H	359	2.00
2	1,679.000	-51.77	-13.00	38.77	20.17	H	285.3	2.00
3	2,488.800	-48.35	-13.00	35.35	23.92	H	144.2	1.00
3	2,518.500	-47.05	-13.00	34.05	24.47	H	144.2	1.00








3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.



3.7.4 TEST RESULTS

Please Refer to Appendix of this test report.



4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



5 INFORMATION ON THE TESTING LABORATORIES

We, Huarui 7layers High Technology (Suzhou) Co., Ltd. ,were founded in 2020 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

If you have any comments, please feel free to contact us at the following:

Suzhou EMC/RF Lab:

Tel: +86 (0557) 368 1008



6 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.