

## Maximum Permissible Exposure

Applicable Standard According to §1.1307(b)(5), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

### For 2.4G WIFI

- 1) The maximum output power is 10.33dBm (10.79mW) at 2437MHz, (with 3.16 numeric antenna gain.)
- 2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

#### Calculation

Given  $E = \sqrt{\frac{30 \times P \times G}{d}}$  &  $S = \frac{E^2}{3770}$

Where  $E$  = Field Strength in Volts / meter  
 $P$  = Power in Watts  
 $G$  = Numeric antenna gain  
 $d$  = Distance in meters  
 $S$  = Power Density in milliwatts / square centimeter

Maximum Permissible Exposure

output power=10.79mW

Numeric Antenna gain=3.16

Substituting the MPE safe distance using  $d=20\text{cm}$  into above equation.

Yields:

$$S=0.000199*P*G$$

Where  $P$  = Power in mW  $G$  = Numeric antenna  
gain  $S$  = Power density in  $\text{mW}/\text{cm}^2$

Total Power density= $0.007\text{mW}/\text{cm}^2$

*(For mobile or fixed location transmitters, the maximum power density is  $1.0\text{ mW}/\text{cm}^2$  even if the calculation indicates that the power density would be larger.)*

Conclusion: PASS