



# **TEST REPORT**

Applicant	ZHONGCHE TOYS INDUSTRIAL CO.,LTD
Address	NO.8, NORTH DENGFENG ROAD, PUMEI, GUANGYI STREET, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA

Manufacturer or Supplier	ZHONGCHE TOYS INDUSTRIAL CO.,LTD
Address	NO.8, NORTH DENGFENG ROAD, PUMEI, GUANGYI STREET, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA
Product	Remote control car
Brand Name	N/A
Model	666-888
Additional Model & Model Difference	666-858, 666-868, 666-878,etc.; See items 3.1
Date of tests	Sep. 01, 2016 ~ Sep. 27, 2016

the tests have been carried out according to the requirements of the following standards:

#### CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

Tested by Ryan Lu	Approved by Glyn He
Project Engineer / EMC Department	Supervisor / EMC Department

Date: Oct. 10, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Page 1 of 21

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080



# **TABLE OF CONTENTS**

R	ELEA	SE C	CONTROL RECORD	3
1	SUI	MMA	ARY OF TEST RESULTS	4
2	ME	ASU	IREMENT UNCERTAINTY	4
3	GE	NER	AL INFORMATION	5
	3.1	GEN	NERAL DESCRIPTION OF EUT	5
	3.2	DES	SCRIPTION OF TEST MODES	6
	3.3	GEN	NERAL DESCRIPTION OF APPLIED STANDARDS	6
	3.4	DES	SCRIPTION OF SUPPORT UNITS	6
4	TES	ST T	YPES AND RESULTS	7
	4.1	RAD	DIATED EMISSION MEASUREMENT	7
	4.1	1.1	LIMITS OF RADIATED EMISSION MEASUREMENT	7
	4.′	1.2	TEST INSTRUMENTS	8
	4.1	1.3	TEST PROCEDURES	. 10
	4.1	1.4	DEVIATION FROM TEST STANDARD	. 10
	4.′	1.5	TEST SETUP	11
	4.1	1.6	EUT OPERATING CONDITIONS	. 12
	4.1	1.7	TEST RESULTS	. 12
	4.2	20d	B BANDWIDTH MEASUREMENT	. 17
	4.	2.1	LIMITS OF 20dB BANDWIDTH MEASUREMENT	
	4.	2.2	TEST INSTRUMENTS	
	4.	2.3	TEST PROCEDURE	
	4.	2.4	DEVIATION FROM TEST STANDARD	
	4.	2.5	TEST SETUP	
	4.	2.6	EUT OPERATING CONDITIONS	
	4.	2.7	TEST RESULTS	. 19
5	PHO	ото	GRAPHS OF THE TEST CONFIGURATION	. 20
6			DIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EU	

Report Version 1



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF160901N076	Original release	Oct. 10, 2016

# 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C , SECTION 15.227(2012-10)					
STANDARD SECTION	TEST TYPE AND LIMIT RESULT REMARK				
§15.207 (a)	Conducted Emission	N/A	EUT is powered by battery		
§15.209 §15.227	Radiated Emission	PASS	Compliant		
§15.215(c)	20dB Bandwidth Test	PASS	Compliant		

# 2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY	
	9KHz ~ 30MHz	2.90dB	
Radiated emissions	30MHz ~ 1GHz	3.83dB	
Radiated emissions	1GHz ~ 18GHz	4.93dB	
	18GHz ~ 40GHz	4.80dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080

Email: DGservice@cn.bureauveritas.com



# 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Remote control car		
MODEL NO.	666-888		
ADDITIONAL MODELS	666-858, 666-868, 666-878, 666-898, 666-918, 666-928, 666-938, 666-958, 666-968, 666-978, 666-988, 666-998, 666-808, 666-818, 666-828, 666-838, 666-618, 666-628, 666-638, 666-658, 666-678, 666-688, 666-698, 666-518, 666-528, 666-538, 666-558, 666-588, 666-598, 666-128, 666-118, 666-168, 666-188, 666-198		
FCC ID	2AJPBZC201691		
NOMINAL VOLTAGE	DC 3V(1.5V*AAA*2) from battery		
MODULATION TYPE	ASK		
OPERATING FREQUENCY	27.052MHz		
NUMBER OF CHANNEL	1		
ANTENNA TYPE	Wire Antenna with 0dBi gain		
I/O PORTS	Refer to user's manual		

#### NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- 3. Please refer to the EUT photo document (Reference No.: 160901N076) for detailed product photo.
- 4. Additional models (See above table) are identical with test 666-888 except the appearance, trade name and model no. for trading purpose

#### 3.2 DESCRIPTION OF TEST MODES

The EUT was tested under the following mode.

FREQUENCY	TEST MODES	
27.052 MHz	Transmitting	

#### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, 15.227 ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

#### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessories or support units.

# 4 TEST TYPES AND RESULTS

#### **4.1 RADIATED EMISSION MEASUREMENT**

#### 4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.227(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [µV/m]	Field Strength of Fundamental Emission [Average] [µV/m]
26.96 - 27.28	100,000 (100 dBμV/m)	10,000 (80 dBμV/m)

#### NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



BUREAU VERITAS Test Report No.: RF160901N076

# 4.1.2 TEST INSTRUMENTS

#### Below 30MHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Agilent	E4446A	MY46180622	Nov. 25,15	Nov. 24,16
Spectrum Analyzer (10Hz–40GHz)	Rohde&Schwarz	FSV40	101003	Nov. 25,15	Nov. 24,16
Signal Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 25,15	Nov. 24,16
EMI Test Receiver	Rohde&Schwarz	ESVS10	841431/004	May 17,16	May 16,17
Loop antenna (9kHz~30MHz)	Daze	ZN30900A	0708	Dec. 05,15	Dec. 05,16
Bilog Antenna	Teseq	CBL 6111D	27089	Dec. 05,15	Dec. 05,16
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	Oct. 18, 15	Oct. 17, 16
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Nov. 25,15	Nov. 24,16
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 13,16	May 12,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 30, 15	Oct. 29, 16
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8 .8m	NSEMC006	May 15, 16	May 14, 17
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A

**NOTE:** 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

- 2. The test was performed in 10m Chamber
- 3. The FCC Site Registration No. is 502831.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>DGservice@cn.bureauveritas.com</u>

Page 8 of 21



#### **Below 1G**

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwar z	FSV7	102331	Nov. 09,15	Nov. 08,16
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 18,16	May 17,17
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 16	Aug. 07, 17
3m Semi-anechoic Chamber	ETS-LINDGRE N	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
Horn Antenna	SCHWARZBEC K	BBHA 9170	BBHA9170242	Mar. 12,16	Mar. 11,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,16	Mar. 03, 17
Pre-Amplifier(1-18G)	HP	8449B	3008A00409	Apr. 25,16	Apr. 24,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,15	Nov. 19,16
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwar z	CBT32	100811	Aug. 08,16	Aug. 07,17

#### NOTE:

- 1. The test was performed in 966 Chamber.
- 2. The calibration interval of the above test instruments are 12, 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.
- 4. The FCC Site Registration No. is 494399.



#### 4.1.3 TEST PROCEDURES

The basic test procedure was in accordance with ANSI C63.4 (section 12).

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3m chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. (Below 1000MHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10m chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. (Below 30MHz)
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level.
- h. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

#### NOTE:

- 1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 4. Margin value = Emission level Limit value.
- 5. Fundamental AV value =PK Emission +duty cycle.


#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.




# 4.1.5 TEST SETUP

# **Below 30MHz**



#### 30MHz~1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Page 11 of 21



VERITAS Test Report No.: RF160901N076

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power of equipment.
- b. Hold down the TX of button, then the EUT was operating.
- c. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

#### 4.1.7 TEST RESULTS

#### FIELD STRENGTH OF FUNDAMENTAL

#### **ANTENNA POLARITY: 0°**

No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
*	27.05(PK)	-8.60	56.67	48.07	100	-51.93
*	27.05(AV)	-4.38	-	43.69	80	-36.31

#### **ANTENNA POLARITY: 90°**

No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
*	27.05(PK)	-8.60	59.78	51.18	100	-48.82
*	27.05(AV)	-4.38	-	46.82	80	-33.18

**REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).

- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.
- 6. The average value of fundamental frequency is: Average value = Peak value +AV factor, where the AV factor is calculated from following formula: AV factor=20 log (Duty cycle) = 20 log (60.42%) = -4.38dB, Please see page 13~14 for plotted duty.

VERITAS Test Report No.: RF160901N076


# **Duty Cycle:**

Tp = 18.2536ms

Ton = Ton1 \* Number+ Ton2 \* Number =1.50725\*4 +0.5000 \*10= 11.029ms

Duty Cycle = Ton / Tp \* 100% = 11.029/ 18.2536= 60.42%

# **Tp**=18.2536ms




Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com


Report Version 1



Ton1=1.50725ms



**Ton2**= 0.5ms



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: <u>DGservice@cn.bureauveritas.com</u>

Page 14 of 21




FREQUENCY RANGE	130MHz ~ 1GHz	DETECTOR FUNCTION	Quasi-Peak (QP)
-----------------	---------------	----------------------	-----------------

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	CORRECTIO N FACTOR (dB/m)	RAW VALUE (dBuV)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	
1	54.10	-22.92	44.66	21.74	40.00	-18.26	100	0	
2	81.17	-21.30	48.63	27.33	40.00	-12.67	100	0	
3	108.21	-17.78	45.33	27.55	43.50	-15.95	100	0	
4	135.28	-17.04	35.50	18.46	43.50	-25.04	100	0	
5	162.34	-17.33	41.60	24.27	43.50	-19.23	100	0	
6	189.35	-19.58	41.44	21.86	43.50	-21.64	100	0	

#### **REMARKS:**

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



Tel: +86 769 8593 5656 Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Page 15 of 21




FREQUENCY RANGE	30MHz ~ 1GHz	DETECTOR FUNCTION	Quasi-Peak (QP)
-----------------	--------------	----------------------	-----------------

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	CORRECTIO N FACTOR (dB/m)	RAW VALUE (dBuV)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	
1	33.30	-12.40	30.34	17.94	40.00	-22.06	200	0	
2	54.16	-22.94	41.88	18.94	40.00	-21.06	200	0	
3	81.26	-21.27	35.32	14.05	40.00	-25.95	200	0	
4	108.33	-17.77	35.92	18.15	43.50	-25.35	200	0	
5	162.50	-17.35	34.53	17.18	43.50	-26.32	200	0	
6	216.63	-18.18	32.64	14.46	46.00	-31.54	200	0	

#### **REMARKS:**

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.





VERITAS Test Report No.: RF160901N076

# 4.2 BANDWIDTH MEASUREMENT

# 4.2.1 LIMITS OF BANDWIDTH MEASUREMENT

The field strength of any emissions appearing between the band edges and out of band shall be attenuated at least 20 dB below the level of the unmodulated carrier or to the general limits in Section 15.209.

FREQUENCY	Limits	
(MHz)	[MHz]	
27.052	within 26.96-27.28	

#### 4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 04,16	May 03,17
Power Sensor	Keysight	U2021XA	MY55060018	May 04,16	May 03,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct.11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05, 16	Sep. 04,17
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 28,15	Nov. 27,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Nov. 09,15	Nov. 08,16
Agile Signal Generator	Agilent	8645A	Agilent	Aug.08, 16	Aug.07, 17
ESG Vector Signal	Acilont	E4420C	MV/40070505	Amr. 22, 46	Ans 04 47
Generator	Agilent	E4438C	MY49072505	Apr. 22, 16	Apr. 21, 17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.08, 16	Aug.07, 17

#### NOTE:

- 1. The test was performed in RF Oven room.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



# 4.2.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



#### 4.2.6 EUT OPERATING CONDITIONS

Same as item 4.1.6




BUREAU VERITAS Test Report No.: RF160901N076

# 4.2.7 TEST RESULTS

Lower & Upper Test Frequency Point (MHz)	Test Frequency (MHz)	P/F
Lower	27.0191	PASS
Upper	27.0698	PASS

#### **Test Data:**



Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Page 19 of 21



# 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

Page 20 of 21



# 6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---