

# **Certification Exhibit**

FCC ID: 2AJPY-BASGY00

FCC Rule Part: 47 CFR Part 2.1091

**ACS Project Number: 16-3077** 

Applicant: Smart Pet Technologies, LLC

Model: SPT001B

Model: SPT001B FCC ID: 2AJPY-BASGY00

## **General Information:**

Applicant: Smart Pet Technologies, LLC

Device Category: Mobile

Environment: General Population/Uncontrolled Exposure

## **Technical Information:**

Antenna Type: Monopole Flex antenna

Antenna Gain: 0 dBi

Maximum Transmitter Conducted Power: 4.45 dBm, 2.79 mW

Maximum System EIRP: 4.45 dBm, 2.79 mW Exposure Conditions: Greater than 20 centimeters

### **MPE Calculation**

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

#### Where:

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

| MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure* |                         |                              |                        |                          |                             |                  |                            |
|--|-------------------------|------------------------------|------------------------|--------------------------|-----------------------------|------------------|----------------------------|
| Transmit<br>Frequency<br>(MHz)   | Radio<br>Power<br>(dBm) | Power Density Limit (mW/Cm2) | Radio<br>Power<br>(mW) | Antenna<br>Gain<br>(dBi) | Antenna<br>Gain (mW<br>eq.) | Distance<br>(cm) | Power Density<br>(mW/cm^2) |
| 2402   | 4.45                    | 1.00                         | 2.79                   | 0                        | 1.000                       | 20               | 0.001                      |

# **Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

## **RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

#### Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.