


# Walt Disney Parks and Resorts US, Inc.

TPv2/300-004278

FCC 15.247:2018 902 – 928 MHz FHSS Transceiver

Report # SYNA0242.5







This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government of the United States of America. This Report shall not be reproduced, except in full without written approval of the laboratory.

EAR-Controlled Data - This document contains technical data whose export and reexport/retransfer is subject to control by the U.S. Department of Commerce under the Export Administration Act and the Export Administration Regulations. The Department of Commerce's prior written approval may be required for the export or reexport/retransfer of such technical data to any foreign person, foreign entity or foreign organization whether in the United States or abroad.

More: https://www.bis.doc.gov/index.php/forms-documents/regulations-docs/14-commerce-country-chart/fileT

# **CERTIFICATE OF TEST**



Last Date of Test: June 6, 2018
Walt Disney Parks and Resorts US, Inc.
Model: TPv2/300-004278

# **Radio Equipment Testing**

### **Standards**

| Specification   | Method           |
|-----------------|------------------|
| FCC 15.247:2018 | ANSI C63.10:2013 |

### Results

| Method   |                                     |         |         |  |
|----------|-------------------------------------|---------|---------|--|
| Clause   | Test Description                    | Applied | Results | Comments   |
| 6.2      | Powerline Conducted<br>Emissions    | No      | N/A     | Not tested for evaluation of a Permissive Change due to a change of enclosure. |
| 6.5, 6.6 | Spurious Radiated Emissions         | Yes     | Pass    |  |
| 7.5      | Duty Cycle                          | Yes     | N/A     | Characterization of radio operation.   |
| 7.8.2    | Carrier Frequency Separation        | No      | N/A     | Not tested for evaluation of a Permissive Change due to a change of enclosure. |
| 7.8.3    | Number of Hopping Frequencies       | No      | N/A     | Not tested for evaluation of a Permissive Change due to a change of enclosure. |
| 7.8.4    | Dwell Time                          | No      | N/A     | Not tested for evaluation of a Permissive Change due to a change of enclosure. |
| 7.8.5    | Output Power                        | Yes     | Pass    |  |
| 7.8.6    | Band Edge Compliance                | No      | N/A     | Not tested for evaluation of a Permissive Change due to a change of enclosure. |
| 7.8.6    | Band Edge Compliance - Hopping Mode | No      | N/A     | Not required for DTS devices.  |
| 7.8.7    | Occupied Bandwidth                  | Yes     | Pass    |  |
| 7.8.8    | Spurious Conducted Emissions        | No      | N/A     | Not tested for evaluation of a Permissive Change due to a change of enclosure. |
| 11.10.2  | Power Spectral Density              | No      | N/A     | Not required for FHSS devices.   |

### **Deviations From Test Standards**

None

Approved By:

Rod Munro, Operations Manager

Product compliance is the responsibility of the client; therefore, the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test. This report reflects only those tests from the referenced standards shown in the certificate of test. It does not include inspection or verification of labels, identification, marking or user information.

# **REVISION HISTORY**



| Revision<br>Number | Description | Date | Page Number |
|--------------------|-------------|------|-------------|
| 00                 | None        |      |             |

# ACCREDITATIONS AND AUTHORIZATIONS



### **United States**

FCC - Designated by the FCC as a Telecommunications Certification Body (TCB). Certification chambers, Open Area Test Sites, and conducted measurement facilities are listed with the FCC.

**A2LA** - Accredited by A2LA to ISO / IEC 17065 as a product certifier. This allows Element to certify transmitters to FCC and IC specifications.

NVLAP - Each laboratory is accredited by NVLAP to ISO 17025

### Canada

**ISED** - Recognized by Innovation, Science and Economic Development Canada as a Certification Body (CB). Certification chambers and Open Area Test Sites are filed with ISED.

### **European Union**

European Commission - Within Element, we have a EU Notified Body validated for the EMCD and RED Directives.

### Australia/New Zealand

ACMA - Recognized by ACMA as a CAB for the acceptance of test data.

### Korea

MSIT / RRA - Recognized by KCC's RRA as a CAB for the acceptance of test data.

### **Japan**

VCCI - Associate Member of the VCCI. Conducted and radiated measurement facilities are registered.

### **Taiwan**

**BSMI** – Recognized by BSMI as a CAB for the acceptance of test data.

NCC - Recognized by NCC as a CAB for the acceptance of test data.

### **Singapore**

**IDA** – Recognized by IDA as a CAB for the acceptance of test data.

### Israel

MOC - Recognized by MOC as a CAB for the acceptance of test data.

### **Hong Kong**

**OFCA** – Recognized by OFCA as a CAB for the acceptance of test data.

### **Vietnam**

**MIC** – Recognized by MIC as a CAB for the acceptance of test data.

### **SCOPE**

For details on the Scopes of our Accreditations, please visit:

http://portlandcustomer.element.com/ts/scope/scope.htm http://gsi.nist.gov/global/docs/cabs/designations.html


# **FACILITIES**







| <b>California</b> Labs OC01-17 41 Tesla Irvine, CA 92618 (949) 861-8918 | Minnesota<br>Labs MN01-10<br>9349 W Broadway Ave.<br>Brooklyn Park, MN 55445<br>(612)-638-5136 | New York<br>Labs NY01-04<br>4939 Jordan Rd.<br>Elbridge, NY 13060<br>(315) 554-8214 | Oregon Labs EV01-12 6775 NE Evergreen Pkwy #400 Hillsboro, OR 97124 (503) 844-4066 | <b>Texas</b> Labs TX01-09 3801 E Plano Pkwy Plano, TX 75074 (469) 304-5255 | <b>Washington</b> Labs NC01-05 19201 120 <sup>th</sup> Ave NE Bothell, WA 98011 (425)984-6600 |  |
|---|--|---|--|--|---|--|
|   |  | NV  | LAP  |  |   |  |
| NVLAP Lab Code: 200676-0  | NVLAP Lab Code: 200881-0   | NVLAP Lab Code: 200761-0  | NVLAP Lab Code: 200630-0   | NVLAP Lab Code:201049-0  | NVLAP Lab Code: 200629-0  |  |
|   | Innovation, Science and Economic Development Canada  |   |  |  |   |  |
| 2834B-1, 2834B-3  | 2834E-1, 2834E-3   | N/A   | 2834D-1, 2834D-2   | 2834G-1  | 2834F-1   |  |
|   |  | BS  | МІ   |  |   |  |
| SL2-IN-E-1154R  | SL2-IN-E-1152R   | N/A   | SL2-IN-E-1017  | SL2-IN-E-1158R   | SL2-IN-E-1153R  |  |
|   | VCCI   |   |  |  |   |  |
| A-0029  | A-0109   | N/A   | A-0108   | A-0201   | A-0110  |  |
|   | Recognized Phase I CAB for ACMA, BSMI, IDA, KCC/RRA, MIC, MOC, NCC, OFCA                       |   |  |  |   |  |
| US0158  | US0175   | N/A   | US0017   | US0191   | US0157  |  |



# MEASUREMENT UNCERTAINTY



### **Measurement Uncertainty**

When a measurement is made, the result will be different from the true or theoretically correct value. The difference is the result of tolerances in the measurement system that cannot be completely eliminated. To the extent that technology allows us, it has been our aim to minimize this error. Measurement uncertainty is a statistical expression of measurement error qualified by a probability distribution.

A measurement uncertainty estimation has been performed for each test per our internal quality document QM205.4.6. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty (K=2) can be found included as part of the applicable test description page. Our measurement data meets or exceeds the measurement uncertainty requirements of the applicable specification; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for estimating measurement uncertainty are based upon ETSI TR 100 028 (or CISPR 16-4-2 as applicable), and are available upon request.


The following table represents the Measurement Uncertainty (MU) budgets for each of the tests that may be contained in this report.

| <u>Test</u>                           | + MU    | - MU     |
|---------------------------------------|---------|----------|
| Frequency Accuracy (Hz)               | 0.0007% | -0.0007% |
| Amplitude Accuracy (dB)               | 1.2 dB  | -1.2 dB  |
| Conducted Power (dB)                  | 0.3 dB  | -0.3 dB  |
| Radiated Power via Substitution (dB)  | 0.7 dB  | -0.7 dB  |
| Temperature (degrees C)               | 0.7°C   | -0.7°C   |
| Humidity (% RH)                       | 2.5% RH | -2.5% RH |
| Voltage (AC)                          | 1.0%    | -1.0%    |
| Voltage (DC)                          | 0.7%    | -0.7%    |
| Field Strength (dB)                   | 0       | 0        |
| AC Powerline Conducted Emissions (dB) | 0       | 0        |


# **Test Setup Block Diagrams**




### **Antenna Port Conducted Measurements**



### **Near Field Test Fixture Measurements**



### **Spurious Radiated Emissions**



# PRODUCT DESCRIPTION



### **Client and Equipment Under Test (EUT) Information**

| Company Name:                  | Walt Disney Parks and Resorts US, Inc.                     |
|--------------------------------|--|
| Address:                       | PO Box 1000  |
| City, State, Zip:              | Lake Buena Vista, Florida 32830                            |
| Test Requested By:             | Brian Piquette of Synapse Product Development on behalf of |
| rest Requested by.             | Walt Disney Parks and Resorts US, Inc.                     |
| Model:                         | TPv2/300-004278  |
| First Date of Test:            | June 4, 2018   |
| Last Date of Test:             | June 6, 2018   |
| Receipt Date of Samples:       | June 4, 2018   |
| <b>Equipment Design Stage:</b> | Production   |
| <b>Equipment Condition:</b>    | No Damage  |
| Purchase Authorization:        | Verified   |

### Information Provided by the Party Requesting the Test

### **Functional Description of the EUT:**

Multi-ticket media reader with Ethernet network interface Device containing an HF RFID reader (ISO 14443), UHF FHSS RFID Reader (ISO 18000), BT/BLE Radio, and proprietary 2.4GHz DTS radio.

### **Testing Objective:**

Seeking to demonstrate compliance of the UHF FHSS RFID radio under FCC 15.247:2018 for operation in the 902 - 928 MHz Band for a Permissive Change under FCC ID: 2AJS4-TP-R1G2.

# **CONFIGURATIONS**



# **Configuration SYNA0242-2**

| Software/Firmware Running during test |         |  |
|---------------------------------------|---------|--|
| Description                           | Version |  |
| UHF Tool                              | N/A     |  |

| EUT          |  |                   |               |
|--------------|--|-------------------|---------------|
| Description  | Manufacturer                           | Model/Part Number | Serial Number |
| Access Point | Walt Disney Parks and Resorts US, Inc. | TPv2/300-004278   | SN03          |

| Peripherals in test setup boundary                       |       |             |      |  |  |  |
|--|-------|-------------|------|--|--|--|
| Description Manufacturer Model/Part Number Serial Number |       |             |      |  |  |  |
| Laptop PC  | Apple | MacBook Pro | None |  |  |  |
| DC Power Supply Mastech HY3003D-2 None                   |       |             |      |  |  |  |

| Cables         |        |            |         |                 |                 |
|----------------|--------|------------|---------|-----------------|-----------------|
| Cable Type     | Shield | Length (m) | Ferrite | Connection 1    | Connection 2    |
| DC Power       | No     | 0.7m       | No      | DC Power Supply | Access Point    |
| 3v3 FTDI Cable | No     | 1.0m       | No      | Access Point    | Laptop PC       |
| AC Power       | No     | 1.8m       | No      | AC Mains        | DC Power Supply |

# **CONFIGURATIONS**



# **Configuration SYNA0242-5**

| Software/Firmware Running during test |         |  |  |
|---------------------------------------|---------|--|--|
| Description                           | Version |  |  |
| UHF Tool                              | N/A     |  |  |

| EUT          |  |                   |               |
|--------------|--|-------------------|---------------|
| Description  | Manufacturer                           | Model/Part Number | Serial Number |
| Access Point | Walt Disney Parks and Resorts US, Inc. | TPv2/300-004278   | SN05          |

| Remote Equipment Outside of Test Setup Boundary          |       |             |      |  |  |  |  |  |  |
|--|-------|-------------|------|--|--|--|--|--|--|
| Description Manufacturer Model/Part Number Serial Number |       |             |      |  |  |  |  |  |  |
| Laptop PC  | Apple | MacBook Pro | None |  |  |  |  |  |  |
| DC Power Supply Mastech HY3003D-2 None                   |       |             |      |  |  |  |  |  |  |

| Cables     |        |            |         |                 |                 |  |  |  |  |
|------------|--------|------------|---------|-----------------|-----------------|--|--|--|--|
| Cable Type | Shield | Length (m) | Ferrite | Connection 1    | Connection 2    |  |  |  |  |
| AC Power   | No     | 1.8m       | No      | AC Mains        | DC Power Supply |  |  |  |  |
| DC Power   | No     | 3.0m       | No      | DC Power Supply | Access Point    |  |  |  |  |
| Ethernet   | No     | 5.0m       | No      | Access Point    | Laptop PC       |  |  |  |  |

# **MODIFICATIONS**



# **Equipment Modifications**

| Item | Date     | Test   | Modification                         | Note  | Disposition of EUT   |
|------|----------|--|--------------------------------------|---|--|
| 1    | 6/4/2018 | Output<br>Power  | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT remained at Element following the test.                      |
| 2    | 6/4/2018 | Occupied<br>Bandwidth                                    | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | EUT was taken home by the client before the next scheduled test. |
| 3    | 6/6/2018 | Field Strength of Spurious Emissions Greater than 30 MHz | Tested as delivered to Test Station. | No EMI suppression devices were added or modified during this test. | Scheduled testing was completed.                                 |

# SPURIOUS RADIATED EMISSIONS



PSA-ESCI 2018.05.04

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data. The test data represents the configuration / operating mode/ model that produced the highest emission levels as compared to the specification limit.

### **MODES OF OPERATION**

Transmitting at Default Max Power, ASK Modulation.

#### **CHANNELS TESTED**

Low Channel, 902.75 MHz

Mid Channel, 915.25 MHz

High Channel, 927.25 MHz

### **POWER SETTINGS INVESTIGATED**

24 VDC

#### **CONFIGURATIONS INVESTIGATED**

SYNA0242 - 5

### FREQUENCY RANGE INVESTIGATED

### **SAMPLE CALCULATIONS**

Radiated Emissions: Field Strength = Measured Level + Antenna Factor + Cable Factor - Amplifier Gain + Distance Adjustment Factor + External Attenuation

### **TEST EQUIPMENT**

| Description                  | Manufacturer  | Model                    | ID  | Last Cal.   | Interval |
|------------------------------|---------------|--------------------------|-----|-------------|----------|
| Analyzer - Spectrum Analyzer | Agilent       | E4440A                   | AFE | 24-Jun-2017 | 12 mo    |
| Filter - High Pass           | Micro-Tronics | HPM50114                 | HFN | 13-Dec-2017 | 12 mo    |
| Filter - Band Pass/Notch     | K&L Microwave | 3TNF-500/1000-N/N        | ННО | 23-Mar-2018 | 12 mo    |
| Filter - Low Pass            | Micro-Tronics | LPM50004                 | LFF | 13-Dec-2017 | 12 mo    |
| Filter - Low Pass            | Micro-Tronics | LPM50003                 | LFE | 19-Oct-2017 | 12 mo    |
| Antenna - Biconilog          | Teseq         | CBL 6141B                | AYL | 11-Aug-2017 | 24 mo    |
| Antenna - Double Ridge       | ETS Lindgren  | 3115                     | AHW | 12-Jul-2016 | 24 mo    |
| Antenna - Standard Gain      | EMCO          | 3160-07                  | AHP | NCR         | 0 mo     |
| Amplifier - Pre-Amplifier    | Miteq         | AM-1616-1000             | PAB | 11-Jul-2017 | 12 mo    |
| Amplifier - Pre-Amplifier    | Miteq         | AMF-3D-00100800-32-13P   | AVZ | 4-May-2018  | 12 mo    |
| Amplifier - Pre-Amplifier    | Miteq         | AMF-6F-08001200-30-10P   | AOK | 18-Aug-2017 | 12 mo    |
| Cable                        | Northwest EMC | Bilog Cables             | NC1 | 11-Jul-2017 | 12 mo    |
| Cable                        | Northwest EMC | 3115 Horn Cable          | NC2 | 4-May-2018  | 12 mo    |
| Cable                        | Northwest EMC | Standard Gain Horn Cable | NC3 | 4-May-2018  | 12 mo    |

#### **MEASUREMENT BANDWIDTHS**

| Frequency Range<br>(MHz) | Peak Data<br>(kHz) | Quasi-Peak Data<br>(kHz) | Average Data<br>(kHz) |
|--------------------------|--------------------|--------------------------|-----------------------|
| 0.01 - 0.15              | 1.0                | 0.2                      | 0.2                   |
| 0.15 - 30.0              | 10.0               | 9.0                      | 9.0                   |
| 30.0 - 1000              | 100.0              | 120.0                    | 120.0                 |
| Above 1000               | 1000.0             | N/A                      | 1000.0                |

#### **TEST DESCRIPTION**

The highest gain antenna of each type to be used with the EUT was tested. The EUT was configured for the required transmit frequencies and the modes as showed in the data sheets.

For each configuration, the spectrum was scanned throughout the specified range as part of the exploratory investigation of the emissions. These "pre-scans" are not included in the report. Final measurements on individual emissions were then made and included in this test report.

The individual emissions from the EUT were maximized by rotating the EUT on a turntable, adjusting the position of the EUT and EUT antenna in three orthogonal axis if required, and adjusting the measurement antenna height and polarization (per ANSI C63.10). A preamp and high pass filter (and notch filter) were used for this test in order to provide sufficient measurement sensitivity.

Measurements were made with the required detectors and annotated on the data for each individual point using the following annotation:

QP = Quasi-Peak Detector

PK = Peak Detector

AV = RMS Detector

Measurements were made to satisfy the specific requirements of the test specification for out of band emissions as well as the restricted band requirements.


If there are no detectable emissions above the noise floor, the data included may show noise floor measurements for reference only.

Measurements at the edges of the allowable band may be presented in an alternative method as provided for in the ANSI C63.10 Marker-Delta method. This method involves performing an in-band fundamental measurement followed by a screen capture of the fundamental and out-of-band emission using reduced measurement instrumentation bandwidths. The amplitude delta measured on this screen capture is applied to the fundamental emission value to show the out-of-band emission level as applied to the limit.

# **SPURIOUS RADIATED EMISSIONS**



|                     |  |  |            | EmiR5 2018.05.07 PSA-ESCI 2018.05.04 |  |  |  |  |  |  |
|---------------------|--|--|------------|--------------------------------------|--|--|--|--|--|--|
| Work Order:         | SYNA0242   | Date:  | 6-Jun-2018 | OI N                                 |  |  |  |  |  |  |
| Project:            | None   | Temperature:                                       | 22.5 °C    | VIISI                                |  |  |  |  |  |  |
| Job Site:           | NC01   | Humidity:  | 40.6% RH   | part                                 |  |  |  |  |  |  |
| Serial Number:      | SN05   | Barometric Pres.:                                  | 1018 mbar  | Tested by: Richard Mellroth          |  |  |  |  |  |  |
| EUT:                | TPv2/300-004278  |  |            | ·                                    |  |  |  |  |  |  |
| Configuration:      | 5  |  |            |                                      |  |  |  |  |  |  |
| Customer:           | Walt Disney Parks and  | It Disney Parks and Resorts US, Inc.               |            |                                      |  |  |  |  |  |  |
| Attendees:          | Reily Blackner   | ily Blackner                                       |            |                                      |  |  |  |  |  |  |
| EUT Power:          | 24 VDC   | 4 VDC  |            |                                      |  |  |  |  |  |  |
| Operating Mode:     | Transmitting at Defaul   | Fransmitting at Default Max Power, ASK Modulation. |            |                                      |  |  |  |  |  |  |
| Deviations:         | None   |  |            |                                      |  |  |  |  |  |  |
| Comments:           | Comments:  See comments next to data points for EUT channel and orientation. |  |            |                                      |  |  |  |  |  |  |
| Test Specifications |  |  | Test Met   | hod                                  |  |  |  |  |  |  |
| FCC 15.247:2018     |  |  | ANSI C63   | 3.10:2013                            |  |  |  |  |  |  |



| Freq<br>(MHz) | Amplitude<br>(dBuV) | Factor<br>(dB) | Antenna Height (meters) | Azimuth<br>(degrees) | Test Distance<br>(meters) | External<br>Attenuation<br>(dB) | Polarity/<br>Transducer<br>Type | Detector | Distance<br>Adjustment<br>(dB) | Adjusted<br>(dBuV/m) | Spec. Limit<br>(dBuV/m) | Compared to<br>Spec.<br>(dB) | Comments             |
|---------------|---------------------|----------------|-------------------------|----------------------|---------------------------|---------------------------------|---------------------------------|----------|--------------------------------|----------------------|-------------------------|------------------------------|----------------------|
| 7416.630      | 27.7                | 14.2           | 1.6                     | 221.0                | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 41.9                 | 54.0                    | -12.1                        | High Ch, EUT on Back |
| 7416.555      | 27.7                | 14.2           | 1.6                     | 69.0                 | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 41.9                 | 54.0                    | -12.1                        | High Ch, EUT on Side |
| 7320.985      | 27.8                | 13.7           | 2.5                     | 225.0                | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 41.5                 | 54.0                    | -12.5                        | Mid Ch, EUT on Side  |
| 7320.980      | 27.8                | 13.7           | 3.7                     | 86.0                 | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 41.5                 | 54.0                    | -12.5                        | Mid Ch, EUT on Back  |
| 5417.030      | 26.8                | 10.4           | 1.6                     | 20.0                 | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 37.2                 | 54.0                    | -16.8                        | Low Ch, EUT on Side  |
| 5415.600      | 26.7                | 10.4           | 1.6                     | 229.0                | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 37.1                 | 54.0                    | -16.9                        | Low Ch, EUT on Back  |
| 4512.725      | 27.5                | 7.5            | 1.7                     | 232.0                | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 35.0                 | 54.0                    | -19.0                        | Low Ch, EUT on Back  |
| 4575.705      | 27.4                | 7.6            | 3.1                     | 2.0                  | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 35.0                 | 54.0                    | -19.0                        | Mid Ch, EUT on Side  |
| 4575.050      | 27.4                | 7.6            | 1.6                     | 111.0                | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 35.0                 | 54.0                    | -19.0                        | Mid Ch, EUT on Back  |
| 4635.905      | 27.3                | 7.7            | 4.0                     | 357.0                | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 35.0                 | 54.0                    | -19.0                        | High Ch, EUT on Back |
| 4635.130      | 27.3                | 7.7            | 1.6                     | 21.0                 | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 35.0                 | 54.0                    | -19.0                        | High Ch, EUT on Side |
| 4514.015      | 27.4                | 7.5            | 1.6                     | 89.0                 | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 34.9                 | 54.0                    | -19.1                        | Low Ch, EUT on Side  |
| 7321.080      | 39.7                | 13.7           | 2.5                     | 225.0                | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 53.4                 | 74.0                    | -20.6                        | Mid Ch, EUT on Side  |
| 3708.190      | 29.1                | 4.0            | 2.0                     | 249.0                | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 33.1                 | 54.0                    | -20.9                        | High Ch, EUT on Back |
| 3708.250      | 29.1                | 4.0            | 2.0                     | 75.0                 | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 33.1                 | 54.0                    | -20.9                        | High Ch, EUT on Side |
| 3660.030      | 29.2                | 3.8            | 2.1                     | 287.0                | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 33.0                 | 54.0                    | -21.0                        | Mid Ch, EUT on Side  |
| 3660.090      | 29.2                | 3.8            | 1.6                     | 280.0                | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 33.0                 | 54.0                    | -21.0                        | Mid Ch, EUT on Back  |
| 7416.510      | 38.6                | 14.2           | 1.6                     | 69.0                 | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 52.8                 | 74.0                    | -21.2                        | High Ch, EUT on Side |

| Freq<br>(MHz) | Amplitude<br>(dBuV) | Factor<br>(dB) | Antenna Height<br>(meters) | Azimuth (degrees) | Test Distance<br>(meters) | External<br>Attenuation<br>(dB) | Polarity/<br>Transducer<br>Type | Detector | Distance<br>Adjustment<br>(dB) | Adjusted (dBuV/m) | Spec. Limit<br>(dBuV/m) |       | Comments             |
|---------------|---------------------|----------------|----------------------------|-------------------|---------------------------|---------------------------------|---------------------------------|----------|--------------------------------|-------------------|-------------------------|-------|----------------------|
| 7419.060      | 38.5                | 14.2           | 1.6                        | 221.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 52.7              | 74.0                    | -21.3 | High Ch, EUT on Back |
| 3610.120      | 29.2                | 3.4            | 1.6                        | 355.0             | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 32.6              | 54.0                    | -21.4 | Low Ch, EUT on Back  |
| 3609.820      | 29.1                | 3.4            | 2.0                        | 142.0             | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 32.5              | 54.0                    | -21.5 | Low Ch, EUT on Side  |
| 2708.250      | 32.4                | 0.0            | 3.4                        | 315.0             | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 32.4              | 54.0                    | -21.6 | Low Ch, EUT on Back  |
| 2708.235      | 32.3                | 0.0            | 3.5                        | 350.0             | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 32.3              | 54.0                    | -21.7 | Low Ch, EUT Normal   |
| 7320.640      | 38.6                | 13.7           | 3.7                        | 86.0              | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 52.3              | 74.0                    | -21.7 | Mid Ch, EUT on Back  |
| 2708.195      | 32.1                | 0.0            | 1.7                        | 330.0             | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 32.1              | 54.0                    | -21.9 | Low Ch, EUT on Side  |
| 2708.325      | 31.7                | 0.0            | 2.9                        | 55.0              | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 31.7              | 54.0                    | -22.3 | Low Ch, EUT Normal   |
| 2745.645      | 31.3                | 0.1            | 1.6                        | 35.0              | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 31.4              | 54.0                    | -22.6 | Mid Ch, EUT on Side  |
| 2745.725      | 30.9                | 0.1            | 2.4                        | 318.0             | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 31.0              | 54.0                    | -23.0 | Mid Ch, EUT on Back  |
| 2781.775      | 30.5                | 0.2            | 1.1                        | 30.0              | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 30.7              | 54.0                    | -23.3 | High Ch, EUT on Side |
| 2781.795      | 30.4                | 0.2            | 3.3                        | 310.0             | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 30.6              | 54.0                    | -23.4 | High Ch, EUT on Back |
| 2708.170      | 29.5                | 0.0            | 3.0                        | 270.0             | 3.0                       | 0.0                             | Horz                            | AV       | 0.0                            | 29.5              | 54.0                    | -24.5 | Low Ch, EUT on Back  |
| 2707.655      | 29.3                | 0.0            | 1.6                        | 226.0             | 3.0                       | 0.0                             | Vert                            | AV       | 0.0                            | 29.3              | 54.0                    | -24.7 | Low Ch, EUT on Side  |
| 5415.945      | 38.4                | 10.4           | 1.6                        | 20.0              | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 48.8              | 74.0                    | -25.2 | Low Ch, EUT on Side  |
| 5417.500      | 37.2                | 10.4           | 1.6                        | 229.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 47.6              | 74.0                    | -26.4 | Low Ch, EUT on Back  |
| 4635.170      | 38.6                | 7.7            | 4.0                        | 357.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 46.3              | 74.0                    | -27.7 | High Ch, EUT on Back |
| 4513.890      | 38.5                | 7.5            | 1.7                        | 232.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 46.0              | 74.0                    | -28.0 | Low Ch, EUT on Back  |
| 4512.965      | 38.5                | 7.5            | 1.6                        | 89.0              | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 46.0              | 74.0                    | -28.0 | Low Ch, EUT on Side  |
| 4574.915      | 38.3                | 7.6            | 3.1                        | 2.0               | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 45.9              | 74.0                    | -28.1 | Mid Ch, EUT on Side  |
| 4575.610      | 38.3                | 7.6            | 1.6                        | 111.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 45.9              | 74.0                    | -28.1 | Mid Ch, EUT on Back  |
| 4635.950      | 38.2                | 7.7            | 1.6                        | 21.0              | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 45.9              | 74.0                    | -28.1 | High Ch, EUT on Side |
| 3707.800      | 41.2                | 4.1            | 2.0                        | 249.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 45.3              | 74.0                    | -28.7 | High Ch, EUT on Back |
| 3710.075      | 40.4                | 4.1            | 2.0                        | 75.0              | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 44.5              | 74.0                    | -29.5 | High Ch, EUT on Side |
| 3659.565      | 40.6                | 3.8            | 2.1                        | 287.0             | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 44.4              | 74.0                    | -29.6 | Mid Ch, EUT on Side  |
| 3659.990      | 40.5                | 3.8            | 1.6                        | 280.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 44.3              | 74.0                    | -29.7 | Mid Ch, EUT on Back  |
| 3610.155      | 40.5                | 3.4            | 2.0                        | 142.0             | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 43.9              | 74.0                    | -30.1 | Low Ch, EUT on Side  |
| 3610.835      | 40.1                | 3.4            | 1.6                        | 355.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 43.5              | 74.0                    | -30.5 | Low Ch, EUT on Back  |
| 2708.435      | 42.6                | 0.0            | 3.5                        | 350.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 42.6              | 74.0                    | -31.4 | Low Ch, EUT Normal   |
| 2708.190      | 42.1                | 0.0            | 2.9                        | 55.0              | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 42.1              | 74.0                    | -31.9 | Low Ch, EUT Normal   |
| 2708.670      | 41.8                | 0.0            | 1.7                        | 330.0             | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 41.8              | 74.0                    | -32.2 | Low Ch, EUT on Side  |
| 2708.575      | 41.8                | 0.0            | 3.4                        | 315.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 41.8              | 74.0                    | -32.2 | Low Ch, EUT on Back  |
| 2745.455      | 41.6                | 0.1            | 1.6                        | 35.0              | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 41.7              | 74.0                    | -32.3 | Mid Ch, EUT on Side  |
| 2781.490      | 41.3                | 0.2            | 1.1                        | 30.0              | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 41.5              | 74.0                    | -32.5 | High Ch, EUT on Side |
| 2746.615      | 40.9                | 0.1            | 2.4                        | 318.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 41.0              | 74.0                    | -33.0 | Mid Ch, EUT on Back  |
| 2781.470      | 40.5                | 0.2            | 3.3                        | 310.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 40.7              | 74.0                    | -33.3 | High Ch, EUT on Back |
| 2709.260      | 40.6                | 0.0            | 3.0                        | 270.0             | 3.0                       | 0.0                             | Horz                            | PK       | 0.0                            | 40.6              | 74.0                    | -33.4 | Low Ch, EUT on Back  |
| 2709.150      | 40.2                | 0.0            | 1.6                        | 226.0             | 3.0                       | 0.0                             | Vert                            | PK       | 0.0                            | 40.2              | 74.0                    | -33.8 | Low Ch, EUT on Side  |

# **DUTY CYCLE**



### **TEST DESCRIPTION**

The Duty Cycle (x) were measured for each of the EUT operating modes. The measurements were made using a zero span on the spectrum analyzer to see the pulses in the time domain. The transmit power was set to its default maximum. A direct connection was made between the RF output of the EUT and a spectrum analyzer. Attenuation and a DC block were used

The duty cycle was calculated by dividing the transmission pulse duration (T) by the total period of a single on and total off time.

The EUT operates at 100% Duty Cycle.



XMit 2017 12 13

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

#### **TEST EQUIPMENT**

| Description                  | Manufacturer       | Model                 | ID  | Last Cal. | Cal. Due  |
|------------------------------|--------------------|-----------------------|-----|-----------|-----------|
| Analyzer - Spectrum Analyzer | Keysight           | N9010A                | AFO | 1-May-18  | 1-May-19  |
| Cable                        | Micro-Coax         | UFD150A-1-0720-200200 | NCS | 19-Feb-18 | 19-Feb-19 |
| Attenuator                   | Fairview Microwave | SA4014-20             | TKV | 19-Feb-18 | 19-Feb-19 |
| Block - DC                   | Fairview Microwave | SD3379                | AMU | 19-Feb-18 | 19-Feb-19 |
| Generator - Signal           | Agilent            | N5183A                | TIA | 25-Apr-18 | 25-Apr-20 |

### **TEST DESCRIPTION**

The measurement was made using a direct connection between the RF output of the EUT and a spectrum analyzer. The peak output power was measured with the EUT set to low, medium and high transmit frequencies. The EUT was transmitting in a no hop mode at the data rate(s) listed in the datasheet.

The method found in ANSI C63.10:2013 Section 7.8.5 was used for a FHSS radio.

De Facto EIRP Limit: The EUT meets the de facto EIRP limit of +36dBm.




|                 |                            |                  |        |                  |                   | TbtTx 2018.01.25 BETA | XMit 2017.12.13 |
|-----------------|----------------------------|------------------|--------|------------------|-------------------|-----------------------|-----------------|
| EU              | T: TPv2/300-004278         |                  |        |                  | Work Order:       | SYNA0242              |                 |
| Serial Numbe    | r: SN03                    |                  |        |                  | Date:             | 4-Jun-18              |                 |
| Custome         | r: Walt Disney Parks and F | Resorts US, Inc. |        |                  | Temperature:      | 22.3 °C               |                 |
| Attendees       | s: Reily Blackner          |                  |        |                  | Humidity:         | 42.2% RH              |                 |
| Projec          | t: None                    |                  |        |                  | Barometric Pres.: | 1022 mbar             |                 |
| Tested by       | y: Richard Mellroth        |                  | Power: | 24 VDC           | Job Site:         | NC02                  |                 |
| TEST SPECIFICA  | TIONS                      |                  |        | Test Method      |                   |                       |                 |
| FCC 15.247:2018 |                            |                  |        | ANSI C63.10:2013 |                   |                       |                 |
|                 |                            |                  |        |                  |                   |                       |                 |
| COMMENTS        |                            |                  |        |                  |                   |                       |                 |
| _               | Default Max = 20dB Output  |                  |        |                  |                   |                       |                 |
| None            | JM ILSI STANDAND           |                  |        |                  |                   |                       |                 |
| Configuration # | 2                          | Signature        | Rust   |                  |                   |                       |                 |
|                 |                            |                  |        |                  |                   | Limit                 |                 |
|                 |                            |                  |        |                  | Value             | (<)                   | Result          |
| 900 MHz Radio   | ASK Modulation             |                  |        |                  |                   |                       |                 |
|                 | Low Channe                 | el, 902.75 MHz   |        |                  | 63.664 mW         | 1 W                   | Pass            |
|                 |                            | I, 915.25 MHz    |        |                  | 57.625 mW         | 1 W                   | Pass            |
|                 |                            | el, 927.25 MHz   |        |                  | 55.905 mW         | 1 W                   | Pass            |





900 MHz Radio, ASK Modulation, Low Channel, 902.75 MHz

Limit

Value
(c)
Result
63.664 mW
1 W
Pass










900 MHz Radio, ASK Modulation, High Channel, 927.25 MHz

Limit

Value (<) Result

55.905 mW 1 W Pass





XMit 2017.12.13

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

### **TEST EQUIPMENT**

| Description                  | Manufacturer       | Model                 | ID  | Last Cal. | Cal. Due  |
|------------------------------|--------------------|-----------------------|-----|-----------|-----------|
| Analyzer - Spectrum Analyzer | Keysight           | N9010A                | AFO | 1-May-18  | 1-May-19  |
| Cable                        | Micro-Coax         | UFD150A-1-0720-200200 | NCS | 19-Feb-18 | 19-Feb-19 |
| Attenuator                   | Fairview Microwave | SA4014-20             | TKV | 19-Feb-18 | 19-Feb-19 |
| Block - DC                   | Fairview Microwave | SD3379                | AMU | 19-Feb-18 | 19-Feb-19 |
| Generator - Signal           | Agilent            | N5183A                | TIA | 25-Apr-18 | 25-Apr-20 |

### **TEST DESCRIPTION**

The measurement was made using a direct connection between the RF output of the EUT and a spectrum analyzer. The 20 dB occupied bandwidth was measured with the EUT set to low, medium and high transmit frequencies in the band. The EUT was transmitting at the data rate(s) listed in the datasheet in a no-hop mode.



|  |                           |           |      |  |                   | TbtTx 2018.01.25 BETA | XMit 2017.12.13 |
|--|---------------------------|-----------|------|--|-------------------|-----------------------|-----------------|
| EUT  | TPv2/300-004278           |           |      |  | Work Order:       | SYNA0242              | ,               |
| Serial Number: SN03                              |                           |           |      |  | Date:             | 4-Jun-18              |                 |
| Customer: Walt Disney Parks and Resorts US, Inc. |                           |           |      |  | Temperature:      | 22.3 °C               |                 |
| Attendees: Reily Blackner                        |                           |           |      |  | Humidity:         | 42.2% RH              |                 |
| Project: None                                    |                           |           |      |  | Barometric Pres.: | 1022 mbar             |                 |
| Tested by: Richard Mellroth Power: 24 VDC        |                           |           |      |  | Job Site:         | NC02                  |                 |
| TEST SPECIFICATIONS Test Method                  |                           |           |      |  |                   |                       |                 |
| FCC 15.247:2018 ANSI C63.10:2013                 |                           |           |      |  |                   |                       |                 |
|  |                           |           |      |  |                   |                       |                 |
| COMMENTS   |                           |           |      |  |                   |                       |                 |
|  | Default Max = 20dB Output |           |      |  |                   |                       |                 |
| <b>DEVIATIONS FRO</b>                            | OM TEST STANDARD          |           |      |  |                   |                       |                 |
| None   |                           |           |      |  |                   |                       |                 |
| Configuration #                                  | 2                         | Signature | Wish |  |                   |                       |                 |
|  |                           | -         |      |  |                   | Limit                 |                 |
|  |                           |           |      |  | Value             | (<)                   | Result          |
| 900 MHz Radio                                    |                           |           |      |  |                   |                       |                 |
|  | ASK Modulation            |           |      |  |                   |                       |                 |
|  | Low Channel, 902.75 MHz   |           |      |  | 80.137 kHz        | 250 kHz               | Pass            |
|  | Mid Channel, 915.25 MHz   |           |      |  | 82.443 kHz        | 250 kHz               | Pass            |
|  | High Channel, 927.25 MHz  |           |      |  | 84.508 kHz        | 250 kHz               | Pass            |





900 MHz Radio, ASK Modulation, Low Channel, 902.75 MHz


Limit

Value (-) Result

80.137 kHz 250 kHz Pass









900 MHz Radio, ASK Modulation, High Channel, 927.25 MHz

Limit

Value (<) Result

84.508 kHz 250 kHz Pass

