

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: HKES160700151301

Page: 1 of 86

### **FCC REPORT**

Application No.:HKES1607001513ITApplicant:Kairos Watches LimitedManufacturer:Kairos Watches Limited

Factory: Shenzhen Kaifa Technology Co. Ltd.

Product Name: Mechanical Smart Watch Hybrid

Model No.(EUT): MSW 115
Add Model No.: SSW 158
Trade Mark: Kairos

FCC ID: 2AJSZ- MSW115SSW158

Standards: 47 CFR Part 15, Subpart C (2015)

**Date of Receipt:** 2016-08-29

**Date of Test:** 2016-09-14 to 2016-11-15

**Date of Issue:** 2016-11-17

Test Result: PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-



Report No.: HKES160700151301

Page: 2 of 86

### 2 Version

Revision Record							
Version Chapter Date Modifier Remark							
00		2016-11-17		Original			

Authorized for issue by:		
Tested By	Peter Geng) /Project Engineer	2016-11-15  Date
	(retel delig)/rioject Liigilieei	Date
Checked By	Eric Fu	2016-11-17
	(Eric Fu) /Reviewer	Date



Report No.: HKES160700151301

Page: 3 of 86

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS



Report No.: HKES160700151301

Page: 4 of 86

#### 4 Contents

			Page
1	CC	OVER PAGE	1
2	VE	ERSION	2
3	TE	EST SUMMARY	3
4	CC	ONTENTS	4
5		ENERAL INFORMATION	
	5.1	CLIENT INFORMATION	
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3	TEST ENVIRONMENT	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	8
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	9
6	TE	EST RESULTS AND MEASUREMENT DATA	11
	6.1	Antenna Requirement	
	6.2	CONDUCTED EMISSIONS	
	6.3	CONDUCTED PEAK OUTPUT POWER	
	6.4	20DB OCCUPY BANDWIDTH	
	6.5	CARRIER FREQUENCIES SEPARATION	
	6.6	HOPPING CHANNEL NUMBER	
	6.7 6.8	DWELL TIME	
	6.9	SPURIOUS RF CONDUCTED EMISSIONS	
	6.10	OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	
	6.11	RADIATED SPURIOUS EMISSION	
		11.1 Radiated Emission below 1GHz	
		11.2 Transmitter Emission above 1GHz	
	6.12	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PH	HOTOGRAPHS - EUT TEST SETUP	85
	7.1	CONDUCTED EMISSION	85
	7.2	RADIATED EMISSION	
	7.3	RADIATED SPURIOUS EMISSION	86
8	PH	HOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	86



Report No.: HKES160700151301

Page: 5 of 86

### 5 General Information

#### **5.1** Client Information

Applicant:	Kairos Watches Limited
Address of Applicant:	3A, Yee Lim Industrial Building, Stage 2, 8Ka Ting Road, Kwai Chung.
Manufacturer:	Kairos Watches Limited
Address of Manufacturer:	3A, Yee Lim Industrial Building, Stage 2, 8Ka Ting Road, Kwai Chung.
Factory:	Shenzhen Kaifa Technology Co. Ltd.
Address of Factory:	7006 Caitian Rd. Futian Dist. Shenzhen, China, 518035

#### 5.2 General Description of EUT

Product Name:	Mechanical Smart Watch Hybrid
Model No.:	MSW 115
Trade Mark:	Kairos
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V4.0 dual mode
	This test report is for classic mode.
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channels:	79
Antenna Type:	Chip antenna
Antenna Gain:	0.5dBi
Power Supply:	DC 3.7V 160mAh rechargeable battery charged by DC 5V from adapter Model: JX050100-EU INPUT: AC 100-240V, 50-60Hz OUTPUT: DC 5V,1000mA
Test Voltage:	AC 120V 60Hz
Cable:	USB LINE: 63cm, shielded.

#### Remark:

Model No.: MSW 115, SSW 158

Only the model MSW 115 was tested, since the circuitry design, PCB layout, electrical components used, internal wiring and functions were identical for all above models. Only different on model number and color.



Report No.: HKES160700151301

Page: 6 of 86

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz



Report No.: HKES160700151301

Page: 7 of 86

#### 5.3 Test Environment

Operating Environment:			
Temperature:	25.0 °C		
Humidity:	55 % RH		
Atmospheric Pressure:	1010 mbar		

### 5.4 Description of Support Units

The EUT has been tested independent unit.

#### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: HKES160700151301

Page: 8 of 86

#### 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### • FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

#### 5.7 Deviation from Standards

None.

#### 5.8 Abnormalities from Standard Conditions

None.

#### 5.9 Other Information Requested by the Customer

None.



Report No.: HKES160700151301

Page: 9 of 86

### 5.10 Equipment List

	Conducted Emission								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)			
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13			
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09			
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25			
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8- 02	EMC0120	2016-09-28	2017-09-28			
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4- 02	EMC0121	2016-09-28	2017-09-28			
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2- 02	EMC0122	2016-09-28	2017-09-28			
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25			
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09			

	RF connected test								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)			
1	DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09			
2	Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09			
3	Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25			
4	Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09			



Report No.: HKES160700151301

Page: 10 of 86

	RE in Chamber								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date			
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2016-05-13	2017-05-13			
2	EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESCI	SEM004-01	2016-04-25	2017-04-25			
3	Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29			
4	Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-07-06	2017-07-06			
5	Loop Antenna	ETS-Lindgren	6502	SEM003-08	2015-08-14	2018-08-14			

	RE in Chamber							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)		
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13		
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEM004-04	2016-04-25	2017-04-25		
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15		
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09		
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14		
6	Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2014-11-24	2017-11-24		
7	Horn Antenna (26GHz-40GHz)	A.H.Systems, inc.	SAS-573	SEM003-13	2015-02-12	2018-02-12		
8	Low Noise Amplifier	Black Diamond Series	BDLNA- 0118- 352810	SEM005-05	2016-10-09	2017-10-09		
9	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A		



Report No.: HKES160700151301

Page: 11 of 86

#### 6 Test results and Measurement Data

#### 6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **EUT Antenna:**



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.5dBi.



Report No.: HKES160700151301

Page: 12 of 86


#### 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.2	207			
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	150kHz to 30MHz				
Limit:	Limit (dBuV)				
	Frequency range (MHz)	Quasi-peak	Average		
	0.15-0.5	66 to 56*	56 to 46*		
	0.5-5	56	46		
	5-30	60	50		
	* Decreases with the logarithn	n of the frequency.		•	
Test Procedure:	The mains terminal disturble room.	oance voltage test was	s conducted in a shie	∍lded	
	<ol> <li>The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to</li> </ol>				



Report No.: HKES160700151301

Page: 13 of 86





Report No.: HKES160700151301


Page: 14 of 86

#### **Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



Site : Shielding Room Condition : CE LINE Job No. : 1513IT Test Mode : Charge+TX


		Freq	Cable Loss	LISN Factor	Read Level		Limit Line	Over Limit	Remark
		MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1		0.40831	0.02	9.60	15.76	25.38	47.68	-22.30	AVERAGE
2		0.40831	0.02	9.60	22.67	32.29	57.68	-25.40	QP
3		0.68626	0.02	9.61	16.17	25.81	56.00	-30.19	QP
4		0.68626	0.02	9.61	9.22	18.85	46.00	-27.15	AVERAGE
5		1.032	0.03	9.63	17.09	26.75	56.00	-29.25	QP
6		1.032	0.03	9.63	10.57	20.23	46.00	-25.77	AVERAGE
7		2.540	0.03	9.62	16.10	25.74	56.00	-30.26	QP
8		2.540	0.03	9.62	9.12	18.77	46.00	-27.23	AVERAGE
9	@	4.746	0.02	9.65	21.83	31.50	46.00	-14.50	AVERAGE
10		4.746	0.02	9.65	28.01	37.68	56.00	-18.32	QP
11		9.011	0.12	9.70	4.51	14.34	50.00	-35.66	AVERAGE
12		9.011	0.12	9.70	13.38	23.20	60.00	-36.80	QP



Report No.: HKES160700151301

Page: 15 of 86

#### Neutral line:



Site : Shielding Room Condition : CE NEUTRAL Job No. : 1513IT Test Mode : Charge+TX

	Freq	Cable Loss	LISN Factor	Read Level		Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.16327	0.02	9.61	12.97	22.60	55.30	-32.69	AVERAGE
2	0.16327	0.02	9.61	23.60	33.23	65.30	-32.07	QP
3	0.40187	0.02	9.62	23.17	32.81	57.81	-25.01	QP
4	0.40187	0.02	9.62	20.47	30.11	47.81	-17.71	AVERAGE
5	0.75493	0.03	9.64	13.13	22.79	46.00	-23.21	AVERAGE
6	0.75493	0.03	9.64	16.51	26.18	56.00	-29.82	QP
7	1.037	0.03	9.65	15.62	25.30	56.00	-30.70	QP
8	1.037	0.03	9.65	12.35	22.03	46.00	-23.97	AVERAGE
9	2.285	0.03	9.67	15.05	24.75	56.00	-31.25	QP
10	2.285	0.03	9.67	10.90	20.59	46.00	-25.41	AVERAGE
11	4.721	0.02	9.71	23.89	33.62	56.00	-22.38	QP
12	4.721	0.02	9.71	19.48	29.21	46.00	-16.79	AVERAGE

#### Notes:

- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereor reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and object to the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKES160700151301

Page: 16 of 86

#### 6.3 Conducted Peak Output Power





Report No.: HKES160700151301

Page: 17 of 86

#### **Measurement Data**

Measurement Data						
GFSK mode						
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	2.93	20.97	Pass			
Middle	2.55	20.97	Pass			
Highest	1.68	20.97	Pass			
	π/4DQPSK m	ode				
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	1.52	20.97	Pass			
Middle	1.12	20.97	Pass			
Highest	0.26	20.97	Pass			
	8DPSK mod	de				
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	1.84	20.97	Pass			
Middle	1.62	20.97	Pass			
Highest	0.82	20.97	Pass			




Report No.: HKES160700151301


Page: 18 of 86

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest












Report No.: HKES160700151301

Page: 19 of 86

Test mode: GFSK Test channel: Highest











Report No.: HKES160700151301

Page: 20 of 86

Test mode: π/4DQPSK Test channel: Middle











Report No.: HKES160700151301

Page: 21 of 86

Test mode: 8DPSK Test channel: Lowest










Report No.: HKES160700151301

Page: 22 of 86








Report No.: HKES160700151301

Page: 23 of 86

#### 6.4 20dB Occupy Bandwidth



#### **Measurement Data**

	2	20dB Occupy Bandwidth (kHz	2)
Test channel	GFSK	π/4DQPSK	8DPSK
Lowest	900	1212	1218
Middle	894	1224	1278
Highest	900	1242	1260




Report No.: HKES160700151301


Page: 24 of 86

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: HKES160700151301

Page: 25 of 86

Test mode: GFSK Test channel: Highest











Report No.: HKES160700151301

Page: 26 of 86

Test mode: π/4DQPSK Test channel: Middle











Report No.: HKES160700151301

Page: 27 of 86

Test mode: 8DPSK Test channel: Lowest










Report No.: HKES160700151301

Page: 28 of 86








Report No.: HKES160700151301

Page: 29 of 86

#### 6.5 Carrier Frequencies Separation





Report No.: HKES160700151301

Page: 30 of 86

	GFSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	1000	600	Pass			
	π/4DQPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	1036	828	Pass			
	8DPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	992	852	Pass			

Note: According to section 6.4,

Mode	20dB bandwidth (kHz)	Limit (kHz)
ivioue	(worse case)	(Carrier Frequencies Separation)
GFSK	900	600
π/4DQPSK	1242	828
8DPSK	1278	852




Report No.: HKES160700151301


Page: 31 of 86

#### Test plot as follows:

Test mode: GFSK Test channel: Middle



Test mode: π/4DQPSK Test channel: Middle






Report No.: HKES160700151301

Page: 32 of 86








Report No.: HKES160700151301

Page: 33 of 86

#### 6.6 Hopping Channel Number



#### **Measurement Data**

Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15





Report No.: HKES160700151301

Page: 34 of 86

Test plot as follows










Report No.: HKES160700151301

Page: 35 of 86






Report No.: HKES160700151301

Page: 36 of 86

#### 6.7 Dwell Time



#### **Measurement Data**

Mode	Packet	Dwell time (second)	Limit (second)
	DH1	0.13	≤0.4
GFSK	DH3	0.26	≤0.4
	DH5	0.32	≤0.4
	2-DH1	0.13	≤0.4
π/4DQPSK	2-DH3	0.27	≤0.4
	2-DH5	0.32	≤0.4
	3-DH1	0.13	≤0.4
8DPSK	3-DH3	0.26	≤0.4
	3-DH5	0.32	≤0.4



Report No.: HKES160700151301

Page: 37 of 86

#### Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

On (ms)\*total number=dwell time (ms)

The lowest channel (2441MHz), as below:

DH1 time slot=0.40 (ms)\*total number=128.00 (ms)

DH3 time slot=1.65 (ms)\* total number = 264.00 (ms)

DH5 time slot= $2.88 \text{ (ms)}^*$  total number = 316.80 (ms)

2-DH1 time slot=0.42 (ms)\*total number=134.40 (ms)

2-DH3 time slot=1.68 (ms)\* total number = 268.80 (ms)

2-DH5 time slot=2.91 (ms)\* total number = 320.10 (ms)

3-DH1 time slot=0.42 (ms)\*total number=134.40 (ms)

3-DH3 time  $slot=1.65 (ms)^* total number = 264.00 (ms)$ 

3-DH5 time slot=2.91 (ms)\* total number = 320.10 (ms)





Report No.: HKES160700151301

Page: 38 of 86

#### Test plot as follows:











Report No.: HKES160700151301

Page: 39 of 86











Report No.: HKES160700151301

Page: 40 of 86












Report No.: HKES160700151301

Page: 41 of 86












Report No.: HKES160700151301

Page: 42 of 86











Report No.: HKES160700151301

Page: 43 of 86











Report No.: HKES160700151301

Page: 44 of 86












Report No.: HKES160700151301

Page: 45 of 86












Report No.: HKES160700151301

Page: 46 of 86










Report No.: HKES160700151301

Page: 47 of 86

#### 6.8 Band-edge for RF Conducted Emissions







Report No.: HKES160700151301

Page: 48 of 86

#### Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
	O O		









Report No.: HKES160700151301

Page: 49 of 86











Report No.: HKES160700151301

Page: 50 of 86

Test mode: π/4DQPSK Test channel: Lowest









Report No.: HKES160700151301

Page: 51 of 86

Test mode:  $\pi/4$ DQPSK Test channel: Highest









Report No.: HKES160700151301

Page: 52 of 86

Test mode: 8DPSK Test channel: Lowest









Report No.: HKES160700151301

Page: 53 of 86









Report No.: HKES160700151301

Page: 54 of 86

#### 6.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)					
Test Method:	ANSI C63.10:2013 Section 7.8.8					
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane					
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type					
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.					
Instruments Used:	Refer to section 5.10 for details					
Test Results:	Pass					





Report No.: HKES160700151301

Page: 55 of 86

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: HKES160700151301

Page: 56 of 86











Report No.: HKES160700151301

Page: 57 of 86









Report No.: HKES160700151301

Page: 58 of 86

Test mode: GFSK Test channel: Highest









Report No.: HKES160700151301

Page: 59 of 86











Report No.: HKES160700151301

Page: 60 of 86









Report No.: HKES160700151301

Page: 61 of 86

Test mode: π/4DQPSK Test channel: Middle









Report No.: HKES160700151301

Page: 62 of 86











Report No.: HKES160700151301

Page: 63 of 86









Report No.: HKES160700151301

Page: 64 of 86

Test mode: 8DPSK Test channel: Lowest









Report No.: HKES160700151301

Page: 65 of 86











Report No.: HKES160700151301

Page: 66 of 86









Report No.: HKES160700151301

Page: 67 of 86

Test mode: 8DPSK Test channel: Highest








Report No.: HKES160700151301

Page: 68 of 86



#### Remark:

Use 100kHz RBW to determine the relative limit in the band 2.4GHz to 2.5GHz, and Use 1MHz RBW to measure spurious emissions in the band 30MHz to 10GHz and 10GHz to 25GHz. The sweep points set to 30001.



Report No.: HKES160700151301

Page: 69 of 86

#### 6.10 Other requirements Frequency Hopping Spread Spectrum System

#### Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

#### Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage


outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- · Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)



Report No.: HKES160700151301

Page: 70 of 86

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

#### Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



Report No.: HKES160700151301

Page: 71 of 86

#### **6.11 Radiated Spurious Emission**


Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10: 2013								
Test Site:	Below 1GHz: Measurement Distance: 10m (Semi-Anechoic Chamber) Above 1GHz: Measurement Distance: 3m (Full-Anechoic Chamber)								
Receiver Setup:	Frequency	VBW	Remark						
	0.009MHz-0.090MHz		Peak	10kHz	30kHz	Peak			
	0.009MHz-0.090MHz		Average	10kHz	30kHz	Average			
	0.090MHz-0.110MHz		Quasi-peak	10kHz	30kHz	Quasi-peak			
	0.110MHz-0.490MHz		Peak	10kHz	30kHz	Peak			
	0.110MHz-0.490MHz		Average	10kHz	30kHz	Average			
	0.490MHz -30MHz		Quasi-peak	10kHz	30kHz	Quasi-peak			
	30MHz-1GHz		Quasi-peak	100 kHz	300kHz	Quasi-peak			
	Above 1GHz		Peak	1MHz	3MHz	Peak			
			Peak	1MHz	10Hz	Average			
Limit:	Limit: Frequency Field strength (microvolt/meter)  0.009MHz-0.490MHz 2400/F(kHz)  0.490MHz-1.705MHz 24000/F(kHz)  1.705MHz-30MHz 30		•	Limit (dBuV/m)	Remark	Measurement distance (m)			
			400/F(kHz)	-	-	300			
			1000/F(kHz)	-	-	30			
			30	-	-	30			
	30MHz-88MHz	100		40.0	Quasi-peak	3			
	88MHz-216MHz	150		43.5	Quasi-peak	3			
	216MHz-960MHz	200		46.0	Quasi-peak	3			
	960MHz-1GHz	500		54.0	Quasi-peak	3			
	Above 1GHz	500		54.0	Average	3			
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.								



Report No.: HKES160700151301

Page: 72 of 86

#### Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

#### Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 and 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sqs.com/en/Terms-and-Conditions.aspx">http://www.sqs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sqs.com/en/Terms-and-Conditions/Terms-en-Document.aspx">http://www.sqs.com/en/Terms-en-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKES160700151301

Page: 73 of 86

	EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.  h. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz)  i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.  j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type
	Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case.  Pretest the EUT at Charge + Transmitting mode, For below 1GHz part, through pre-scan, the worst case is the lowest channel.  Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Report No.: HKES160700151301

Page: 74 of 86

#### 6.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Charge + Transmitting	Vertical



Condition: 10m VERTICAL

Job No. : 1513IT Test Mode: charge+BT


	ouc. cha	BC.D.						
		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
_								
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	6.70	12.47	32.97	38.37	24.57	29.50	-4.93
2 pp	33.68	6.70	12.60	32.98	38.46	24.78	29.50	-4.72
3	94.43	7.20	9.01	32.82	31.07	14.46	33.10	-18.64
4	143.83	7.42	13.01	32.75	29.23	16.91	33.10	-16.19
5	470.52	8.48	16.40	32.60	28.64	20.92	35.60	-14.68
6	952.09	9.58	22.74	32.50	27.24	27.06	35.60	-8.54



Report No.: HKES160700151301

Page: 75 of 86

Test mode: Charge + Transmitting Horizontal



Condition: 10m HORIZONTAL

Job No. : 1513IT Test Mode: charge+BT

	Freq			Preamp Factor				Over Limit
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	39.02	6.78	13.19	32.98	26.54	13.53	29.50	-15.97
2	48.33	6.87	12.82	33.00	27.20	13.89	29.50	-15.61
3	58.82	7.00	12.09	32.95	26.24	12.38	29.50	-17.12
4	164.91	7.50	12.91	32.73	28.09	15.77	33.10	-17.33
5 pp	545.18	8.76	17.64	32.60	28.31	22.11	35.60	-13.49
6	975.75	9.60	22.81	32.50	27.62	27.53	43.50	-15.97



Report No.: HKES160700151301

Page: 76 of 86

#### **Below 1GHz**

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

 $L_3 / L_{10} = D_{10} / D_3$ 

Note:

 $L_3$ : Level @ 3m distance. Unit: uV/m;  $L_{10}$ : Level @ 10m distance. Unit: uV/m;

D<sub>3</sub>: 3m distance. Unit: m
D<sub>10</sub>: 10m distance. Unit: m
The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
30.00	24.57	16.92	56.41	35.03	40.00	-4.97	V
33.68	24.78	17.34	57.79	35.24	40.00	-4.76	V
94.43	14.46	5.28	17.61	24.92	43.50	-18.58	V
143.83	16.91	7.01	23.35	27.37	43.50	-16.13	V
470.52	20.92	11.12	37.06	31.38	46.00	-14.62	V
952.09	27.06	22.54	75.14	37.52	46.00	-8.48	V
39.02	13.53	4.75	15.83	23.99	40.00	-16.01	Н
48.33	13.89	4.95	16.50	24.35	40.00	-15.65	Н
58.82	12.38	4.16	13.86	22.84	40.00	-17.16	Н
164.91	15.77	6.14	20.48	26.23	43.50	-17.27	Н
545.18	22.11	12.75	42.50	32.57	46.00	-13.43	Н
975.75	27.53	23.80	79.32	37.99	54.00	-16.01	Н



Report No.: HKES160700151301

Page: 77 of 86

#### 6.11.2 Transmitter Emission above 1GHz

Test mode:	(	GFSK(DH1)	Test	channel:	Lowest	Rema	rk:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3732.570	32.87	7.72	38.58	47.85	49.86	74.00	-24.14	Vertical
4804.000	34.16	8.87	39.03	47.00	51.00	74.00	-23.00	Vertical
6078.201	34.76	10.46	38.95	44.91	51.18	74.00	-22.82	Vertical
7206.000	36.42	10.68	38.18	42.50	51.42	74.00	-22.58	Vertical
9608.000	37.52	12.50	36.99	39.83	52.86	74.00	-21.14	Vertical
12476.260	38.89	14.17	38.79	39.05	53.32	74.00	-20.68	Vertical
3770.567	32.98	7.73	38.60	47.68	49.79	74.00	-24.21	Horizontal
4804.000	34.16	8.87	39.03	46.34	50.34	74.00	-23.66	Horizontal
6025.661	34.72	10.53	38.98	45.29	51.56	74.00	-22.44	Horizontal
7206.000	36.42	10.68	38.18	43.58	52.50	74.00	-21.50	Horizontal
9608.000	37.52	12.50	36.99	39.74	52.77	74.00	-21.23	Horizontal
12085.370	38.65	14.49	38.39	38.27	53.02	74.00	-20.98	Horizontal

Test mode:	G	FSK(DH1)	Test	channel:	Middle	Rema	ırk:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Cable Loss (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over limit (dB)	Polarization
3842.163	33.18	7.76	38.63	46.67	48.98	74.00	-25.02	Vertical
4882.000	34.30	8.98	39.06	46.50	50.72	74.00	-23.28	Vertical
6265.724	34.92	10.22	38.83	44.24	50.55	74.00	-23.45	Vertical
7323.000	36.37	10.72	38.06	42.40	51.43	74.00	-22.57	Vertical
9764.000	37.55	12.58	36.91	39.26	52.48	74.00	-21.52	Vertical
12155.510	38.69	14.43	38.46	38.97	53.63	74.00	-20.37	Vertical
3765.116	32.97	7.73	38.59	46.31	48.42	74.00	-25.58	Horizontal
4882.000	34.30	8.98	39.06	44.84	49.06	74.00	-24.94	Horizontal
6078.201	34.76	10.46	38.95	45.76	52.03	74.00	-21.97	Horizontal
7323.000	36.37	10.72	38.06	42.50	51.53	74.00	-22.47	Horizontal
9764.000	37.55	12.58	36.91	39.99	53.21	74.00	-20.79	Horizontal
12190.740	38.72	14.40	38.50	39.05	53.67	74.00	-20.33	Horizontal



Report No.: HKES160700151301

Page: 78 of 86

Test mode:	(	GFSK(DH1)	Tes	t channel:	Highest	Rema	ırk:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over limit (dB)	Polarization
3903.804	33.34	7.78	38.66	47.66	50.12	74.00	-23.88	Vertical
4960.000	34.43	9.09	39.09	47.50	51.93	74.00	-22.07	Vertical
5947.702	34.67	10.42	39.00	46.62	52.71	74.00	-21.29	Vertical
7440.000	36.32	10.77	37.94	43.79	52.94	74.00	-21.06	Vertical
9920.000	37.58	12.67	36.84	39.52	52.93	74.00	-21.07	Vertical
12085.370	38.65	14.49	38.39	38.37	53.12	74.00	-20.88	Vertical
3858.877	33.22	7.76	38.64	47.15	49.49	74.00	-24.51	Horizontal
4960.000	34.43	9.09	39.09	46.03	50.46	74.00	-23.54	Horizontal
6202.582	34.87	10.30	38.87	44.80	51.10	74.00	-22.90	Horizontal
7440.000	36.32	10.77	37.94	43.67	52.82	74.00	-21.18	Horizontal
9920.000	37.58	12.67	36.84	39.38	52.79	74.00	-21.21	Horizontal
12261.500	38.76	14.34	38.57	38.61	53.14	74.00	-20.86	Horizontal

#### Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



Report No.: HKES160700151301

Page: 79 of 86

### 6.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15	5.209 and 15.205					
Test Method:	ANSI C63.10: 2013						
Test Site:	Below 1GHz:						
	Measurement Distance: 3m (Semi-Anechoic Chamber)						
	Above 1GHz:						
	Measurement Distance: 3m (Full-Anechoic Chamber)						
Limit:	Frequency	Limit (dBuV/m @3m)	Remark				
	30MHz-88MHz	40.0	Quasi-peak Value				
	88MHz-216MHz	43.5	Quasi-peak Value				
	216MHz-960MHz	46.0	Quasi-peak Value				
	960MHz-1GHz	54.0	Quasi-peak Value				
	Al 4011	54.0	Average Value				
	Above 1GHz	74.0	Peak Value				
Test Setup:							
Test Receiver	Pho Controlles Angular Controlles	(Turntable)  Ground Referos Plane  Test Receiver	Antenna Tower  Antenna Tower  Controller				
Figure 1. 30MH	Iz to 1GHz	Figure 2. Abov	re 1 GHz				



Report No.: HKES160700151301

Page: 80 of 86

Exploratory Test Mode:	<ul> <li>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> <li>h. Test the EUT in the lowest channel, the Highest channel</li> <li>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</li> <li>j. Repeat above procedures until all frequencies measured was complete.</li> <li>Non-hopping transmitting mode with all kind of modulation and all kind of data type</li> <li>Charge + Transmitting mode.</li> </ul>
	••
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case.
	Pretest the EUT at Charge + Transmitting mode
	Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass
	1




Report No.: HKES160700151301

Page: 81 of 86

### Test plot as follows:

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Vertical



Condition: 3m VERTICAL Job No: : 1513IT

Mode: : 2402 Band edge

: BT


		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	•							
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
			,					
1	2390.000	5 3/	20 08	39 1/	<b>/</b> 5 12	11 16	7/ 00	32 54
_	2330.000	3.34	25.00	30.14	45.10	41.40	74.00	-32.34
2	pp 2402.250	5.35	29.11	38.15	95.76	92.07	74.00	18.07



Report No.: HKES160700151301

Page: 82 of 86

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 1513IT

Mode: : 2402 Band edge

: BT


	Freq			Preamp Factor				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2377.236							
2	2390.000							
3 pp	2402.250	5.35	29.11	38.15	94.11	90.42	74.00	16.42



Report No.: HKES160700151301

Page: 83 of 86

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Vertical	l
------------------	------------	---------------	---------	---------	------	----------	---



Condition: 3m VERTICAL Job No: : 1513IT

Mode: : 2480 Band edge

: BT

Cable Ant Preamp Read Limit Over
Freq Loss Factor Factor Level Level Line Limit

MHz dB dB/m dB dBuV dBuV/m dBuV/m dBuV/m dBuV/m


1 pp 2480.254 5.41 29.34 38.15 94.64 91.24 74.00 17.24 2 2483.500 5.41 29.35 38.15 48.63 45.24 74.00 -28.76



Report No.: HKES160700151301

Page: 84 of 86

Worse case mode: GFSK(DH5) Test channel: Highest Remark: Peak Horizontal



Condition: 3m HORIZONTAL

Job No: : 1513IT

Mode: : 2480 Band edge

: BT

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	•							
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
			u.,		454.	uou*/	usur,	45
1	p 2479.731	E //1	20 24	20 15	02 19	00 70	74 00	1/ 70
- P	p 24/9./31	3.41	25.54	30.13	32.10	00.70	74.00	14.70
2	2483.500	5.41	29.35	38.15	52.32	48.93	74.00	-25.07

#### Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor




Report No.: HKES160700151301

Page: 85 of 86

### 7 Photographs - EUT Test Setup

Test Model No.: MSW 115

### 7.1 Conducted Emission



#### 7.2 Radiated Emission






Report No.: HKES160700151301

Page: 86 of 86

### 7.3 Radiated Spurious Emission



### 8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for HKES1607001513IT.