

**FCC PART 22 TEST REPORT****FCC Part 22H****Report Reference No.**.....: LCS210812034AEE**FCC ID**.....: 2AJTU-G2**Date of Issue**.....: October 27, 2021**Testing Laboratory Name**.....: Shenzhen LCS Compliance Testing Laboratory Ltd.

Address.....: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

**Applicant's name**.....: South Surveying & Mapping Technology Co., Ltd.

Address.....: No.39, Sicheng Road, Tianhe District, Guangzhou, China

**Test specification**.....:

Standard.....: FCC Part 22H: Cellular Radiotelephone Service

Test Report Form No .....: LCSEMC-1.0

TRF Originator.....: Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF.....: Dated 2011-03

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description**.....: GNSS RECEIVER

Trade Mark.....: SOUTH, KOLIDA, SANDING, RUIDE, TIANYU

Test Model.....: G2

Ratings.....: Please Refer to Page 6

Hardware version.....: SC20-K803\_V2R0

Software version .....: 1.09.210624.RA40PY

Frequency .....: UMTS Band V

Result.....: PASS

**Compiled by:**

Diamond Lu/ Administrators

**Supervised by:**

Jin Wang/ Technique principal

**Approved by:**

Gavin Liang/ Manager



## TEST REPORT

|                   |                        |                  |
|-------------------|------------------------|------------------|
| Test Report No. : | <b>LCS210812034AEE</b> | October 27, 2021 |
|                   |                        | Date of issue    |

|                           |   |
|---------------------------|---|
| EUT.....                  | : GNSS RECEIVER   |
| Test Model.....           | : G2  |
| <b>Applicant</b> .....    | : <b>South Surveying &amp; Mapping Technology Co., Ltd.</b> |
| Address.....              | : No.39, Sicheng Road, Tianhe District, Guangzhou, China    |
| Telephone.....            | : /   |
| Fax.....                  | : /   |
| <b>Manufacturer</b> ..... | : <b>South Surveying &amp; Mapping Technology Co., Ltd.</b> |
| Address.....              | : No.39, Sicheng Road, Tianhe District, Guangzhou, China    |
| Telephone.....            | : /   |
| Fax.....                  | : /   |
| <b>Factory</b> .....      | : <b>South Surveying &amp; Mapping Technology Co., Ltd.</b> |
| Address.....              | : No.39, Sicheng Road, Tianhe District, Guangzhou, China    |
| Telephone.....            | : /   |
| Fax.....                  | : /   |

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



## Revision History

| Revision | Issue Date       | Revisions     | Revised By  |
|----------|------------------|---------------|-------------|
| 000      | October 27, 2021 | Initial Issue | Gavin Liang |
|          |                  |               |             |
|          |                  |               |             |



## Contents

|      |   |    |
|------|---|----|
| 1    | TEST STANDARDS .....                                | 5  |
| 2    | SUMMARY .....                                       | 6  |
| 2.1  | General Remarks                                     | 6  |
| 2.2  | Product Description                                 | 6  |
| 2.3  | Equipment under Test                                | 9  |
| 2.4  | Short description of the Equipment under Test (EUT) | 9  |
| 2.5  | Internal Identification of AE used during the test  | 9  |
| 2.6  | Normal Accessory setting                            | 9  |
| 2.7  | EUT configuration                                   | 10 |
| 2.8  | Related Submittal(s) / Grant (s)                    | 10 |
| 2.9  | Modifications                                       | 10 |
| 2.10 | General Test Conditions/Configurations              | 10 |
| 3    | TEST ENVIRONMENT .....                              | 11 |
| 3.1  | Address of the test laboratory                      | 11 |
| 3.2  | Test Facility                                       | 11 |
| 3.3  | Environmental conditions                            | 11 |
| 3.4  | Test Description                                    | 11 |
| 3.5  | Equipments Used during the Test                     | 12 |
| 3.6  | Measurement uncertainty                             | 13 |
| 4    | TEST CONDITIONS AND RESULTS .....                   | 14 |
| 4.1  | Output Power  | 14 |
| 4.2  | Radiated Spurious Emission                          | 17 |
| 4.3  | Occupied Bandwidth and Emission Bandwidth           | 20 |
| 4.4  | Band Edge Compliance                                | 22 |
| 4.5  | Spurious Emission on Antenna Port                   | 23 |
| 4.6  | Frequency Stability Test                            | 26 |
| 4.7  | Peak-to-Average Ratio (PAR)                         | 28 |
| 5    | TEST SETUP PHOTOS OF THE EUT .....                  | 30 |
| 6    | EXTERNAL PHOTOS OF THE EUT .....                    | 30 |
| 7    | INTERNAL PHOTOS OF THE EUT .....                    | 30 |



## **1 TEST STANDARDS**

The tests were performed according to following standards:

[FCC Part 22H](#): Cellular Radiotelephone Service.

[TIA-603-E March 2016](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[47 CFR FCC Part 15 Subpart B](#): Unintentional Radiators.

[FCC Part 2](#): Frequency Allocations And Radio Treaty Matters; General Rules And Regulations.

[ANSI C63.4:2014](#): Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

[FCC KDB971168 D01](#) Power Meas License Digital Systems v03r01

[ANSI C63.26-2015](#): Compliance Testing of Transmitters Used in Licensed Radio Services.



## 2 SUMMARY

### 2.1 General Remarks

|                                |   |                                   |
|--------------------------------|---|-----------------------------------|
| Date of receipt of test sample | : | August 18, 2021                   |
| Date of Test                   | : | August 18, 2021 ~October 26, 2021 |
| Date of Report                 | : | October 27, 2021                  |

### 2.2 Product Description

The **South Surveying & Mapping Technology Co., Ltd.**’s Model: G2 or the “EUT” as referred to in this report; more general information as follows, for more details, refer to the user’s manual of the EUT.

|                      |   |   |
|----------------------|---|---|
| EUT                  | : | GNSS RECEIVER   |
| Test Model           | : | G2  |
| Additional Model No. | : | T9, T9 Pro, C8, RENO1, R1, K3IMU, K3X, K30 Pro, K58plus, K7, K7X, K8, K8X, K9, K9X, K30, K30X, R93i, T7, T8, C6, C7, C9, P30, G1, G3, G4, G5, G7, G8, G9, S680  |
| Model Declaration    | : | PCB board, structure and internal of these model(s) are the same, So no additional models were tested   |
| Power Supply         | : | For AC Adapter(model: DAS-45PDA FUS)<br>Input:100-240V~, 50/60Hz, 1.5A Max<br>Output: 5.0V=3.0A, 9.0V=3.0A, 12.0V=3.0A, 15.0V=3.0A, 20V=2.25A, 45W Max<br>DC 7.4V by Rechargeable Li-ion Battery, 6800mAh |
| Hardware Version     | : | SC20-K803_V2R0  |
| Software Version     | : | 1.09.210624.RA40PY  |
| Bluetooth            | : |   |
| Frequency Range      | : | 2402MHz ~ 2480MHz   |
| Chanel Number        | : | 79 channels for Bluetooth V4.2(DSS)<br>40 channels for Bluetooth V4.2 (DTS)   |
| Chanel Spacing       | : | 1MHz for Bluetooth V4.2 (DSS)<br>2MHz for Bluetooth V4.2 (DTS)  |
| Modulation Type      | : | GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.2(DSS)<br>GFSK for Bluetooth V4.2 (DTS)   |
| Bluetooth Version    | : | V4.2  |
| Antenna Description  | : | Internal Antenna, 5.5dBi (max.)   |
| WIFI(2.4G Band)      | : |   |
| Frequency Range      | : | 2412MHz ~ 2462MHz   |
| Channel Spacing      | : | 5MHz  |
| Channel Number       | : | 11 Channels for 20MHz bandwidth (2412~2462MHz)<br>7 Channels for 40MHz bandwidth (2422~2452MHz)   |
| Modulation Type      | : | IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)<br>IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)  |
| Antenna Description  | : | Internal Antenna, 5.5dBi (max.)   |



|                     |   |
|---------------------|---|
| 2G                  | :   |
| Support Band        | : <input checked="" type="checkbox"/> GSM 900 (EU-Band) <input checked="" type="checkbox"/> DCS 1800 (EU-Band)<br><input checked="" type="checkbox"/> GSM 850 (U.S.-Band) <input checked="" type="checkbox"/> PCS 1900 (U.S.-Band)  |
| Release Version     | : R99   |
| GPRS Class          | : Class 12  |
| EGPRS Class         | : Class 12  |
| Type Of Modulation  | : GMSK for GSM/GPRS; 8PSK for EGPRS   |
| Antenna Description | : Internal Antenna<br>2.0dBi (max.) For GSM 850<br>2.0dBi (max.) For PCS 1900   |
| 3G                  | :   |
| Support Band        | : <input type="checkbox"/> WCDMA Band II (U.S.-Band)<br><input checked="" type="checkbox"/> WCDMA Band V (U.S.-Band)<br><input type="checkbox"/> WCDMA Band IV (U.S.-Band)<br><input checked="" type="checkbox"/> WCDMA Band I (EU-Band)<br><input checked="" type="checkbox"/> WCDMA Band VIII (EU-Band) |
| Release Version     | : R8  |
| Type Of Modulation  | : WCDMA: QPSK; HSDPA/HSUPA: QPSK  |
| Antenna Description | : Internal Antenna<br>2.0dBi (max.) For WCDMA Band V  |
| LTE                 | :   |
| Support Band        | : <input checked="" type="checkbox"/> E-UTRA Band 5(U.S.-Band)<br><input checked="" type="checkbox"/> E-UTRA Band 7(U.S.-Band)<br><input checked="" type="checkbox"/> E-UTRA Band 38(U.S.-Band)<br><input checked="" type="checkbox"/> E-UTRA Band 41(U.S.-Band)  |
| LTE Release Version | : R9  |
| Type Of Modulation  | : QPSK/16QAM  |
| Antenna Description | : Internal Antenna<br>2.0dBi (max.) For E-UTRA Band 5<br>2.0dBi (max.) For E-UTRA Band 7<br>2.0dBi (max.) For E-UTRA Band 38<br>2.0dBi (max.) For E-UTRA Band 41  |
| Power Class         | : Class 3   |
| NFC                 | :   |
| Operating Frequency | : 13.56MHz;   |
| Modulation Type     | : ASK   |
| Antenna Description | : Loop Antenna, 2.0dBi(Max.)  |
| PMR                 | :   |
| Operating Frequency | : 410 ~ 470MHz  |
| Channel Separation  | : 12.5KHz & 25KHz   |
| Modulation Type     | : GMSK  |
| Emission Designator | : 8K25G1D for GMSK Modulation at 12.5KHz Channel Separation 16K4G1D for GMSK Modulation at 25KHz  |



## Channel Separation Channel Separation

Antenna Type : SMA Antenna

Antenna Gain : 5.0dBi (max.) for PMR

GPS function : Support and only RX

Extreme temp. : -30°C to +50°C

Tolerance

Extreme vol. Limits : 6.3VDC to 8.4VDC (nominal: 7.4VDC)



## 2.3 Equipment under Test

### Power supply system utilised

|                      |   |                                  |                                  |                       |             |
|----------------------|---|----------------------------------|----------------------------------|-----------------------|-------------|
| Power supply voltage | : | <input type="radio"/>            | 120V / 60 Hz                     | <input type="radio"/> | 115V / 60Hz |
|                      |   | <input type="radio"/>            | 12 V DC                          | <input type="radio"/> | 24 V DC     |
|                      |   | <input checked="" type="radio"/> | Other (specified in blank below) | 7.4 V DC              |             |

### Test frequency list

| Test Mode    | TX/RX | RF Channel   |              |              |
|--------------|-------|--------------|--------------|--------------|
|              |       | Low(L)       | Middle (M)   | High (H)     |
| WCDMA Band V | TX    | Channel 4132 | Channel 4182 | Channel 4233 |
|              |       | 826.4 MHz    | 836.4 MHz    | 846.6 MHz    |
|              | RX    | Channel 4357 | Channel 4407 | Channel 4458 |
|              |       | 871.4 MHz    | 881.4 MHz    | 891.6 MHz    |

## 2.4 Short description of the Equipment under Test (EUT)

### 2.4.1 General Description

GNSS RECEIVER is subscriber equipment in the GSM/ WCDMA/ LTE system. GSM/GPRS/EGPRS frequency band is Band II/V. The HSPA/UMTS frequency band is Band V. LTE frequency band is band 5/7/38/41. The HSPA/UMTS frequency band II and Band V test data included in this report. The GNSS RECEIVER implements such functions as RF signal receiving/transmitting, GSM/GPRS/EGPRS/ HSPA/UMTS/LTE protocol processing, video MMS service and etc. Externally it provides SIM card interface.

## 2.5 Internal Identification of AE used during the test

| AE ID* | Description                     |
|--------|---------------------------------|
| AE1    | Rechargeable Li-Polymer Battery |
| AE2    | Switching Adapter               |

AE2

Adapter Model: DSA-45PDA-FCH

Adapter Input: 100-240V~, 50/60Hz, 1400mA

Adapter Output: 12V==3000mA

## 2.6 Normal Accessory setting

N/A



## 2.7 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

|               |                |   |
|---------------|----------------|---|
| ○ Power Cable | Length (m) :   | / |
|               | Shield :       | / |
|               | Detachable :   | / |
| ○ Multimeter  | Manufacturer : | / |
|               | Model No. :    | / |

## 2.8 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AJTU-G2 filing to comply with FCC Part 22H

## 2.9 Modifications

No modifications were implemented to meet testing criteria.

## 2.10 General Test Conditions/Configurations

### 2.10.1 Test Modes

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

| Test Mode | Test Modes Description        |
|-----------|-------------------------------|
| UMTS/TM1  | WCDMA system, QPSK modulation |
| UMTS/TM2  | HSDPA system, QPSK modulation |
| UMTS/TM3  | HSUPA system, QPSK modulation |

Note: As WCDMA, HSDPA and HSUPA with the same emission designator, test result recorded in this report at the worst case UMTS/TM1 only after exploratory scan.

### 2.10.2 Test Environment

| Environment Parameter | Selected Values During Tests |         |
|-----------------------|------------------------------|---------|
| Relative Humidity     | Ambient                      |         |
| Temperature           | TN                           | Ambient |
|                       | VL                           | DC 6.3V |
| Voltage               | VN                           | DC 7.4V |
|                       | VH                           | DC 8.4V |

NOTE: VL=lower extreme test voltage VN=nominal voltage

VH=upper extreme test voltage TN=normal temperature



### 3 TEST ENVIRONMENT

#### 3.1 Address of the test laboratory

##### Shenzhen LCS Compliance Testing Laboratory Ltd

101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

The sites are constructed in conformance with the requirements of ANSI C63.4 (2014) and CISPR Publication 22.

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912

#### 3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 15-35 ° C    |
| Humidity:             | 30-60 %      |
| Atmospheric pressure: | 950-1050mbar |

(1)expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

#### 3.4 Test Description

##### 3.4.1 Cellular Band (824-849MHz paired with 869-894MHz) (Band V)

| Test Item                                  | FCC Rule No.     | Requirements  | Verdict |
|--|------------------|---|---------|
| Effective(Isotropic) Radiated Output Power | §2.1046, §22.913 | FCC: ERP ≤ 7W.  | Pass    |
| Modulation Characteristics                 | §2.1047          | Digital modulation  | N/A     |
| Bandwidth                                  | §2.1049          | OBW: No limit. EBW: No limit.   | Pass    |
| Band Edges Compliance                      | §2.1051, §22.917 | ≤-13dBm/1%*EBW, in 1MHz bands immediately outside and adjacent to The frequency block.                      | Pass    |
| Spurious Emission at Antenna Terminals     | §2.1051, §22.917 | ≤ -13dBm/100kHz, from 9kHz to 10 <sup>th</sup> harmonics but outside authorized operating frequency ranges. | Pass    |
| Field Strength of Spurious Radiation       | §2.1053, §22.917 | ≤ -13dBm/100kHz.  | Pass    |
| Frequency Stability                        | §2.1055, §22.355 | ≤ ±2.5ppm.  | Pass    |
| Peak-Average Ratio                         | §24.232          | ≤13dB   | Pass    |

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".



### 3.5 Equipments Used during the Test

| Item | Equipment                                 | Manufacturer         | Model No.     | Serial No. | Cal Date   | Due Date   |
|------|---|----------------------|---------------|------------|------------|------------|
| 1    | Power Meter                               | R&S                  | NRVS          | 100444     | 2021-06-21 | 2022-06-20 |
| 2    | Power Sensor                              | R&S                  | NRV-Z81       | 100458     | 2021-06-21 | 2022-06-20 |
| 3    | Power Sensor                              | R&S                  | NRV-Z32       | 10057      | 2021-06-21 | 2022-06-20 |
| 4    | LTE Test Software                         | Tonscend             | JS1120-1      | N/A        | N/A        | N/A        |
| 5    | RF Control Unit                           | Tonscend             | JS0806        | 158060009  | 2020-11-26 | 2021-11-25 |
| 6    | MXA Signal Analyzer                       | Agilent              | N9020A        | MY51250905 | 2020-11-17 | 2021-11-16 |
| 7    | WIDEBAND RADIO<br>COMMUNICATION<br>TESTER | R&S                  | CMW 500       | 103818     | 2021-06-21 | 2022-06-20 |
| 8    | DC Power Supply                           | Agilent              | E3642A        | N/A        | 2020-11-26 | 2021-11-25 |
| 9    | EMI Test Software                         | Farad                | EZ            | N/A        | N/A        | N/A        |
| 10   | 3m Semi Anechoic<br>Chamber               | SIDT<br>FRANKONIA    | SAC-3M        | 03CH03-HY  | 2021-06-21 | 2022-06-20 |
| 11   | Positioning Controller                    | MF                   | MF7082        | MF78020803 | 2021-06-21 | 2022-06-20 |
| 12   | Active Loop Antenna                       | SCHWARZBECK          | FMZB<br>1519B | 00005      | 2021-07-25 | 2024-07-24 |
| 13   | By-log Antenna                            | SCHWARZBECK          | VULB9163      | 9163-470   | 2021-07-25 | 2024-07-24 |
| 14   | Horn Antenna                              | SCHWARZBECK          | BBHA<br>9120D | 9120D-1925 | 2021-07-01 | 2024-06-30 |
| 15   | Broadband Horn Antenna                    | SCHWARZBECK          | BBHA 9170     | 791        | 2020-09-20 | 2023-09-19 |
| 16   | Broadband Preamplifier                    | SCHWARZBECK          | BBV9745       | 9719-025   | 2021-06-21 | 2022-06-20 |
| 17   | EMI Test Receiver                         | R&S                  | ESR 7         | 101181     | 2021-06-21 | 2022-06-20 |
| 18   | RS SPECTRUM<br>ANALYZER                   | R&S                  | FSP40         | 100503     | 2020-11-17 | 2021-11-16 |
| 19   | Broadband Preamplifier                    | /                    | BP-01M18G     | P190501    | 2021-06-21 | 2022-06-20 |
| 20   | 6dB Attenuator                            | /                    | 100W/6dB      | 1172040    | 2021-06-21 | 2022-06-20 |
| 21   | 3dB Attenuator                            | /                    | 2N-3dB        | /          | 2020-11-17 | 2021-11-16 |
| 22   | Temperature & Humidity<br>Chamber         | GUANGZHOU<br>GOGNWEN | GDS-100       | 70932      | 2020-10-08 | 2021-10-07 |
|      |   |                      |               |            | 2021-10-07 | 2022-10-06 |



### 3.6 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to ETSI TR 100 028 " Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics" and is documented in the Shenzhen LCS Compliance Testing Laboratory Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen LCS Compliance Testing Laboratory Ltd. is reported:

| Test                                | Range      | Measurement Uncertainty | Notes |
|-------------------------------------|------------|-------------------------|-------|
| Radiated Emission                   | 30~1000MHz | 3.10 dB                 | (1)   |
| Radiated Emission                   | 1~18GHz    | 3.80 dB                 | (1)   |
| Radiated Emission                   | 18-40GHz   | 3.90 dB                 | (1)   |
| Conducted Disturbance               | 0.15~30MHz | 1.63 dB                 | (1)   |
| Conducted Power                     | 9KHz~18GHz | 0.61 dB                 | (1)   |
| Spurious RF Conducted Emission      | 9KHz~40GHz | 1.22 dB                 | (1)   |
| Band Edge Compliance of RF Emission | 9KHz~40GHz | 1.22 dB                 | (1)   |
| Occupied Bandwidth                  | 9KHz~40GHz | -                       | (1)   |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

## 4 TEST CONDITIONS AND RESULTS


### 4.1 Output Power

#### TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S WIDEBAND RADIO COMMUNICATION TESTER (CMW 500) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### 4.1.1. Conducted Output Power

#### TEST CONFIGURATION



#### TEST PROCEDURE

##### **Conducted Power Measurement:**

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a CMW 500 by an Att.
- EUT Communicate with CMW 500 then selects a channel for testing.
- Add a correction factor to the display CMW 500, and then test.

#### TEST RESULTS

| Item     | band           | WCDMA Band V result (dBm) |                |       |
|----------|----------------|---------------------------|----------------|-------|
|          |                | Channel/Frequency(MHz)    |                |       |
| sub-test | 4132/<br>826.4 | 4182/<br>836.4            | 4233/<br>846.6 |       |
|          | Sub -Test 1    | 23.00                     | 22.81          | 22.89 |
| RMC      | 12.2kbps RMC   | 23.46                     | 23.62          | 23.52 |
| HSDPA    | Sub -Test 2    | 22.87                     | 22.80          | 22.79 |
|          | Sub -Test 3    | 22.71                     | 22.89          | 22.89 |
|          | Sub -Test 4    | 22.79                     | 22.90          | 22.73 |
|          | Sub -Test 5    | 22.86                     | 22.73          | 22.77 |
| HSUPA    | Sub -Test 2    | 22.81                     | 22.70          | 22.88 |
|          | Sub -Test 3    | 22.89                     | 22.86          | 22.82 |
|          | Sub -Test 4    | 22.72                     | 22.87          | 22.80 |
|          | Sub -Test 5    | 22.86                     | 22.76          | 22.72 |


#### 4.1.1 Radiated Output Power

##### TEST DESCRIPTION

This is the test for the maximum radiated power from the EUT.

Rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

##### TEST CONFIGURATION



##### TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=10MHz, VBW=10MHz, And the maximum value of the receiver should be recorded as ( $P_r$ ).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.



5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ) ,the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.  
The measurement results are obtained as described below:  
$$\text{Power(EIRP)} = P_{Mea} + P_{Ag} - P_{cl} + G_a$$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$ .

### TEST LIMIT

According to 22.913(a)(5)the ERP(EIRP) should be not exceeding following table limits:

|             |  | Burst Average ERP                |
|-------------|--|----------------------------------|
| UMTS Band V |  | FCC: $\leq 38.45\text{dBm}$ (7W) |

### TEST RESULTS

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2.  $EIRP = P_{Mea}(\text{dBm}) - P_{cl}(\text{dB}) + P_{Ag}(\text{dB}) + G_a(\text{dBi})$
3.  $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$  as EIRP by subtracting the gain of the dipole.
4. Margin = Emission Level - Limit
5. We test the H direction and V direction recorded worst case.

UMTS/TM1/UMTS Band V


| Frequency (MHz) | $P_{Mea}$ (dBm) | $P_{cl}$ (dB) | $G_a$ Antenna Gain (dB) | Correction (dB) | $P_{Ag}$ (dB) | Burst Average ERP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|-----------------|---------------|-------------------------|-----------------|---------------|-------------------------|-------------|-------------|--------------|
| 826.4           | -16.32          | 3.45          | 8.45                    | 2.15            | 33.79         | 20.32                   | 38.45       | -18.13      | V            |
| 836.4           | -16.47          | 3.49          | 8.45                    | 2.15            | 33.85         | 20.19                   | 38.45       | -18.26      | V            |
| 846.6           | -16.54          | 3.55          | 8.36                    | 2.15            | 33.88         | 20.00                   | 38.45       | -18.45      | V            |

## 4.2 Radiated Spurious Emission

### TEST APPLICABLE

According to the TIA-603-E:2016 and FCC Part 2.1033 test method, The Receiver or Spectrum was scanned from lowest frequency frequency generated within the equipment to the 10<sup>th</sup> harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set as outlined in Part 22.917, The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band V.

### TEST CONFIGURATION



### TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as ( $P_r$ ).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.



5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{\text{Mea}} + P_{\text{Ag}} - P_{\text{cl}} + G_a$$

6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

7. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $\text{ERP} = \text{EIRP} - 2.15 \text{ dBi}$ .

8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

| Working Frequency         | Subrange (GHz) | RBW    | VBW    | Sweep time (s) |
|---------------------------|----------------|--------|--------|----------------|
| UMTS/TM1/<br>WCDMA Band V | 0.00009~0.15   | 1KHz   | 3KHz   | 30             |
|                           | 0.00015~0.03   | 10KHz  | 30KHz  | 10             |
|                           | 0.03~1         | 100KHz | 300KHz | 10             |
|                           | 1~2            | 1 MHz  | 3 MHz  | 2              |
|                           | 2~5            | 1 MHz  | 3 MHz  | 3              |
|                           | 5~8            | 1 MHz  | 3 MHz  | 3              |
|                           | 8~10           | 1 MHz  | 3 MHz  | 3              |

## TEST LIMITS

According to 22.917, specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

| Frequency                 | Channel | Frequency Range | Verdict |
|---------------------------|---------|-----------------|---------|
| UMTS/TM1/ WCDMA<br>Band V | Low     | 9KHz - 10GHz    | PASS    |
|                           | Middle  | 9KHz - 10GHz    | PASS    |
|                           | High    | 9KHz - 10GHz    | PASS    |

## TEST RESULTS

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2.  $\text{EIRP} = P_{\text{Mea}}(\text{dBm}) - P_{\text{cl}}(\text{dB}) + P_{\text{Ag}}(\text{dB}) + G_a(\text{dBi})$
3.  $\text{ERP} = \text{EIRP} - 2.15 \text{ dBi}$  as EIRP by subtracting the gain of the dipole.
4. Margin = EIRP - Limit

### UMTS/TM1/ WCDMA Band V \_ Low Channel

| Frequency (MHz) | $P_{\text{Mea}}$ (dBm) | $P_{\text{cl}}$ (dB) | Diatance | $G_a$ Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|----------|------------------------|-----------------|-------------|-------------|--------------|
| 1652.8          | -48.27                 | 3.86                 | 3.00     | 8.56                   | -43.57          | -13.00      | -30.57      | H            |
| 2479.2          | -48.87                 | 4.29                 | 3.00     | 6.98                   | -46.18          | -13.00      | -33.18      | H            |
| 1652.8          | -44.23                 | 3.86                 | 3.00     | 8.56                   | -39.53          | -13.00      | -26.53      | V            |
| 2479.2          | -44.92                 | 4.29                 | 3.00     | 6.98                   | -42.23          | -13.00      | -29.23      | V            |

### UMTS/TM1/ WCDMA Band V \_ Middle Channel

| Frequency (MHz) | $P_{\text{Mea}}$ (dBm) | $P_{\text{cl}}$ (dB) | Diatance | $G_a$ Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|----------|------------------------|-----------------|-------------|-------------|--------------|
| 1672.8          | -49.28                 | 3.9                  | 3.00     | 8.58                   | -44.60          | -13.00      | -31.60      | H            |
| 2509.2          | -51.41                 | 4.32                 | 3.00     | 6.8                    | -48.93          | -13.00      | -35.93      | H            |
| 1672.8          | -45.55                 | 3.9                  | 3.00     | 8.58                   | -40.87          | -13.00      | -27.87      | V            |
| 2509.2          | -44.89                 | 4.32                 | 3.00     | 6.8                    | -42.41          | -13.00      | -29.41      | V            |



## UMTS/TM1/ WCDMA Band V \_ High Channel


| Frequency (MHz) | P <sub>Mea</sub> (dBm) | P <sub>cl</sub> (dB) | Diatance | G <sub>a</sub> Antenna Gain(dB) | Peak EIRP (dBm) | Limit (dBm) | Margin (dB) | Polarization |
|-----------------|------------------------|----------------------|----------|---------------------------------|-----------------|-------------|-------------|--------------|
| 1693.2          | -51.71                 | 3.91                 | 3.00     | 9.06                            | -46.56          | -13.00      | -33.56      | H            |
| 2539.8          | -54.22                 | 4.32                 | 3.00     | 6.65                            | -51.89          | -13.00      | -38.89      | H            |
| 1693.2          | -49.86                 | 3.91                 | 3.00     | 9.06                            | -44.71          | -13.00      | -31.71      | V            |
| 2539.8          | -50.97                 | 4.32                 | 3.00     | 6.65                            | -48.64          | -13.00      | -35.64      | V            |

## 4.3 Occupied Bandwidth and Emission Bandwidth

### TEST APPLICABLE

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. The table below lists the measured 99% Bandwidth and -26dBc Bandwidth.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The Occupied bandwidth and Emission Bandwidth were measured with Agilent Spectrum Analyzer N9020A (peak);
3. Set RBW=100KHz,VBW=300KHz,Span=10MHz,SWT=Auto;
4. Set SPA Max hold and View, Set 99% Occupied Bandwidth/ Set -26dBc Occupied Bandwidth
5. These measurements were done at 3 frequencies for WCDMA band V. (low, middle and high of operational frequency range).

### TEST RESULTS

| Test Mode                    | Channel | Frequency (MHz) | Occupied Bandwidth (99% BW) (MHz) | Emission Bandwidth (-26 dBc BW) (MHz) | Verdict |
|------------------------------|---------|-----------------|-----------------------------------|---------------------------------------|---------|
| UMTS/TM1/<br>WCDMA Band<br>V | 4132    | 826.4           | 4.1610                            | 4.720                                 | PASS    |
|                              | 4182    | 836.4           | 4.1741                            | 4.719                                 | PASS    |
|                              | 4233    | 846.6           | 4.1678                            | 4.706                                 | PASS    |


#### Remark:

1. Test results including cable loss;
2. Please refer to following plots;




## Occupied Bandwidth and Emission Bandwidth

## UMTS/TM1/ WCDMA Band V




/

## Channel 4132 / 826.4 MHz



/

## Channel 4182 / 836.4 MHz




/

## 4.4 Band Edge Compliance

### TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S WIDEBAND RADIO COMMUNICATION TESTER (CMW 500) to ensure max power transmission and proper modulation.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Spectrum Analyzer N9020A;

3. Set RBW=100KHz,VBW=300KHz,Span=2MHz,SWT=Auto,Detector: RMS;


These measurements were done at 2 frequencies for WCDMA Band V. (low and high of operational frequency range).

### TEST RESULTS

| UMTS/TM1/WCDMA Band V |         |                 |                           |              |         |
|-----------------------|---------|-----------------|---------------------------|--------------|---------|
| Test Mode             | Channel | Frequency (MHz) | Band Edg Compliance (dBm) | Limits (dBm) | Verdict |
| UMTS/TM1/WCDMA Band V | 4132    | 826.4           | <-13dBm                   | -13dBm       | PASS    |
|                       | 4233    | 846.6           | <-13dBm                   | -13dBm       |         |

Remark:

1. Test results including cable loss;
2. Please refer to following plots;




## 4.5 Spurious Emission on Antenna Port

### TEST APPLICABLE

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA band II/IV, this equates to a frequency range of 9 KHz to 20GHz, data taken from 30 MHz to 20 GHz. For WCDMA Band V, this equates to a frequency range of 9 KHz to 20 GHz, data taken from 30 MHz to 20 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; if the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give an optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:  
The trace mode is set to MaxHold to get the highest signal at each frequency;  
Wait 25 seconds;  
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Spectrum Analyzer N9020A;
3. These measurements were done at 3 frequencies for WCDMA band V. (low, middle and high of operational frequency range).

### TEST LIMIT

Part 22.917, specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.


## TEST RESULTS

| Test Mode             | Channel | Frequency (MHz) | Spurious RF Conducted Emission (dBm) | Limits (dBm) | Verdict |
|-----------------------|---------|-----------------|--------------------------------------|--------------|---------|
| UMTS/TM1/WCDMA Band V | 4132    | 826.4           | <-13dBm                              | -13dBm       | PASS    |
|                       | 4182    | 836.4           | <-13dBm                              | -13dBm       |         |
|                       | 4233    | 846.6           | <-13dBm                              | -13dBm       |         |

### Remark:

1. Test results including cable loss;
2. Please refer to following plots;
3. Not reordered test plots from 9 KHz to 30 MHz as emission levels 20dB lower than emission limit;





## 4.6 Frequency Stability Test

### TEST APPLICABLE


1. According to FCC Part 2 Section 2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -25°C to +65°C centigrade.
2. According to FCC Part 2 Section 2.1055 (e)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
3. Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried voltage equipment and the end voltage point was 7.4V.

### TEST PROCEDURE

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S WIDEBAND RADIO COMMUNICATION TESTER (CMW 500).

1. Measure the carrier frequency at room temperature;
2. Subject the EUT to overnight soak at -30°C;
3. With the EUT, powered via nominal voltage, connected to the CMW 500 and in a simulated call on middle channel of WCDMA Band II/IV/V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1 Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 0.5 hours unpowered, to allow any self-heating to stabilize, before continuing;
6. Subject the EUT to overnight soak at +50°C;
7. With the EUT, powered via nominal voltage, connected to the CMW 500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
8. Repeat the above measurements at 10°C increments from +50°C to -30°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure;

### TEST CONFIGURATION





## TEST LIMITS

### **For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 6.30VDC and 8.40VDC, with a nominal voltage of 7.4DC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

### **For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

## TEST RESULTS


| UMTS/TM1/WCDMA Band V |                  |                     |                      |             |         |
|-----------------------|------------------|---------------------|----------------------|-------------|---------|
| DC Power              | Temperature (°C) | Frequency error(Hz) | Frequency error(ppm) | Limit (ppm) | Verdict |
| 6.3                   | 25               | 3                   | 0.004                | 2.50        | PASS    |
| 7.4                   | 25               | 2                   | 0.002                | 2.50        | PASS    |
| 8.4                   | 25               | 3                   | 0.004                | 2.50        | PASS    |
| 7.4                   | -30              | 13                  | 0.016                | 2.50        | PASS    |
| 7.4                   | -20              | -8                  | -0.010               | 2.50        | PASS    |
| 7.4                   | -10              | -8                  | -0.010               | 2.50        | PASS    |
| 7.4                   | 0                | -15                 | -0.018               | 2.50        | PASS    |
| 7.4                   | 10               | 11                  | 0.013                | 2.50        | PASS    |
| 7.4                   | 20               | 1                   | 0.001                | 2.50        | PASS    |
| 7.4                   | 30               | -4                  | -0.005               | 2.50        | PASS    |
| 7.4                   | 40               | 14                  | 0.017                | 2.50        | PASS    |
| 7.4                   | 50               | 6                   | 0.007                | 2.50        | PASS    |

## 4.7 Peak-to-Average Ratio (PAR)

### LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

### TEST CONFIGURATION



### TEST PROCEDURE


1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
  - 1). for continuous transmissions, set to 1 ms,
  - 2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

### TEST RESULTS

| Test Mode                    | Channel | Frequency (MHz) | PAPR Value (dB) | Limits (dB) | Verdict |
|------------------------------|---------|-----------------|-----------------|-------------|---------|
| UMTS/TM1/<br>WCDMA Band<br>V | 4132    | 826.4           | 2.77            | 13.0        | PASS    |
|                              | 4182    | 836.4           | 2.87            | 13.0        | PASS    |
|                              | 4233    | 846.6           | 2.76            | 13.0        | PASS    |

*Remark:*

1. *Test results including cable loss;*
2. *Please refer to following plots;*





## **5 Test Setup Photos of the EUT**

Please refer to separated files for Test Setup Photos of the EUT.

## **6 External Photos of the EUT**

Please refer to separated files for External Photos of the EUT.

## **7 Internal Photos of the EUT**

Please refer to separated files for Internal Photos of the EUT.

.....**End of Report**.....