RADIO TEST REPORT FCC ID: 2AJU3RT707

Product: Mini Wireless Game Controller Mouse

Keyboard Combo

Trade Mark: Rii

Model No.: RT707

RT707S, RT707+, RT707BT, RK707, RK707S, RK707+, RK707BT, ZW-707, ZW RT707+

Family Model: ZW-RT707, ZW-RT707S, ZW-RT707+,

ZW-RT707BT, ZW-RK707, ZW-RK707S, ZW-RK707+,

ZW-RK707BT

Report No.: \$19041703001001

Issue Date: May 08, 2019

Prepared for

Shenzhen Reiie intelligent technology Co.,ltd 401,4F, NO.1 Building,Zhongkenuo Industry Park, Hezhou Development Zone, Xixiang Street, Baoan District, Shenzhen City, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599 Website:http://www.ntek.org.cn

Version.1.2 Page 1 of 42





TABLE OF CONTENTS

1 T	EST RESULT CERTIFICATION	3
2 S	UMMARY OF TEST RESULTS	4
3 F	ACILITIES AND ACCREDITATIONS	5
3.1	FACILITIES	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS	
3.3	MEASUREMENT UNCERTAINTY	5
4 G	ENERAL DESCRIPTION OF EUT	6
5 D	ESCRIPTION OF TEST MODES	8
6 S	ETUP OF EQUIPMENT UNDER TEST	9
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	
6.2	SUPPORT EQUIPMENT	10
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS	
7 T	EST REQUIREMENTS	13
7.1	CONDUCTED EMISSIONS TEST	13
7.2	RADIATED SPURIOUS EMISSION	18
7.3	6DB BANDWIDTH	
7.4	PEAK OUTPUT POWER	
7.5	POWER SPECTRAL DENSITY	33
7.6	CONDUCTED BAND EDGE MEASUREMENT	
7.7	SPURIOUS RF CONDUCTED EMISSIONS	
7.8	ANTENNA APPLICATION	42





1 TEST RESULT CERTIFICATION

Applicant's name	Shenzhen Reiie intelligent technology Co.,ltd		
Address	401,4F, NO.1 Building,Zhongkenuo Industry Park, Hezhou Developme Zone, Xixiang Street, Baoan District, Shenzhen City, China		
Manufacturer's Name	Shenzhen Reiie intelligent technology Co.,ltd		
Address	401,4F, NO.1 Building,Zhongkenuo Industry Park, Hezhou Development Zone, Xixiang Street, Baoan District, Shenzhen City, China		
Product description			
Product name:	Mini Wireless Game Controller Mouse Keyboard Combo		
Model and/or type reference:	RT707		
Family Model:	Refer to page 1		

Measurement Procedure Used:

APPLICABLE STANDARDS				
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT			
FCC 47 CFR Part 2, Subpart J				
FCC 47 CFR Part 15, Subpart C				
KDB 174176 D01 Line Conducted FAQ v01r01	Complied			
ANSI C63.10-2013				
KDB 558074 D01 15.247 Meas Guidance v05r02				

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test		14 Apr. 2019 ~ 07 May. 2019
Testing Engineer	: <u> </u>	Eileen Wu.
		(Eileen Liu)
Technical Manager	:	Jason chen
· ·		(Jason Chen)
		Sam. Cher
Authorized Signatory	:	
		(Sam Chen)

Version.1.2 Page 3 of 42

SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C						
Standard Section Test Item Verdict Remark						
15.207	Conducted Emission	PASS				
15.247 (a)(2)	6dB Bandwidth	PASS				
15.247 (b)	Peak Output Power	PASS				
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS				
15.247 (e)	Power Spectral Density	PASS				
15.247 (d)	Band Edge Emission	PASS				
15.247 (d)	Spurious RF Conducted Emission	PASS				
15.203	Antenna Requirement	PASS				

Remark:

- "N/A" denotes test is not applicable in this Test Report.
 All test items were verified and recorded according to the standards and without any deviation during the test.

Version.1.2 Page 4 of 42

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Laboratory has been assessed and proved to be in compliance with

CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)

The Certificate Registration Number is L5516.

IC-Registration The Certificate Registration Number is 9270A-1.

FCC- Accredited Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab. The Certificate Registration Number is 4298.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for

the competence of testing and calibration laboratories.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang

Street, Bao'an District, Shenzhen 518126 P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±2.80dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(30MHz~1GHz)	±2.64dB
5	All emissions, radiated(1GHz~6GHz)	±2.40dB
6	All emissions, radiated(>6GHz)	±2.52dB
7	Temperature	±0.5°C
8	Humidity	±2%

Version.1.2 Page 5 of 42

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification						
Equipment Mini Wireless Game Controller Mouse Keyboard Combo						
Trade Mark Rii						
FCC ID	2AJU3RT707					
Model No.	RT707					
Family Model	RT707S, RT707+, RT707BT, RK707, RK707S, RK707+, RK707BT, ZW-707, ZW-RT707, ZW-RT707S, ZW-RT707+, ZW-RT707BT, ZW-RK707, ZW-RK707BT					
Model Difference	All models are the same circuit and RF module, except the model name.					
Operating Frequency	2407MHz~2477MHz					
Modulation GFSK						
Number of Channels	16 Channels					
Antenna Type	PCB Antenna					
Antenna Gain	1dBi					
Power supply	☑DC supply: DC 3.7V/650mAh from Battery or DC 5V from USB Port					
	☐Adapter supply:					
HW Version	RT707_2.4G_game_20180829_V5.0					
SW Version RT707_2535_Tx_20180816_,bin						

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Version.1.2 Page 6 of 42





Revision History

Report No.	Version	Description	Issued Date
S19041703001001	Rev.01		May 08, 2019
319041703001001	Rev.u1	Initial issue of report	Way 06, 2019

Version.1.2 Page 7 of 42





5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2407	7	2435	13	2467
2	2408	8	2437	14	2468
3	2410	9	2440	15	2469
4	2414	10	2441	16	2477
5	2421	11	2442		
6	2428	12	2455		

The following summary table is showing all test modes to demonstrate in compliance with the standard

The following summary table is showing all test modes to demonstrate in compliance with the standard.					
Test Cases					
Test Item	Data Rate/ Modulation				
rest item	GFSK				
AC Conducted Emission	Mode 1: normal link mode				
	Mode 1: normal link mode				
Radiated Test	Mode 2: 2.4G Tx Ch01_2407MHz_1Mbps				
Cases	Mode 3: 2.4G Tx Ch09_2440MHz_1Mbps				
	Mode 4: 2.4G Tx Ch16_2477MHz_1Mbps				
Conducted Test	Mode 2: 2.4G Tx Ch01_2407MHz_1Mbps				
Conducted rest	Mode 3: 2.4G Tx Ch09_2440MHz_1Mbps				
Cases	Mode 4: 2.4G Tx Ch16_2477MHz_1Mbps				

Note:

- The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
- 2. AC power line Conducted Emission was tested under maximum output power.
- 3. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.
- 4. EUT is set to continuous transmission mode. duty cycle greater than 98%.
- 5. EUT built-in battery-powered. The battery is fully-charged.


Version.1.2 Page 8 of 42






6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



For Radiated Test Cases

EUT



Note:The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Version.1.2 Page 9 of 42





6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

icolo.					
Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
AE-1	Adapter	SIMP	KSAPK0110500200D5	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.0m
C-2	RF Cable	YES	NO	0.1m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

Version.1.2 Page 10 of 42





6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Radiatio	on& Conducted I	lest equipment					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibrati on period
1	Spectrum Analyzer	Aglient	E4407B	MY45108040	2018.05.19	2019.05.18	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2018.10.08	2019.10.07	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2018.10.08	2019.10.07	1 year
4	Test Receiver	R&S	ESPI7	101318	2018.05.19	2019.05.18	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2019.04.15	2020.04.14	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2018.05.19	2020.05.18	2 year
7	Horn Antenna	EM	EM-AH-1018 0	2011071402	2019.04.15	2020.04.14	1 year
8	Broadband Horn Antenna	SCHWARZBE CK	BBHA 9170	803	2018.12.11	2019.12.10	1 year
9	Amplifier	EMC	EMC051835 SE	980246	2018.08.05	2019.08.04	1 year
10	Active Loop Antenna	SCHWARZBE CK	FMZB 1519 B	055	2018.12.11	2019.12.10	1 year
11	Power Meter	DARE	RPR3006W	15I00041SN O84	2018.08.05	2019.08.04	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
15	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year
16	Filter	TRILTHIC	2400MHz	29	2017.04.19	2020.04.18	3 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test And this temporary antenna connector is listed within the instrument list

Version.1.2 Page 11 of 42





AC Co	AC Conduction Test equipment						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2018.05.19	2019.05.18	1 year
2	LISN	R&S	ENV216	101313	2018.10.08	2019.10.07	1 year
3	LISN	SCHWARZBE CK	NNLK 8129	8129245	2018.05.19	2019.05.18	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2018.05.19	2020.05.18	2 year
5	Test Cable (9KHz-30MH z)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MH z)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MH z)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

Version.1.2 Page 12 of 42





7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

7.1.2 Conformance Limit

Fraguanov(MHz)	Conducted Emission Limit			
Frequency(MHz)	Quasi-peak	Average		
0.15-0.5	66-56*	56-46*		
0.5-5.0	56	46		
5.0-30.0	60	50		


Note: 1. *Decreases with the logarithm of the frequency

- 2. The lower limit shall apply at the transition frequencies
- 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
- 2. The EUT was placed on a table which is 0.8m above ground plane.
- 3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- 4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
- 5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- 6. LISN at least 80 cm from nearest part of EUT chassis.
- 7. The frequency range from 150KHz to 30MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
- 9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Version.1.2 Page 13 of 42






7.1.6 **Test Results**

 - •		Model Name :	RT707
Temperature:	126 T	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.5020	18.12	9.74	27.86	46.00	-18.14	AVG
0.5060	30.20	9.74	39.94	56.00	-16.06	QP
0.8900	23.63	9.74	33.37	56.00	-22.63	QP
0.8900	13.77	9.74	23.51	46.00	-22.49	AVG
2.6220	18.50	9.80	28.30	56.00	-27.70	QP
2.6740	7.16	9.80	16.96	46.00	-29.04	AVG

Remark:



Version.1.2 Page 14 of 42






I = I I I A	Mini Wireless Game Controller Mouse Keyboard Combo	Model Name:	RT707
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Lact Valtage .	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.4940	28.85	9.75	38.60	56.10	-17.50	QP
0.5020	21.08	9.75	30.83	46.00	-15.17	AVG
0.8900	22.38	9.75	32.13	56.00	-23.87	QP
0.8900	14.27	9.75	24.02	46.00	-21.98	AVG
1.6019	19.36	9.78	29.14	56.00	-26.86	QP
1.9260	10.61	9.79	20.40	46.00	-25.60	AVG

Remark:

- All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.



Version.1.2 Page 15 of 42






EUT:	Mini Wireless Game Controller Mouse Keyboard Combo	Model Name:	RT707
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Domork
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.3540	27.14	9.74	36.88	58.87	-21.99	QP
0.3540	16.30	9.74	26.04	48.87	-22.83	AVG
0.5140	31.29	9.74	41.03	56.00	-14.97	QP
0.5140	19.07	9.74	28.81	46.00	-17.19	AVG
0.8900	28.77	9.74	38.51	56.00	-17.49	QP
0.8900	17.08	9.74	26.82	46.00	-19.18	AVG
1.4580	25.56	9.76	35.32	56.00	-20.68	QP
1.4580	13.40	9.76	23.16	46.00	-22.84	AVG

Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Factor = Insertion Loss + Cable Loss.



Version.1.2 Page 16 of 42






H-111.	Mini Wireless Game Controller Mouse Keyboard Combo	Model Name:	RT707
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Lact Valtage .	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Domark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.3699	26.42	9.75	36.17	58.50	-22.33	QP
0.3699	19.98	9.75	29.73	48.50	-18.77	AVG
0.5140	31.67	9.75	41.42	56.00	-14.58	QP
0.5140	23.84	9.75	33.59	46.00	-12.41	AVG
0.8820	26.82	9.75	36.57	56.00	-19.43	QP
0.8820	19.55	9.75	29.30	46.00	-16.70	AVG
1.4539	25.44	9.77	35.21	56.00	-20.79	QP
1.4539	18.08	9.77	27.85	46.00	-18.15	AVG

Remark:

- All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.



Version.1.2 Page 17 of 42





7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

According to FCC Part 15.205, Restricted bands						
MHz	MHz	MHz	GHz			
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15			
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46			
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75			
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5			
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2			
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5			
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7			
6.26775-6.26825	123-138	2200-2300	14.47-14.5			
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2			
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4			
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12			
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0			
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8			
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5			
12.57675-12.57725	322-335.4	3600-4400	(2)			
13.36-13.41		_				

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

reducted band openined on release(a), then the release (a) mint in the table below had to be relieved.						
Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBµV/m)	Measurement Distance			
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300			
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30			
1.705~30.0	30	29.5	30			
30-88	100	40	3			
88-216	150	43.5	3			
216-960	200	46	3			
Above 960	500	54	3			

Limits of Radiated Emission Measurement(Above 1000MHz)

Fragues av (MHz)	Class B (dBuV/m) (at 3M)			
Frequency(MHz)	PEAK	AVERAGE		
Above 1000	74	54		

Remark :1. Emission level in dBuV/m=20 log (uV/m)

- 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. For Frequency 9kHz~30MHz: Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz: Distance extrapolation factor =20log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.

Version.1.2 Page 18 of 42






7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



Version.1.2 Page 19 of 42





7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For the radiated emission test above 1GHz:
 - Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- g. For the actual test configuration, please refer to the related Item -EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

Version.1.2 Page 20 of 42





During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
A1 4000	Peak	1 MHz	1 MHz
Above 1000	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Mini Wireless Game Controller Mouse Keyboard Combo	Model No.:	RT707
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Freq.	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK AV		PK	AV	PK	AV

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Version.1.2 Page 21 of 42








Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT:	Mini Wireless Game Controller Mouse Keyboard Combo	Model Name:	RT707
Temperature:	20 ℃	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Mode 1
Test Voltage:	DC 3.7V		

Polar	Frequency	Meter Reading	Factor Emission Limits Margin		Margin	Remark		
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m) (dB)		. todirit	
V	31.9546	8.30	18.22	26.52	40.00	-13.48	QP	
V	48.3318	14.53	10.98	25.51	40.00	-14.49	QP	
V	61.7781	17.00	6.41	23.41	40.00	-16.59	QP	
V	113.3163	12.26	12.92	25.18	43.50	-18.32	QP	
V	194.4534	15.84	9.87	25.71	43.50	-17.79	QP	
V	556.7744	6.45	24.43	30.88	46.00	-15.12	QP	

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




Version.1.2 Page 22 of 42





Polar	Frequency	Meter ReadingFactorEmission LevelLimitsMargin		Margin	Remark			
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m) (dB			
Н	124.1330	11.75	13.29	25.04	43.50	-18.46	QP	
Н	228.4904	11.03	12.08	23.11	46.00	-22.89	QP	
Н	356.6758	11.37	17.77	29.14	46.00	-16.86	QP	
Н	752.7432	7.54	27.51	35.05	46.00	-10.95	QP	

Remark:



Version.1.2 Page 23 of 42





■ Spurious Emission Above 1GHz (1GHz to 25GHz)						
EUT:	Mini Wireless Game Controller Mouse Keyboard Combo	Model No.:	RT707			
Temperature:	20 ℃	Relative Humidity:	48%			
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu			

Frequenc y	Read Level	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
			Low	Channel (2	407 MHz)-	Above 1G			
4814.321	64.32	5.21	35.59	44.30	60.82	74.00	-13.18	Pk	Vertical
4814.321	41.13	5.21	35.59	44.30	37.63	54.00	-16.37	AV	Vertical
7221.112	62.54	6.48	36.27	44.60	60.69	74.00	-13.31	Pk	Vertical
7221.112	41.45	6.48	36.27	44.60	39.60	54.00	-14.40	AV	Vertical
4814.321	66.63	5.21	35.55	44.30	63.09	74.00	-10.91	Pk	Horizontal
4814.321	44.63	5.21	35.55	44.30	41.09	54.00	-12.91	AV	Horizontal
7221.112	63.29	6.48	36.27	44.52	61.52	74.00	-12.48	Pk	Horizontal
7221.112	42.33	6.48	36.27	44.52	40.56	54.00	-13.44	AV	Horizontal
			Mid	Channel (24	440 MHz)- <i>i</i>	Above 1G			
4880.473	61.12	5.21	35.66	44.20	57.79	74.00	-16.21	Pk	Vertical
4880.473	43.29	5.21	35.66	44.20	39.96	54.00	-14.04	AV	Vertical
7320.265	60.47	7.10	36.50	44.43	59.64	74.00	-14.36	Pk	Vertical
7320.265	40.11	7.10	36.50	44.43	39.28	54.00	-14.72	AV	Vertical
4880.366	66.59	5.21	35.66	44.20	63.26	74.00	-10.74	Pk	Horizontal
4880.366	46.65	5.21	35.66	44.20	43.32	54.00	-10.68	AV	Horizontal
7320.234	60.53	7.10	36.50	44.43	59.70	74.00	-14.30	Pk	Horizontal
7320.234	38.95	7.10	36.50	44.43	38.12	54.00	-15.88	AV	Horizontal
			High	Channel (2	477 MHz)-	Above 1G			
4954.517	67.44	5.21	35.52	44.21	63.96	74.00	-10.04	Pk	Vertical
4954.517	48.86	5.21	35.52	44.21	45.38	54.00	-8.62	AV	Vertical
7431.323	62.54	7.10	36.53	44.60	61.57	74.00	-12.43	Pk	Vertical
7431.323	42.43	7.10	36.53	44.60	41.46	54.00	-12.54	AV	Vertical
4954.517	62.56	5.21	35.52	44.21	59.08	74.00	-14.92	Pk	Horizontal
4954.517	42.61	5.21	35.52	44.21	39.13	54.00	-14.87	AV	Horizontal
7431.323	61.22	7.10	36.53	44.60	60.25	74.00	-13.75	Pk	Horizontal
7431.323	41.14	7.10	36.53	44.60	40.17	54.00	-13.83	AV	Horizontal

Note:

(1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor (2)All other emissions more than 20dB below the limit.

Version.1.2 Page 24 of 42





 Spurious Emission 	i in Restricted Band 23 i	0-2390MHZ and 2483.	5-25UUIVIHZ
	Mini Wireless Game		
EUT:	Controller Mouse	Model No.:	RT707
	Keyboard Combo		

Temperature: 20 °C Relative Humidity: 48%

Test Mode: Mode2/ Mode4 Test By: Eileen Liu

Frequenc	Meter Reading	Cable	Antenna Factor	Preamp Factor	Emission	Limits	Margin	Detector	Commont
/\/_\	J	Loss			Level	(dDu\//m)	(AD)	Tyrno	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type	
				GF	SK				
2310.00	61.34	2.97	27.80	43.80	48.31	74	-25.69	Pk	Horizontal
2310.00	42.29	2.97	27.80	43.80	29.26	54	-24.74	AV	Horizontal
2310.00	62.59	2.97	27.80	43.80	49.56	74	-24.44	Pk	Vertical
2310.00	48.74	2.97	27.80	43.80	35.71	54	-18.29	AV	Vertical
2390.00	63.35	3.14	27.21	43.80	49.90	74	-24.10	Pk	Vertical
2390.00	42.13	3.14	27.21	43.80	28.68	54	-25.32	AV	Vertical
2390.00	60.69	3.14	27.21	43.80	47.24	74	-26.76	Pk	Horizontal
2390.00	41.17	3.14	27.21	43.80	27.72	54	-26.28	AV	Horizontal
2483.50	62.67	3.58	27.70	44.00	49.95	74	-24.05	Pk	Vertical
2483.50	43.33	3.58	27.70	44.00	30.61	54	-23.39	AV	Vertical
2483.50	60.58	3.58	27.70	44.00	47.86	74	-26.14	Pk	Horizontal
2483.50	42.28	3.58	27.70	44.00	29.56	54	-24.44	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

Version.1.2 Page 25 of 42





■ Spurious Emission in Restricted Band 3260MHz-18000MHz					
EUT:	Mini Wireless Game Controller Mouse Keyboard Combo	Model No.:	RT707		
Temperature:	20 ℃	Relative Humidity:	48%		
Test Mode:	Mode2/ Mode4	Test By:	Eileen Liu		

Frequenc	Readin g Level	Cable Loss	Antenn a	Preamp Factor	Emission Level	Limits	Margin	Detect or	_
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµ V/m)	(dBµ V/m)	(dB)	Туре	Comment
3260	62.23	4.04	29.57	44.70	51.14	74	-22.86	Pk	Vertical
3260	51.14	4.04	29.57	44.70	40.05	54	-13.95	AV	Vertical
3260	62.59	4.04	29.57	44.70	51.50	74	-22.50	Pk	Horizontal
3260	53.37	4.04	29.57	44.70	42.28	54	-11.72	AV	Horizontal
3332	62.22	4.26	29.87	44.40	51.95	74	-22.05	Pk	Vertical
3332	53.29	4.26	29.87	44.40	43.02	54	-10.98	AV	Vertical
3332	62.95	4.26	29.87	44.40	52.68	74	-21.32	Pk	Horizontal
3332	53.28	4.26	29.87	44.40	43.01	54	-10.99	AV	Horizontal
17797	42.27	10.99	43.95	43.50	53.71	74	-20.29	Pk	Vertical
17797	32.26	10.99	43.95	43.50	43.70	54	-10.30	AV	Vertical
17788	43.21	11.81	43.69	44.60	54.11	74	-19.89	Pk	Horizontal
17788	31.19	11.81	43.69	44.60	42.09	54	-11.91	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

Version.1.2 Page 26 of 42





7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.2.

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows Subclause 11.8 of ANSI C63.10

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) ≥ 3*RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3.6 Test Results


EUT:	Mini Wireless Game Controller Mouse Keyboard Combo	Model No.:	RT707
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2407	717.194	≥500	Pass
Middle	2440	789.082	≥500	Pass
High	2477	775.639	≥500	Pass


Version.1.2 Page 27 of 42







Version.1.2 Page 28 of 42



Version.1.2 Page 29 of 42





7.4 PEAK OUTPUT POWER

7.4.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.3.1.

7.4.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows Subclause 11.9.1.1 of ANSI C63.10

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Set the RBW ≧DTS bandwidth.

Set VBW = 3*RBW.

Set the span ≥3*RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

7.4.6 Test Results


IFIII.	Mini Wireless Game Controller Mouse Keyboard Combo	Model No.:	RT707
Temperature:	120 ('	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu

Test Channel	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	LIMIT (dBm)	Verdict	
	1Mbps					
01	2407	Default	-0.45	30	PASS	
09	2440	Default	-0.52	30	PASS	
16	2477	Default	-1.05	30	PASS	

Version.1.2 Page 30 of 42








Version.1.2 Page 31 of 42





Version.1.2 Page 32 of 42







7.5.1 **Applicable Standard**

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.4.

7.5.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.5.3 **Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 **Test Procedure**

The testing follows Measurement Procedure Subclause 11.10.2 of ANSI C63.10

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5*DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW ≥ 3 RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Version.1.2 Page 33 of 42






7.5.6 Test Results

EUT:	Mini Wireless Game Controller Mouse Keyboard Combo	Model No.:	RT707
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Eileen Liu


Test Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Limit (dBm/3KHz)	Verdict		
	1Mbps					
01	2407	-6.85	8	PASS		
09	2440	-6.52	8	PASS		
16	2477	-7.04	8	PASS		



Version.1.2 Page 34 of 42







Version.1.2 Page 35 of 42

7.6 CONDUCTED BAND EDGE MEASUREMENT

7.6.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.

Report No.:S19041703001001

7.6.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows FCC KDB 558074 D01 15.247 Meas Guidance v05 Section 8.7.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.


7.6.6 Test Results

EUT:	Mini Wireless Game Controller Mouse Keyboard Combo	Model No.:	RT707
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode4	Test By:	Eileen Liu

Version.1.2 Page 36 of 42







Version.1.2 Page 37 of 42

Certificate #4298.01 Report No.:S19041703001001

7.7 SPURIOUS RF CONDUCTED EMISSIONS

7.7.1 Conformance Limit

- 1. Below -20dB of the highest emission level in operating band.
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

7.7.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.3 Test Setup

Please refer to Section 6.1 of this test report.

7.7.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequeny range from 9KHz to 26.5GHz.

7.7.5 Test Results

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.


Version.1.2 Page 38 of 42






Test Plot


GFSK on channel 01




GFSK on channel 01



GFSK on channel 01



GFSK on channel 01




Version.1.2 Page 39 of 42






Test Plot


GFSK on channel 09




GFSK on channel 09



GFSK on channel 09



GFSK on channel 09




Version.1.2 Page 40 of 42






Test Plot


GFSK on channel 16




GFSK on channel 16



GFSK on channel 16



GFSK on channel 16



Version.1.2 Page 41 of 42



7.8 ANTENNA APPLICATION

7.8.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.8.2 **Result**

The EUT antenna is permanent attached PCB antenna(Gain:1dBi).	It comply with the standard
requirement.	

END OF REPORT

Version.1.2 Page 42 of 42