RF Exposure Requirements

Product Description: Bluetooth Keyboard

Model No.: RT709, K09, K09+, RKM709, RT721, K12, WW-709

FCC ID: 2AJU3RT709

According to the KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,16 where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Bluetooth(BLE)

Conducted	Max. Power	Distance	Frequency	Result	Limit
Power (dBm)	(mW)	(mm)	(GHz)		
-0.285	0.94	5	2.402	0.29	3

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}]: 0.94/5*\sqrt{2.402}=0.29$

The exclusion thresholds is less than 3, therefore, the RF exposure evaluation is not required.