

ISSUED BY Shenzhen BALUN Technology Co., Ltd.



**FOR** 

## RHF1S001 IP64 T&H sensor

**ISSUED TO** RuiXingHengFang Network(Shenzhen) CO., Ltd

Suite B3019, 3rd tower of Elite(YiLiDa) building, NO.1092 NanShan blvd. NanShan District, Shenzhen 518054 China



Tested by: Date No Approved by: Liao Jianming (Technical Director) Date NOV. 15. 2016

Report No.: **EUT Type:** Model Name: **Brand Name:** 

Test Standard:

FCC ID:

Test conclusion: Test Date:

BL-SZ1690394-602

RHF1S001 IP64 T&H sensor

RHF1S001

RisingHF

47 CFR Part 15 Subpart C

2AJUZ1S001

Pass

Oct. 19, 2016 ~ Nov. 01, 2016

Nov. 15, 2016

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Date of Issue:



# **Revision History**

 Version
 Issue Date

 Rev. 01
 Nov. 08, 2016

 Rev. 02
 Nov. 15, 2016

**Revisions Content** 

Initial Issue

Correct the restricted band range of

the EUT.

# **TABLE OF CONTENTS**

1	ADMIN	IISTRATIVE DATA (GENERAL INFORMATION)	5
	1.1	Identification of the Testing Laboratory	5
	1.2	Identification of the Responsible Testing Location	5
	1.3	Laboratory Condition	5
	1.4	Announce	5
2	PROD	UCT INFORMATION	6
	2.1	Applicant Information	6
	2.2	Manufacturer Information	6
	2.3	Factory Information	6
	2.4	General Description for Equipment under Test (EUT)	6
	2.5	Ancillary Equipment	6
	2.6	Technical Information	7
	2.7	Additional Instructions	7
3	SUMM	ARY OF TEST RESULTS	8
	3.1	Test Standards	8
	3.2	Verdict	8
4	GENE	RAL TEST CONFIGURATIONS	9
	4.1	Test Environments	9
	4.2	Test Equipment List	9
	4.3	Measurement Uncertainty	10
	4.4	Description of Test Setup	10
	4.4.1	For Antenna Port Test	10
	4.4.2	For AC Power Supply Port Test	11
	4.4.3	For Radiated Test (Below 30 MHz)	11



	4.4.4	For Radiated Test (30 MHz-1 GHz)	12
	4.4.5	For Radiated Test (Above 1 GHz)	12
	4.5	Measurement Results Explanation Example	13
	4.5.1	For conducted test items:	13
	4.5.2	For radiated band edges and spurious emission test:	13
5	TEST I	ITEMS	14
	5.1	Antenna Requirements	14
	5.1.1	Standard Applicable	14
	5.1.2	Antenna Anti-Replacement Construction	14
	5.1.3	Antenna Gain	15
	5.2	Output Power	16
	5.2.1	Test Limit	16
	5.2.2	Test Setup	16
	5.2.3	Test Procedure	16
	5.2.4	Test Result	17
	5.3	Occupied Bandwidth	18
	5.3.1	Limit	18
	5.3.2	Test Setup	18
	5.3.3	Test Procedure	18
	5.3.4	Test Result	18
	5.4	Conducted Spurious Emission	19
	5.4.1	Limit	19
	5.4.2	Test Setup	19
	5.4.3	Test Procedure	19
	5.4.4	Test Result	20
	5.5	Band Edge (Authorized-band band-edge)	21
	5.5.1	Limit	21
	5.5.2	Test Setup	21
	5.5.3	Test Procedure	21
	5.5.4	Test Result	21
	5.6	Conducted Emission	22



5.6.1	Limit	22
5.6.2	Test Setup	22
5.6.3	Test Procedure	22
5.6.4	Test Result	22
5.7	Radiated Spurious Emission	23
5.7.1	Limit	23
5.7.2	Test Setup	23
5.7.3	Test Procedure	23
5.7.4	Test Result	24
5.8	Band Edge (Restricted-band band-edge)	25
5.8.1	Limit	25
5.8.2	Test Setup	25
5.8.3	Test Procedure	25
1.1.1	Test Result	25
5.9	Power Spectral density (PSD)	26
5.9.1	Limit	26
5.9.2	Test Setup	26
5.9.3	Test Procedure	26
5.9.4	Test Result	26
ANNEX A	TEST RESULT	27
A.1	Output Power	27
A.2	Occupied Bandwidth	28
A.3	Conducted Spurious Emissions	30
A.4	Band Edge (Authorized-band band-edge)	33
A.5	Conducted Emissions	34
A.6	Radiated Spurious Emission	35
A.7	Band Edge (Restricted-band band-edge)	42
A.8	Power Spectral Density (PSD)	43
ANNEX B	TEST SETUP PHOTOS	44
ANNEX C	EUT EXTERNAL PHOTOS	44
ANNEX D	EUT INTERNAL PHOTOS	44



# 1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

## 1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

## 1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.		
A didwood	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,		
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China		
	The laboratory has been listed by Industry Canada to perform		
	electromagnetic emission measurements. The recognition numbers of		
	test site are 11524A-1.		
Approditation	The laboratory has been listed by US Federal Communications		
Accreditation Certificate	Commission to perform electromagnetic emission measurements. The		
Certificate	recognition numbers of test site are 832625.		
	The laboratory is a testing organization accredited by China National		
	Accreditation Service for Conformity Assessment (CNAS) according to		
	ISO/IEC 17025. The accreditation certificate number is L6791.		
	All measurement facilities used to collect the measurement data are		
Description	located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi		
Description	Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China		
	518055		

# 1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

## 1.4 Announce

- (1) The test report reference to the report template version v5.4.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



# **2 PRODUCT INFORMATION**

# 2.1 Applicant Information

Applicant	RuiXingHengFang Network(Shenzhen)CO., Ltd
A ddraga	Suite B3019, 3rd tower of Elite(YiLiDa) building, NO.1092 NanShan
Address	blvd. NanShan District, Shenzhen 518054 China

# 2.2 Manufacturer Information

Manufacturer	RuiXingHengFang Network(Shenzhen)CO., Ltd
Address	Suite B3019, 3rd tower of Elite(YiLiDa) building, NO.1092 NanShan
Address	blvd. NanShan District, Shenzhen 518054 China

# 2.3 Factory Information

Factory	RuiXingHengFang Network(Shenzhen)CO., Ltd
Address	Suite B3019, 3rd tower of Elite(YiLiDa) building, NO.1092 NanShan
Address	blvd. NanShan District, Shenzhen 518054 China

# 2.4 General Description for Equipment under Test (EUT)

EUT Type	RHF1S001 IP64 T&H sensor	
Model Name Under	RHF1S001	
Test		
Series Model Name	N/A	
Description of Model	N/A	
name differentiation	N/A	
Hardware Version	V1.0	
Software Version	RHF1S001: V2.0.3	
Dimensions (Approx.)	N/A	
Weight (Approx.)	N/A	
Network and Wireless connectivity	Lora Spread Spectrum, LoraWAN	

# 2.5 Ancillary Equipment

	Battery	
	Brand Name	EVE Energy Co., Ltd
	Model No.	ER34615
Ancillary Equipment 1	Serial No.	N/A
	Capacitance	19000 mAh
	Rated Voltage	3.6 V
	Limit Charge Voltage	N/A



## 2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DTS
Modulation Type	LoRa
Product Type	Mobile and portable
Frequency Range	The frequency range used is 902 MHz to 928 MHz.
Number of channel	8
Tested Channel	0 (903 MHz), 4 (909.4 MHz), 7 (914.2 MHz)
Antenna Type	PIFA Antenna
Antenna Gain	-2 dBi (All involve the antenna gain test item, has been included in the final results)
Antenna System(MIMO Smart Antenna)	N/A
About the Product	The EUT is supply the DTS, Frequency hopping system and Hybrid system, only the DTS was tested in this report.

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	903.00	4	909.40
1	904.60	5	911.00
2	906.20	6	912.60
3	907.80	7	914.20

## 2.7 Additional Instructions

**EUT Software Settings:** 

	Special software is used.
Mode	The software provided by client to enable the EUT under
Wode	transmission condition continuously at specific channel
	frequencies individually.

During testing. Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software				
Test Software Version				
Mode	Channel	Soft Set		
LoRa	ALL	14		

Run Software

D:\>CD D:\rcfg

D:\rcfg>rcfg.exe -t RXCLORA -P "902500000,7,500000,12,12,14"



# 3 SUMMARY OF TEST RESULTS

# 3.1 Test Standards

No.	Identity	Document Title
	47 CFR Part 15,	
1	1 Subpart C Miscellaneous Wireless Communications Services	
(10-1-15 Edition)		
KDB Publication Guidance for Performing Compliance Measurements on		Guidance for Performing Compliance Measurements on
	558074 D01v03r05	Digital Transmission Systems (DTS) Operating Under §15.247
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

## 3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	N/A		Pass <sup>Note1</sup>
2	Output Power	15.247(b)	Low/Middle/High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	Low/Middle/High	ANNEX A.3	Pass
5	Band Edge(Authorized- band band-edge)	15.247(d)	Low/ High	ANNEX A.4	Pass
6	Conducted Emission	15.207	Low/Middle/High	ANNEX A.5	N/A Note2
7	Radiated Spurious Emission	15.209 15.247(d)	Low/Middle/High	ANNEX A.6	Pass
8	Band Edge(Restricted- band band-edge)	15.209 15.247(d)	Low/Middle/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	Low/Middle/High	ANNEX A.8	Pass

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: The EUT is supply by battery, so the Conducted Emission is not applicable.



# **4 GENERAL TEST CONFIGURATIONS**

# **4.1 Test Environments**

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.6 V

# 4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2016.07.13	2017.07.12
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2016.07.13	2017.07.12
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2016.07.13	2017.07.12
Switch Unit with OSP- B157	ROHDE&SCHWARZ	OSP120	101270	2016.07.13	2017.07.12
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2015.10.15	2016.10.14
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2016.07.05	2017.07.04
LISN	SCHWARZBECK	NSLK 8127	8127-687	2016.07.05	2017.07.04
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2016.07.13	2017.07.12
Power Splitter	KMW	DCPD-LDC	1305003215		
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2016.07.13	2017.07.12
Attenuator (20 dB)	KMW	ZA-S1-201	110617091		
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189		
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2016.07.13	2017.07.12
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2016.07.13	2017.07.12
Test Antenna- Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna- Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna- Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna- Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2015.02.28	2017.02.27
Shielded Enclosure	ChangNing	CN-130701	130703		



# 4.3 Measurement Uncertainty


The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value	
Occupied Channel Bandwidth	±4%	
RF output power, conducted	±1.4 dB	
Power Spectral Density, conducted	±2.5 dB	
Unwanted Emissions, conducted	±2.8 dB	
All emissions, radiated	±5.4 dB	
Temperature	±1°C	
Humidity	±4%	

## 4.4 Description of Test Setup


#### 4.4.1 For Antenna Port Test



(Diagram 1)




## 4.4.2 For AC Power Supply Port Test



(Diagram 2)


# 4.4.3 For Radiated Test (Below 30 MHz)



(Diagram 3)




# 4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

# 4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)



## 4.5 Measurement Results Explanation Example

#### 4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

## 4.5.2 For radiated band edges and spurious emission test:

$$E = EIRP - 20log D + 104.8$$

#### where:

 $E = electric field strength in dB\mu V/m$ ,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)



## 5 TEST ITEMS

## 5.1 Antenna Requirements

#### 5.1.1 Standard Applicable

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.


If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

## 5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	The antenna is welded on the mainboard, can't be replaced by the
	consumer





## 5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 5.2 Output Power

#### 5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (4)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

#### 5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

#### 5.2.3 Test Procedure

#### a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW ≥ DTS bandwidth.

Set VBW ≥ 3 x RBW.

Set span ≥ 3 x RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

#### b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of



sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \le 16.7$  microseconds.)

## 5.2.4 Test Result

Please refer to ANNEX A.1.



# 5.3 Occupied Bandwidth

## 5.3.1 Limit

FCC §15.247(a); RSS-247, 5.1 (1); RSS-GEN, 6.6

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

## 5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

#### 5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 5.3.4 Test Result

Please refer to ANNEX A.2.



## 5.4 Conducted Spurious Emission

#### 5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

## 5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

#### 5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to  $\geq$  1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW  $\geq$  3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.



#### Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW  $\geq$  3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

#### 5.4.4 Test Result

Please refer to ANNEX A.3.



## 5.5 Band Edge (Authorized-band band-edge)

#### 5.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

## 5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

#### 5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle  $\geq$  98%). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than  $\pm$  2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW ≥  $3 \times RBW$ .

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission)  $\pm$  0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission  $\pm$  0.5 MHz.

#### 5.5.4 Test Result

Please refer to ANNEX A.4.



## 5.6 Conducted Emission

#### 5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a  $50\mu\text{H}/50\Omega$  line impedance stabilization network (LISN).

Frequency range	Conducted Limit (dBµV)				
(MHz)	Quai-peak Average				
0.15 - 0.50	66 to 56 56 to 46				
0.50 - 5	56	46			
0.50 - 30	60	50			

## 5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

#### 5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

## 5.6.4 Test Result

Please refer to ANNEX A.5.



## 5.7 Radiated Spurious Emission

#### 5.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

#### Note:

- 1. Field Strength ( $dB\mu V/m$ ) = 20\*log[Field Strength ( $\mu V/m$ )].
- 2. In the emission tables above, the tighter limit applies at the band edges.
- For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
- For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

#### 5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

#### 5.7.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured



RBW = 1 MHz for  $f \ge 1$  GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

## 5.7.4 Test Result

Please refer to ANNEX A.6.



# 5.8 Band Edge (Restricted-band band-edge)

#### 5.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

#### 5.8.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

#### 5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \ge 1$  GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

#### 1.1.1 Test Result

Please refer to ANNEX A.7.



## 5.9 Power Spectral density (PSD)

#### 5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (2)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

#### 5.9.2 Test Setup

See section 4.4.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

#### 5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .

Set the VBW ≥ 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### 5.9.4 Test Result

Please refer to ANNEX A.7.




# ANNEX A TEST RESULT

# **A.1 Output Power**

## Peak Power Test Data

	Measured Outpo	ut Peak Power	Limit			
Channel	LoF	Ra	dDm	mW	Verdict	
	dBm	mW	dBm	IIIVV		
Low	13.84	24.21			Pass	
Middle	13.77	23.82	30	1000	Pass	
High	13.75	23.71			Pass	

## Test plots








# A.2 Occupied Bandwidth


#### Test Data

Test Mode		LoRa		
Channel	6 dB Bandwidth	99% Bandwidth	6 dB Bandwidth	
Channel	(kHz)	(kHz)	Limits (kHz)	
Low Channel	720	640	≥500	
Middle Channel	624	588	≥500	
High Channel	685	584	≥500	

## Test plots (6 dB Bandwidth)







Date: 1.NOV.2016 15:58:14



#### Test plots (99% Bandwidth)



#### HIGH CHANNEL






# A.3 Conducted Spurious Emissions

#### Test Data

		LoRa		
	Measured Max. Out of	Limit (d	dBm)	V
Channel	Band Emission (dBm)	Carrier Level	Calculated 20 dBc Limit	Verdict
Low	-39.51	13.83	-6.17	Pass
Middle	-38.97	13.75	-6.25	Pass
High	-38.12	13.73	-6.27	Pass

## **Test Plots**

#### LOW CHANNEL . CARRIER LEVEL




Date: 1.NOV.2016 15:45:18

#### LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz D1 -6.170 D1 -6.170 Start 30.0 MHz Start 2.0 GH Y-value Function 13.97 dBm -39.51 dBm Y-value Function -53.08 dBm -60.45 dBm **Function Result Function Result** Date: 1.NOV.2016 15:45:53 Date: 1.NOV.2016 15:46:04





## MIDDLE CHANNEL, CARRIER LEVEL



Date: 1.NOV.2016 15:56:54


#### MIDDLE CHANNEL . SPURIOUS 30 MHz ~ 3 GHz MIDDLE CHANNEL . SPURIOUS 3 GHz ~ 25 GHz






Date: 1.NOV.2016 15:57:10 Date: 1.NOV.2016 15:57:10

#### High CHANNEL, CARRIER LEVEL



Date: 1.NOV.2016 15:58:27







# A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


	Measured Max. Band	Limit	(dBm)	
Channel	Edge Emission (dBm)	Carrier Level	Calculated 20 dBc Limit	Verdict
Low Channel	-46.28	13.59	-6.41	Pass
High Channel	-30.68	13.73	-6.27	Pass

#### **Test Plots**

## LOW CHANNEL, Carrier level



## LOW CHANNEL, Reference level




Date: 1.NOV.2016 15:46:41

## LOW CHANNEL, Band Edge






#### High CHANNEL, Carrier level








Date: 1.NOV.2016 15:59:31

# LOW CHANNEL, Band Edge



Date: 1.NOV.2016 15:59:59

## **A.5 Conducted Emissions**

N/A



## A.6 Radiated Spurious Emission

#### Cabinet Radiated spurious emission test

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The marked spikes near 900 MHz with circle should be ignored because they are Fundamental signal.

#### Test Data and Plots


#### 903 MHz, ANT V




No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	43.819	23.75	-18.92	40.0	16.25	Peak	7.70	100	Vertical	Pass
2	119.945	26.88	-21.74	43.5	16.62	Peak	7.70	100	Vertical	Pass
3	235.346	22.99	-19.34	46.0	23.01	Peak	0.30	100	Vertical	Pass
4	416.448	26.97	-14.72	46.0	19.03	Peak	3.30	100	Vertical	Pass
5	711.012	36.03	-8.88	46.0	9.97	Peak	1.20	100	Vertical	Pass
6	902.782	106.92	-5.63	46.0	-60.92	Peak	27.50	100	Vertical	N/A



#### 903 MHz ANT F






No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	48.183	23.58	-18.65	40.0	16.42	Peak	347.40	100	Horizontal	Pass
2	89.398	21.29	-22.09	43.5	22.21	Peak	178.30	100	Horizontal	Pass
3	165.766	20.80	-22.91	43.5	22.70	Peak	302.20	100	Horizontal	Pass
4	300.805	25.46	-17.68	46.0	20.54	Peak	312.30	100	Horizontal	Pass
5	567.246	32.06	-11.70	46.0	13.94	Peak	232.10	100	Horizontal	Pass
6	903.000	106.14	-5.63	46.0	-60.14	Peak	312.30	100	Horizontal	N/A




#### 909 4 MHz ANT \




No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	36.546	23.87	-20.80	40.0	16.13	Peak	352.70	100	Vertical	Pass
2	101.762	28.42	-20.13	43.5	15.08	Peak	308.40	100	Vertical	Pass
3	239.225	24.17	-19.14	46.0	21.83	Peak	178.60	100	Vertical	Pass
4	459.603	28.89	-14.30	46.0	17.11	Peak	114.50	100	Vertical	Pass
5	712.224	35.50	-8.88	46.0	10.50	Peak	24.70	100	Vertical	Pass
6	909.085	111.37	-5.38	46.0	-65.37	Peak	357.00	100	Vertical	N/A



# 909.4 MHz, ANT H






No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	49.153	22.67	-18.67	40.0	17.33	Peak	8.90	100	Horizontal	Pass
2	105.884	21.83	-20.22	43.5	21.67	Peak	23.30	100	Horizontal	Pass
3	202.374	24.11	-20.15	43.5	19.39	Peak	77.90	100	Horizontal	Pass
4	399.963	26.45	-15.13	46.0	19.55	Peak	88.20	100	Horizontal	Pass
5	709.073	35.94	-8.89	46.0	10.06	Peak	240.40	100	Horizontal	Pass
6	909.570	106.17	-5.35	46.0	-60.17	Peak	315.50	100	Horizontal	N/A




# 914.2MHz, ANT V



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	46.486	23.87	-18.69	40.0	16.13	Peak	46.10	100	Vertical	Pass
2	101.277	23.23	-20.20	43.5	20.27	Peak	277.40	100	Vertical	Pass
3	190.737	21.88	-21.13	43.5	21.62	Peak	359.30	100	Vertical	Pass
4	353.414	25.99	-16.14	46.0	20.01	Peak	107.00	100	Vertical	Pass
5	609.673	33.67	-10.44	46.0	12.33	Peak	167.70	100	Vertical	Pass
6	914.661	105.72	-5.33	46.0	-59.72	Peak	172.90	100	Vertical	N/A



# 914.2 MHz, ANT H



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	45.516	24.90	-18.80	40.0	15.10	Peak	43.10	100	Horizontal	Pass
2	92.792	22.37	-21.26	43.5	21.13	Peak	84.00	100	Horizontal	Pass
3	177.888	20.85	-22.17	43.5	22.65	Peak	114.70	100	Horizontal	Pass
4	299.108	26.79	-17.67	46.0	19.21	Peak	78.90	100	Horizontal	Pass
5	507.121	30.18	-13.08	46.0	15.82	Peak	0.00	100	Horizontal	Pass
6	914.904	103.07	-5.31	46.0	-57.07	Peak	119.50	100	Horizontal	N/A



# LOW CHANNEL 1 GHz to 10 GHz, ANT V

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	1269.43	43.04	-4.84	74	30.96	Peak	136.3	150	Vertical	Pass
2	1533.87	40.80	-4.35	74	33.20	Peak	302.5	150	Vertical	Pass
3	1891.78	42.82	-2.95	74	31.18	Peak	318.9	150	Vertical	N/A
4	6965.89	43.06	14.17	74	30.94	Peak	264.6	150	Vertical	Pass
5	8302.41	42.71	10.23	74	31.30	Peak	68.4	150	Vertical	Pass
6	8785.36	45.79	11.25	74	28.21	Peak	39.2	150	Vertical	Pass

# LOW CHANNEL 1 GHz to 10 GHz, ANT H

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	1341.92	42.43	-4.72	74	31.57	Peak	60	150	Horizontal	Pass
2	1433.39	45.46	1.70	74	28.54	Peak	219.3	150	Horizontal	Pass
3	1926.77	46.51	13.62	74	27.49	Peak	247.4	150	Horizontal	Pass
4	6359.40	43.89	18.91	74	30.11	Peak	297.1	150	Horizontal	Pass
5	8313.64	42.10	9.15	74	31.91	Peak	106.6	150	Horizontal	Pass
6	8830.28	46.80	10.81	74	27.20	Peak	143.7	150	Horizontal	Pass

## MIDDLE CHANNEL 1 GHz to 10 GHz, ANT V

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	1232.94	42.50	-6.33	74	31.50	Peak	268.1	150	Vertical	Pass
2	1504.37	41.69	-4.21	74	32.31	Peak	89.4	150	Vertical	Pass
3	1793.30	46.12	-3.11	74	27.88	Peak	5.1	150	Vertical	Pass
4	7549.92	42.18	18.46	74	31.82	Peak	231.7	150	Vertical	Pass
5	8336.11	45.51	10.41	74	28.49	Peak	69.4	150	Vertical	Pass
6	8863.98	43.07	8.62	74	30.93	Peak	50.5	150	Vertical	Pass



#### MIDDLE CHANNEL 1 GHz to 10 GHz. ANT H

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	1099.48	42.84	-5.27	74	31.16	Peak	254.3	150	Horizontal	Pass
2	1566.86	44.06	1.81	74	29.94	Peak	327.2	150	Horizontal	Pass
3	1842.79	47.98	13.15	74	26.02	Peak	89.7	150	Horizontal	Pass
4	7257.90	43.41	20.60	74	30.59	Peak	64.3	150	Horizontal	Pass
5	8324.88	45.57	9.66	74	28.43	Peak	340.4	150	Horizontal	Pass
6	8538.27	45.89	10.50	74	28.11	Peak	203.8	150	Horizontal	Pass

#### HIGH CHANNEL 1 GHz to 10 GHz. ANT V

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	1040.49	40.51	-6.05	74	33.49	Peak	354.7	150	Vertical	Pass
2	1540.37	44.83	-4.58	74	29.17	Peak	356.3	150	Vertical	Pass
3	1747.31	41.92	-4.37	74	32.08	Peak	335.9	150	Vertical	Pass
4	6651.41	48.18	14.41	74	25.82	Peak	317.8	150	Vertical	Pass
5	8313.64	44.16	10.75	74	29.84	Peak	73.4	150	Vertical	Pass
6	8515.81	45.88	9.34	74	28.12	Peak	123.4	150	Vertical	Pass

#### HIGH CHANNEL 1 GHz to 10 GHz, ANT H

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	1355.41	39.12	-2.41	74	34.88	Peak	214	150	Horizontal	Pass
2	1502.87	47.23	1.90	74	26.77	Peak	161	150	Horizontal	Pass
3	1670.83	47.19	11.56	74	26.81	Peak	247.3	150	Horizontal	Pass
4	7336.52	46.35	18.38	74	27.65	Peak	211.6	150	Horizontal	Pass
5	8313.64	43.47	11.91	74	30.53	Peak	212.5	150	Horizontal	Pass
6	9122.30	48.21	12.86	74	25.79	Peak	301	150	Horizontal	Pass

# A.7 Band Edge (Restricted-band band-edge)

## **PASS**

Note: The adjacent to the restricted frequency band (608-614MHz and 960-1240MHz) is far away the fundamental, it is noise only. Please refer to Section A.6 for test data.



# A.8 Power Spectral Density (PSD)


## Test Data

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict	
Low Channel	0.61	8	Pass	
Middle Channel	0.60	8	Pass	
High Channel	0.53	8	Pass	

## Test plots

# 





Date: 1.NOV.2016 15:57:27





Date: 1.NOV.2016 16:00:06



# ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ1690394-AR.PDF".

# ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL- SZ1690394-AW.PDF".

# ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL- SZ1690394-AI.PDF".

--END OF REPORT--