RF Exposure Requirements

Product Description: Q9 smart bracelet

Model No.: Q9, QS90, QS100, Q9 pro, Q10, Q11, Q12, Q15, Q16, Q18, Q20, Q66, Q88, Q99,

Q520, Q521

FCC ID: 2AJVI-Q9

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation 17
- The result is rounded to one decimal place for comparison

Calculation Result:

Tx frequency range: 2402-2480MHz Min. test separation distance: 5mm

Maximum Conducted Output Power: 4.480dBm

Tune-Up output power: 5dBm

RF channel transmit frequency: 2480MHz

Result: 1.0 Limit: 3.0

The exclusion thresholds is $1.0 \le 3$, so the transmitter complies with the RF exposure requirements and the SAR is not required.