


# RF EVALUATION TEST REPORT

Applicant..... : Foto Electric Supply Co., INC.  
Address..... : 1 Rewe St. Brooklyn, New York 11211 United States  
Manufacturer..... : Foto Electric Supply Co., INC.  
Address..... : 1 Rewe St. Brooklyn, New York 11211 United States  
Factory..... : Foto Electric Supply Co., INC.  
Address..... : 1 Rewe St. Brooklyn, New York 11211 United States  
Product Name..... : Wireless Speaker & Magnetic Phone Stand  
Brand Name..... : Chargeworx, COBY  
Model No. .... : KH5342, KH5342WH, KH5342BK, CX5342WH, CX5342PK, CX5342BL,  
CX5342BK (For model difference refer to section 2.)  
FCC ID..... : 2AJVKKH5342  
Measurement Standard..... : 47 CFR PART 2, Section 2.1093  
Receipt Date of Samples..... : July 08, 2025  
Date of Tested..... : July 16, 2025 to July 24, 2025  
Date of Report..... : August 25, 2025

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Alina Guo / Project Engineer



TESTED by

Iori Fan / Authorized Signatory

---

## Table of Contents

|                                             |   |
|---------------------------------------------|---|
| 1. General Description of EUT .....         | 4 |
| 2. Test Facility and Location .....         | 6 |
| 3. Applicable Standards and References..... | 6 |
| 4. Maximum Permissible Exposure Limit ..... | 7 |
| 5. RF Exposure Evaluation Results .....     | 9 |



## 1. General Description of EUT

| Product Information     |                                                                                                                                                                                                                                                                                      |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:           | Wireless Speaker & Magnetic Phone Stand                                                                                                                                                                                                                                              |
| Main Model Name:        | KH5342                                                                                                                                                                                                                                                                               |
| Additional Model Name:  | KH5342WH, KH5342BK, CX5342WH, CX5342PK, CX5342BL, CX5342BK                                                                                                                                                                                                                           |
| Model difference:       | These models have the same circuit schematic, structure, PCB Layout and critical components. The differences are model number, color and brand name due to trading purpose.                                                                                                          |
| S/N:                    | 2507-5004                                                                                                                                                                                                                                                                            |
| Brand Name:             | Chargeworx, COBY                                                                                                                                                                                                                                                                     |
| Hardware Version:       | 5368E-LTK5313                                                                                                                                                                                                                                                                        |
| Software Version:       | fw5000.upd                                                                                                                                                                                                                                                                           |
| Rating:                 | DC 5V come from charging case; DC 3.7V come from internal li-ion battery                                                                                                                                                                                                             |
| Typical Arrangement:    | Tabletop                                                                                                                                                                                                                                                                             |
| I/O Port:               | Refer to the user manual                                                                                                                                                                                                                                                             |
| Accessories Information |                                                                                                                                                                                                                                                                                      |
| Adapter                 | N/A                                                                                                                                                                                                                                                                                  |
| Cable:                  | USB line: 0.3m, unshielded, detachable                                                                                                                                                                                                                                               |
| Other:                  | N/A                                                                                                                                                                                                                                                                                  |
| Additional Information  |                                                                                                                                                                                                                                                                                      |
| Note:                   | <ol style="list-style-type: none"> <li>1. According to the model differences and manufacturer's requirements, all tests were performed on model KH5342.</li> <li>2. The product comes in two color appearance, all the tests are conducted based on the black appearance.</li> </ol> |
| Remark:                 | All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.                                                                                                                                                       |

| Technical Specification |                                                  |
|-------------------------|--------------------------------------------------|
| Bluetooth Version:      | V5.3                                             |
| Frequency Range:        | 2402-2480MHz                                     |
| Modulation Type:        | GFSK, $\pi/4$ -DQPSK, 8DPSK                      |
| Number of Channel:      | 79 (refer to following channel list for details) |
| Channel Space:          | 1MHz                                             |
| Antenna Type:           | PCB Antenna                                      |
| Number of Antenna       | 1                                                |
| Antenna Gain:           | 1.7 dBi (Declared by manufacturer)               |
| Remark:                 | This product only supports BDR/EDR technology.   |

## 2. Test Facility and Location

|                                   |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Site                         | : | Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Accreditations and Authorizations | : | <p>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01</p> <p>Listed by CNAS, August 13, 2018</p> <p>The Certificate Registration Number is L5795.</p> <p>The Certificate is valid until August 13, 2030</p><br><p>The Laboratory has been assessed and proved to be in compliance with ISO17025</p> <p>Listed by A2LA, November 01, 2017</p> <p>The Certificate Registration Number is 4429.01</p> <p>The Certificate is valid until December 31, 2025</p><br><p>Listed by FCC, November 06, 2017</p> <p>Test Firm Registration Number: 907417</p><br><p>Listed by Industry Canada, June 08, 2017</p> <p>The Certificate Registration Number. Is 46405-9743A</p> <p>The CAB identifier number: CN0015</p> |
| Test Site Location                | : | Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## 3. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

### Test Standards:

47 CFR Part 1, 1.1307  
47 CFR Part 2, 2.1093  
KDB 447498 D04 v01

#### 4. Maximum Permissible Exposure Limit

According to 47 CFR Part 1, 1.1307, for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if: 47 CFR Part 1, 1.1307

(A) The available maximum time- averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time- averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where,

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

And,

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the minimum separation distance (cm) in any direction from any part of the device antenna(s) or radiating structure(s) to the body of the device user.

For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time- averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where,

$a$  = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

$b$  = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

$c$  = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source  $i$ .

$ERP_j$  = the ERP of fixed, mobile, or portable RF source  $j$ .

$ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

$E_{evaluated,k}$  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$E_{exposure\ limit,k}$  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

## 5. RF Exposure Evaluation Results

| Single RF Source |                 |                            |                    |                 |                |                           |                          |                                      |
|------------------|-----------------|----------------------------|--------------------|-----------------|----------------|---------------------------|--------------------------|--------------------------------------|
| Mode             | Frequency (MHz) | Max. Conducted Power (dBm) | Antenna Gain (dBi) | Max. EIRP (dBm) | Max. ERP (dBm) | Max. Conducted Power (mW) | Separation Distance (cm) | Part 1.1307 Option (B) $P_{th}$ (mW) |
| GFSK             | 2402            | -6.359                     | 1.7                | -4.659          | -6.809         | 0.23                      | 0.5                      | 2.79                                 |
|                  | 2441            | -7.552                     | 1.7                | -5.852          | -8.002         | 0.18                      | 0.5                      | 2.75                                 |
|                  | 2480            | -9.236                     | 1.7                | -7.536          | -9.686         | 0.12                      | 0.5                      | 2.72                                 |
| $\pi/4$ -DQPSK   | 2402            | -4.322                     | 1.7                | -2.622          | -4.772         | 0.37                      | 0.5                      | 2.79                                 |
|                  | 2441            | -5.765                     | 1.7                | -4.065          | -6.215         | 0.27                      | 0.5                      | 2.75                                 |
|                  | 2480            | -7.359                     | 1.7                | -5.659          | -7.809         | 0.18                      | 0.5                      | 2.72                                 |
| 8DPSK            | 2402            | -3.892                     | 1.7                | -2.192          | -4.342         | 0.41                      | 0.5                      | 2.79                                 |
|                  | 2441            | -5.268                     | 1.7                | -3.568          | -5.718         | 0.30                      | 0.5                      | 2.75                                 |
|                  | 2480            | -6.855                     | 1.7                | -5.155          | -7.305         | 0.21                      | 0.5                      | 2.72                                 |

### Conclusion:

According to 47 CFR §1.1307 (b)(3)(i)(B), the RF exposure analysis concludes that the product is compliant with the FCC RF exposure requirements in mobile exposure condition.

---End---