RF Exposure evaluation

FCC ID: 2AJWZ-W2

1. Reference

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] • [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,

Where:

f (GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

and

eirp =
$$p_t \times g_t = (E \times d)^2 / 30$$

Where:

 p_t = transmitter output power in watts,

 g_t = numeric gain of the transmitting antenna (unitless),

 $E = electric \ field \ strength \ in \ V/m, --- \ 10^{((dBuV/m)/20)}/10^6$

d = measurement distance in meters (m) ---3m

2. Result

As the antenna EUT used was 0dBi and the Max field strength level measured with duty cycle ≥98% in EMI test report, the sar exclusion value can obtained.

According to the formula described above:

 E_{max} =**97.47** dBuV/m =**0.0747**V/m, d=3m, gt=1

Pt=
$$(E \times d)^2/(30 \times gt) = (0.0747x3)^2/(30x1) = 0.001675 = 1.68 \text{mW}$$

The value is within the tune up 2 ± 1 dBm stated by the manufacturer Worse case is as below:

			TX	Separation		
Frequency (MHz)	Field	d TX	Power	Distance	calculated value	exclusion thresholds
	strength	Power	with	(mm)		
	dBuV/m	(mw)	tune-up			
			(mw)			
2441	97.47	1.68	2.00	5	0.6	3

3. Conclusion

The SAR evaluation is not required.