



Certification Exhibit

FCC ID: 2AJXX100286

FCC Rule Part: 47 CFR Part 2.1091

TÜV SÜD Project Number: 72143509

Manufacturer: Current Products Corp.
Model: CP19MTDZ-01

RF Exposure

General Information:

Applicant: Current Products Corp.
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Monopole
 Antenna Gain: 5.19 dBi
 Maximum Transmitter Conducted Power: 12.59 dBm, 18.1552 mW
 Maximum System EIRP: 17.78 dBm, 59.9791 mW
 Exposure Conditions: 20 centimeters or greater

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Table 1: MPE Calculation

Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm ²)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm ²)
2405	12.59	1.00	18.16	5.19	3.304	20	0.012