



Certification Exhibit

FCC ID: 2AJXX100289

FCC Rule Part: 47 CFR Part 2.1093

TÜV SÜD Project Number: 72143462

Manufacturer: Current Products Corp
Model: CP19DRCZ-01

RF Exposure

General Information:

Applicant: Current Products Corp
Environment: General Population/Uncontrolled Exposure
Exposure Conditions: Portable

Technical Information:

Minimum Test Separation Distance: 5 mm
Highest Operating Frequency: 2480 MHz
Antenna Type: PCB Trace Antenna
Antenna Gain: 3.3 dBi
Maximum Transmitter Conducted Power: 1.57 dBm, 1.44 mW
Maximum Transmitter EIRP: 4.87 dBm, 3.07 mW

Justification for SAR Test Exclusion:**Standalone SAR Test Exclusion:**

Per KDB 447498 D01 General RF Exposure Guidance v05r02, the standalone 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$= (1.44 / 5) \cdot (\sqrt{2.48}) = 0.5$$

0.5 < 3

Standalone SAR test exclusion is applied.